

Wavelength band	Frequencies	Emission types authorized	Standards see § 97.307, paragraph(s):
(xix) 10 m ..	28.5–29.0 MHz	Phone, image	(f)(1), (2).
(xx) 10 m ...	29.0–29.7 MHz	Phone, image	(f)(2).
(4) VHF:			
(i) 6 m	50.1–51.0 MHz	MCW, phone, image, RTTY, data	(f)(2), (5).
(ii) 6 m	51.0–54.0 MHz	MCW, phone, image, RTTY, data, test	(f)(2), (5), (8).
(iii) 2 m	144.1–148.0 MHz	MCW, phone, image, RTTY, data, test	(f)(2), (5), (8).
(iv) 1.25 m	219–220 MHz	Data	(f)(13).
(v) 1.25m ...	222–225 MHz	RTTY, data, test MCW, phone, SS, image.	(f)(2), (6), (8).
(5) UHF:			
(i) 70 cm	Entire band	MCW, phone, image, RTTY, data, SS, test.	(f)(6), (8).
(ii) 33 cm ...	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(iii) 23 cm ...	Entire band	MCW, phone, image, RTTY, data, SS, test.	(f)(7), (8), and (12).
(iv) 13 cm ..	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(6) SHF:			
(i) 5 cm	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(ii) 3 cm	Entire band	MCW, phone, image, RTTY, data, SS, test.	(f)(7), (8), and (12).
(iii) 1.2 cm ..	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(7) EHF:			
(i) 6 mm	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(ii) 4 mm	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(iii) 2.5 mm	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(iv) 2 mm ...	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(v) 1 mm	Entire band	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).
(vi) 1 mm ...	Above 275 GHz	MCW, phone, image, RTTY, data, SS, test, pulse.	(f)(7), (8), and (12).

[54 FR 25857, June 20, 1989; 54 FR 39536, Sept. 27, 1989; 55 FR 22013, May 30, 1990, as amended at 55 FR 30457, July 26, 1990; 60 FR 15688, Mar. 27, 1995; 64 FR 51471, Sept. 23, 1999; 71 FR 66465, Nov. 15, 2006; 75 FR 27204, May 14, 2010; 77 FR 5412, Feb. 3, 2012; 82 FR 27215, June 14, 2017; 85 FR 64069, Oct. 9, 2020; 88 FR 85127, Dec. 7, 2023]

§ 97.307 Emission standards.

(a) No amateur station transmission shall occupy more bandwidth than necessary for the information rate and emission type being transmitted, in accordance with good amateur practice.

(b) Emissions resulting from modulation must be confined to the band or segment available to the control operator. Emissions outside the necessary bandwidth must not cause splatter or keyclick interference to operations on adjacent frequencies.

(c) All spurious emissions from a station transmitter must be reduced to the greatest extent practicable. If any spurious emission, including chassis or power line radiation, causes harmful interference to the reception of another radio station, the licensee of the

interfering amateur station is required to take steps to eliminate the interference, in accordance with good engineering practice.

(d) For transmitters installed after January 1, 2003, the mean power of any spurious emission from a station transmitter or external RF power amplifier transmitting on a frequency below 30 MHz must be at least 43 dB below the mean power of the fundamental emission. For transmitters installed on or before January 1, 2003, the mean power of any spurious emission from a station transmitter or external RF power amplifier transmitting on a frequency below 30 MHz must not exceed 50 mW and must be at least 40 dB below the mean power of the fundamental emission. For a transmitter of mean power

less than 5 W installed on or before January 1, 2003, the attenuation must be at least 30 dB. A transmitter built before April 15, 1977, or first marketed before January 1, 1978, is exempt from this requirement.

(e) The mean power of any spurious emission from a station transmitter or external RF power amplifier transmitting on a frequency between 30–225 MHz must be at least 60 dB below the mean power of the fundamental. For a transmitter having a mean power of 25 W or less, the mean power of any spurious emission supplied to the antenna transmission line must not exceed 25 μ W and must be at least 40 dB below the mean power of the fundamental emission, but need not be reduced below the power of 10 μ W. A transmitter built before April 15, 1977, or first marketed before January 1, 1978, is exempt from this requirement.

(f) The following standards and limitations apply to transmissions on the frequencies specified in § 97.305(c).

(1) No angle-modulated emission may have a modulation index greater than 1 at the highest modulation frequency.

(2) No non-phone emission shall exceed the bandwidth of a communications quality phone emission of the same modulation type. The total bandwidth of an independent sideband emission (having B as the first symbol), or a multiplexed image and phone emission, shall not exceed that of a communications quality A3E emission.

(3) Only a RTTY or data emission using a specified digital code listed in § 97.309(a) may be transmitted. The authorized bandwidth is 2.8 kHz except in the 2200 m band and 630 m band. In the 2200 m band and the 630 m band the symbol rate must not exceed 300 bauds, or for frequency-shift keying, the frequency shift between mark and space must not exceed 1 kHz.

(4) [Reserved]

(5) A RTTY, data or multiplexed emission using a specified digital code listed in § 97.309(a) may be transmitted. The symbol rate must not exceed 19.6 kilobauds. A RTTY, data or multiplexed emission using an unspecified digital code under the limitations list-

ed in § 97.309(b) also may be transmitted. The authorized bandwidth is 20 kHz.

(6) A RTTY, data or multiplexed emission using a specified digital code listed in § 97.309(a) may be transmitted. The symbol rate must not exceed 56 kilobauds. A RTTY, data or multiplexed emission using an unspecified digital code under the limitations listed in § 97.309(b) also may be transmitted. The authorized bandwidth is 100 kHz.

(7) A RTTY, data or multiplexed emission using a specified digital code listed in § 97.309(a) or an unspecified digital code under the limitations listed in § 97.309(b) may be transmitted.

(8) A RTTY or data emission having designators with A, B, C, D, E, F, G, H, J or R as the first symbol; 1, 2, 7, 9 or X as the second symbol; and D or W as the third symbol is also authorized.

(9) A station having a control operator holding a Novice or Technician Class operator license may only transmit a CW emission using the international Morse code.

(10) A station having a control operator holding a Novice Class operator license or a Technician Class operator license may only transmit a CW emission using the international Morse code or phone emissions J3E and R3E.

(11) Phone and image emissions may be transmitted only by stations located in ITU Regions 1 and 3, and by stations located within ITU Region 2 that are west of 130° West longitude or south of 20° North latitude.

(12) Emission F8E may be transmitted.

(13) A data emission using an unspecified digital code under the limitations listed in § 97.309(b) also may be transmitted. The authorized bandwidth is 100 kHz.

(14) *In the 60 m band:*

(i) A station may transmit only phone, RTTY, data, and CW emissions using the emission designators and any additional restrictions that are specified in the table below (except that the use of a narrower necessary bandwidth is permitted):

TABLE 1 TO PARAGRAPH (F)(14)(I)—60 M BAND EMISSION REQUIREMENTS

Emission type	Emission designator	Restricted to:
Phone	2K80J3E	Upper sideband transmissions (USB).
Data	2K80J2D	USB (for example, PACTOR-III).
RTTY	60H0J2B	USB (for example, PSK31).
CW	150HA1A	Morse telegraphy by means of on-off keying.

(ii) The following requirements also apply:

(A) When transmitting the phone, RTTY, and data emissions, the suppressed carrier frequency may be set as specified in § 97.303(h).

(B) The control operator of a station transmitting data or RTTY emissions must exercise care to limit the length of transmission so as to avoid causing harmful interference to United States Government stations.

[54 FR 25857, June 20, 1989; 54 FR 30823, July 24, 1989, as amended at 54 FR 39537, Sept. 27, 1989; 60 FR 15688, Mar. 27, 1995; 65 FR 6550, Feb. 10, 2000; 69 FR 24997, May 5, 2004; 77 FR 5412, Feb. 3, 2012; 79 FR 35291, June 20, 2014; 88 FR 85128, Dec. 7, 2023]

§ 97.309 RTTY and data emission codes.

(a) Where authorized by §§ 97.305(c) and 97.307(f) of the part, an amateur station may transmit a RTTY or data emission using the following specified digital codes:

(1) The 5-unit, start-stop, International Telegraph Alphabet No. 2, code defined in ITU-T Recommendation F.1, Division C (commonly known as “Baudot”).

(2) The 7-unit code specified in ITU-R Recommendations M.476-5 and M.625-3 (commonly known as “AMTOR”).

(3) The 7-unit, International Alphabet No. 5, code defined in IT-T Recommendation T.50 (commonly known as “ASCII”).

(4) An amateur station transmitting a RTTY or data emission using a digital code specified in this paragraph may use any technique whose technical characteristics have been documented publicly, such as CLOVER, G-TOR, or PacTOR, for the purpose of facilitating communications.

(b) Where authorized by §§ 97.305(c) and 97.307(f), a station may transmit a RTTY or data emission using an unspecified digital code, except to a sta-

tion in a country with which the United States does not have an agreement permitting the code to be used. RTTY and data emissions using unspecified digital codes must not be transmitted for the purpose of obscuring the meaning of any communication. When deemed necessary by a Regional Director to assure compliance with the FCC Rules, a station must:

(1) Cease the transmission using the unspecified digital code;

(2) Restrict transmissions of any digital code to the extent instructed;

(3) Maintain a record, convertible to the original information, of all digital communications transmitted.

[54 FR 25857, June 20, 1989, as amended at 54 FR 39537, Sept. 27, 1989; 56 FR 56172, Nov. 1, 1991; 60 FR 55486, Nov. 1, 1995; 71 FR 25982, May 3, 2006; 71 FR 66465, Nov. 15, 2006; 80 FR 53753, Sept. 8, 2015]

§ 97.311 SS emission types.

(a) SS emission transmissions by an amateur station are authorized only for communications between points within areas where the amateur service is regulated by the FCC and between an area where the amateur service is regulated by the FCC and an amateur station in another country that permits such communications. SS emission transmissions must not be used for the purpose of obscuring the meaning of any communication.

(b) A station transmitting SS emissions must not cause harmful interference to stations employing other authorized emissions, and must accept all interference caused by stations employing other authorized emissions.

(c) When deemed necessary by a Regional Director to assure compliance with this part, a station licensee must:

(1) Cease SS emission transmissions;

(2) Restrict SS emission transmissions to the extent instructed; and

(3) Maintain a record, convertible to the original information (voice, text,