

Proposed Rules

Federal Register

Vol. 62, No. 35

Friday, February 21, 1997

This section of the FEDERAL REGISTER contains notices to the public of the proposed issuance of rules and regulations. The purpose of these notices is to give interested persons an opportunity to participate in the rule making prior to the adoption of the final rules.

DEPARTMENT OF AGRICULTURE

Food Safety and Inspection Service

9 CFR Parts 304, 308, 310, 320, 327, 381, 416, and 417

[Docket No. 93-016-12N]

Publication of Salmonella Testing Data

AGENCY: Food Safety and Inspection Service, USDA.

ACTION: Meeting notice.

SUMMARY: The Food Safety and Inspection Service (FSIS) will hold a meeting regarding the publication of *Salmonella* testing data. Participants will discuss methods of making available to the public FSIS-generated testing data on the prevalence of *Salmonella* found on inspected products.

DATES: The meeting will be held on March 6, 1997, from 8:30 a.m. until 11:30 a.m.

ADDRESSES: The meeting will be held in Room 107A, Jamie L. Whitten Federal Building, 12th and Jefferson Dr. SW, Washington, DC 20250-3700.

FOR FURTHER INFORMATION CONTACT: To register for the meeting, call (202) 501-7136, FAX (202) 501-7642, or E-mail usdafs/s=confer@mhs.attmail.com.

SUPPLEMENTARY INFORMATION: On July 25, 1996, FSIS published a final rule, "Pathogen Reduction; Hazard Analysis and Critical Control Point (HACCP) Systems" (61 FR 38806). The rule established that FSIS will obtain samples from slaughter establishments and establishments producing raw ground product or fresh pork sausage and test those samples for *Salmonella* to ensure that pathogen reduction performance standards are being met. As stated in the rule, the test results will be available to the public.

FSIS is considering making the test results available via the Internet on the FSIS Homepage. FSIS also is interested in receiving public input on other methods for making the test results available. Therefore, the Agency will

hold a public meeting regarding the publication of *Salmonella* testing data.

Done at Washington, DC, on: February 18, 1997.

Thomas J. Billy,
Administrator.

[FR Doc. 97-4409 Filed 2-18-97; 4:42 pm]

BILLING CODE 3410-DM-P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 23

[Docket No. 135CE, Notice No. 23-ACE-87]

Special Conditions; Sino Swearingen Model SJ30-2 Airplane

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Notice of proposed special conditions.

SUMMARY: This notice proposes special conditions for the Sino Swearingen Aircraft Company Model SJ30-2 airplane. This new airplane will have novel and unusual design features not typically associated with normal, utility, acrobatic, and commuter category airplanes. These design features include a high operating altitude (49,000 feet), engine location, swept wings and stabilizer, performance characteristics, large fuel capacity, and protection for the electronic engine control system, flight, and navigation system from high intensity radiated fields, for which the applicable regulations do not contain adequate or appropriate airworthiness standards. This notice contains the additional airworthiness standards which the Administrator considers necessary to establish a level of safety equivalent to the airworthiness standards applicable to these airplanes.

DATES: Comments must be received on or before March 24, 1997.

ADDRESSES: Comments on this proposal may be mailed in duplicate to: Federal Aviation Administration, Office of the Assistant Chief Counsel, ACE-7, Attention: Rules Docket Clerk, Docket No. 135CE, Room No. 1558, 601 East 12th Street, Kansas City, Missouri 64106. All comments must be marked: Docket No 135CE. Comments may be inspected in the Rules Docket weekdays, except Federal holidays, between 7:30 a.m. and 4 p.m.

FOR FURTHER INFORMATION CONTACT:

Lowell Foster, Aerospace Engineer, Standards Office (ACE-110), Small Airplane Directorate, Aircraft Certification Service, Federal Aviation Administration, Room 1544, 601 East 12th Street, Kansas City, Missouri 64106; telephone (816) 426-5688.

SUPPLEMENTARY INFORMATION:

Comments Invited

Interested persons are invited to participate in the making of these special conditions by submitting such written data, views, or arguments as they may desire. Communications should identify the regulatory docket or notice number and be submitted in duplicate to the address specified above. All communications received on or before the closing date for comments specified above will be considered by the Administrator before taking further rulemaking action on this proposal. Commenters wishing the FAA to acknowledge receipt of their comments submitted in response to this notice must include a self-addressed, stamped postcard on which the following statement is made: "Comments to Docket No. 135CE." The postcard will be date stamped and returned to the commenter. The proposals contained in this notice may be changed in light of the comments received. All comments received will be available, both before and after the closing date for comments, in the rules docket for examination by interested parties. A report summarizing each substantive public contact with FAA personnel concerned with this rulemaking will be filed in the docket.

Background

On October 9, 1995, Sino Swearingen Aircraft Company, 1770 Sky Place Boulevard, San Antonio, Texas 78216, made application for normal category type certification of its Model SJ30-2 airplane, a six-to-eight place, all metal, low-wing, T-tail, twin turboprop engine powered airplane with fully enclosed retractable landing gear. The SJ30-2 will have a V_{MO}/M_{MO} of 320 kts/M=83, and has engines mounted aft on the fuselage.

Type Certification Basis

Type certification basis of the Model SJ30-2 airplane is: 14 CFR Part 23, effective February 1, 1965, through amendment 23-51, effective March 11, 1996; 14 CFR Part 36, effective

December 1, 1969, through the amendment effective on the date of type certification; 14 CFR Part 34; exemptions, if any; and any special conditions that may result from this notice.

Discussion

Sino Swearingen plans to incorporate certain novel and unusual design features into the SJ30-2 airplane for which the airworthiness regulations do not contain adequate or appropriate safety standards. These features include engine location, operation up to an altitude of 49,000 feet, and certain performance characteristics necessary for this type of airplane that were not envisioned by the existing regulations.

Special conditions may be issued and amended, as necessary, as part of the type certification basis if the Administrator finds that the airworthiness standards designated in accordance with 14 CFR Part 21, § 21.17(a)(1), do not contain adequate or appropriate safety standards because of novel or unusual design features of an airplane. Special conditions, as appropriate, are issued in accordance with 14 CFR Part 11, § 11.49 after public notice, as required by §§ 11.28 and 11.29(b), effective October 14, 1980, and become part of the type certification basis as provided by part 21, § 21.17(a)(2).

Protection of Systems From High Intensity Radiated Fields (HIRF)

The aviation industry uses electrical and electronic systems that perform functions required for continued safe flight and landing. Due to the sensitive solid state components in analog and digital electronics circuits, these systems, if unprotected, are responsive to the transient effects of induced electrical current and voltage caused by the HIRF. The HIRF can degrade electronic systems performance by damaging components or upsetting system functions.

Furthermore, the electromagnetic environment has changed from the time when the current requirements were developed. Also, the population of transmitters has increased significantly and they are radiating higher energy levels. There is, however, uncertainty concerning the effectiveness of shielding for HIRF. Additionally, coupling to cockpit installed equipment through the cockpit window apertures is undefined.

The combined effect of the technological advances in aircraft design and the changing environment has resulted in an increased level of vulnerability of electrical and electronic

systems required for the continued safe flight and landing of the aircraft. Effective measures against the effects of exposure to HIRF must be provided by the design and installation of these systems.

The accepted maximum energy levels in which civilian airplane system installations must be capable of operating safely are based on surveys and analysis of existing radio frequency emitters. These special conditions require that the airplane be evaluated under these energy levels for the protection of the electronic system and its associated wiring harness. These external threat levels are believed to represent the worst case to which an airplane would be exposed in the operating environment.

These special conditions require qualification of systems that perform critical functions, as installed in aircraft, to the defined HIRF environment in paragraph (1) or, as an option to a fixed value using laboratory tests, in paragraph (2), as follows:

(1) The applicant may demonstrate that the operation and operational capability of the installed electrical and electronic systems that perform critical functions are not adversely affected when the aircraft is exposed to the HIRF environment, defined below:

FIELD STRENGTH VOLTS/METER

Frequency	Peak	Average
10-100 KHz	50	50
100-500	60	60
500-2000	70	70
2-30 MHz	200	200
30-70	30	30
70-100	30	30
100-200	150	33
200-400	70	70
400-700	4020	935
700-1000	1700	170
1-2 GHz	5000	990
2-4	6680	840
4-6	6850	310
6-8	3600	670
8-12	3500	1270
12-18	3500	360
18-40	2100	750

or:

(2) The applicant may demonstrate by a laboratory test that the electrical and electronic systems that perform critical functions can withstand a peak electromagnetic field strength of 100 volts per meter (v/m) peak electrical field strength, from 10KHz to 18GHz. When using a laboratory test to show compliance with the HIRF requirements, no credit is given for signal attenuation due to installation.

A preliminary hazard analysis must be performed by the applicant for

approval by the FAA to identify electrical and/or electronic systems that perform critical functions. The term "critical" means those functions whose failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the aircraft. The systems identified by the hazard analysis that perform critical functions are candidates for the application of HIRF requirements. A system may perform both critical and non-critical functions. Primary electronic flight display systems, and their the associated components, perform critical functions such as attitude, altitude, and airspeed indication. The HIRF requirements apply only to critical functions.

Compliance with HIRF requirements may be demonstrated by tests, analysis, models, similarity with existing systems, or a combination of these. Service experience alone is not acceptable since such experience in normal flight operations may not include an exposure to the HIRF environment. Reliance on a system with similar design features for redundancy as a means of protection against the effects of external HIRF is generally insufficient since all elements of a redundant system are likely to be exposed to the fields concurrently.

Performance

The Sino Swearingen Model SJ30-2 has a main wing with 30 degrees of leading-edge sweepback that employs leading-edge slats and double-slotted Fowler flaps. The airplane has a T-tail with trimmable horizontal stabilizer and 30 degrees of leading-edge sweepback. There are two medium bypass ratio turbofan engines mounted on the aft fuselage.

Previous certification and operational experience with airplanes of like design in the transport category reveal certain unique characteristics compared to conventional aircraft certificated under part 23. These characteristics have caused significant safety problems in the past when pilots attempted takeoffs and landings, particularly with a large variation in temperature and altitude, using procedures and instincts developed with conventional airplanes.

One of the major distinguishing features of a swept-wing design not considered in current part 23 is a characteristically flatter lift curve without a "stall" break near the maximum coefficient of lift, as in a conventional wing. The "stall" separation point may occur at a much higher angle of attack than the point of maximum lift and the angle of attack for maximum lift can be only recognized by

precise test measurements or specific detection systems. This phenomena is not apparent to a pilot accustomed to operating a conventional airplane where increasing angle of attack produces increased lift to the point where the wing stalls. In a swept-wing design, if the pilot does not operate in accordance with established standards developed through a dedicated test program, increasing angle of attack may produce very little lift yet increase drag markedly to the point where flight is impossible. These adverse conditions may be further compounded by the characteristics of turbofan engines, including specified N_1/N_2 rotational speeds, temperature, and pressure limits that make its variation in thrust output with changes in temperature and altitude more complex and difficult to predict. In recognition of these characteristics, Special Civil Air Regulations No. SR-422, and follow-on regulations, established weight-altitude-temperature (WAT) limitations and procedures for scheduling takeoff and landing for turbine powered transport category airplanes, so the pilot could achieve reliable and repeatable results under all expected conditions of operation. This entails specific tests such as minimum unstuck speed, V_{MU} , to ensure that rotation and fly-out speeds are correct and that the airplane speed schedule will not allow the airplane to lift off in ground effect and then be unable to accelerate and continue to climb out. In conjunction with the development of takeoff and landing procedures, it was also necessary to establish required climb gradients and data for flight path determination under all approved weights, altitudes, and temperatures. This enables the pilot to determine, before takeoff, that a safe takeoff, departure, and landing at destination can be achieved.

Takeoff

Based upon the knowledge and experience gained with similar high speed, high efficiency, turbojet airplanes with complex high lift devices for takeoff and landing, special conditions are proposed for the performance requirements of takeoff, takeoff speeds, accelerate-stop distance, takeoff path, takeoff distance, takeoff run, and takeoff flight path.

Additionally, procedures for takeoff, accelerate stop, and landing are proposed as those established for operation in service and be executable by pilots of average skill and include reasonably expected time delays.

Climb

To maintain a level of safety that is consistent with the requirements of the proposed special conditions for takeoff, takeoff speeds, takeoff path, takeoff distance, and takeoff run, it is appropriate to propose associate requirements that specify climb gradients, airplane configurations, and consideration of atmospheric conditions that will be encountered. Special conditions are proposed for climb with one engine inoperative, balked landing climb, and general climb conditions.

Landing

Landing distance determined for the same parameters, plus the effects of wind, is consistent with takeoff information for the range of weights, altitudes, and temperatures approved for operation. Further, it is necessary to consider time delays to provide for in-service variation in the activation of deceleration devices, such as spoilers and brakes. Special conditions are also proposed to cover these items.

Trim

Special conditions are issued to maintain a level of safety that is consistent with the use of V_{MO}/M_{MO} and the requirements established for previous part 23 jet airplanes. Current standards in part 23 did not envision this type of airplane and the associated trim considerations.

Demonstration of Static Longitudinal Stability

To maintain a level of safety consistent with the proposed static longitudinal stability requirements, it is necessary to establish corresponding requirements for the demonstration of static longitudinal stability. Current standards in part 23 did not envision this type of airplane and the associated stability considerations proposed. In keeping with the concept of V_{MO}/M_{MO} being a maximum operational speed limit, rather than a limiting speed for the demonstration of satisfactory flight characteristics, it is appropriate to extend the speed for demonstration of longitudinal stability characteristics from the V_{MO}/M_{MO} of 14 CFR part 23 to the maximum speed for stability characteristics, V_{FC}/M_{FC} , for this airplane. A special condition to do this is proposed.

Static Directional and Lateral Stability

In keeping with the concept of V_{MO}/M_{MO} being a maximum operational speed limit, rather than a limiting speed for the demonstration of satisfactory flight characteristics, it is appropriate to extend the speed for demonstration of

lateral/directional stability characteristics from the V_{MO}/M_{MO} of part 23 to the maximum speed for stability characteristics, V_{FC}/M_{FC} , for this airplane. A special condition to do this is proposed.

Current transport category regulations have eliminated the independent lateral stability demonstration requirement (picking up the low wing with rudder application). This requirement was originally intended to provide adequate controllability in the event of lateral control system failure. Because the SJ30 flight control system reliability requirement are not to current transport category levels, it is appropriate to retain the prior transport category requirements to retain the independent dihedral effect and skid recovery demonstration requirement.

Stall Characteristics

In order to maintain consistency with the level of safety previously applied to other jet powered small airplanes, it is appropriate to specify the conditions under which level flight, turning flight, and accelerated entry stall characteristics should be demonstrated. Current rules contained in part 23 did not envision this high performance airplane with the associated high thrust-to-weight ratio. Special conditions are required to define stall characteristics demonstrations.

Vibration and Buffeting

The Sino Swearingen Model SJ30-2 will be operated at high altitudes where stall-Mach buffet encounters (small speed margin between stall and transonic flow buffet) are likely to occur, which is not presently addressed in part 23. A special condition is proposed that will require buffet onset tests and the inclusion of information in the Airplane Flight Manual (AFM) to provide guidance to the flightcrew. This information will enable the flightcrew to plan flight operations that will maximize the maneuvering capability during high altitude cruise flight and preclude intentional operations exceeding the boundary of perceptible buffet. Buffeting is considered to be a warning to the pilot that the airplane is approaching an undesirable and eventually dangerous flight regime, that is, stall buffeting, high speed buffeting or maneuvering (load factor) buffeting. In straight flight, therefore, such buffet warning should not occur at any normal operating speed up to the maximum operating limit speed, V_{MO}/M_{MO} .

High Speed Characteristics and Maximum Operating Limit Speed

The Sino Swearingen Model SJ30-2 will be operated at high altitude and high speeds and the proposed operating envelope includes areas in which Mach effects, which have not been considered in part 23, may be significant. The anticipated low drag of the airplane and the proposed operating envelope are representative of the conditions not envisioned by the existing part 23 regulations. These conditions may degrade the ability of the flightcrew to promptly recover from inadvertent excursions beyond maximum operating speeds. The ability to pull a positive load factor is needed to ensure, during recovery from upset, that the airplane speed does not continue to increase to a value where recovery may not be achievable by the average pilot or flightcrew.

Additionally, to allow the aircraft designer to conservatively design to higher speeds than may be operationally required for the airplane, the concept of V_{DF}/M_{DF} , the highest demonstrated flight speed for the type design, is appropriate for this airplane. This permits V_D/M_D the design dive speed, to be higher than the speed actually required to be demonstrated in flight. Accordingly, special conditions are proposed to allow determination of a maximum demonstrated flight speed and to relate the determination of V_{MO}/M_{MO} to the speed V_{DF}/M_{DF} .

Flight Flutter Tests

Flight flutter test special conditions are proposed to V_{DF}/M_{DF} rather than to V_D in keeping with the V_{DF}/M_{DF} concept.

Out-of-Trim Characteristics

High speed airplanes have experienced a number of upset incidents involving out-of-trim conditions. This is particularly true for swept-wing airplanes and airplanes with a trimmable stabilizer. Service experience has shown that out-of-trim conditions can occur in flight for various reasons and that the control and maneuvering characteristics of the airplane may be critical in recovering from upsets. The existing part 23 regulations do not address high speed out-of-trim conditions. Special conditions are proposed that test the out-of-trim flight characteristics by requiring the longitudinal trim control be displaced from the trimmed position by the amount resulting from the three-second movement of the trim system at this normal rate with no aerodynamic load, or the maximum mis-trim that the

autopilot can sustain in level flight in the high speed cruise condition, whichever is greater. The proposal would require the maneuvering characteristics, including stick force per g, be explored throughout a specified maneuver load factor speed envelope. The dive recovery characteristics of the aircraft in the out-of-trim condition specified would be investigated to determine that safe recovery can be made from the demonstrated flight dive speed V_{DF}/M_{DF} .

Pressure Vessel Integrity

Damage tolerance methods are proposed to be used to ensure pressure vessel integrity while operating at the higher altitudes instead of the 1/2 bay crack criterion used in some previous special conditions. Crack growth data are used to prescribe an inspection program that should detect cracks before an opening in the pressure vessel would allow rapid depressurization. Initial crack sizes for detection are determined under § 23.573. The cabin altitude after failure must not exceed the cabin altitude/time curve limits shown in Figures 3 and 4.

Flight Control System Integrity

The Sino Swearingen Model SJ30-2 will be operated at high altitude and speeds such that a reduction or loss of pitch, yaw, or roll control capability or response could preclude continued flight and landing within the design limitations of the airplane using normal pilot skill and strength. Consequently, a greater reliability of the fasteners in the flight control system is necessary than previously considered. Removable fasteners whose loss could result in the conditions described above are required to have dual locking devices.

Fuel System Protection During Collapse of Landing Gear

The SJ30-2 maximum fuel weight is 39 percent of the maximum weight. This percentage is typical of the turbofan powered business jet class of airplanes. Part 23 did not envision that the applicable airplane designs would have such a large fraction of maximum weight as fuel. Part 23 does not contain fuel system protection requirements during landing gear collapse, except for § 23.721, which pertains to commuter category airplanes that have a passenger seating configuration of 10 seats or more. In the SJ30-2 design, there is a large fuselage fuel tank and the placement of the engines on the aft fuselage requires that the fuel lines be routed through the fuselage, making the fuel lines more vulnerable to damage, or rupture, if the landing gear collapses. A

special condition is proposed based on 14 CFR part 25, § 25.721(a)(1) that is applicable to airplanes having a passenger seating configuration of nine seats, or fewer.

Oxygen System Equipment and Supply

Continuous flow passenger oxygen equipment is certified for use up to 40,000 feet; however, for rapid decompressions above 34,000 feet, reverse diffusion leads to low oxygen partial pressures in the lungs to the extent that a small percentage of passengers may lose useful consciousness at 35,000 feet even with the use of the continuous flow system. To prevent permanent physiological damage, the cabin altitude must not exceed 25,000 feet for more than 2 minutes. The maximum peak cabin altitude of 40,000 feet is consistent with the standards established for previous certification programs. In addition, at high altitudes the other aspects of decompression sickness have a significant detrimental effect on pilot performance (for example, a pilot can be incapacitated by internal expanding gases).

Decompression above the 37,000 foot limit depicted in Figure 4 approaches the physiological limits of the average person; therefore, every effort must be made to provide the pilots with adequate oxygen equipment to withstand these severe decompressions. Reducing the time interval between pressurization failure and the time the pilots receive oxygen will provide a safety margin against being incapacitated and can be accomplished by the use of mask-mounted regulators. The proposed special condition, therefore, would require pressure demand masks with mask-mounted regulators for the flightcrew. This combination of equipment will provide the best practical protection for the failures covered by this special conditions and for improbable failures not covered by the special conditions, provided the cabin altitude is limited.

Airspeed Indicating System

To maintain a level of safety consistent with that applied to previous part 23 jet airplanes, and to be consistent with the establishment of speed schedule performance requirements, it is appropriate to establish applicable requirements for determining and providing airspeed indicating system calibration information. Additionally, it is appropriate to establish special conditions requiring protection of the pitot tube from malfunctions associated with icing conditions. Current standards

in part 23 did not envision this type of airplane and the associated airspeed indicating system requirements. Special conditions are proposed to establish airspeed indicating system calibration and pitot tube ice protection requirements applicable to transport category jet airplanes.

Static Pressure System

To maintain a level of safety consistent with that applied to previous part 23 jet airplanes, and to be consistent with the establishment of speed schedule performance requirements, it is appropriate to establish applicable requirements for providing static pressure system calibration information in the AFM. Since aircraft of this type are frequently equipped with devices to correct the altimeter indication, it is also appropriate to establish requirements to ensure the continued availability of altitude information where such a device malfunctions. Current standards in part 23 did not envision this type of airplane and the associated static pressure requirements.

Minimum Flightcrew

The Sino Swearingen Model SJ30-2 operates at high altitudes and speeds not envisioned in part 23 and must be flown in a precise speed schedule to achieve flight manual takeoff and landing distances. Therefore, it is appropriate to specify workload considerations. Special conditions are proposed to specify the items to be considered in workload determination.

Airplane Flight Manual (AFM) Information

To be consistent with the performance special conditions, it is also necessary to require the maximum takeoff and landing weights, takeoff distances, and associated atmospheric conditions be made available to the pilot in the AFM and that the airplane be operated within its performance capabilities. Special conditions are proposed to add maximum takeoff weights, maximum landing weights, and minimum takeoff distances as limitations in the AFM. Additionally, special conditions are proposed to add takeoff flight path and procedures necessary to achieve the performance in the limitations section as information in the AFM.

Conclusion

In view of the design features discussed for the SJ30-2 Model airplane, the following special conditions are proposed. This action is not a rule of general applicability and affects only the model/series of airplane

identified in these final special conditions.

List of Subjects in 14 CFR Part 23

Aircraft, Aviation safety, Signs and symbols.

Citation

The authority citation for these Special Conditions is as follows:

Authority: 49 U.S.C. 106(g); 40113, and 44701; 14 CFR 21.16 and 101; and 14 CFR 11.28 and 11.29.

The Proposed Special Conditions

Accordingly, pursuant to the authority delegated to me by the Administrator, the Federal Aviation Administration proposes the following special conditions as part of the type certification basis for the Sino Swearingen Model SJ30-2 airplane:

1. *Protection of Electrical and Electronic Systems From High Intensity Radiated Field*

Each system that performs critical functions must be designed and installed to ensure that the operation and operational capabilities of these systems to perform critical functions are not adversely affected when the airplane is exposed to high intensity radiated fields external to the airplane.

2. *Performance: General*

In addition to the requirements of § 23.45, the following apply:

(a) Unless otherwise prescribed, the applicant must select the takeoff, enroute, approach, and landing configurations for the airplane.

(b) The airplane configurations may vary with weight, altitude, and temperature, to the extent that they are compatible with the operating procedures required by paragraph (c) of this special condition.

(c) Unless otherwise prescribed, in determining the accelerate-stop distances, takeoff flight paths, takeoff distances, and landing distances, changes in the airplane's configuration, speed, power, and thrust, must be made in accordance with procedures established by the applicant for operation in service.

(d) Procedures for the execution of balked landings and discontinued approaches associated with the conditions prescribed in special conditions 10(d) and 12 must be established.

(e) The procedures established under paragraphs (c) and (d) of this special condition must:

(1) Be able to be consistently executed in service by crews of average skill;

(2) Use methods or devices that are safe and reliable; and

(3) Include allowance for any time delays, in the execution of the procedures, that may reasonably be expected in service.

3. *Takeoff*

Instead of complying with § 23.53, the following apply:

(a) In special conditions 4, 5, 6, and 7, the takeoff speeds, the accelerate-stop distance, the takeoff path, the takeoff distance, and takeoff run described must be determined:

(1) At each weight, altitude, and ambient temperature within the operation limits selected by the applicant; and

(2) In the selected configuration for takeoff.

(b) No takeoff made to determine the data required by this section may require exceptional piloting skill or alertness.

(c) The takeoff data must be based on a smooth, dry, hard-surfaced runway.

(d) The takeoff data must include, within the established operational limits of the airplane, the following operational correction factors:

(1) Not more than 50 percent of nominal wind components along the takeoff path opposite to the direction of takeoff, and not less than 150 percent of nominal wind components along the takeoff path in the direction of takeoff.

(2) Effective runway gradients.

4. *Takeoff Speeds*

Instead of compliance with § 23.51, the following apply:

(a) V_1 must be established in relation to V_{EF} , as follows:

(1) V_{EF} is the calibrated airspeed at which the critical engine is assumed to fail. V_{EF} must be selected by the applicant, but may not be less than V_{MCG} determined under § 23.149(f).

(2) V_1 , in terms of calibrated airspeed, is the takeoff decision speed selected by the applicant; however, V_1 may not be less than V_{EF} plus the speed gained with the critical engine inoperative during the time interval between the instant at which the critical engine failed and the instant at which the pilot recognizes and reacts to the engine failure, as indicated by the pilot's application of the first retarding means during the accelerate-stop test.

(b) $V_{2\ min}$, in terms of calibrated airspeed, may not be less than the following:

(1) $1.2 V_{S1}$

(2) 1.10 times V_{MC} established under § 23.149.

(c) V_2 , in terms of calibrated airspeed, must be selected by the applicant to provide at least the gradient of climb required by special condition 10,

paragraph (b), but may not be less than the following:

- (1) V_2 min, and
- (2) V_R plus the speed increment attained (in accordance with special condition 6(c)(2)) before reaching a height of 35 feet above the takeoff surface.
- (d) V_{MU} is the calibrated airspeed at and above which the airplane can safely lift off the ground and continue the takeoff. V_{MU} speeds must be selected by the applicant throughout the range of thrust-to-weight ratios to be certified. These speeds may be established from free-air data if these data are verified by ground takeoff tests.
- (e) V_R , in terms of calibrated airspeed, must be selected in accordance with the following conditions of paragraphs (e)(1) through (e)(4) of this special condition:
 - (1) V_R may not be less than the following:
 - (i) V_1 ;
 - (ii) 105 percent of V_{MC} ;
 - (iii) The speed (determined in accordance with special condition 6, paragraph (c)(2)) that allows reaching V_2 before reaching a height of 35 feet above the takeoff surface; or
 - (iv) A speed that, if the airplane is rotated at its maximum practicable rate, will result in a V_{LOF} of not less than 110 percent of V_{MU} in the all-engines-operating condition and not less than 105 percent of V_{MU} determined at the thrust-to-weight ratio corresponding to the one-engine-inoperative condition.
 - (2) For any given set of conditions (such as weight, configuration, and temperature), a single value of V_R , obtained in accordance with this special condition, must be used to show compliance with both the one-engine-inoperative and the all-engines-operating takeoff provisions.
 - (3) It must be shown that the one-engine-inoperative takeoff distance, using a rotation speed of 5 knots less than V_R , established in accordance with paragraphs (e)(1) and (e)(2) of this special condition, does not exceed the corresponding one-engine-inoperative takeoff distance using the established V_R . The takeoff distances must be determined in accordance with special condition 7, paragraph (a)(1).
 - (4) Reasonably expecting variations in service from the established takeoff procedures for the operation of the airplane (such as over-rotation of the airplane and out-of-trim conditions) may not result in unsafe flight characteristics or in marked increases in the scheduled takeoff distances established in accordance with special condition 7.

(f) V_{LOF} is the calibrated airspeed at which the airplane first becomes airborne.

5. Accelerate-Stop Distance

In the absence of specific accelerate-stop distance requirements, the following apply:

- (a) The accelerate-stop distance is the sum of the distances necessary to—
 - (1) Accelerate the airplane from a standing start to V_{EF} with all engines operating;
 - (2) Accelerate the airplane from V_{EF} to V_1 , assuming that the critical engine fails at V_{EF} ; and
 - (3) Come to a full stop from the point at which V_1 is reached assuming that, in the case of engine failure, the pilot has decided to stop as indicated by application of the first retarding means at the speed V_1 .
- (b) Means other than wheel brakes may be used to determine the accelerate-stop distance if that means—
 - (1) Is safe and reliable;
 - (2) Is used so that consistent results can be expected under normal operating conditions; and
 - (3) Is such that exceptional skill is not required to control the airplane.
- (c) The landing gear must remain extended throughout the accelerate-stop distance.

6. Takeoff Path

In the absence of specific takeoff path requirements, the following apply:

- (a) The takeoff path extends from a standing start to a point in the takeoff at which the airplane is 1,500 feet above the takeoff surface, or at which the transition from the takeoff to the enroute configuration is completed and a speed is reached at which compliance with special condition 10, paragraph (c), is shown, whichever point is higher. In addition the following apply:
 - (1) The takeoff path must be based on procedures prescribed in special condition 2.
 - (2) The airplane must be accelerated on the ground to V_{EF} , at which point the critical engine must be made inoperative and remain inoperative for the rest of the takeoff; and
 - (3) After reaching V_{EF} , the airplane must be accelerated to V_2 .
- (b) During the acceleration to speed V_2 , the nose gear may be raised off the ground at a speed not less than V_R . However, landing gear retraction may not begin until the airplane is airborne.
- (c) During the takeoff path determination, in accordance with paragraphs (a) and (b) of this special condition, the following apply:
 - (1) The slope of the airborne part of the takeoff path must be positive at each point;

(2) The airplane must reach V_2 before it is 35 feet above the takeoff surface and must continue at a speed as close as practical to, but not less than, V_2 until it is 400 feet above the takeoff surface;

(3) At each point along the takeoff path, starting at the point at which the airplane reaches 400 feet above the takeoff surface, the available gradient of climb may not be less than 1.2 percent;

(4) Except for gear retraction, the airplane configuration may not be changed, and no change in power or thrust that requires action by the pilot may be made, until the airplane is 400 feet above the takeoff surface.

(d) The takeoff path must be determined by a continuous demonstrated takeoff or by synthesis from segments. If the takeoff path is determined by the segmental method, the following apply:

- (1) The segments must be clearly defined and must be related to the distinct changes in the configuration, speed, and power or thrust;
- (2) The weight of the airplane, the configuration, and the power or thrust must be constant throughout each segment and must correspond to the most critical condition prevailing in the segment;
- (3) The flight path must be based on the airplane's performance without ground effect; and
- (4) The takeoff path data must be checked by continuous demonstrated takeoffs, up to the point at which the airplane is out of ground effect and its speed is stabilized, to ensure that the path is conservative relative to the continuous path.

Note: The airplane is considered to be out of the ground effect when it reaches a height equal to its wing span.

7. Takeoff Distance and Takeoff Run

In the absence of specific takeoff distance and takeoff run requirements, the following apply:

- (a) Takeoff distance is the greater of the following:
 - (1) The horizontal distance along the takeoff path from the start of the takeoff to the point at which the airplane is 35 feet above the takeoff surface, determined under special condition 6; or
 - (2) 115 percent of the horizontal distance along the takeoff path, with all engines operating, from the start of the takeoff to the point at which the airplane is 35 feet above the takeoff surface, as determined by a procedure consistent with special condition 6.
- (b) If the takeoff distance includes a clear way, the takeoff run is the greater of:

(1) The horizontal distance along the takeoff path from the start of the takeoff to a point equidistant between the point at which V_{LOF} is reached and the point at which the airplane is 35 feet above the takeoff surface, as determined under special condition 6; or

(2) 115 percent of the horizontal distance along the takeoff path, with all engines operating, from the start of the takeoff to a point equidistant between the point at which V_{LOF} is reached and the point at which the airplane is 35 feet above the takeoff surface, determined by a procedure consistent with special condition 6.

8. Takeoff Flight Path

In the absence of specific takeoff flight path requirements, the following apply:

(a) The takeoff flight path begins 35 feet above the takeoff surface at the end of the takeoff distance determined in accordance with special condition 7.

(b) The net takeoff flight path data must be determined so that they represent the actual takeoff flight paths (determined in accordance with special condition 6 and with paragraph (a) of this special condition) reduced at each point by a gradient of climb equal to 0.8 percent.

(c) The prescribed reduction in climb gradient may be applied as an equivalent reduction in acceleration along that part of the takeoff flight path at which the airplane is accelerated in level flight.

9. Climb: General

Instead of compliance with § 23.63, the following applies: Compliance with the requirements of special conditions 10 and 12 must be shown at each weight, altitude, and ambient temperature within the operational limits established for the airplane and with the most unfavorable center of gravity for each configuration.

10. Climb: One Engine Inoperative

Instead of compliance with § 23.67, the following apply:

(a) Takeoff; landing gear extended. In the critical takeoff configuration existing along the flight path (between the points at which the airplane reaches V_{LOF} and at which the landing gear is fully retracted) and in the configuration used in special condition 6 without ground effect, unless there is a more critical power operating condition existing later along the flight path before the point at which the landing gear is fully retracted, the steady gradient of climb must be positive at V_{LOF} and with the following:

(1) The critical engine inoperative and the remaining engines at the power or thrust available when retraction of the

landing gear begins in accordance with special condition 6, and

(2) The weight equal to the weight existing when retraction of the landing gear begins, determined under special condition 6.

(b) Takeoff; landing gear retracted. In the takeoff configuration existing at the point of the flight path at which the landing gear is fully retracted and in the configuration used in special condition 6, without ground effect, the steady gradient of climb may not be less than 2.4 percent at V_2 and with the following:

(1) The critical engine inoperative, the remaining engines at the takeoff power or thrust available at the time the landing gear is fully retracted, determined under special condition 6 unless there is a more critical power operating condition existing later along the flight path but before the point where the airplane reaches a height of 400 feet above the takeoff surface; and

(2) The weight equal to the weight existing when the airplane's landing gear is fully retracted, determined under special condition 6.

(c) Final takeoff. In the enroute configuration at the end of the takeoff path, determined in accordance with special condition 6, the steady gradient of climb may not be less than 1.2 percent at not less than $1.25 V_S$ and with the following:

(1) The critical engine inoperative and the remaining engines at the available maximum continuous power or thrust; and

(2) The weight equal to the weight existing at the end of the takeoff path, determined under special condition 6.

(d) Approach. In the approach configuration corresponding to the normal all-engines-operating procedure in which V_S for this configuration does not exceed 110 percent of the V_S for the related landing configuration, the steady gradient of climb may not be less than 2.1 percent with the following:

(1) The critical engine inoperative, the remaining engine at the available in-flight takeoff power or thrust;

(2) The maximum landing weight; and

(3) A climb speed established in connection with normal landing procedures, but not exceeding $1.5 V_S$.

11. Landing

Instead of compliance with § 23.75, the following apply:

(a) The horizontal distance necessary to land and to come to a complete stop from a point 50 feet above the landing surface must be determined (for each weight, altitude, temperature, and wind within the operational limits established by the applicant for the airplane), as follows:

(1) The airplane must be in the landing configuration.

(2) A steady approach at a gradient of descent not greater than 5.2 percent (3 degrees), with an airspeed of not less than V_{REF} , determined in accordance with § 23.73(b), must be maintained down to the 50-foot height.

(3) Changes in configuration, power or thrust, and speed, must be made in accordance with the established procedures for service operation.

(4) The landing must be made without excessive vertical acceleration, tendency to bounce, nose over, ground loop, or porpoise.

(5) The landings may not require exceptional piloting skill or alertness.

(6) It must be shown that a safe transition to the balked landing conditions of special condition 12 can be made from the conditions that exist at the 50-foot height.

(b) The landing distance must be determined on a level, smooth, dry, hard-surfaced runway. In addition, the following apply:

(1) The brakes may not be used so as to cause excessive wear of brakes or tires; and

(2) Means other than wheel brakes may be used if that means is as follows:

(i) Is safe and reliable;

(ii) Is used so that consistent results can be expected in service; and

(iii) Is such that exceptional skill is not required to control the airplane.

(c) The landing distance data must include correction factors for not more than 50 percent of the nominal wind components along the landing path opposite to the direction of landing and not less than 150 percent of the nominal wind components along the landing path in the direction of landing.

(d) If any device is used that depends on the operation of any engine, and if the landing distance would be noticeably increased when a landing is made with that engine inoperative, the landing distance must be determined with that engine inoperative unless the use of compensating means will result in a landing distance not more than that with each engine operating.

12. Balked Landing

Instead of compliance with § 23.77, the following apply:

In the landing configuration, the steady gradient of climb may not be less than 3.2 percent with the following:

(a) The engines at the power or thrust that is available eight seconds after initiation of movement of the power or thrust controls from the minimum flight idle to the inflight takeoff position; and

(b) A climb speed of not more than V_{REF} as defined in § 23.73(a).

13. Stall Speed

Instead of compliance with § 23.49, the following apply:

(a) V_S is the calibrated stalling speed, or the minimum steady flight speed, in knots, at which the airplane is controllable, with—

(1) Zero thrust at the stalling speed, or, if the resultant thrust has no appreciable effect on the stalling speed, with engines idling and throttles closed;

(2) The weight used when V_S is being used as a factor to determine compliance with a required performance standard; and

(3) The most unfavorable center of gravity allowable.

(b) The stalling speed V_S is the minimum speed obtained as follows:

(1) Trim the airplane for straight flight at any speed not less than $1.2 V_S$ or more than $1.4 V_S$. At a speed sufficiently above the stall speed to ensure steady conditions, apply the elevator control at a rate so that the airplane speed reduction does not exceed one knot per second.

(2) Meet the flight characteristics provisions of special condition 19.

14. Trim

Instead of compliance with § 23.161, the following apply:

(a) General. Each airplane must meet the trim requirements of this special condition after being trimmed, and without further pressure upon or movement of the primary controls or their corresponding trim controls by the pilot or the automatic pilot.

(b) Lateral and directional trim. The airplane must maintain lateral and directional trim with the most adverse lateral displacement of the center of gravity within the relevant operating limitations during normally expected conditions of operation (including operation at any speed from $1.4 V_{S1}$ to V_{MO}/M_{MO} .)

(c) Longitudinal trim. The airplane must maintain longitudinal trim during the following:

(1) A climb with maximum continuous power at a speed not more than $1.4 V_{S1}$, with the landing gear retracted, and the flaps in the following positions:

- (i) Retracted, and
- (ii) In the takeoff position.

(2) A power approach with a 3 degree angle of descent, the landing gear extended, and with the following:

- (i) The wing flaps retracted and at a speed of $1.4 V_{S1}$; and
- (ii) The applicable airspeed and flap position used in showing compliance with special condition 11.

(3) Level flight at any speed from $1.4 V_{S1}$ to V_{MO}/M_{MO} with the landing gear

and flaps retracted, and from $1.4 V_{S1}$ to VLE with the landing gear extended.

(d) Longitudinal, directional, and lateral trim. The airplane must maintain longitudinal, directional, and lateral trim (for the lateral trim, the angle of bank may not exceed five degrees) at $1.4 V_{S1}$ during climbing flight with the following:

- (1) The critical engine inoperative;
- (2) The remaining engine at maximum continuous power or thrust; and
- (3) The landing gear and flaps retracted.

15. Static Longitudinal Stability

Instead of compliance with § 23.173, the following apply:

Under the conditions specified in special condition 16, the characteristics of the elevator control forces (including friction) must be as follows:

(a) A pull must be required to obtain and maintain speeds below the specified trim speed, and a push must be required to obtain and maintain speeds above the specified trim speed. This must be shown at any speed that can be obtained except speeds higher than the landing gear or wing flap operating limit speeds or V_{FC}/M_{FC} , whichever is appropriate, or lower than the minimum speed for steady unstalled flight.

(b) The airspeed must return to within 10 percent of the original trim speed for the climb, approach, and landing conditions specified in special condition 16, paragraph (a), (c), and (d), and must return to within 7.5 percent of the original trim speed for the cruising condition specified in special condition 16, paragraph (b), when the control force is slowly released from any speed within the range specified in paragraph (a) of this special condition.

(c) The average gradient of the stable slope of the stick force versus speed curve may not be less than 1 pound for each 6 knots.

(d) Within the free return speed range specified in paragraph (b) of this special condition, it is permissible for the airplane, without control forces, to stabilize on speeds above or below the desired trim speeds if exceptional attention on the part of the pilot is not required to return to and maintain the desired trim speed and altitude.

16. Demonstration of Static Longitudinal Stability

Instead of compliance with § 23.175, static longitudinal stability must be shown as follows:

(a) Climb. The stick force curve must have a stable slope at speeds between 85 and 115 percent of the speed at which the airplane—

(1) Is trimmed, with—

- (i) Wing flaps retracted;
- (ii) Landing gear retracted;
- (iii) Maximum takeoff weight; and
- (iv) The maximum power or thrust selected by the applicant as an operating limitation for use during climb; and

(2) Is trimmed at the speed for best rate of climb except that the speed need not be less than $1.4 V_{S1}$.

(b) Cruise. Static longitudinal stability must be shown in the cruise condition as follows:

(1) With the landing gear retracted at high speed, the stick force curve must have a stable slope at all speeds within a range which is the greater of 15 percent of the trim speed plus the resulting free return speed range, or 50 knots plus the resulting free return speed range, above and below the trim speed (except that the speed range need not include speeds less than $1.4 V_{S1}$, nor speeds greater than V_{FC}/M_{FC} , nor speeds that require a stick force of more than 50 pounds), with—

- (i) The wing flaps retracted;
- (ii) The center of gravity in the most adverse position;
- (iii) The most critical weight between the maximum takeoff and maximum landing weights;
- (iv) The maximum cruising power selected by the applicant as an operating limitation, except that the power need not exceed that required at V_{MO}/M_{MO} ; and

(v) The airplane trimmed for level flight with the power required in paragraph (b)(1)(iv) of this special condition.

(2) With the landing gear retracted at low speed, the stick force curve must have a stable slope at all speeds within a range which is the greater of 15 percent of the trim speed plus the resulting free return speed range, or 50 knots plus the resulting free return speed range, above and below the trim speed (except that the speed range need not include speeds less than $1.4 V_{S1}$, nor speeds greater than the minimum speed of the applicable speed range prescribed in paragraph (b)(1), nor speeds that require a stick force of more than 50 pounds), with—

- (i) Wing flaps, center of gravity position, and weight as specified in paragraph (b)(1) of this special condition;

(ii) Power required for level flight at a speed equal to $(V_{MO} + 1.4 V_{S1})/2$; and

(iii) The airplane trimmed for level flight with the power required in paragraph (b)(2)(ii) of this special condition.

(3) With the landing gear extended, the stick force curve must have a stable slope at all speeds within a range which

is the greater of 15 percent of the trim speed plus the resulting free return speed range, or 50 knots plus the resulting free return speed range, above and below the trim speed (except that the speed range need not include speeds less than $1.4 V_{S1}$, nor speeds greater than V_{LE} , nor speeds that require a stick force of more than 50 pounds), with—

(i) Wing flap, center of gravity position, and weight as specified in paragraph (b)(1) of this section;

(ii) The maximum cruising power selected by the applicant as an operating limitation, except that the power need not exceed that required for level flight at V_{LE} ; and

(iii) The aircraft trimmed for level flight with the power required in paragraph (b)(3)(ii) of this section.

(c) Approach. The stick force curve must have a stable slope at speeds between $1.1 V_{S1}$ and $1.8 V_{S1}$, with—

(1) Wing flaps in the approach position;

(2) Landing gear retracted;

(3) Maximum landing weight; and

(4) The airplane trimmed at $1.4 V_{S1}$ with enough power to maintain level flight at this speed.

(d) Landing. The stick force curve must have a stable slope, and the stick force may not exceed 80 pounds, at speeds between $1.1 V_{S0}$ and $1.3 V_{S0}$ with—

(1) Wing flaps in the landing position;

(2) Landing gear extended;

(3) Maximum landing weight;

(4) Power or thrust off on the engines;

and

(5) The airplane trimmed at $1.4 V_{S0}$ with power or thrust off.

17. Static Directional and Lateral Stability

Instead of compliance with § 23.177, the following apply:

(a) The static directional stability (as shown by the tendency to recover from a skid with the rudder free) must be positive for any landing gear and flap position, and it must be positive for any symmetrical power condition to speeds from $1.2 V_{S1}$ up to V_{FE} , V_{LE} , or V_{FC}/M_{FC} (as appropriate).

(b) The static lateral stability (as shown by the tendency to raise the low wing in a sideslip with the aileron controls free and for any landing gear position and flap position, and for any symmetrical power conditions) may not be negative at any airspeed (except speeds higher than V_{FE} or V_{LE} , when appropriate) in the following airspeed ranges:

(1) From $1.2 V_{S1}$ to V_{MO}/M_{MO} .

(2) From V_{MO}/M_{MO} to V_{FC}/M_{FC} , unless the Administrator finds that the divergence is—

(i) Gradual;

(ii) Easily recognizable by the pilot; and

(iii) Easily controllable by the pilot.

(c) In straight, steady, sideslips (unaccelerated forward slips) the aileron and rudder control movement and forces must be substantially proportional to the angle of the sideslip. The factor of proportionality must lie between limits found necessary for safe operation throughout the range of sideslip angles appropriate to the operation of the airplane. At greater angles, up to the angle at which full rudder control is used or when a rudder pedal force of 180 pounds is obtained, the rudder pedal forces may not reverse and increased rudder deflection must produce increased angles of sideslip. Unless the airplane has a yaw indicator, there must be enough bank accompanying sideslipping to clearly indicate any departure from steady unyawed flight.

18. Stall Demonstration

Instead of compliance with § 23.201, the following apply:

(a) Stalls must be shown in straight flight and in 30 degree banked turns with—

(1) Power off; and

(2) The power necessary to maintain level flight at $1.6 V_{S1}$ (where V_{S1} corresponds to the stalling speed with flaps in the approach position, the landing gear retracted, and maximum landing weight).

(b) In each condition required by paragraph (a) of this section, it must be possible to meet the applicable requirements of special condition 19 with—

(1) Flaps, landing gear, and deceleration devices in any likely combination of positions approved for operation;

(2) Representative weights within the range for which certification is requested;

(3) The most adverse center of gravity for recovery; and

(4) The airplane trimmed for straight flight at the speed prescribed in special condition 13).

(c) The following procedures must be used to show compliance with special condition 19;

(1) Starting at a speed sufficiently above the stalling speed to ensure that a steady rate of speed reduction can be established, apply the longitudinal control so that the speed reduction does not exceed one knot per second until the airplane is stalled.

(2) In addition, for turning flight stalls, apply the longitudinal control to achieve airspeed deceleration rates up to 3 knots per second.

(3) As soon as the airplane is stalled, recover by normal recovery techniques.

(d) The airplane is considered stalled when the behavior of the airplane gives the pilot a clear and distinctive indication of an acceptable nature that the airplane is stalled. Acceptable indications of a stall, occurring either individually or in combination, are—

(1) A nose-down pitch that cannot be readily arrested;

(2) Buffeting, of a magnitude and severity that is a strong and effective deterrent to further speed reduction; or

(3) The pitch control reaches the aft stop and no further increase in pitch attitude occurs when the control is held full aft for a short time before recovery is initiated.

19. Stall Characteristics

Instead of compliance with § 23.203, the following applies:

(a) It must be possible to produce and to correct roll and yaw by unreversed use of the aileron and rudder controls, up to the time the airplane is stalled. No abnormal nose up pitching may occur. The longitudinal control force must be positive up to and throughout the stall. In addition, it must be possible to promptly prevent stalling and to recover from a stall by normal use of the controls.

(b) For level wing stalls, the roll occurring between the stall and the completion of the recovery may not exceed approximately 20 degrees.

(c) For turning flight stalls, the action of the airplane after the stall may not be so violent or extreme as to make it difficult, with normal piloting skill, to effect a prompt recovery and to regain control of the airplane. The maximum bank angle that occurs during the recovery may not exceed—

(1) Approximately 60 degrees in the original direction of the turn, or 30 degrees in the opposite direction, for deceleration rates up to 1 knot per second; and

(2) Approximately 90 degrees in the original direction of the turn, or 60 degrees in the opposite direction, for deceleration rates in excess of 1 knot per second.

20. Stall Warning

Instead of compliance with § 23.207, the following applies:

(a) Stall warning with sufficient margin to prevent inadvertent stalling with the flaps and landing gear in any normal position must be clear and distinctive to the pilot in straight and turning flight.

(b) The warning may be furnished either through the inherent aerodynamic qualities of the airplane or by a device

that will give clearly distinguishable indications under expected conditions of flight. However, a visual stall warning device that requires the attention of the crew within the cockpit is not acceptable by itself. If a warning device is used, it must provide a warning in each of the airplane configurations prescribed in paragraph (a) of this special condition at the speed prescribed in paragraph (c) of this special condition.

(c) The stall warning must begin at a speed exceeding the stalling speed (i.e., the speed at which the airplane stalls or the minimum speed demonstrated, whichever is applicable under the provisions of special condition 18, paragraph (d)) by seven percent or at any lesser margin if the stall warning has enough clarity, duration, distinctiveness, or similar properties.

21. *Vibration and Buffeting*

Instead of compliance with § 23.251, the following apply:

(a) The airplane must be designed to withstand any vibration and buffeting that might occur in any likely operating condition. This must be shown by calculations, resonance tests, or other tests found necessary by the Administrator.

(b) Each part of the airplane must be shown in flight to be free from excessive vibration, under any appropriate speed and power conditions up to V_{DF}/M_{DF} . The maximum speeds shown must be used in establishing the operating limitations of the airplane in accordance with special condition 36.

(c) Except as provided in paragraph (d) of this special condition, there may be no buffeting condition in normal flight, including configuration changes during cruise, severe enough to interfere with the control of the airplane, to cause excessive fatigue to the flightcrew, or to cause structural damage. Stall warning buffeting within these limits is allowable.

(d) There may be no perceptible buffeting condition in the cruise configuration in straight flight at any speed up to V_{MO}/M_{MO} , except that stall warning buffeting is allowable.

(e) With the airplane in the cruise configuration, the positive maneuvering load factors at which the onset of perceptible buffeting occurs must be determined for the ranges of airspeed or Mach Number, weight, and altitude for which the airplane is to be certified. The envelopes of load factor, speed, altitude, and weight must provide a sufficient range of speeds and load factors for normal operations. Probable inadvertent excursions beyond the boundaries of the

buffet onset envelopes may not result in unsafe conditions.

22. *High Speed Characteristics*

Instead of compliance with § 23.253, the following apply:

(a) Speed increase and recovery characteristics. The following speed increase and recovery characteristics must be met:

(1) Operating conditions and characteristics likely to cause inadvertent speed increases (including upsets in pitch and roll) must be simulated with the airplane trimmed at any likely cruise speed up to V_{MO}/M_{MO} . These conditions and characteristics include gust upsets, inadvertent control movements, low stick force gradient in relation to control friction, passenger movement, leveling off from climb, and descent from mach to airspeed limit altitudes.

(2) Allowing for pilot reaction time after effective inherent or artificial speed warning occurs, it must be shown that the airplane can be recovered to a normal attitude and its speed reduced to V_{MO}/M_{MO} without the following:

- (i) Exceptional piloting strength or skill;
- (ii) Exceeding V_D/M_D , or V_{DF}/M_{DF} , or the structural limitations; and
- (iii) Buffeting that would impair the pilot's ability to read the instruments or control the airplane for recovery.

(3) There may be no control reversal about any axis at any speed up to V_{DF}/M_{DF} with the airplane trimmed at V_{MO}/M_{MO} . Any tendency of the airplane to pitch, roll or yaw must be mild and readily controllable, using normal piloting techniques. When the airplane is trimmed at V_{MO}/M_{MO} , the slope of the elevator control force versus speed curve need not be stable at speeds greater than V_{FC}/M_{FC} , but there must be a push force at all speeds up to V_{DF}/M_{DF} and there must be no sudden or excessive reduction of elevator control force as V_{DF}/M_{DF} is reached.

(b) Maximum speed for stability characteristics. V_{FC}/M_{FC} . V_{FC}/M_{FC} is the maximum speed at which the requirements of special conditions 15, 16, 17, and § 23.181 must be met with the flaps and landing gear retracted. It may not be less than a speed midway between V_{MO}/M_{MO} and V_{DF}/M_{DF} except that, for altitudes where Mach number is the limiting factor, M_{FC} need not exceed the Mach number at which effective speed warning occurs.

23. *Flight Flutter Testing*

Instead of the term/speed V_D in § 23.629(b), use V_{DF}/M_{DF} .

24. *Out-of-Trim Characteristics*

In the absence of specific requirements for out-of-trim characteristics, the Sino Swearingen Model SJ30-2 must comply with the following:

(a) From an initial condition with the airplane trimmed at cruise speeds up to V_{MO}/M_{MO} , the airplane must have satisfactory maneuvering stability and controllability with the degree of out-of-trim in both the airplane nose-up and nose-down directions, which results from the greater of the following:

(1) A three-second movement of the longitudinal trim system at its normal rate for the particular flight condition with no aerodynamic load (or an equivalent degree of trim for airplanes that do not have a power-operated trim system), except as limited by stops in the trim system including those required by § 23.655(b) for adjustable stabilizers; or

(2) The maximum mis-trim that can be sustained by the autopilot while maintaining level flight in the high speed cruising condition.

(b) In the out-of-trim condition specified in paragraph (a) of this special condition, when the normal acceleration is varied from +1 g to the positive and negative values specified in paragraph (c) of this special condition, the following apply:

(1) The stick force versus g curve must have a positive slope at any speed up to and including V_{FC}/M_{FC} ; and

(2) At speeds between V_{FC}/M_{FC} and V_{DF}/M_{DF} , the direction of the primary longitudinal control force may not reverse.

(c) Except as provided in paragraph (d) and (e) of this special condition, compliance with the provisions of paragraph (a) of this special condition must be demonstrated in flight over the acceleration range as follows:

- (1) -1 g to +2.5 g; or
- (2) 0 g to 2.0 g, and extrapolating by an acceptable method to -1 g and +2.5 g.

(d) If the procedure set forth in paragraph (c)(2) of this special condition is used to demonstrate compliance and marginal conditions exist during flight test with regard to reversal of primary longitudinal control force, flight tests must be accomplished from the normal acceleration at which a marginal condition is found to exist to the applicable limit specified in paragraph (b)(1) of this special condition.

(e) During flight tests required by paragraph (a) of this special condition, the limit maneuvering load factors, prescribed in §§ 23.333(b) and 23.337, need not be exceeded. Also, the

maneuvering load factors associated with probable inadvertent excursions beyond the boundaries of the buffet onset envelopes determined under special condition 21, paragraph (e), need not be exceeded. In addition, the entry speeds for flight test demonstrations at normal acceleration values less than 1 g must be limited to the extent necessary to accomplish a recovery without exceeding V_{DF}/M_{DF} .

(f) In the out-of-trim condition specified in paragraph (a) of this special condition, it must be possible from an overspeed condition at V_{DF}/M_{DF} to produce at least 1.5 g for recovery by applying not more than 125 pounds of longitudinal control force using either the primary longitudinal control alone or the primary longitudinal control and the longitudinal trim system. If the longitudinal trim is used to assist in producing the required load factor, it must be shown at V_{DF}/M_{DF} that the longitudinal trim can be actuated in the airplane nose-up direction with the primary surface loaded to correspond to the least of the following airplane nose-up control forces:

(1) The maximum control forces expected in service, as specified in §§ 23.301 and 23.397.

(2) The control force required to produce 1.5 g.

(3) The control force corresponding to buffeting or other phenomena of such intensity that is a strong deterrent to further application of primary longitudinal control force.

25. Pressure Vessel Integrity

(a) The maximum extent of failure and pressure vessel opening that can be demonstrated to comply with special condition 31 (Pressurization) of these special conditions must be determined. It must be demonstrated by crack propagation and damage tolerance analysis supported by testing that a larger opening or a more severe failure than demonstrated will not occur in normal operations.

(b) Inspection schedules and procedures must be established to ensure that cracks and normal fuselage leak rates will not deteriorate to the extent that an unsafe condition could exist during normal operation.

(c) With regard to the fuselage structure design for cabin pressure capability above 45,000 feet, the pressure vessel structure, including doors and windows, must comply with § 23.365(d), using a factor of 1.67 instead of the 1.33 factor prescribed.

26. Fasteners

In addition to the requirements of § 23.607, the following apply to fasteners:

(a) Each removable bolt, screw, nut, pin, or their removable fastener must incorporate two separate locking devices if the following apply:

(1) Its loss could preclude continued flight and landing within the design limitations of the airplane using normal pilot skill and strength, or

(2) Its loss could result in reduction in pitch, yaw, or roll control capability or response below that required by subpart B of this chapter and these special conditions.

(b) The fasteners specified in paragraph (a) of this section and their locking devices may not be adversely affected by the environmental conditions associated with the particular installation.

27. Landing Gear

The main landing gear system must be designed so that if it fails due to overloads during takeoff or landing (assuming the overloads to act in the upward and aft directions), the failure mode is not likely to cause the spillage of enough fuel from any fuel system in the fuselage to constitute a fire hazard.

28. Ventilation

In addition to the requirements of § 23.831(b), the ventilation system must be designed to provide a sufficient amount of uncontaminated air to enable the crewmembers to perform their duties without undue discomfort or fatigue and to provide reasonable passenger comfort during normal operation conditions and in the event of any probable failure of any system on the airplane that would adversely affect the cabin ventilating air. For normal operations, crewmembers and passengers must be provided with at least 10 cubic feet of fresh air per minute per person, or the equivalent in filtered recirculated air, based on the volume and composition at the corresponding cabin pressure altitude of no more than 8,000 feet.

29. Air Conditioning

In addition to the requirements of § 23.831, cabin cooling systems must be designed to meet the following conditions during flight above 15,000 feet MSL:

(a) After any probable failure, the cabin temperature/time history may not exceed the values shown in Figure 1. During this time period, the humidity shall never exceed a level that corresponds to a water vapor pressure of

20mm Hg. Time = 0 minutes when the flightcrew recognizes the failure.

(b) After any improbable failure, the cabin temperature/time history may not exceed the values shown in Figure 2. During this time period, the humidity shall never exceed a level that corresponds to a water vapor pressure of 20mm Hg. Time = 0 minutes when the flightcrew recognizes the failure.

30. Pressurization

In addition to the requirements of § 23.841, the following apply—

(a) The pressurization system—which includes, for this purpose, bleed air, air conditioning, and pressure control systems—must prevent the cabin altitude from exceeding the cabin altitude-time history shown in Figure 3 after each of the following:

(1) Any probable malfunction or failure of the pressurization system. The existence of undetected, latent malfunctions or failures in conjunction with probable failures must be considered.

(2) Any single failure in the pressurization system, combined with the occurrence of a leak produced by a complete loss of a door seal element, or a fuselage leak through an opening having an effective area 2.0 times the effective area that produces the maximum permissible fuselage leak rate approved for normal operation, whichever produces a more severe leak.

(b) The cabin altitude-time history may not exceed that shown in Figure 4 after each of the following:

(1) The maximum pressure vessel opening resulting from an initially detectable crack propagating for a period encompassing four normal inspection intervals. Mid-panel cracks and cracks through skin-stringer and skin-frame combinations must be considered.

(2) The pressure vessel opening or duct failure resulting from probable damage (failure effect) while under maximum operating cabin pressure differential due to a tire burst, engine rotor burst, loss of antennas or stall warning vanes, or any probable equipment failure (bleed air, pressure control, air conditioning, electrical sources(s), etc.) that affects pressurization.

(3) Complete loss of thrust from all engines.

(c) In showing compliance with paragraphs (a) and (b) of this special condition (Pressurization), it may be assumed that an emergency descent is made by approved emergency procedure. A seventeen-second flightcrew recognition and reaction time must be applied between cabin altitude

warning and the initiation of an emergency descent.

Note: For the flight evaluation of the rapid descent, the test article must have the cabin volume representative of what is expected to be normal, such that Sino Swearingen must reduce the total cabin volume by that which would be occupied by the furnishings and total number of people.

31. Airspeed Indicating System

In addition to the requirements of § 23.1323, the following apply:

(a) The airspeed indicating system must be calibrated to determine the system error in flight and during the accelerate-takeoff ground run. The ground run calibration must be determined as follows:

(1) From 0.8 of the minimum value of V_1 to the maximum value of V_2 , considering the approved ranges of altitude and weight; and

(2) With the flaps and power settings corresponding to the values determined in the establishment of the takeoff path under special condition 6, assuming that the critical engine fails at the minimum value of V_1 .

(b) The information showing the relationship between IAS and CAS, determined in accordance with paragraph (a) of this special condition, must be shown in the Airplane Flight Manual.

32. Static Pressure System

In addition to the requirements of § 23.1325, the following apply:

(a) The altimeter system calibration required by § 23.1325(e) must be shown in the Airplane Flight Manual.

(b) If an altimeter system is fitted with a device that provides corrections to the altimeter indication, the device must be designed and installed in such manner that it can be by-passed when it malfunctions, unless an alternate altimeter system is provided. Each correction device must be fitted with a means for indicating the occurrence of reasonably probable malfunctions, including power failure, to the flightcrew. The indicating means must be effective for any cockpit lighting condition likely to occur.

33. Oxygen Equipment and Supply

(a) In addition to the requirements of § 23.1441(d), the following applies: A quick-donning oxygen mask system with a pressure-demand, mask mounted regulator must be provided for the flightcrew. It must be shown that each quick-donning mask can, with one hand and within 5 seconds, be placed on the face from its ready position, properly secured, sealed, and supplying oxygen upon demand.

(b) In addition to the requirements of § 23.1443, the following applies: A continuous flow oxygen system must be provided for the passengers.

(c) In addition to the requirements of § 23.1445, the following applies: If the flightcrew and passengers share a common source of oxygen, a means to separately reserve the minimum supply required by the flightcrew must be provided.

34. Maximum Operating Limit Speed

Instead of compliance with § 23.1505(c), the following applies: The maximum operating limit speed (V_{MO}/M_{MO} airspeed or Mach number, whichever is critical at a particular altitude) is a speed that may not be deliberately exceeded in any regime of flight (climb, cruise, or descent), unless a higher speed is authorized for flight test or pilot training operations. V_{MO}/M_{MO} must be established so that it is not greater than the design cruising speed, V_C , and so that it is sufficiently below V_D/M_D , or V_{DF}/M_{DF} , to make it highly improbable that the latter speeds will be inadvertently exceeded in operations. The speed margin between V_{MO}/M_{MO} and V_D/M_D , or V_{DF}/M_{DF} , may not be less than that determined under § 23.335(b) or found necessary during the flight tests conducted under special condition 22.

35. Minimum Flightcrew

Instead of compliance with § 23.1523, the following apply:

The minimum flightcrew must be established so that it is sufficient for safe operation considering:

(a) The workload on individual flightcrew members and each flightcrew member workload determination must consider the following:

- (1) Flight path control,
- (2) Collision avoidance,
- (3) Navigation,
- (4) Communications,
- (5) Operation and monitoring of all essential airplane systems,
- (6) Command decisions, and
- (7) The accessibility and ease of operation of necessary controls by the appropriate flightcrew member during all normal and emergency operations when at the flightcrew member station.

(b) The accessibility and ease of operation of necessary controls by the appropriate flightcrew member; and

(c) The kinds of operation authorized under § 23.1525.

36. Airplane Flight Manual

Instead of compliance with § 23.1581, the following applies:

(a) Furnishing information. An Airplane Flight Manual must be furnished with each airplane, and it must contain the following:

(1) Information required by special conditions 39, 40, and 41.

(2) Other information that is necessary for safe operation because of design, operating, or handling characteristics.

(3) Any limitation, procedure, or other information established as a condition of compliance with the applicable noise standards of Part 36 of this chapter.

(b) Approved Information. Each part of the manual listed in special conditions 39, 40, and 41, that is appropriate to the airplane, must be furnished, verified, and approved, and must be segregated, identified, and clearly distinguished from each unapproved part of that manual.

(c) Airplane Flight Manual. Each Airplane Flight Manual must include a table of contents if the complexity of the manual indicates a need for it.

(d) Airplane Flight Manual. Each page of the Airplane Flight Manual containing information prescribed in this section must be of a type that is not easily erased, disfigured, or misplaced, and is capable of being inserted in a manual provided by the applicant, or in a folder, or in any other permanent binder.

(e) Airplane Flight Manual. Provision must be made for stowing the Airplane Flight Manual in a suitable fixed container which is readily accessible to the pilot.

(f) Revisions and amendments. Each Airplane Flight Manual (AFM) must contain a means for recording the incorporation of revisions and amendments.

37. Operating Limitations

Instead of the requirements of § 23.1583, the following apply:

(a) Airspeed limitations. The following airspeed limitations and any other airspeed limitations necessary for safe operation must be furnished:

(1) The maximum operating limit speed, V_{MO}/M_{MO} , and a statement that this speed limit may not be deliberately exceeded in any regime of flight (climb, cruise, or descent) unless a higher speed is authorized for flight test or pilot training.

(2) If an airspeed limitation is based upon compressibility effects, a statement to this effect and information as to any symptoms, the probable behavior of the airplane, and the recommended recovery procedures.

(3) The maneuvering speed, V_O , and a statement that full application of rudder and aileron controls, as well as maneuvers that involve angles of attack

near the stall, should be confined to speeds below this value.

(4) The maximum speed for flap extension, V_{FE} , for the takeoff, approach, and landing positions.

(5) The landing gear operating speed or speeds, V_{LO} .

(6) The landing gear extended speed, V_{LE} if greater than V_{LO} , and a statement that this is the maximum speed at which the airplane can be safely flown with the landing gear extended.

(b) Powerplant limitations. The following information must be furnished:

(1) Limitations required by § 23.1521.

(2) Explanation of the limitations, when appropriate.

(3) Information necessary for marking the instruments, required by §§ 23.1549 through 23.1553.

(c) Weight and loading distribution. The weight and extreme forward and aft center of gravity limits required by §§ 23.23 and 23.25 must be furnished in the Airplane Flight Manual. In addition, all of the following information and the information required by § 23.1589 must be presented either in the Airplane Flight Manual or in a separate weight and balance control and loading document, which is incorporated by reference in the Airplane Flight Manual:

(1) The condition of the airplane and the items included in the empty weight, as defined in accordance with § 23.29.

(2) Loading instructions necessary to ensure loading of the airplane within the weight and center of gravity limits, and to maintain the loading within these limits in flight.

(d) Maneuvers. A statement that acrobatic maneuvers, including spins, are not authorized.

(e) Maneuvering flight load factors. The positive maneuvering limit load factors for which the structure is proven, described in terms of accelerations, and a statement that these accelerations limit the angle of bank in turns and limit the severity of pull-up maneuvers must be furnished.

(f) Flightcrew. The number and functions of the minimum flightcrew must be furnished.

(g) Kinds of operation. The kinds of operation (such as VFR, IFR, day, or night) and the meteorological conditions in which the airplane may or may not be used must be furnished. Any installed equipment that affects any operating limitation must be listed and identified as to operational function.

(h) Additional operating limitations must be established as follows:

(1) The maximum takeoff weights must be established as the weights at which compliance is shown with the applicable provisions of part 23

(including the takeoff climb provisions of special condition 10 (a) through (c) for altitudes and ambient temperatures).

(2) The maximum landing weights must be established as the weights at which compliance is shown with the applicable provisions of part 23 (including the approach climb and balked landing climb provisions of special conditions 10(d) and 12 for altitudes and ambient temperatures).

(3) The minimum takeoff distances must be established as the distances at which compliance is shown with the applicable provisions of part 23 (including the provisions of special conditions 5 and 7 for weights, altitudes, temperatures, wind components, and runway gradients).

(4) The extremes for variable factors (such as altitude, temperature, wind, and runway gradients) are those at which compliance with the applicable provision of part 23 and these special conditions is shown.

(i) Maximum operating altitude. The maximum altitude established under § 23.1527 must be furnished.

(j) Maximum passenger seating configuration. The maximum passenger seating configuration must be furnished.

38. Operating Procedures

Instead of the requirements of § 23.1585, the following applies:

(a) Information and instruction regarding the peculiarities of normal operations (including starting and warming the engines, taxiing, operation of wing flaps, slats, landing gear, speed brake, and the automatic pilot) must be furnished, together with recommended procedures for the following:

(1) Engine failure (including minimum speeds, trim, operation of the remaining engine, and operation of flaps);

(2) Restarting turbine engines in flight (including the effects of altitude);

(3) Fire, decompression, and similar emergencies;

(4) Use of ice protection equipment;

(5) Operation in turbulence (including recommended turbulence penetration airspeeds, flight peculiarities, and special control instructions);

(6) The demonstrated crosswind velocity and procedures and information pertinent to operation of the airplane in crosswinds.

(b) Information identifying each operating condition in which the fuel system independence prescribed in § 23.953 is necessary for safety must be furnished, together with instructions for placing the fuel system in a configuration used to show compliance with that section.

(c) For each airplane showing compliance with § 23.1353(g)(2) or

(g)(3), the operating procedures for disconnecting the battery from its charging source must be furnished.

(d) If the unusable fuel supply in any tank exceeds 5 percent of the tank capacity, or 1 gallon, whichever is greater, information must be furnished indicating that, when the fuel quantity indicator reads "zero" in level flight, any fuel remaining in the fuel tank cannot be used safely in flight.

(e) Information on the total quantity of usable fuel for each fuel tank must be furnished.

(f) The buffet onset envelopes determined under special condition 21 must be furnished. The buffet onset envelopes presented may reflect the center of gravity at which the airplane is normally loaded during cruise if corrections for the effect of different center of gravity locations are furnished.

39. Performance Information

Instead of the requirements of § 23.1587, the following applies:

(a) Each Airplane Flight Manual must contain information to permit conversion of the indicated temperature to free air temperature if other than a free air temperature indicator is used to comply with the requirements of § 23.1303(d).

(b) Each Airplane Flight Manual must contain the performance information computed under the applicable provisions of this part for the weights, altitudes, temperatures, wind components, and runway gradients, as applicable, within the operational limits of the airplane, and must contain the following:

(1) The conditions under which the performance information was obtained, including the speeds associated with the performance information.

(2) V_S determined in accordance with special condition 13.

(3) The following performance information (determined by extrapolation and computed for the range of weights between the maximum landing and maximum takeoff weights):

(i) Climb in the landing configuration.

(ii) Climb in the approach configuration.

(iii) Landing distance.

(4) Procedures established under special condition 2, paragraph (c), (d), and (e) that are related to the limitations and information required by paragraph (h) of special condition 39 and by this paragraph. These procedures must be in the form of guidance material, including any relevant limitations or information.

(5) An explanation of significant or unusual flight or ground handling characteristics of the airplane.

Issued in Kansas City, Missouri on
February 10, 1997.

Henry A. Armstrong,
Acting Manager, Small Airplane Directorate,
Aircraft Certification Service.

BILLING CODE 4910-13-P



