

("Department") regulations are to 19 CFR Part 351 (2002).

SUPPLEMENTARY INFORMATION:

Background

On July 31, 2001, a respondent in this proceeding, Jilin Pharmaceutical Import and Export Company, Jilin Pharmaceutical (U.S.A.) Inc., and Jilin Pharmaceutical Limited Company (collectively, "Jilin Pharmaceutical") notified the Department that in 1999, its corporate name changed to Jilin Henghe Pharmaceutical Company Ltd. ("Jilin Henghe"). On December 14, 2001, Jilin Pharmaceutical stated that during the period of review ("POR") of the concurrent administrative review (*see Initiation of Antidumping and Countervailing Duty Administrative Reviews and Requests for Revocation in Part*, 66 FR 43570 (August 20, 2001)), the export operations for subject merchandise, which were handled by Jilin Pharmaceutical Import and Export Company during the original investigation (*see Notice of Final Determination of Sales at Less than Fair Value: Bulk Aspirin from the People's Republic of China*, 65 FR 39598 (May 25, 2000) ("LTFV investigation")), were handled by the sales department for medicinal materials of Jilin Henghe. Jilin Pharmaceutical also stated that during the POR, subject merchandise was produced at the same facilities that Jilin Pharmaceutical used to produce subject merchandise during the LTFV investigation. On May 24, 2002, Jilin Pharmaceutical provided documentation to support this claim, consisting of a government document approving its name change and its continuing right to export subject merchandise to the United States.

The information submitted by Jilin Pharmaceutical shows changed circumstances sufficient to warrant a review. Therefore, we are initiating a changed circumstances administrative review pursuant to section 751(b)(1) of the Act to determine whether entries naming Jilin Henghe as manufacturer or exporter should receive the cash deposit rate currently applied to Jilin Pharmaceutical.

Scope of the Review

The merchandise subject to this review is bulk acetylsalicylic acid, commonly referred to as bulk aspirin, whether or not in pharmaceutical or compound form, not put up in dosage form (tablet, capsule, powders or similar form for direct human consumption). Bulk aspirin may be imported in two forms, as pure ortho-acetylsalicylic acid or as mixed ortho-acetylsalicylic acid. Pure ortho-acetylsalicylic acid can be

either in crystal form or granulated into a fine powder (pharmaceutical form). This product has the chemical formula $C_9H_8O_4$. It is defined by the official monograph of the United States Pharmacopoeia ("USP") 23. It is classified under the *Harmonized Tariff Schedule of the United States* ("HTSUS") subheading 2918.22.1000.

Mixed ortho-acetylsalicylic acid consists of ortho-acetylsalicylic acid combined with other inactive substances such as starch, lactose, cellulose, or coloring materials and/or other active substances. The presence of other active substances must be in concentrations less than that specified for particular nonprescription drug combinations of aspirin and active substances as published in the *Handbook of Nonprescription Drugs*, eighth edition, American Pharmaceutical Association. This product is classified under HTSUS subheading 3003.90.0000. Although the HTSUS subheadings are provided for convenience and customs purposes, the written description of the merchandise under review is dispositive.

Initiation of Changed Circumstances Review

Pursuant to section 751(b)(1) of the Act, the Department will conduct a changed circumstances review upon receipt of information concerning, or a request from an interested party of, an antidumping duty order which shows changed circumstances sufficient to warrant a review of the order.

Jilin Pharmaceutical contends that its corporate name and successor-in-interest have changed and that no changes have occurred with respect to its production facilities. We therefore find good cause to conduct a changed circumstances review. *See* 19 CFR 351.216(c). Therefore, in accordance with section 751(b)(1) of the Act, we are initiating a changed circumstances review based upon the information contained in Jilin Pharmaceutical's submissions.

The Department will publish in the **Federal Register** a notice of preliminary results of changed circumstances antidumping duty administrative review, concurrent with the ongoing administrative review, in accordance with 19 CFR 351.221(b)(4) and 351.221(c)(3)(i), which will set forth the Department's preliminary factual and legal conclusions. The Department will issue its final results of review in accordance with the time limits set forth in 19 CFR 351.216(e).

This notice is in accordance with section 751(b)(1) of the Act.

Dated: June 3, 2002.

Richard W. Moreland,

Deputy Assistant Secretary for Import Administration, Group 1.

[FR Doc. 02-14380 Filed 6-6-02; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-588-824]

Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Initiation and Preliminary Results of Changed Circumstances Review of the Antidumping Order, and Intent To Revoke Order in Part

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

ACTION: Notice of initiation and preliminary results of changed circumstances antidumping duty review, and intent to revoke order in part.

SUMMARY: In accordance with 751(b) of the Tariff Act of 1930 ("the Act") and section 351.216(b) of the Department of Commerce's ("the Department") regulations, Mitsubishi International Steel Inc. ("MISI") filed a request for a changed circumstances review of the antidumping order on certain corrosion-resistant carbon steel flat products from Japan with respect to the products known as diffusion-annealed nickel plant and next generation diffusion-annealed nickel plate described below. Domestic producers of the like product have affirmatively expressed no interest in continuation of the order with respect to these particular products. In response to MISI's request, the Department is initiating a changed circumstances review and issuing a notice of intent to revoke in part the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. Interested parties are invited to comment on these preliminary results.

EFFECTIVE DATE: June 7, 2002.

FOR FURTHER INFORMATION CONTACT:

Catherine Bertrand, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW., Washington, DC 20230; telephone: (202) 482-3207.

The Applicable Statute and Regulations: Unless otherwise indicated, all citations to the statute are references to the provisions effective January 1, 1995, the effective date of the amendments made to the Tariff Act of 1930, as amended, by the Uruguay

Round Agreements Act. In addition, unless otherwise indicated, all citations to the Department's regulations are to the regulations as codified at 19 CFR part 351 (2001).

SUPPLEMENTARY INFORMATION:

Background

On May 6, 2002, MISI requested that the Department revoke in part the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. Specifically, MISI requested that the Department revoke the order with respect to imports meeting the following specifications: (1) diffusion annealed, non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet ("CRBG") with both sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0–5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004" (0.10mm) to 0.030" (0.762mm) and conforming to the following chemical specifications (%): C ≤ 0.08; Mn ≤ 0.45; P ≤ 0.02; S ≤ 0.02; Al ≤ 0.15; and Si ≤ 0.10; and the following physical specifications: Tensile = 65 KSI maximum; Yield = 32–55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85–150 Vickers; Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7–12; Delta r value = aim less than ±0.2; Lankford value = ≥ 1.2.; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) Nickel-graphite plated, diffusion annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: top side: nickel-graphite, tin-nickel layer ≥ 1.0 micrometers; tin layer only ≥ 0.05 micrometers, nickel-graphite layer only

> 0.2 micrometers, and bottom side: nickel layer ≥ 1.0 micrometers; (b) nickel-graphite, diffusion annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer ≥ 1.0 micrometers; nickel-graphite layer ≥ 0.5 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer ≥ 1.0 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated

material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer ≥ 1.0 micrometers; nickel-phosphorous layer ≥ 0.1 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin-nickel combination layer ≥ 1.0 micrometers; tin layer only ≥ 0.05 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer ≥ 1 micrometer; tin layer alone ≥ 0.05 micrometers; bottom side: nickel layer ≥ 1.0 micrometer.

Scope of Review

The products covered by the antidumping duty order include flat-rolled carbon steel products, of rectangular shape, either clad, plated, or coated with corrosion-resistant metals such as zinc, aluminum, or zinc-, aluminum-, nickel- or iron-based alloys, whether or not corrugated or painted, varnished or coated with plastics or other nonmetallic substances in

addition to the metallic coating, in coils (whether or not in successively superimposed layers) and of a width of 0.5 inch or greater, or in straight lengths which, if of a thickness less than 4.75 millimeters, are of a width of 0.5 inch or greater and which measures at least 10 times the thickness or if of a thickness of 4.75 millimeters or more are of a width which exceeds 150 millimeters and measures at least twice the thickness, as currently classifiable in the HTSUS under item numbers 7210.30.0030, 7210.30.0060, 7210.41.0000, 7210.49.0030, 7210.49.0090, 7210.61.0000, 7210.69.0000, 7210.70.6030, 7210.70.6060, 7210.70.6090, 7210.90.1000, 7210.90.6000, 7210.90.9000, 7212.20.0000, 7212.30.1030, 7212.30.1090, 7212.30.3000, 7212.30.5000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7212.60.0000, 7215.90.1000, 7215.90.3000, 7215.90.5000, 7217.20.1500, 7217.30.1530, 7217.30.1560, 7217.90.1000, 7217.90.5030, 7217.90.5060, 7217.90.5090. Included in this order are corrosion-resistant flat-rolled products of non-rectangular cross-section where such cross-section is achieved subsequent to the rolling process (*i.e.*, products which have been "worked after rolling")—for example, products which have been beveled or rounded at the edges.

Excluded from this order are flat-rolled steel products either plated or coated with tin, lead, chromium, chromium oxides, both tin and lead ("terne plate"), or both chromium and chromium oxides ("tin-free steel"), whether or not painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating.

Also excluded from this order are clad products in straight lengths of 0.1875 inch or more in composite thickness and of a width which exceeds 150 millimeters and measures at least twice the thickness.

Also excluded from this order are certain clad stainless flat-rolled products, which are three-layered corrosion-resistant carbon steel flat-rolled products less than 4.75 millimeters in composite thickness that consist of a carbon steel flat-rolled product clad on both sides with stainless steel in a 20%–60%–20% ratio.

Also excluded from this order are certain corrosion-resistant carbon steel flat products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2)

thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of chromate, and finally a layer consisting of silicate.

Also excluded from this order are carbon steel flat products measuring 1.84 millimeters in thickness and 43.6 millimeters or 16.1 millimeters in width consisting of carbon steel coil (SAE 1008) clad with an aluminum alloy that is balance aluminum, 20% tin, 1% copper, 0.3% silicon, 0.15% nickel, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Also excluded from this order are carbon steel flat products measuring 0.97 millimeters in thickness and 20 millimeters in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% to 11% tin, 9% to 11% lead, less than 1% zinc, less than 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 45% to 55% lead, 38% to 50% PTFE, 3% to 5% molybdenum disulfide and less than 2% other materials.

Also excluded from this order are doctor blades meeting the following specifications: carbon steel coil or strip, plated with nickel phosphorous, having a thickness of 0.1524 millimeters (0.006 inches), a width between 31.75 millimeters (1.25 inches) and 50.80 millimeters (2.00 inches), a core hardness between 580 to 630 HV, a surface hardness between 900–990 HV; the carbon steel coil or strip consists of the following elements identified in percentage by weight: 0.90% to 1.05% carbon; 0.15% to 0.35% silicon; 0.30% to 0.50% manganese; less than or equal to 0.03% of phosphorous; less than or equal to 0.006% of sulfur; other elements representing 0.24%; and the remainder of iron.

Also excluded from this order are products meeting the following specifications: carbon steel flat products measuring 1.64 millimeters in thickness and 19.5 millimeters in width consisting of carbon steel coil (SAE 1008) with a lining clad with an aluminum alloy that

is balance aluminum; 10 to 15% tin; 1 to 3% lead; 0.7 to 1.3% copper; 1.8 to 3.5% silicon; 0.1 to 0.7% chromium, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Also, excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring 1.93 millimeters or 2.75 millimeters (0.076 inches or 0.108 inches) in thickness, 87.3 millimeters or 99 millimeters (3.437 inches or 3.900 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 0.3% antimony, 2.5% silicon, 1% maximum total other (including iron), and remainder aluminum.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, clad with aluminum, measuring 1.75 millimeters (0.069 inches) in thickness, 89 millimeters or 94 millimeters (3.500 inches or 3.700 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 2.5% silicon, 0.3% antimony, 1% maximum total other (including iron), and remainder aluminum.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring a minimum of and including 1.10mm to a maximum of and including 4.90mm in overall thickness, a minimum of and including 76.00mm to a maximum of and including 250.00mm in overall width, with a low carbon steel back comprised of: carbon under 0.10%, manganese under 0.40%, phosphorous under 0.04%, sulfur under 0.05%, and silicon under 0.05%; clad with aluminum alloy comprised of: under 2.51% copper, under 15.10% tin, and remainder aluminum as listed on the mill specification sheet.

Initiation of Changed Circumstances Antidumping Duty Administrative Review, and Intent to Revoke Order in Part

Pursuant to sections 751(d)(1) and 782(h)(2) of the Act, the Department may revoke an antidumping or countervailing duty order, in whole or in part, based on a review under section 751(b) of the Act (*i.e.*, a changed circumstances review) where the

Department determines that "producers accounting for substantially all of the production of that domestic like product have expressed a lack of interest in issuance of an order." Section 782(h)(2) of the Act. *See, e.g., Certain Cold-Rolled Carbon Steel Flat Products From the Netherlands: Initiation and Preliminary Results of Changed Circumstances Review*, 66 FR 57415, 57416 (November 15, 2001). Section 751(b)(1) of the Act requires a changed circumstances review to be conducted upon receipt of a request which shows changed circumstances sufficient to warrant a review. Section 351.222(g) of the Department's regulations provides that the Department will conduct a changed circumstances administrative review under 19 CFR 351.216, and may revoke an order (in whole or in part), if it determines that producers accounting for substantially all of the production of the domestic like product to which the order pertains have expressed a lack of interest in the relief provided by the order, in whole or in part, or if other changed circumstances sufficient to warrant revocation exist.

In addition, in the event that the Department concludes that expedited action is warranted, 19 CFR 351.221(c)(3)(ii) permits the Department to combine the notices of initiation and preliminary results.

In accordance with sections 751(d)(1) and 782(h)(2) of the Act, and 19 CFR 351.216 and 351.222(g), based on affirmative statements by domestic producers of the like product, Bethlehem Steel Corporation; National Steel Corporation; and United States Steel Corporation ("Domestic Producers"), no further interest exists in continuing the order with respect to certain corrosion-resistant carbon steel flat products meeting the following specifications: (1) Diffusion annealed, non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet ("CRBG") with both sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0–5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004" (0.10mm) to 0.030" (0.762mm) and conforming to the following chemical specifications (%): C ≤ 0.08; Mn ≤ 0.45; P ≤ 0.02; S ≤ 0.02; Al ≤ 0.15; and Si ≤ 0.10; and the following physical specifications: Tensile = 65 KSI maximum; Yield = 32–55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85–150 Vickers;

Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7–12; Delta r value = aim less than ± 0.2; Lankford value = ≥ 1.2.; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) Nickel-graphite plated, diffusion annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: top side: nickel-graphite, tin-nickel layer ≥ 1.0 micrometers; tin layer only ≥ 0.05 micrometers, nickel-graphite layer only > 0.2 micrometers, and bottom side: nickel layer ≥ 1.0 micrometers; (b) nickel-graphite, diffusion annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: Nickel-graphite, tin-nickel layer ≥ 1.0 micrometers; nickel-graphite layer ≥ 0.5 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite

composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer ≥ 1.0 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer ≥ 1.0 micrometers; nickel-phosphorous layer ≥ 0.1 micrometers; bottom side : nickel layer ≥ 1.0 micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin-nickel combination layer ≥ 1.0 micrometers; tin layer only ≥ 0.05 micrometers; bottom side: nickel layer ≥ 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to

chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer ≥ 1 micrometer; tin layer alone ≥ 0.05 micrometers; bottom side: nickel layer ≥ 1.0 micrometer. See Domestic Producers' May 14, 2002, letter to the Department. Therefore, we are initiating this changed circumstances administrative review.

Furthermore, because domestic producers have expressed a lack of interest, we determine that expedited action is warranted, and we preliminarily determine that continued application of the order with respect to certain corrosion-resistant carbon steel flat products falling within the description above is no longer of interest to domestic interested parties. Because we have concluded that expedited action is warranted, we are combining these notices of initiation and preliminary results. Therefore, we are hereby notifying the public of our intent to revoke in part the antidumping duty order with respect to imports of certain corrosion-resistant carbon steel flat products meeting the above-mentioned specifications from Japan.

If the final revocation in part occurs, we intend to instruct the U.S. Customs Service ("Customs") to liquidate without regard to antidumping duties, as applicable, and to refund any estimated antidumping duties collected for all unliquidated entries of certain corrosion-resistant carbon steel flat products meeting the specifications indicated above, not subject to final results of administrative review as of the date of publication in the **Federal Register** of the final results of this changed circumstances review in accordance with 19 CFR 351.222. We will also instruct Customs to pay interest on such refunds in accordance with section 778 of the Act. The current requirement for a cash deposit of estimated antidumping duties on certain corrosion-resistant carbon steel flat products meeting the above specifications will continue unless and until we publish a final determination to revoke in part.

Public Comment

Interested parties are invited to comment on these preliminary results. Parties who submit argument in this proceeding are requested to submit with the argument (1) a statement of the issue, and (2) a brief summary of the argument. Parties to the proceedings may request a hearing within 14 days of publication. Any hearing, if requested, will be held no later than two days after the deadline for the submission of rebuttal briefs, or the first workday thereafter. Case briefs may be submitted by interested parties not later than 14 days after the date of publication of this notice. Rebuttal briefs and rebuttals to written comments, limited to the issues raised in those comments, may be filed not later than five days after the deadline for submission of case briefs. All written comments shall be submitted in accordance with 19 CFR 351.303 and shall be served on all interested parties on the Department's service list in accordance with 19 CFR 351.303. Persons interested in attending the hearing should contact the Department for the date and time of the hearing.

This notice is published in accordance with section 751(b)(1) of the Act and 19 CFR 351.216 and 351.222.

Dated: June 3, 2002.

Faryar Shirzad,

Assistant Secretary for Import Administration.

[FR Doc. 02-14379 Filed 6-6-02; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-201-827]

Certain Large Diameter Carbon and Alloy Seamless Standard, Line and Pressure Pipe from Mexico: Extension of Preliminary Results of Antidumping Duty Administrative Review

AGENCY: AGENCY: Import Administration, International Trade Administration, Department of Commerce.

EFFECTIVE DATE: June 7, 2002.

FOR FURTHER INFORMATION CONTACT: Geoffrey Craig or Brian Ledgerwood at (202) 482-4161 or (202) 482-3836, Office of AD/CVD Enforcement VI, Group II, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Ave, NW, Washington, DC 20230.

SUPPLEMENTARY INFORMATION:

TIME LIMITS:

Statutory Time Limits

Section 751(a)(3)(A) of the Tariff Act of 1930, as amended (the Act), requires the Department of Commerce (the Department) to issue the preliminary results of a review within 245 days after the last day of the anniversary month of an order or finding for which a review is requested and the final results within 120 days after the date on which the preliminary results are published. However, if it is not practicable to complete the review within that time period, section 751(a)(3)(A) of the Act allows the Department to extend the time limit for the preliminary results to a maximum of 365 days and for the final results to 180 days (or 300 days if the Department does not extend the time limit for the preliminary results) from the date of the publication of the preliminary results.

Background

On October 1, 2001, the Department published in the Federal Register the notice of initiation of this antidumping duty administrative review with respect to certain large diameter carbon and alloy seamless standard, line, and pressure pipe, covering the period February 4, 2000 through July 31, 2001 (66 FR 49924). The preliminary results were originally due on May 3, 2002. On May 10, 2002 (67 FR 17397) the Department published a 30-day extension of the preliminary results. On May 29, 2002, petitioner in this case made a submission arguing that the review should not be rescinded. Because it is not practicable to address the issues raised by June 3, 2002, we are postponing the preliminary determination an additional 90 days, until September 3, 2002, in accordance with 751(a)(3)(A) of the Act.

Extension of Preliminary Results of Review

We determine that it is not practicable to complete the preliminary results of this review within the time limit. Therefore, we are extending the time limit for completion of the preliminary results until no later than September 3, 2002. See Decision Memorandum from Melissa Skinner to Bernard Carreau, dated May 31, 2002, which is on file in the Central Records Unit, B-099 of the main Commerce Building. We intend to issue the final results no later than 120 days after the publication of the notice of preliminary results of this review.

This extension is in accordance with section 751(a)(3)(A) of the Act.