

if one is requested, must submit a written request within 30 days of the publication of this notice. Requests should specify the number of participants and provide a list of the issues to be discussed. Oral presentations will be limited to issues raised in the briefs.

As noted above, the Department will make its final determination within 135 days after the date of the publication of the preliminary determination.

This determination is issued and published pursuant to section 733(f) and 777(i)(1) of the Act.

Dated: December 10, 2004.

Joseph A. Spetrini,

Acting Assistant Secretary for Import Administration.

[FR Doc. E4-3742 Filed 12-17-04; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-588-824]

Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Initiation and Preliminary Results of Antidumping Duty Changed Circumstances Review and Intent To Revoke, in Part

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

SUMMARY: In accordance with 19 CFR 351.216(b), Taiho Corporation of America (Taiho) filed a request for a changed circumstances review of the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan with respect to 24 products lined with a bushing alloy as defined below. In response to this request, the Department of Commerce is initiating a changed circumstances review and issuing a notice of preliminary intent to revoke in part the order on certain corrosion-resistant carbon steel flat products from Japan with respect to corrosion-resistant carbon steel coil. Interested parties are invited to comment on these preliminary results.

DATES: *Effective Date:* December 20, 2004.

FOR FURTHER INFORMATION CONTACT:

George McMahan, Christopher Hargett, or James Terpstra, AD/CVD Operations, Office 3, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW., Washington, DC 20230; telephone (202)

482-1167, (202) 482-4161, or (202) 482-3965, respectively.

SUPPLEMENTARY INFORMATION:

Background

On August 19, 1993, the Department of Commerce (the Department) published an antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. *See Antidumping Duty Orders: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan*, 58 FR 44163 (August 19, 1993). On October 26, 2004, Taiho requested that the Department revoke the antidumping duty order on 24 separate bushing alloy-lined corrosion-resistant carbon steel coil products from Japan through the initiation of a changed circumstances review. Taiho also requested that the Department conduct an expedited changed circumstances review pursuant to 19 CFR 351.221(c)(3)(ii).

Taiho asserts that the domestic producers do not have any interest in the continuation of the order with respect to the 24 products. The Department received a letter on November 22, 2004, on behalf of United States Steel Corporation stating they have no objection to the initiation of the changed circumstances review, and on December 3, 2004, received a letter on behalf of International Steel Group, attesting to their lack of interest regarding continuation of the order with respect to the specified 24 products.

Scope of the Order

The products subject to this order include flat-rolled carbon steel products, of rectangular shape, either clad, plated, or coated with corrosion-resistant metals such as zinc, aluminum, or zinc-, aluminum-, nickel- or iron-based alloys, whether or not corrugated or painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating, in coils (whether or not in successively superimposed layers) and of a width of 0.5 inch or greater, or in straight lengths which, if of a thickness less than 4.75 millimeters, are of a width of 0.5 inch or greater and which measures at least 10 times the thickness or if of a thickness of 4.75 millimeters or more are of a width which exceeds 150 millimeters and measures at least twice the thickness, as currently classifiable in the Harmonized Tariff Schedule under item numbers: 7210.30.0030, 7210.30.0060, 7210.41.0000, 7210.49.0030, 7210.49.0090, 7210.61.0000, 7210.69.0000, 7210.70.6030, 7210.70.6060, 7210.70.6090, 7210.90.1000, 7210.90.6000, 7210.90.9000,

7212.20.0000, 7212.30.1030, 7212.30.1090, 7212.30.3000, 7212.30.5000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7212.60.0000, 7215.90.1000, 7215.90.3000, 7215.90.5000, 7217.20.1500, 7217.30.1530, 7217.30.1560, 7217.90.1000, 7217.90.5030, 7217.90.5060, and 7217.90.5090.

Included in the order are flat-rolled products of nonrectangular cross-section where such cross-section is achieved subsequent to the rolling process (*i.e.*, products which have been “worked after rolling”)—for example, products which have been bevelled or rounded at the edges.

Excluded from the scope of the order are flat-rolled steel products either plated or coated with tin, lead, chromium, chromium oxides, both tin and lead (“terne plate”), or both chromium and chromium oxides (“tin-free steel”), whether or not painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating. Also excluded from the scope of the order are certain clad stainless flat-rolled products, which are three-layered corrosion-resistant carbon steel flat-rolled products less than 4.75 millimeters in composite thickness that consist of a carbon steel flat-rolled product clad on both sides with stainless steel in a 20%–60%–20% ratio. *See Antidumping Duty Orders: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan*, 58 FR 44163 (August 19, 1993).

Also excluded from the scope of this order are imports of certain corrosion-resistant carbon steel flat products meeting the following specifications: widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Antidumping Duty Administrative Review, and Revocation in Part of Antidumping Duty Order*, 62 FR 66848 (December 22, 1997).

Also excluded from the scope of this order are imports of subject

merchandise meeting all of the following criteria: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of chromate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Antidumping Duty Administrative Review, and Revocation in Part of Antidumping Duty Order*, 64 FR 14861 (March 29, 1999).

Also excluded from the scope of this order are: (1) Carbon steel flat products measuring 1.84 mm in thickness and 43.6 mm or 16.1 mm in width consisting of carbon steel coil (SAE 1008) clad with an aluminum alloy that is balance aluminum, 20% tin, 1% copper, 0.3% silicon, 0.15% nickel, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys; and (2) carbon steel flat products measuring 0.97 mm in thickness and 20 mm in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% to 11% tin, 9% to 11% lead, less than 1% zinc, less than 1% other materials and meeting the requirements of SAE standard 792 for bearing and bushing alloys, the second layer consisting of 45% to 55% lead, 38% to 50% PTFE, 3% to 5% molybdenum disulfide and less than 2% other materials. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 64 FR 57032 (October 22, 1999).

Also excluded from the scope of the order are imports of doctor blades meeting the following specifications: Carbon steel coil or strip, plated with nickel phosphorous, having a thickness of 0.1524 millimeters (0.006 inches), a width between 31.75 millimeters (1.25 inches) and 50.80 millimeters (2.00 inches), a core hardness between 580 to 630 HV, a surface hardness between 900–990 HV; the carbon steel coil or

strip consists of the following elements identified in percentage by weight: 0.90% to 1.05% carbon; 0.15% to 0.35% silicon; 0.30% to 0.50% manganese; less than or equal to 0.03% of phosphorous; less than or equal to 0.006% of sulfur; other elements representing 0.24%; and the remainder of iron. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 65 FR 53983 (September 6, 2000).

Also excluded from the scope of the order are imports of carbon steel flat products meeting the following specifications: Carbon steel flat products measuring 1.64 millimeters in thickness and 19.5 millimeters in width consisting of carbon steel coil (SAE 1008) with a lining clad with an aluminum alloy that is balance aluminum; 10 to 15% tin; 1 to 3% lead; 0.7 to 1.3% copper; 1.8 to 3.5% silicon; 0.1 to 0.7% chromium; less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 8778 (February 2, 2001).

Also excluded from the scope of the order are carbon steel flat products meeting the following specifications: (1) Carbon steel flat products measuring 0.975 millimeters in thickness and 8.8 millimeters in width consisting of carbon steel coil (SAE 1012) clad with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9%–11% tin, 9%–11% lead, maximum 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 13%–17% carbon, 13%–17% aromatic polyester, with a balance (approx. 66%–74%) of polytetrafluorethylene (PTFE); and (2) carbon steel flat products measuring 1.02 millimeters in thickness and 10.7 millimeters in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9%–11% tin, 9%–11% lead, less than 0.35% iron, and meeting the requirements of SAE standard 792 for bearing and bushing alloys, the second layer consisting of 45%–55% lead, 3%–5% molybdenum disulfide, with a balance (approx. 40%–52%) of polytetrafluorethylene (PTFE). *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation*

in Part of Antidumping Duty Order, 66 FR 15075 (March 15, 2001).

Also excluded from this order are products meeting the following specifications: Carbon steel coil or strip, measuring 1.93 millimeters or 2.75 millimeters (0.076 inches or 0.108 inches) in thickness, 87.3 millimeters or 99 millimeters (3.437 inches or 3.900 inches) in width, with a low carbon steel back comprised of: Carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 0.3% antimony, 2.5% silicon, 1% maximum total other (including iron), and remainder aluminum. Also excluded from this order are products meeting the following specifications: Carbon steel coil or strip, clad with aluminum, measuring 1.75 millimeters (0.069 inches) in thickness, 89 millimeters or 94 millimeters (3.500 inches or 3.700 inches) in width, with a low carbon steel back comprised of: Carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 2.5% silicon, 0.3% antimony, 1% maximum total other (including iron), and remainder aluminum. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 20967 (April 26, 2001).

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring a minimum of and including 1.10mm to a maximum of and including 4.90mm in overall thickness, a minimum of and including 76.00mm to a maximum of and including 250.00mm in overall width, with a low carbon steel back comprised of: carbon under 0.10%, manganese under 0.40%, phosphorous under 0.04%, sulfur under 0.05%, and silicon under 0.05%; clad with aluminum alloy comprised of: under 2.51% copper, under 15.10% tin, and remainder aluminum as listed on the mill specification sheet. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 67 FR 7356 (February 19, 2002).

Also excluded from this order are products meeting the following specifications: (1) Diffusion annealed, non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet ("CRBG") with both

sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0–5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004" (0.10mm) to 0.030" (0.762mm) and conforming to the following chemical specifications (%): C \leq 0.08; Mn \leq 0.45; P \leq 0.02; S \leq 0.02; Al \leq 0.15; and Si \leq 0.10; and the following physical specifications: Tensile = 65 KSI maximum; Yield = 32–55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85–150 Vickers; Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7–12; Delta r value = aim less than +/-0.2; Lankford value = \leq 1.2.; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) Nickel-graphite plated, diffusion annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: top side: nickel-graphite, tin-nickel layer \leq 1.0 micrometers; tin layer only \leq 0.05 micrometers, nickel-graphite layer only \leq 0.2 micrometers, and bottom side: nickel layer \leq 1.0 micrometers; (b) nickel-graphite, diffusion annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-

graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer \leq 1.0 micrometers; nickel-graphite layer \leq 0.5 micrometers; bottom side: nickel layer \leq 1.0 micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer \leq 1.0 micrometers; bottom side: nickel layer \leq 1.0 micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer \leq 1.0 micrometers; nickel-phosphorous layer \leq 0.1 micrometers; bottom side: nickel layer \leq 1.0 micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the

nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin-nickel combination layer \leq 1.0 micrometers; tin layer only \leq 0.05 micrometers; bottom side: nickel layer \leq 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer \leq 1 micrometer; tin layer alone \leq 0.05 micrometers; bottom side: nickel layer \leq 1.0 micrometer. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order, 67 FR 47768 (July 22, 2002).*

Also excluded from this order are products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of phosphate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of phosphate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice*

of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order, 67 FR 52708 (September 9, 2002).

Also excluded from this order are products meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) Having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40 percent by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): carbon not over 0.06 percent by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over 0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) Products with one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron-diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron-diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface coating layer of hard nickel and a topmost nickel-phosphorus-plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5

microns in length; (C) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent-added nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order, 68 FR 19970 (April 23, 2003).*

Products and Descriptions Subject to This Review

Taiho defines the 24 separate corrosion-resistant carbon steel coil products to be excluded as meeting the following specifications:

Product 1

Products described in industry usage as of carbon steel, measuring 1.625 mm to 1.655 mm in thickness and 19.3 mm to 19.7 mm in width, consisting of carbon steel coil (SAE 1010) with a lining clad with an aluminum alloy containing by weight 10 percent or more but not more than 15 percent of tin, 1 percent or more but not more than 3 percent of lead, 0.7 percent or more but not more than 1.3 percent of copper, 1.8 percent or more but not more than 3.5 percent of silicon, 0.1 percent or more but not more than 0.7 percent of chromium and less than or equal to 1 percent of other materials, and meeting the requirements of SAE standard 788 for Bearing and Bushing Alloys.

Product 2

Products described in industry usage as of carbon steel, measuring 0.955 mm to 0.985 mm in thickness and 8.6 mm to 9.0 mm in width, consisting of carbon steel coil (SAE 1012) clad with a two-layer lining, the first layer consisting of a copper-lead alloy powder that contains by weight 9 percent or more but not more than 11 percent of tin, 9 percent or more but not more than 11 percent of lead, less than 0.05 percent phosphorus, less than 0.35 percent iron and less than or equal to 1 percent other materials, and meeting the requirements of SAE standard 797 for Bearing and Bushing Alloys, with the second layer containing by weight 13 percent or more but not more than 17 percent of carbon, 13 percent or more but not more than 17 percent of aromatic polyester, and the remainder (approx. 66–74 percent) of polytetrafluorethylene (PTFE).

Product 3

Products described in industry usage as of carbon steel, measuring 1.01 mm to 1.03 mm in thickness and 10.5 mm to 10.9 mm in width, consisting of carbon steel coil (SAE 1010) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that contains by weight 9 percent or more but not more than 11 percent of tin, 9 percent or more but not more than 11 percent of lead, less than 1 percent zinc and less than or equal to 1 percent other materials, and meeting the requirements of SAE standard 797 for Bearing and Bushing Alloys, with the second layer containing by weight 45 percent or more but not more than 55 percent of lead, 3 percent or more but not more than 5 percent of molybdenum disulfide, and the remainder made up of PTFE (approximately 38 percent to 52 percent) and less than 2 percent in the aggregate of other materials.

Product 4

Products described in industry usage as of carbon steel, measuring 1.8 mm to 1.88 mm in thickness and 43.4 mm to 43.8 mm or 16.1 mm to 1.65 mm in width, consisting of carbon steel coil (SAE 1010) clad with an aluminum alloy that contains by weight 19 percent to 20 percent tin, 1 percent to 1.2 percent copper, less than 0.3 percent silicon, 0.15 percent nickel and less than 1 percent in the aggregate other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Product 5

Products described in industry usage as of carbon steel, measuring 0.95 mm to 0.98 mm in thickness and 19.95 mm

to 20 mm in width, consisting of carbon steel coil (SAE 1010) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that contains by weight 9 percent or more but not more than 11 percent of tin, 9 percent or more but not more than 11 percent of lead, less than 1 percent of zinc and less than or equal to 1 percent in the aggregate of other materials and meeting the requirements of SAE standard 797 for Bearing and Bushing Alloys, with the second layer consisting by weight of 45 percent or more but not more than 55 percent of lead, 3 percent or more but not more than 5 percent of molybdenum disulfide and with the remainder made up of polytetrafluoroethylene (PTFE) (approximately 38 percent to 52 percent) and up to 2 percent in the aggregate of other materials.

Product 6

Products described in industry usage as of carbon steel, measuring 0.96 mm to 0.98 mm in thickness and 18.75 mm to 18.95 mm in width; base of SAE 1010 steel with a two-layer lining, the first layer consisting of copper-base alloy powder with chemical composition (percent by weight): tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35, and other materials less than 1 percent; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of lead 33 to 37 percent, aromatic polyester 28 to 32 percent, and other materials less than 2 percent with a balance of polytetrafluoroethylene (PTFE).

Product 7

Products described in industry usage as of carbon steel, measuring 1.21 mm to 1.25 mm in thickness and 19.4 mm to 19.6 mm in width; base of SAE 1012 steel with lining of copper base alloy with chemical composition (percent by weight): Tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35 and other materials less than 1 percent; meeting the requirements of SAE standard 797 for bearing and bushing alloys.

Product 8

Products described in industry usage as of carbon steel, measuring 0.96 mm to 0.98 mm in thickness and 21.5 mm to 21.7 mm in width; base of SAE 1010 steel with a two-layer lining, the first layer consisting of copper-base alloy powder with chemical composition (percent by weight): Tin 9 to 11, lead 9 to 11, phosphorus less than 0.05 percent, ferrous group less than 0.35 and other materials less than 1; meeting the requirements of SAE standard 797

for bearing and bushing alloys; the second layer consisting of (percent by weight) lead 33 to 37, aromatic polyester 28 to 32 and other materials less than 2 with a balance of polytetrafluoroethylene (PTFE).

Product 9

Products described in industry usage as of carbon steel, measuring 0.96 mm to 0.99 mm in thickness and 7.65 mm to 7.85 mm in width; base of SAE 1012 steel with a two-layer lining, the first layer consisting of copper-based alloy powder with chemical composition (percent by weight): Tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35 and other materials less than 1; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of (percent by weight) carbon 13 to 17 and aromatic polyester 13 to 17, with a balance of polytetrafluoroethylene ("PTFE").

Product 10

Products described in industry usage as of carbon steel, measuring 0.955 mm to 0.985 mm in thickness and 13.6 mm to 14 mm in width; base of SAE 1012 steel with a two-layer lining, the first layer consisting of copper-based alloy powder with chemical composition (percent by weight): Tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35 and other materials less than 1; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of (percent by weight) carbon 13 to 17, aromatic polyester 13 to 17, with a balance (approximately 66 to 74) of polytetrafluoroethylene (PTFE).

Product 11

Products described in industry usage as of carbon steel, measuring 1.2 mm to 1.24 mm in thickness; 20 mm to 20.4 mm in width; consisting of carbon steel coils (SAE 1012) with a lining of sintered phosphorus bronze alloy with chemical composition (percent by weight): Tin 5.5 to 7; phosphorus 0.03 to 0.35; lead less than 1 and other non-copper materials less than 1.

Product 12

Products described in industry usage as of carbon steel, measuring 1.8 mm to 1.88 mm in thickness and 43.3 mm to 43.7 mm in width; base of SAE 1010 steel with a lining of aluminum based alloy with chemical composition (percent by weight): Tin 10 to 15, lead 1 to 3, copper 0.7 to 1.3, silicon 1.8 to 3.5, chromium 0.1 to 0.7 and other materials less than 1; meeting the

requirements of SAE standard 788 for bearing and bushing alloys.

Product 13

Products described in industry usage as of carbon steel, measuring 1.8 mm to 1.88 mm in thickness and 24.2 mm to 24.6 mm in width; base of SAE 1010 steel with a lining of aluminum alloy with chemical composition (percent by weight): Tin 10 to 15, lead 1 to 3, copper 0.7 to 1.3, silicon 1.8 to 3.5, chromium 0.1 to 0.7 and other materials less than 1; meeting the requirements of SAE standard 788 for bearing and bushing alloys.

Product 14

Flat-rolled coated SAE 1009 steel in coils, with thickness not less than 0.915 mm but not over 0.965 mm, width not less than 19.75 mm or more but not over 20.35 mm; with a two-layer coating; the first layer consisting of tin 9 to 11 percent, lead 9 to 11 percent, zinc less than 1 percent, other materials (other than copper) not over 1 percent and balance copper; the second layer consisting of lead 45 to 55 percent, molybdenum disulfide (MoS₂) 3 to 5 percent, other materials not over 2 percent, balance polytetrafluoroethylene (PTFE).

Product 15

Flat-rolled coated SAE 1009 steel in coils with thickness not less than 0.915 mm or more but not over 0.965 mm; width not less than 18.65 mm or more but not over 19.25 mm; with a two-layer coating; the first layer consisting of tin 9 to 11 percent, lead 9 to 11 percent, zinc less than 1 percent, other materials (other than copper) not over 1 percent, balance copper; the second layer consisting of lead 33 to 37 percent, aromatic polyester 13 to 17 percent, other materials (other than polytetrafluoroethylene (PTFE)) less than 2 percent, balance PTFE.

Product 16

Flat-rolled coated SAE 1009 steel in coils with thickness not less than 0.920 mm or more but not over 0.970 mm; width not less than 21.35 mm or more but not over 21.95 mm; with a two-layer coating; the first layer consisting of tin 9 to 11 percent, lead 9 to 11 percent, zinc less than 1 percent, other materials (other than copper) not over 1 percent, balance copper; the second layer consisting of lead 33 to 37 percent, aromatic polyester 13 to 17 percent, other materials (other than PTFE) less than 2 percent, balance PTFE.

Product 17

Flat-rolled coated SAE 1009 steel in coils with thickness not less than 1.80 mm or more but not over 1.85 mm, width not less than 14.7 mm or more but not over 15.3 mm; with a lining consisting of tin 2.5 to 4.5 percent, lead 21.0 to 25.0 percent, zinc less than 3 percent, iron less than 0.35 percent, other materials (other than copper) less than 1 percent, balance copper.

Product 18

Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 14.5 mm or more but not over 15.1 mm; with a lining consisting of tin 2.3 to 4.2 percent, lead 20 to 25 percent, iron 1.5 to 4.5 percent, phosphorus 0.2 to 2.0 percent, other materials (other than copper) less than 1 percent, balance copper.

Product 19

Flat-rolled coated SAE 1009 steel in coils with thickness not less than 1.75 mm or more but not over 1.8 mm; width not less than 18.0 mm or more but not over 18.6 mm; with a lining consisting of tin 2.3 to 4.2 percent, lead 20 to 25 percent, iron 1.5 to 4.5 percent, phosphorus 0.2 to 2.0 percent, other materials (other than copper) less than 1 percent, balance copper.

Product 20

Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 13.6 mm or more but not over 14.2 mm; with a lining consisting of tin 2.3 to 4.2 percent, lead 20 to 25 percent, iron 1.5 to 4.5 percent, phosphorus 0.2 to 2.0 percent, other materials (other than copper) less than 1 percent, with a balance copper.

Product 21

Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 11.5 mm or more but not over 12.1 mm; with a lining consisting of tin 2.3 to 4.2 percent, lead 20 to 25 percent, iron 1.5 to 4.5 percent, phosphorus 0.2 to 2.0 percent, other materials (other than copper) less than 1 percent, balance copper.

Product 22

Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 11.2 mm or more but not over 11.8 mm, with a lining consisting of copper 0.7 to 1.3 percent, tin 17.5 to 22.5 percent, silicon less than 0.3 percent, nickel less than

0.15 percent, other materials less than 1 percent, balance aluminum.

Product 23

Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 7.2 mm or more but not over 7.8 mm; with a lining consisting of copper 0.7 to 1.3 percent, tin 17.5 to 22.5 percent, silicon less than 0.3 percent, nickel less than 0.15 percent, other materials (other than copper) less than 1 percent, balance copper.

Product 24

Flat-rolled coated SAE 1009 steel in coils with thickness 1.72 mm or more but not over 1.77 mm; width 7.7 mm or more but not over 8.3 mm; with a lining consisting of copper 0.7 to 1.3 percent, tin 17.5 to 22.5 percent, silicon less than 0.3 percent, nickel less than 0.15 percent, other materials (other than copper) less than 1 percent, balance copper.

Initiation of Changed Circumstances Review, Preliminary Results, and Intent To Revoke Antidumping Duty Order, in Part

Pursuant to sections 751(d)(1) and 782(h)(2) of the Tariff Act of 1930, as amended ("the Act"), the Department may revoke an antidumping or countervailing duty order based on a review under section 751(b) of the Act (*i.e.*, a changed circumstances review). Section 751(b)(1) of the Act requires a changed circumstances review to be conducted upon receipt of a request which shows changed circumstances sufficient to warrant a review.

Section 351.222(g) of the Department's regulations provides that the Department will conduct a changed circumstances review under 19 CFR 351.216, and may revoke an order (in whole or in part), if it determines that producers accounting for substantially all of the production of the domestic like product to which the order (or the part of the order to be revoked) pertains have expressed a lack of interest in the relief provided by the order, in whole or in part, or if changed circumstances exist sufficient to warrant revocation. Furthermore, 19 CFR 351.221(c)(3)(ii) permits the Department to combine the notice of initiation of a changed circumstances review and the notice of preliminary results in a single notice, if the Department concludes that expedited action is warranted.

In this case, the Department finds that the information submitted provides sufficient evidence of changed circumstances to warrant a review. Therefore, in accordance with sections

751(d)(1) and 782 (h)(2) of the Act, and 19 CFR 351.216 and 351.222(g), based on the information provided by Taiho, we are initiating this changed circumstances review. Furthermore, based on the apparent lack of interest in continuation of the order with respect to the specified corrosion-resistant carbon steel coil products by domestic producers, we determine that expedited action is warranted and we preliminarily find that the continued relief provided by the order with respect to the products defined above is no longer of interest to the domestic industry. Because we have concluded that expedited action is warranted, we are combining these notices of initiation and preliminary results. Therefore, we preliminarily find that the request from Taiho meets all of the criteria under 19 CFR 351.222(g) and thus, we intend to revoke the order on certain corrosion-resistant carbon steel flat products from Japan with respect to imports of the corrosion-resistant carbon steel coil products specified above.

If the final revocation, in part, occurs, we intend to instruct U.S. Customs and Border Protection (CBP) to liquidate without regard to antidumping duties all unliquidated entries of the 24 specified products not subject to final results of an administrative review. The Department will further instruct CBP to refund with interest any estimated antidumping duties collected with respect to unliquidated entries of corrosion-resistant carbon steel coil entered, or withdrawn from warehouse, for consumption on or after the publication date of the final results of this changed circumstances review, in accordance with section 778 of the Act and 19 CFR 351.222(g)(4). The current requirement for a cash deposit of estimated antidumping duties on corrosion-resistant carbon steel coil from Japan will continue unless and until we publish a final decision to revoke.

Public Comment

Interested parties may submit case briefs not later than 21 days after the date of publication of this notice. *See* 19 CFR 351.309(c)(ii). Rebuttal briefs, which must be limited to issues raised in such case briefs, may be filed not later than 26 days after the date of publication of this notice. *See* 19 CFR 351.309(d). Parties who submit arguments are requested to submit with the argument (1) a statement of the issue, (2) a brief summary of the argument, and (3) a table of authorities. Any interested party may request a hearing within 14 days of publication of this notice. *See* 19 CFR 351.310(c). Any

hearing, if requested, may be held 22 days after the date of publication of this notice, or the first working day thereafter, as practicable. Consistent with section 351.216(e) of the Department's regulations, we will issue the final results of this changed circumstance reviews not later than 270 days after the date on which this review was initiated, or within 45 days if all parties agree to our preliminary finding.

We are issuing and publishing this finding and notice in accordance with sections 751(b)(1) and 777(i)(1) of the Act and section 351.216 of the Department's regulations.

Dated: December 13, 2004.

James J. Jochum,

Assistant Secretary for Import Administration.

[FR Doc. E4-3749 Filed 12-17-04; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-570-868]

Folding Metal Tables and Chairs From the People's Republic of China: Final Results and Partial Rescission of First Antidumping Duty Administrative Review

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

SUMMARY: On July 6, 2004, the Department of Commerce ("the Department") published the preliminary results of the first antidumping duty administrative review of the antidumping duty order on folding metal tables and chairs from the People's Republic of China ("PRC"). This administrative review covers two exporters (see "Background" section below for further discussion). The period of review is December 3, 2001, through May 30, 2003. We gave interested parties an opportunity to comment on our preliminary results.

Based on the additional publicly available information used in these final results and the comments received from the interested parties, we have made changes in the margin calculation for Dongguan Shichang Metals Factory Co., Ltd. ("Shichang") (i.e., the respondent which fully cooperated in this review). The final weighted-average dumping margins for the reviewed firms are listed below in the section entitled "Final Results of Review."

EFFECTIVE DATE: December 20, 2004.

FOR FURTHER INFORMATION CONTACT: Amber Musser at (202) 482-1777 or

Brian C. Smith at (202) 482-1766, AD/CVD Operations, Office 9, Import Administration, International Trade Administration, U.S. Department of Commerce, Washington, DC 20230.

SUPPLEMENTARY INFORMATION:

Background

While the Department initiated an administrative review of four companies, based on a request by the petitioner¹ and certain exporters, this administrative review now covers only two exporters: Shichang and Wok & Pan Industry, Inc. ("Wok and Pan") (see "Partial Rescission of Administrative Review" section of this notice for further discussion).

On July 6, 2004, the Department published in the **Federal Register** the preliminary results of the first administrative review of the antidumping duty order on folding metal tables and chairs from the PRC (see *Folding Metal Tables and Chairs From the People's Republic of China: Preliminary Results of First Antidumping Duty Administrative Review*, 69 FR 40602 (July 6, 2004) ("Preliminary Results")).

On July 26, 2004, the petitioner submitted publicly available information to value the factors of production in this review.

On August 17, 2004, the Department published in the **Federal Register** a notice of postponement of the final results until no later than December 13, 2004 (69 FR 51061).

Shichang submitted its case brief on September 10, 2004. The petitioner and Wok and Pan did not submit case or rebuttal briefs.

Neither the petitioner nor the respondents in this review requested a hearing.

On October 20, 2004, the Department received a request from U.S. Customs and Border Protection ("CBP") to add Harmonized Tariff Schedule of the United States ("HTSUS") subheadings 9403708010, 9403708020, 9403708030 to the AD/CVD module. We have updated the module and amended the scope accordingly (see October 20, 2004, memorandum to the file titled Request for AD/CVD Module Update with the Addition of HTSUS Numbers for Folding Metal Tables and Chairs from the People's Republic of China (A-577-868); and the "Scope of the Order" section of this notice).

The Department has conducted this administrative review in accordance with section 751 of the Tariff Act of 1930, as amended ("the Act").

Scope of the Order

The products covered by this order consist of assembled and unassembled folding tables and folding chairs made primarily or exclusively from steel or other metal, as described below:

- 1) Assembled and unassembled folding tables made primarily or exclusively from steel or other metal ("folding metal tables"). Folding metal tables include square, round, rectangular, and any other shapes with legs affixed with rivets, welds, or any other type of fastener, and which are made most commonly, but not exclusively, with a hardboard top covered with vinyl or fabric. Folding metal tables have legs that mechanically fold independently of one another, and not as a set. The subject merchandise is commonly, but not exclusively, packed singly, in multiple packs of the same item, or in five piece sets consisting of four chairs and one table. Specifically excluded from the scope of folding metal tables are the following:
 - a. Lawn furniture;
 - b. Trays commonly referred to as "TV trays";
 - c. Side tables;
 - d. Child-sized tables;
 - e. Portable counter sets consisting of rectangular tables 36" high and matching stools; and
 - f. Banquet tables. A banquet table is a rectangular table with a plastic or laminated wood table top approximately 28" to 36" wide by 48" to 96" long and with a set of folding legs at each end of the table. One set of legs is composed of two individual legs that are affixed together by one or more cross-braces using welds or fastening hardware. In contrast, folding metal tables have legs that mechanically fold independently of one another, and not as a set.
- 2) Assembled and unassembled folding chairs made primarily or exclusively from steel or other metal ("folding metal chairs"). Folding metal chairs include chairs with one or more cross-braces, regardless of shape or size, affixed to the front and/or rear legs with rivets, welds or any other type of fastener. Folding metal chairs include: those that are made solely of steel or other metal; those that have a back pad, a seat pad, or both a back pad and a seat pad; and those that have seats or backs made of plastic or other materials. The subject merchandise is commonly, but not exclusively, packed singly,

¹ The petitioner is Mecor Corporation.