

Eurasia and other regions. They are trained by government agencies, non-government offices (NGOs) and U.S. companies in various business practices and principles. This unique private sector-U.S. Government partnership was created in order to tap the U.S. private sector's expertise assisting the transition of developing regions to market economies while boosting trade between the United States and other countries. Participant applications and feedback (exit) surveys are needed to enable SABIT to find the most qualified people for the training programs and to track the success of the program as regards to trade between the U.S. and the countries SABIT covers, as well as to improve the content and administration of the programs. Alumni feedback forms are used by SABIT staff to record success information but on occasion are sent to alumni to be completed. The closing date for applications and supplemental materials is based upon the starting date of the program and is published, with the application, on the program's English-language Web site at <http://www.trade.gov/sabit>, and also on the Russian-language Web site at <http://www.sabitprogram.org>, if applicable. Pursuant to section 632(a) of the Foreign Assistance Act of 1961, as amended, funding for the programs will be provided by the Agency for International Development (AID).

II. Method of Collection

Applications are sent to program candidates via electronic mail, facsimile, or mail upon request. Applications are also available to be downloaded from the SABIT English and Russian language Web sites at <http://www.trade.gov/sabit> and <http://www.sabitprogram.org>. Feedback surveys are given to program participants at the completion of programs.

III. Data

OMB Control Number: 0625-0225.

Form Number(s): None.

Type of Review: Regular submission.

Affected Public: Individuals or households; business or other for-profit organizations.

Estimated Number of Respondents: 2,000.

Estimated Time per Response: 3 hours for application; 1 hour for program feedback form; 1 hour for alumni feedback form.

Estimated Total Annual Burden Hours: 40,500.

Estimated Total Annual Cost to Public: \$18,000.

IV. Request for Comments

Comments are invited on: (a) Whether the proposed collection of information is necessary for the proper performance of the functions of the agency, including whether the information shall have practical utility; (b) the accuracy of the agency's estimate of the burden (including hours and cost) of the proposed collection of information; (c) ways to enhance the quality, utility, and clarity of the information to be collected; and (d) ways to minimize the burden of the collection of information on respondents, including through the use of automated collection techniques or other forms of information technology.

Comments submitted in response to this notice will be summarized and/or included in the request for OMB approval of this information collection; they also will become a matter of public record.

Dated: March 14, 2011.

Gwellnar Banks,

Management Analyst, Office of the Chief Information Officer.

[FR Doc. 2011-6341 Filed 3-17-11; 8:45 am]

BILLING CODE 3510-HE-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-588-854]

Certain Tin Mill Products From Japan: Rescission of Antidumping Duty Administrative Review

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

SUMMARY: In response to a request from an interested party, the Department of Commerce (the Department) initiated an administrative review of the antidumping duty order covering certain tin mill products from Japan. The period of review is August 1, 2009, through July 31, 2010. Based on the withdrawal of request from U.S. Steel Corporation (U.S. Steel), we are now rescinding this administrative review.

DATES: *Effective Date:* March 18, 2011.

FOR FURTHER INFORMATION CONTACT: John Drury or Angelica Mendoza, AD/CVD Operations, Office 7, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW., Washington, DC 20230; telephone: (202) 482-0195 or (202) 482-3019 respectively.

SUPPLEMENTARY INFORMATION:

Background

On August 2, 2010, the Department published a notice announcing an opportunity for interested parties to request an administrative review of the antidumping duty order on certain tin mill products from Japan. See *Antidumping or Countervailing Duty Order, Finding, or Suspended Investigation; Opportunity To Request Administrative Review*, 75 FR 45094 (August 2, 2010). On August 31, 2010, U.S. Steel filed a request that the Department initiate an administrative review of the antidumping duty order on certain tin mill products from Japan with respect to JFE Steel Corporation, Kawasaki Steel Corporation, Nippon Steel Corporation, NKK Corporation, and Toyo Kohan Co., Ltd. Based on U.S. Steel's request, on September 29, 2010, the Department published a notice of initiation of the administrative review of the antidumping duty order on certain tin mill products from Japan. See *Initiation of Antidumping and Countervailing Duty Administrative Reviews and Requests for Revocation in Part*, 75 FR 60076 (September 29, 2010).

Scope of the Order

The merchandise subject to the antidumping duty order is certain tin mill products from Japan. The scope of this order includes tin mill flat-rolled products that are coated or plated with tin, chromium or chromium oxides. Flat-rolled steel products coated with tin are known as tin plate. Flat-rolled steel products coated with chromium or chromium oxides are known as tin-free steel or electrolytic chromium-coated steel. The scope includes all the noted tin mill products regardless of thickness, width, form (in coils or cut sheets), coating type (electrolytic or otherwise), edge (trimmed, untrimmed or further processed, such as scroll cut), coating thickness, surface finish, temper, coating metal (tin, chromium, chromium oxide), reduction (single-or double-reduced), and whether or not coated with a plastic material. All products that meet the written physical description are within the scope of this order unless specifically excluded. The following products, by way of example, are outside and/or specifically excluded from the scope of this order:

—Single reduced electrolytically chromium coated steel with a thickness 0.238 mm (85 pound base box) (+/- 10%) or 0.251 mm (90 pound base box) (+/- 10%) or 0.255 mm (+/- 10%) with 770 mm (minimum width) (+/- 1.588 mm) by 900 mm (maximum length if sheared) sheet size or 30.6875 inches

(minimum width) (+/- 1/16 inch) and 35.4 inches (maximum length if sheared) sheet size; with type MR or higher (per ASTM) A623 steel chemistry; batch annealed at T2 1/2 anneal temper, with a yield strength of 31 to 42 kpsi (214 to 290 Mpa); with a tensile strength of 43 to 58 kpsi (296 to 400 Mpa); with a chrome coating restricted to 32 to 150 mg/square meter; with a chrome oxide coating restricted to 6 to 25 mg/m with a modified 7B ground roll finish or blasted roll finish; with roughness average (Ra) 0.10 to 0.35 micrometers, measured with a stylus instrument with a stylus radius of 2 to 5 microns, a trace length of 5.6 mm, and a cut-off of 0.8 mm, and the measurement traces shall be made perpendicular to the rolling direction; with an oil level of 0.17 to 0.37 grams/base box as type BSO, or 2.5 to 5.5 mg/square meter as type DOS, or 3.5 to 6.5 mg/square meter as type ATBC; with electrical conductivity of static probe voltage drop of 0.46 volts drop maximum, and with electrical conductivity degradation to 0.70 volts drop maximum after stoving (heating to 400 degrees F for 100 minutes followed by a cool to room temperature).

—Single reduced electrolytically chromium- or tin-coated steel in the gauges of 0.0040 inch nominal, 0.0045 inch nominal, 0.0050 inch nominal, 0.0061 inch nominal (55 pound base box weight), 0.0066 inch nominal (60 pound base box weight), and 0.0072 inch nominal (65 pound base box weight), regardless of width, temper, finish, coating or other properties.

—Single reduced electrolytically chromium coated steel in the gauge of 0.024 inch, with widths of 27.0 inches or 31.5 inches, and with T-1 temper properties.

—Single reduced electrolytically chromium coated steel, with a chemical composition of 0.005% max carbon, 0.030% max silicon, 0.25% max manganese, 0.025% max phosphorous, 0.025% max sulfur, 0.070% max aluminum, and the balance iron, with a metallic chromium layer of 70–130 mg/square meter, with a chromium oxide layer of 5–30 mg/square meter, with a tensile strength of 260–440 N/square millimeter, with an elongation of 28–48%, with a hardness (HR-30T) of 40–58, with a surface roughness of 0.5–1.5 microns Ra, with magnetic properties of Bm (kg) 10.0 minimum, Br (kg) 8.0 minimum, Hc (Oe) 2.5–3.8, and Mu 1400 minimum, as measured with a Riken Denshi DC magnetic characteristic measuring machine, Model BHU-60.

—Bright finish tin-coated sheet with a thickness equal to or exceeding 0.0299 inch, coated to thickness of 3/4 pound (0.000045 inch) and 1 pound (0.00006 inch).

—Electrolytically chromium coated steel having ultra flat shape defined as oil can maximum depth of 5/64 inch (2.0 mm) and edge wave maximum of 5/64 inch (2.0 mm) and no wave to penetrate more than 2.0 inches (51.0 mm) from the strip edge and coilset or curling requirements of average maximum of 5/64 inch (2.0 mm) (based on six readings, three across each cut edge of a 24 inches (61 cm) long sample with no single reading exceeding 4/32 inch (3.2 mm) and no more than two readings at 4/32 inch (3.2 mm)) and (for 85 pound base box item only: Crossbuckle maximums of 0.001 inch (0.0025 mm) average having no reading above 0.005 inch (0.127 mm)), with a camber maximum of 1/4 inch (6.3 mm) per 20 feet (6.1 meters), capable of being bent 120 degrees on a 0.002 inch radius without cracking, with a chromium coating weight of metallic chromium at 100 mg/square meter and chromium oxide of 10 mg/square meter, with a chemistry of 0.13% maximum carbon, 0.60% maximum manganese, 0.15% maximum silicon, 0.20% maximum copper, 0.04% maximum phosphorous, 0.05% maximum sulfur, and 0.20% maximum aluminum, with a surface finish of Stone Finish 7C, with a DOS-A oil at an aim level of 2 mg/square meter, with not more than 15 inclusions/foreign matter in 15 feet (4.6 meters) (with inclusions not to exceed 1/32 inch (0.8 mm) in width and 3/64 inch (1.2 mm) in length), with thickness/temper combinations of either 60 pound base box (0.0066 inch) double reduced CADR8 temper in widths of 25.00 inches, 27.00 inches, 27.50 inches, 28.00 inches, 28.25 inches, 28.50 inches, 29.50 inches, 29.75 inches, 30.25 inches, 31.00 inches, 32.75 inches, 33.75 inches, 35.75 inches, 36.25 inches, 39.00 inches, or 43.00 inches, or 85 pound base box (0.0094 inch) single reduced CAT4 temper in widths of 25.00 inches, 27.00 inches, 28.00 inches, 30.00 inches, 33.00 inches, 33.75 inches, 35.75 inches, 36.25 inches, or 43.00 inches, with width tolerance of +/- 1/8 inch, with a thickness tolerance of +/- 0.0005 inch, with a maximum coil weight of 20,000 pounds (9071.0 kg), with a minimum coil weight of 18,000 pounds (8164.8 kg) with a coil inside diameter of 16 inches (40.64 cm) with

a steel core, with a coil maximum outside diameter of 59.5 inches (151.13 cm), with a maximum of one weld (identified with a paper flag) per coil, with a surface free of scratches, holes, and rust.

—Electrolytically tin coated steel having differential coating with 1.00 pound/base box equivalent on the heavy side, with varied coating equivalents in the lighter side (detailed below), with a continuous cast steel chemistry of type MR, with a surface finish of type 7B or 7C, with a surface passivation of 0.7 mg/square foot of chromium applied as a cathodic dichromate treatment, with coil form having restricted oil film weights of 0.3–0.4 grams/base box of type DOS-A oil, coil inside diameter ranging from 15.5 to 17 inches, coil outside diameter of a maximum 64 inches, with a maximum coil weight of 25,000 pounds, and with temper/coating/dimension combinations of: (1) CAT 4 temper, 1.00/.050 pound/base box coating, 70 pound/base box (0.0077 inch) thickness, and 33.1875 inch ordered width; or (2) CAT5 temper, 1.00/0.50 pound/base box coating, 75 pound/base box (0.0082 inch) thickness, and 34.9375 inch or 34.1875 inch ordered width; or (3) CAT5 temper, 1.00/0.50 pound/base box coating, 107 pound/base box (0.0118 inch) thickness, and 30.5625 inch or 35.5625 inch ordered width; or (4) CADR8 temper, 1.00/0.50 pound/base box coating, 85 pound/base box (0.0093 inch) thickness, and 35.5625 inch ordered width; or (5) CADR8 temper, 1.00/0.25 pound/base box coating, 60 pound/base box (0.0066 inch) thickness, and 35.9375 inch ordered width; or (6) CADR8 temper, 1.00/0.25 pound/base box coating, 70 pound/base box (0.0077 inch) thickness, and 32.9375 inch, 33.125 inch, or 35.1875 inch ordered width.

—Electrolytically tin coated steel having differential coating with 1.00 pound/base box equivalent on the heavy side, with varied coating equivalents on the lighter side (detailed below), with a continuous cast steel chemistry of type MR, with a surface finish of type 7B or 7C, with a surface passivation of 0.5 mg/square foot of chromium applied as a cathodic dichromate treatment, with ultra flat scroll cut sheet form, with CAT 5 temper with 1.00/0.10 pound/base box coating, with a lithograph logo printed in a uniform pattern on the 0.10 pound coating side with a clear protective coat, with both sides waxed to a level of 15–20 mg/216 sq. in., with ordered dimension combinations of (1) 75

- pound/base box (0.0082 inch) thickness and 34.9375 inch x 31.748 inch scroll cut dimensions; or (2) 75 pound/base box (0.0082 inch) thickness and 34.1875 inch x 29.076 inch scroll cut dimensions; or (3) 107 pound/base box (0.0118 inch) thickness and 30.5625 inch x 34.125 inch scroll cut dimension.
- Tin-free steel coated with a metallic chromium layer between 100–200 mg/square meter and a chromium oxide layer between 5–30 mg/square meter; chemical composition of 0.05% maximum carbon, 0.03% maximum silicon, 0.60% maximum manganese, 0.02% maximum phosphorous, and 0.02% maximum sulfur; magnetic flux density (“Br”) of 10 kg minimum and a coercive force (“Hc”) of 3.8 Oe minimum.
- Tin-free steel laminated on one or both sides of the surface with a polyester film, consisting of two layers (an amorphous layer and an outer crystal layer), that contains no more than the indicated amounts of the following environmental hormones: 1 mg/kg BADGE (BisPhenol A Di-glycidyl Ether), 1 mg/kg BFDGE (BisPhenol F Di-glycidyl Ether), and 3 mg/kg BPA (BisPhenol A).
- The merchandise subject to this order is classified in the Harmonized Tariff Schedule of the United States (“HTSUS”), under HTSUS subheadings 7210.11.0000, 7210.12.0000, 7210.50.0000, 7212.10.0000, and 7212.50.0000 if of non-alloy steel and under HTSUS subheadings 7225.99.0090, and 7226.99.0180 if of alloy steel. Although the subheadings are provided for convenience and customs purposes, our written description of the scope of this order is dispositive.

Rescission of Review

In accordance with 19 CFR 351.213(d)(1), the Department will rescind an administrative review, “in whole or in part, if a party that requested a review withdraws the request within 90 days of the date of publication of notice of initiation of the requested review. The Secretary may extend this time limit if the Secretary decides that it is reasonable to do so.” On February 8, 2011, U.S. Steel withdrew its request for a review of the order with respect to JFE Steel Corporation, Kawasaki Steel Corporation, Nippon Steel Corporation, NKK Corporation, and Toyo Kohan Co., Ltd. Although the party submitted a letter withdrawing their review request after the 90-day regulatory deadline, the Department finds it is reasonable to

extend the deadline for withdrawing the review request because it has not yet devoted significant time or resources to the review.

Because of the withdrawal of the request for review and because we received no other requests for review, we are rescinding the administrative review of the order with respect to JFE Steel Corporation, Kawasaki Steel Corporation, Nippon Steel Corporation, NKK Corporation, and Toyo Kohan Co., Ltd. This rescission is in accordance with 19 CFR 351.213(d)(1).

Assessment

The Department will instruct U.S. Customs and Border Protection (“CBP”) to assess antidumping duties on all appropriate entries. For these five companies, the antidumping duties shall be assessed at rates equal to the cash deposit of estimated antidumping duties required at the time of entry, or withdrawal from warehouse, for consumption, in accordance with 19 CFR 351.212(c)(1)(i). The Department intends to issue appropriate assessment instructions to CBP 15 days after publication of this notice.

Notifications

This notice serves as a final reminder to importers of their responsibility under 19 CFR 351.402(f) to file a certificate regarding the reimbursement of antidumping duties prior to liquidation of the relevant entries during this review period. Failure to comply with this requirement could result in the Department’s presumption that reimbursement of antidumping duties occurred and the subsequent assessment of doubled antidumping duties.

This notice also serves as a reminder to parties subject to administrative protective order (APO) of their responsibility concerning destruction of proprietary information disclosed under an APO in accordance with 19 CFR 351.305(a)(3). Timely written notification of the destruction of APO materials or conversion to judicial protective order is hereby requested. Failure to comply with the regulations and terms of an APO is a violation which is subject to sanction.

This notice is published in accordance with sections 751(a)(1) and 777(i)(1) of the Tariff Act of 1930, as amended, and 19 CFR 351.213(d)(4).

Dated: March 8, 2011.

Christian Marsh,

Deputy Assistant Secretary for Antidumping and Countervailing Duty Operations.

[FR Doc. 2011–6015 Filed 3–17–11; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

Executive-Led Trade Mission to Afghanistan

AGENCY: International Trade Administration, Department of Commerce.

ACTION: Notice.

I. Mission Description

The United States Department of Commerce’s International Trade Administration is organizing a business development trade mission to Kabul, Afghanistan in September 2011. This mission will be led by a Senior Commerce Department official. Targeted sectors include: Construction (including engineering, architecture, transportation and logistics, and infrastructure); mining (including equipment, technology, and services); agribusiness; and information and communications technology. The mission’s goal is to help U.S. companies explore long-term business opportunities in Afghanistan and enhance U.S.-Afghan commercial relations by providing U.S. participants with first-hand market information, access to government decision makers as well as one-on-one meetings with business contacts, including potential agents, distributors, and partners, to position themselves to enter or expand their presence in the targeted sectors.

II. Commercial Setting

The Government of the Islamic Republic of Afghanistan (GIROA) is taking steps to develop its market economy and increase both domestic and foreign private investment. GIROA continues to develop legal and administrative regulatory frameworks that will lead to a market more conducive to trade, investment and private sector development. For example, Afghanistan adopted an investment law that allows investments to be 100% foreign-owned. Additionally, on October 28, 2010, Afghanistan and Pakistan signed the Afghanistan Pakistan Transit Trade Agreement (APTTA), allowing Afghan container trucks to drive through Pakistan to the Indian border, and also to port cities such as Karachi.

After 30 years of war reconstruction and development efforts are required to grow and stabilize Afghanistan’s economy. The GIROA is committed to promoting economic development, increasing production and earnings, promoting technology transfer, improving national prosperity and advancing Afghans’ standard of living in