

Date	Document	ADAMS Accession No./Web link/ <b>Federal Register</b> citation
January 28, 1971 .....	SECY-R-143, "Amendment to Title 10 of the Code of Federal Regulations (10 CFR) Section 50—General Design Criteria for Nuclear Power Plants".	ML072420278.
July 11, 1967 .....	General Design Criteria for Nuclear Power Plant Construction Permits.	32 FR 10213.
May 1980 .....	NUREG-75/087, Standard Review Plan for the Review of Safety Analysis Reports for Nuclear Power Plants: LWR Edition.	ML042080088.
May 2010 .....	NUREG-0800, Standard Review Plan for the Review of Safety Analysis Reports for Nuclear Power Plants: LWR Edition, Section 8.2, "Offsite Power System".	ML100740246.
October 1975 .....	WASH-1400 (NUREG-75/014), Reactor Safety Study: An Assessment of Accident Risks in U.S. Commercial Nuclear Power Plants.	ML072350618.
June 1988 .....	NUREG-1032, "Evaluation of Station Blackout Accidents at Nuclear Power Plants, Technical Findings Related to Unresolved Safety Issue A-44".	Accessible from U. S. Department of Energy's Information Bridge at <a href="http://www.osti.gov/bridge/purl.cover.jsp?purl=/5122568-gvK0cy/5122568.pdf">http://www.osti.gov/bridge/purl.cover.jsp?purl=/5122568-gvK0cy/5122568.pdf</a> .
March 21, 1986 .....	Notice of Proposed Rulemaking: Station Blackout (10 CFR 50.63) ..	51 FR 9829.
June 21, 1988, Sept. 22, 1998	Station Blackout (10 CFR 50.63) .....	53 FR 23203, 63 FR 50480.
March 27, 2009 .....	10 CFR 50.54(hh)(2) .....	74 FR 13969.
March 23, 2011 .....	Tasking Memorandum from Chairman Gregory B. Jaczko to the Executive Director for Operations (COMGBJ-11-0002): NRC Actions Following the Events in Japan.	ML110950110.
November 2011 .....	INPO-11-005, "Special Report on the Nuclear Accident at the Fukushima Dai-ichi Nuclear Power Station".	ML11347A454.
March 15, 2011 .....	PRM-50-96 .....	<a href="http://www.regulations.gov">http://www.regulations.gov</a> by searching on Docket ID NRC-2011-0069.
February 20, 1971 .....	Amendment to 10 CFR Part 50—General Design Criteria For Nuclear Power Plants.	76 FR 26223. 36 FR 3256.
July 6, 1970 .....	Status Report On General Design Criteria .....	ML003726549.
August 28, 2007 .....	Appendix A to Part 50—General Design Criteria for Nuclear Power Plants.	72 FR 49505.
April 1, 2002 .....	Staff Guidance on Scoping of Equipment Relied on to Meet the Requirements of the Station Blackout (SBO) Rule (10 CFR 50.63) for License Renewal (10 CFR 54.4(a)(3)).	ML020920464.
August 28, 2007 .....	Final Rule: Licenses, Certifications, and Approvals for Nuclear Power Plants.	72 FR 49352.
December 16, 2011 .....	NEI Submittal of An Integrated, Safety-Focused Approach to Expediting Implementation of Fukushima Daiichi Lessons Learned.	ML11353A008.
October 13, 2011 .....	Initial ACRS Review of: (1) the NRC Near-Term Task Force Report on Fukushima and (2) Staff's Recommended Actions to be Taken Without Delay.	ML11284A136.
August 1988 .....	NRC Regulatory Guide 1.155, "Station Blackout" .....	ML003740034.
November 1987 .....	"Guidelines and Technical Bases for NUMARC Initiatives Addressing Station Blackout at Light Water Reactors," NUMARC 8700.	ML12074A007.

Dated at Rockville, Maryland, this 12th day of March 2012.

For the Nuclear Regulatory Commission.

**R.W. Borchardt,**

*Executive Director for Operations.*

[FR Doc. 2012-6665 Filed 3-19-12; 8:45 am]

**BILLING CODE 7590-01-P**

## DEPARTMENT OF ENERGY

### 10 CFR Part 430

[Docket No. EERE-2011-BT-NOA-0013]

#### Energy Conservation Program: Data Collection and Comparison With Forecasted Unit Sales of Five Lamp Types

**AGENCY:** Office of Energy Efficiency and Renewable Energy, Department of Energy.

**ACTION:** Notice of data availability.

**SUMMARY:** The U.S. Department of Energy (DOE) is informing the public of its collection of shipment data and creation of spreadsheet models to provide comparisons between actual and benchmark estimate unit sales of five lamp types (*i.e.*, rough service lamps, vibration service lamps, 3-way incandescent lamps, 2,601–3,300 lumen general service incandescent lamps, and shatter-resistant lamps), which are currently exempt from energy conservation standards. As the actual sales do not exceed the forecasted estimate by 100 percent for any lamp type (*i.e.*, the threshold triggering a rulemaking for an energy conservation standard for that lamp type has not been exceeded), DOE has determined that no regulatory action is necessary at this

time. However, DOE will continue to track sales data for these exempted lamps. Relating to this activity, DOE has prepared, and is making available on its Web site, a spreadsheet showing the comparisons of anticipated versus actual sales, as well as the model used to generate the original sales estimates. The spreadsheet is available at: [http://www1.eere.energy.gov/buildings/appliance\\_standards/residential/five\\_lamp\\_types.html](http://www1.eere.energy.gov/buildings/appliance_standards/residential/five_lamp_types.html).

**FOR FURTHER INFORMATION CONTACT:** Ms. Lucy deButts, U.S. Department of Energy, Office of Energy Efficiency and Renewable Energy, Building Technologies, EE-2J, 1000 Independence Avenue SW., Washington, DC 20585-0121. Telephone: (202) 287-1604. Email: [Lucy.Debutts@ee.doe.gov](mailto:Lucy.Debutts@ee.doe.gov).

Mr. Eric Stas, U.S. Department of Energy, Office of the General Counsel, GC-71, 1000 Independence Avenue SW., Washington, DC 20585-0121. Telephone: (202) 586-9507. Email: [Eric.Stas@hq.doe.gov](mailto:Eric.Stas@hq.doe.gov).

#### SUPPLEMENTARY INFORMATION:

##### Table of Contents

- I. Background
- II. Definitions
  - A. Rough Service Lamps
  - B. Vibration Service Lamps
  - C. Three-Way Incandescent Lamps
  - D. 2,601–3,300 Lumen General Service Incandescent Lamps
  - E. Shatter-Resistant Lamps
- III. Comparison Methodology
- IV. Comparison Results
  - A. Rough Service Lamps
  - B. Vibration Service Lamps
  - C. Three-Way Incandescent Lamps
  - D. 2,601–3,300 Lumen General Service Incandescent Lamps
  - E. Shatter-Resistant Lamps
- V. Conclusion

##### I. Background

The Energy Independence and Security Act of 2007 (EISA 2007; Pub. L. 110-140) was enacted on December 19, 2007. Among the requirements of subtitle B (Lighting Energy Efficiency) of title III of EISA 2007 were provisions directing DOE to collect, analyze, and monitor unit sales of five lamp types (*i.e.*, rough service lamps, vibration service lamps, 3-way incandescent lamps, 2,601–3,300 lumen general service incandescent lamps, and shatter-resistant lamps). In relevant part, section 321(a)(3)(B) of EISA 2007 amended section 325(l) of the Energy Policy and Conservation Act of 1975 (EPCA) by adding paragraph (4)(B), which generally directs DOE, in consultation with the National Electrical Manufacturers Association (NEMA), to: (1) collect unit sales data for each of the five lamp types for calendar years 1990 through 2006 in order to determine the historical growth rate for each lamp type; and (2) construct a model for each of the five lamp types based on coincident economic indicators that closely match the historical annual growth rates of each lamp type to provide a neutral comparison benchmark estimate of future unit sales. (42 U.S.C. 6295(l)(4)(B)) Section 321(a)(3)(B) of EISA 2007 also amends section 325(l) of EPCA by adding paragraph (4)(C), which, in relevant part, directs DOE to collect unit sales data for calendar years 2010 through 2025, in consultation with NEMA, for each of the five lamp types. DOE must then compare the actual lamp sales in that year with the benchmark estimate, determine if the unit sales projection

has been exceeded, and issue the findings within 90 days after the end of the analyzed calendar year. (42 U.S.C. 6295(l)(4)(C)).

On December 18, 2008, DOE issued a notice of data availability (NODA) for the *Report on Data Collection and Estimated Future Unit Sales of Five Lamp Types* (hereafter the “2008 analysis”),<sup>1</sup> which was published in the *Federal Register* on December 24, 2008. 73 FR 79072. The 2008 analysis presented the 1990 through 2006 shipment data collected in consultation with NEMA, the spreadsheet model DOE constructed for each lamp type, and the benchmark unit sales estimates for 2010 through 2025. On April 4, 2011, DOE published a NODA in the *Federal Register* (hereafter the “2010 comparison”) announcing the availability of updated spreadsheet models presenting the benchmark estimates from the 2008 analysis and the collected sales data from 2010 for the first annual comparison.<sup>2</sup> 76 FR 18425. Today’s NODA presents the second annual comparison; specifically, section IV of this report compares the actual unit sales against benchmark unit sales estimates for 2011.

EISA 2007 also amends section 325(l) of EPCA by adding paragraphs (4)(D) through (4)(H) which state that if DOE finds that the unit sales for a given lamp type in any year between 2010 and 2025 exceed the benchmark estimate of unit sales by at least 100 percent (*i.e.*, more than double the anticipated sales), then DOE must take regulatory action to establish an energy conservation standard for such lamps. (42 U.S.C. 6295(l)(4)(D)–(H)) For 2,601–3,300 lumen general service incandescent lamps, DOE must adopt a statutorily-prescribed energy conservation standard, and for the other four types of lamps, the statute requires DOE to initiate an accelerated rulemaking to establish energy conservation standards. If the Secretary does not complete the accelerated rulemakings within one year of the end of the previous calendar year, there is a “backstop requirement” for each lamp type, which would establish energy conservation standard levels and related requirements by statute. *Id.*

As in the 2008 analysis and 2010 comparison, DOE uses manufacturer shipments as a surrogate for unit sales

in this NODA because manufacturer shipment data is tracked and aggregated by the trade organization, NEMA. DOE believes that annual shipments track closely with actual unit sales of these five lamp types, as DOE presumes that retailer inventories remain constant from year to year. DOE believes this is a reasonable assumption because the markets for these five lamp types have existed for many years, thereby enabling manufacturers and retailers to establish appropriate inventory levels that reflect market demand. Furthermore, in the long-run, unit sales could not increase in any one year without manufacturer shipments increasing either that year or the following one. In either case, increasing unit sales must eventually result in increasing manufacturer shipments. This is the same methodology presented in DOE’s 2008 analysis and 2010 comparison, and the Department did not receive any comments challenging this assumption or the general approach.

##### II. Definitions

###### A. Rough Service Lamps

Section 321(a)(1)(B) of EISA 2007 amended section 321(30) of EPCA by adding the definition of a “rough service lamp.” The statutory definition reads as follows: “The term ‘rough service lamp’ means a lamp that—(i) has a minimum of 5 supports with filament configurations that are C-7A, C-11, C-17, and C-22 as listed in Figure 6–12 of the 9th edition of the IESNA [Illuminating Engineering Society of North America] Lighting handbook, or similar configurations where lead wires are not counted as supports; and (ii) is designated and marketed specifically for ‘rough service’ applications, with—(I) the designation appearing on the lamp packaging; and (II) marketing materials that identify the lamp as being for rough service.” (42 U.S.C. 6291(30)(X)).

As noted above, rough service incandescent lamps must have a minimum of five filament support wires (not counting the two connecting leads at the beginning and end of the filament), and must be designated and marketed for “rough service” applications. This type of incandescent lamp is typically used in applications where the lamp would be subject to mechanical shock or vibration while it is operating. Standard incandescent lamps have only two support wires (which also serve as conductors), one at each end of the filament coil. When operating (*i.e.*, when the tungsten filament is glowing so hot that it emits light), a standard incandescent lamp’s filament is brittle, and rough service

<sup>1</sup> The Report on the 2008 analysis is available on the DOE Web site at: [www1.eere.energy.gov/buildings/appliance\\_standards/residential/pdfs/five\\_lamp\\_types\\_report.pdf](http://www1.eere.energy.gov/buildings/appliance_standards/residential/pdfs/five_lamp_types_report.pdf).

<sup>2</sup> These 2010 spreadsheet models are also available on the DOE Web site at: [http://www1.eere.energy.gov/buildings/appliance\\_standards/residential/docs/five\\_lamp\\_types\\_2010\\_shipment\\_comparison.xlsx](http://www1.eere.energy.gov/buildings/appliance_standards/residential/docs/five_lamp_types_2010_shipment_comparison.xlsx).

applications could cause it to break prematurely. To address this problem, lamp manufacturers developed lamp designs that incorporate additional support wires along the length of the filament to ensure that it has support not just at each end, but at several other points as well. The additional support protects the filament during operation and enables longer operating life for incandescent lamps in rough service applications. Typical applications for these rough service lamps might include commercial hallways and stairwells, gyms, storage areas, and security areas.

### B. Vibration Service Lamps

Section 321(a)(1)(B) of EISA 2007 amended section 321(30) of EPCA by adding the definition of a “vibration service lamp.” The statutory definition reads as follows: “The term ‘vibration service lamp’ means a lamp that—(i) Has filament configurations that are C–5, C–7A, or C–9, as listed in Figure 6–12 of the 9th Edition of the IESNA Lighting Handbook or similar configurations; (ii) has a maximum wattage of 60 watts; (iii) is sold at retail in packages of 2 lamps or less; and (iv) is designated and marketed specifically for vibration service or vibration-resistant applications, with—(I) the designation appearing on the lamp packaging; and (II) marketing materials that identify the lamp as being vibration service only.” (42 U.S.C. 6291(30)(AA))

The statute mentions three examples of filament configurations for vibration service lamps in Figure 6–12 of the *IESNA Lighting Handbook*, one of which (*i.e.*, C–7A) is also listed in the statutory definition of “rough service lamp.” The definition of “vibration service lamp” requires that such lamps have a maximum wattage of 60 watts and be sold at a retail level in packages of two lamps or fewer. Similar to rough service lamps, vibration service lamps must be designated and marketed for vibration service or vibration-resistant applications. As the name suggests, this type of incandescent lamp is generally used in applications where the incandescent lamp would be subject to a continuous low level of vibration, such as in a ceiling fan light kit. In such applications, standard incandescent lamps without additional filament support wires may not achieve the full rated life, because the filament wire is brittle and would be subject to breakage at typical operating temperature. To address this problem, lamp manufacturers typically use a more malleable tungsten filament to avoid damage and short circuits between coils.

### C. Three-Way Incandescent Lamps

Section 321(a)(1)(B) of EISA 2007 amended section 321(30) of EPCA by adding the definition of a “3-way incandescent lamp.” The statutory definition reads as follows: “The term ‘3-way incandescent lamp’ includes an incandescent lamp that—(i) employs 2 filaments, operated separately and in combination, to provide 3 light levels; and (ii) is designated on the lamp packaging and marketing materials as being a 3-way incandescent lamp.” (42 U.S.C. 6291(30)(Y)).

Three-way lamps are commonly found in wattage combinations such as 50, 100, and 150 watts or 30, 70, and 100 watts. These lamps use two filaments (*e.g.*, a 30-watt and a 70-watt filament) and can be operated separately or together to produce three different lumen outputs (*e.g.*, 305 lumens with one filament, 995 lumens with the other, or 1,300 lumens using the filaments together). When used in three-way sockets, these lamps allow users to control the light level. Three-way incandescent lamps are typically used in residential multi-purpose areas, where consumers may adjust the light level to be appropriate for the task they are performing.

### D. 2,601–3,300 Lumen General Service Incandescent Lamps

The statute does not provide a definition of “2,601–3,300 Lumen General Service Incandescent Lamps”; however, DOE is interpreting this term to be a general service incandescent lamp<sup>3</sup> that emits between 2,601 and 3,300 lumens. In this lumen range, the wattages of covered general service incandescent lamps are between 140 and 170 watts. Within that range, the only commonly made lamp that meets other general service incandescent lamp criteria is rated at 150 watts. Should other rated wattages enter the market that fall within this lumen range, they will be immediately recognizable because as required by the Energy Policy Act of 1992, Public Law 102–486, all general service incandescent lamps must be labeled with lamp lumen output.<sup>4</sup> These lamps are used in

<sup>3</sup> “General service incandescent lamp” is defined as a standard incandescent or halogen type lamp that—(I) Is intended for general service applications; (II) has a medium screw base; (III) has a lumen range of not less than 310 lumens and not more than 2,600 lumens; and (IV) is capable of being operated at a voltage range at least partially within 110 and 130 volts. (42 U.S.C. 6291(30)(D)).

<sup>4</sup> The Federal Trade Commission issued the lamp labeling requirements in 1994 (*see* 59 FR 25176 (May 13, 1994)). Further amendments were made to the lamp labeling requirements in 2007 (*see* 16 CFR 305.15(b); 72 FR 49948, 49971–72 (August 29, 2007)). The package must display the lamp’s light

general service applications when high light output is needed.

### E. Shatter-Resistant Lamps

Section 321(a)(1)(B) of EISA 2007 amended section 321(30) of EPCA by adding the definition of a “shatter-resistant lamp, shatter-proof lamp, or shatter-protected lamp.” The statutory definition reads as follows: “The terms ‘shatter-resistant lamp,’ ‘shatter-proof lamp,’ and ‘shatter-protected lamp’ mean a lamp that—(i) has a coating or equivalent technology that is compliant with [National Sanitation Foundation/American National Standards Institute] NSF/ANSI 51 and is designed to contain the glass if the glass envelope of the lamp is broken; and (ii) is designated and marketed for the intended application, with—(I) the designation on the lamp packaging; and (II) marketing materials that identify the lamp as being shatter-resistant, shatter-proof, or shatter-protected.” (42 U.S.C. 6291(30)(Z)) Although the definition provides three names commonly used to refer to these lamps, DOE simply refers to them collectively as “shatter-resistant lamps.”

Shatter-resistant lamps incorporate a special coating designed to prevent glass shards from being strewn if a lamp’s glass envelope breaks. Shatter-resistant lamps incorporate a coating compliant with industry standard NSF/ANSI 51,<sup>5</sup> “Food Equipment Materials,” and are labeled and marketed as shatter-resistant, shatter-proof, or shatter-protected. The coatings protect the lamp from breakage in applications subject to heat and thermal shock that may occur from water, sleet, snow, soldering, or welding.

### III. Comparison Methodology

In the 2008 analysis, DOE reviewed each of the five sets of shipment data that were collected in consultation with NEMA and applied two curve fits to generate unit sales estimates for the five lamp types after calendar year 2006. One curve fit applied a linear regression to the historical data and extends that line into the future. The other curve fit applied an exponential growth function to the shipment data and projects unit sales into the future. For this calculation, linear regression treats the year as a dependent variable and shipments as the independent variable. The linear regression curve fit is modeled by minimizing the differences

output (in lumens), energy use (in watts), and lamp life (in hours).

<sup>5</sup> NSF/ANSI 51 applies specifically to materials and coatings used in the manufacturing of equipment and objects destined for contact with foodstuffs.

among the data points and the best curve-fit linear line using the least squares function.<sup>6</sup> The exponential curve fit is also a regression function and uses the same least squares function to find the best fit. For some data sets, an exponential curve provides a better characterization of the historical data, and, therefore, a better projection of the future data.

For 3-way incandescent lamps, 2,601–3,300 lumen general service incandescent lamps, and shatter-resistant lamps, DOE found that the linear regression and exponential growth curve fits produced nearly the same estimates of unit sales (*i.e.*, the difference between the two forecasted values was less than 1 or 2 percent). However, for rough service and vibration service lamps, the linear regression curve fit projects lamp unit sales would decline to zero for both lamp types by 2018. In contrast, the exponential growth curve fit projected a more gradual decline in unit sales, such that lamps will still be sold beyond 2018, and it was, therefore, considered the more realistic forecast. While DOE would be satisfied that either the linear regression or exponential growth spreadsheet model would generate a reasonable benchmark unit sales estimate for 3-way incandescent lamps, 2,601–3,300 lumen general service incandescent lamps, and shatter-resistant lamps, DOE is selecting the exponential growth curve fit for these lamp types for consistency with the selection made for rough service and vibration service lamps.<sup>7</sup> DOE examines the benchmark unit sales estimates and actual sales for each of the five lamp types in the following section and also makes the comparisons available in a spreadsheet online at: [http://www1.eere.energy.gov/buildings/appliance\\_standards/residential/five\\_lamp\\_types.html](http://www1.eere.energy.gov/buildings/appliance_standards/residential/five_lamp_types.html).

#### IV. Comparison Results

##### A. Rough Service Lamps

For rough service lamps, the exponential growth forecast projected the benchmark unit sales estimate for 2011 to be 6,080,000 units. The NEMA-

provided shipment data reported shipments of 6,829,000 rough service lamps in 2011. As this finding exceeds the estimate by only 12.3 percent, DOE will continue to track rough service lamp sales data and will not initiate regulatory action for this lamp type at this time.

##### B. Vibration Service Lamps

For vibration service lamps, the exponential growth forecast projected the benchmark unit sales estimate for 2011 to be 3,176,000 units. The NEMA-provided shipment data reported shipments of 914,000 vibration service lamps in 2011. As this finding is only 28.8 percent of the estimate, DOE will continue to track vibration service lamp sales data and will not initiate regulatory action for this lamp type at this time.

##### C. Three-Way Incandescent Lamps

For 3-way incandescent lamps, the exponential growth forecast projected the benchmark unit sales estimate for 2011 to be 50,652,000 units. The NEMA-provided shipment data reported shipments of 31,619,000 3-way incandescent lamps in 2011. As this finding is only 62.4 percent of the estimate, DOE will continue to track 3-way incandescent lamp sales data and will not initiate regulatory action for this lamp type at this time.

##### D. 2,601–3,300 Lumen General Service Incandescent Lamps

For 2,601–3,300 lumen general service incandescent lamps, the exponential growth forecast projected the benchmark unit sales estimate for 2011 to be 33,913,000 units. The NEMA-provided shipment data reported shipments of 9,878,000 2,601–3,300 lumen general service incandescent lamps in 2011. As this finding is 29.1 percent of the estimate, DOE will continue to track 2,601–3,300 lumen general service incandescent lamp sales data and will not initiate regulatory action for this lamp type at this time.

##### E. Shatter-Resistant Lamps

For shatter-resistant lamps, the exponential growth forecast projected the benchmark unit sales estimate for 2011 to be 1,659,000 units. The NEMA-provided shipment data reported shipments of 1,210,000 shatter-resistant lamps in 2011. As this finding is only 72.9 percent of the estimate, DOE will continue to track shatter-resistant lamp sales data and will not initiate regulatory action for this lamp type at this time.

#### V. Conclusion

None of the shipments for the rough service lamps, vibration service lamps, 3-way incandescent lamps, 2,601–3,300 lumen general service incandescent lamps, or shatter-resistant lamps crossed the statutory threshold for a standard. DOE will monitor the situation for these five currently exempted lamp types and will reassess 2012 sales by March 31, 2013, in order to determine whether energy conservation standards rulemaking is required, consistent with 42 U.S.C. 6295(l)(4)(D)–(H).

Issued in Washington, DC, on March 6, 2012.

**Kathleen B. Hogan,**

*Deputy Assistant Secretary for Energy Efficiency, Energy Efficiency and Renewable Energy.*

[FR Doc. 2012–6746 Filed 3–19–12; 8:45 am]

**BILLING CODE 6450–01–P**

---

#### DEPARTMENT OF TRANSPORTATION

##### Federal Aviation Administration

##### 14 CFR Part 39

[Docket No. FAA–2012–0269; Directorate Identifier 2011–NM–105–AD]

RIN 2120–AA64

##### Airworthiness Directives; Dassault Aviation Airplanes

**AGENCY:** Federal Aviation Administration (FAA), DOT.

**ACTION:** Notice of proposed rulemaking (NPRM).

**SUMMARY:** We propose to adopt a new airworthiness directive (AD) for certain Dassault Aviation Model FALCON 7X airplanes. This proposed AD was prompted by a report that a passenger oxygen pipe at frame 10 was chafing against the forward lavatory rear structure, raising the risk of the oxygen pipe developing a crack. This proposed AD would require modifying the routing of and, if necessary, replacing, the oxygen pipe. We are proposing this AD to prevent rupture of the oxygen pipe which, in case of a cabin depressurization, would impair operation of the passenger oxygen distribution system.

**DATES:** We must receive comments on this proposed AD by May 4, 2012.

**ADDRESSES:** You may send comments by any of the following methods:

- *Federal eRulemaking Portal:* Go to <http://www.regulations.gov>. Follow the instructions for submitting comments.
- *Fax:* (202) 493–2251.
- *Mail:* U.S. Department of Transportation, Docket Operations, M–

<sup>6</sup> The least squares function is an analytical tool that DOE uses to minimize the sum of the squared residual differences between the actual historical data points and the modeled value (*i.e.*, the linear curve fit). In minimizing this value, the resulting curve fit will represent the best fit possible to the data provided.

<sup>7</sup> This selection is consistent with the 2010 comparison. See DOE's 2008 forecast spreadsheet models of the lamp types for greater detail of the estimates. The spreadsheet models are available at: [www1.eere.energy.gov/buildings/appliance\\_standards/residential/docs/five\\_lamp\\_types\\_models.xls](http://www1.eere.energy.gov/buildings/appliance_standards/residential/docs/five_lamp_types_models.xls).