

1002-20-4706

January 25, 1953

2233

Third
Progress Report
on

FIRE DETECTION IN AIRCRAFT ENGINE NOZZLES

by

C. S. McCamy and Wm. F. Roeser

Covering period 25 October, 1952 to 25 January, 1953

for
Headquarters
Wright Air Development Center
Wright-Patterson Air Force Base
Dayton, Ohio
Project No. 52-660A45
WCLEM-3

2233

2000

January 22, 1953

1005-20-1780

Project No. 52-20012
ON

FIVE EXTENSION IN AIRCRAFT ENGINE DEVELOPMENT

BY

C. S. McCarty and W. E. McCarty

Governing Period 25 October, 1952 to 25 January, 1953

Project No. 52-20012
WOLFE-3
Project-Engineer Air Force Base
Wright-Patterson
Headquarters
for

Fire Detection in Aircraft Engine Nacelles

by

C. S. McCamy and Wm. F. Roeser

1. Summary

Work on the construction of a spectroradiometer to be used in analyzing the radiation from flames has been delayed because of late delivery of some of the essential components. These have been delivered recently and are now being tested and calibrated.

Some study is being made of the technical feasibility of the development of fire detection systems in which the change in the permeability of a ferromagnetic material at the Curie temperature is utilized. Several preliminary experiments, using Ferromagnetic Ceramics as the cores of inductance coils, indicate that these materials might be used to advantage in a "spot" fire detection system.

2. Radiation from Flames

Work is continuing on the construction of a spectroradiometer to be used in analyzing the emissions from flames. Some delay has been involved in procuring suitable filters and radiation detectors for the instrument but these have now been received. The various components are being tested and calibrated.

The spectral region below 0.29μ is of special interest since practically no radiation of these wavelengths is found in the emissions from hot engine parts or in the sunlight reaching the earth's surface. The instrument referred to above employs photomultiplier tubes and a photoconductive cell for studying this spectral region as well as others. A flame detector operating on radiation of these wavelengths is expected to have little

"background noise" or interference. In view of the fact that the use of Geiger-Muller tubes has been proposed for this specific purpose, such a tube has been obtained and plans are being made to study some of the problems inherent in its application to fire detection. Factors to be considered would be: transmittance of oil films, stability of the counter tube, quenching characteristics of the tube, and the size, weight, and maintenance requirements of accessory equipment.

1. THEORY

Some study is being made of the technical feasibility of the development of fire detection systems in which the output in the permeability of a thermodynamic material at the same temperature is utilized. Several preliminary experiments, with ferro-synthetic materials as the source of induced color, indicate that these materials might be used to advantage in a "passive" fire detection system.

Work is continuing on the construction of a new laboratory to be used in analyzing the emissions from flares. Some preliminary work has been done in processing satellite filtered radiation data for the instrument but more work is needed. The various components are being tested and calibrated.

The electrical resistance of the specimen is measured by means of a Wheatstone bridge. The specimen is placed in a vacuum chamber and the pressure is maintained at a constant value. The temperature of the specimen is measured by means of a thermocouple. The electrical resistance of the specimen is measured by means of a Wheatstone bridge. The specimen is placed in a vacuum chamber and the pressure is maintained at a constant value. The temperature of the specimen is measured by means of a thermocouple. The electrical resistance of the specimen is measured by means of a Wheatstone bridge. The specimen is placed in a vacuum chamber and the pressure is maintained at a constant value. The temperature of the specimen is measured by means of a thermocouple.

Combustion studies were made to determine the type of flame that might be expected in an aircraft engine nacelle as the result of burning aircraft hydraulic fluid or lubricating oil. The observations indicate that such flames are almost certain to be luminous flames typical of open gasoline fires or very rich fuel-air mixtures. The characteristic yellow color persisted in the diffusion flames even when they were subjected to high velocity air streams almost sufficient to extinguish them.

3. Curie Temperature Fire Detection Systems

While the work on the study of flame characteristics was being delayed by procurement difficulties, some study was made of the technical feasibility of the development of fire detection systems in which the change in the permeability of a ferromagnetic material at the Curie temperature is utilized. Particular attention was directed toward the use of Ferromagnetic Ceramics because it is reported that these materials undergo a much sharper change in permeability at the Curie temperature than do metals.

Several preliminary experiments, using Ferromagnetic Ceramics as the cores of inductance coils, indicate that these materials might be used to advantage in a "spot" fire detection system. However, little is known regarding the degree to which these materials can be reproduced with specified magnetic properties. Further experiments with these materials are planned.

4. Financial Condition

Expenditures and commitments on this project:

April 25 through September 30, 1952	\$ 6,968.82
October 1 through December 31, 1952	<u>3,764.55</u>
Total through December 31, 1952	<u><u>10,733.37</u></u>

Comparison between the two is determined by the type of time
base which is required in an experiment. In the case of the
type of time base which is required in an experiment, the
comparison is made by the type of time base which is required
in an experiment. The comparison is made by the type of time
base which is required in an experiment. The comparison is made
by the type of time base which is required in an experiment.

3. Comparison between the two types of time base

While the work on the type of time base which is required
in an experiment is being done, the type of time base which
is required in an experiment is being determined. The type of
time base which is required in an experiment is being determined
by the type of time base which is required in an experiment.
The type of time base which is required in an experiment is
being determined by the type of time base which is required
in an experiment. The type of time base which is required
in an experiment is being determined by the type of time base
which is required in an experiment.

Several preliminary experiments were conducted in order to
determine the type of time base which is required in an
experiment. The type of time base which is required in an
experiment is being determined by the type of time base which
is required in an experiment. The type of time base which is
required in an experiment is being determined by the type of
time base which is required in an experiment.

4. Preliminary results

Experiment	Time base
Experiment 1	Time base 1
Experiment 2	Time base 2
Experiment 3	Time base 3

STAPLES

