

(May 1932)

Originally issued
February 25, 1919 as
Communication B516

at of print. Revised copy is
ing stenciled. This copy does
not contain tables and figures, and
it has not been
checked.

**IMPORTANT EUROPEAN SCREW THREAD SYSTEMS
AND DIMENSIONS OF BOLT AND SCREW HEADS AND NUTS**

CONTENTS

I. Introduction

II. British standard Whitworth and British standard fine screw threads.

1. British standard Whitworth and British standard fine screw threads.
2. Dimensions, allowances, and tolerances.
3. British standard automobile threads.
4. Interchangeability of U.S. National Coarse and British standard Whitworth threads.

III. British Association Screw Threads

IV. British standard pipe threads

1. British standard pipe thread for iron and steel tubes.
2. British standard thread for steel conduit.
3. British standard dimensions for copper tubes and their screw threads.
4. Gaging British standard pipe threads.

V. British standard bolt heads, nuts, and screw heads

1. British standard bolt heads and nuts.
2. British standard automobile bolt heads and nuts.
3. British standard heads for British Association screws.

VI. International metric screw thread standard

VII. Screw thread standards in use in France

VIII. Standard dimensions of bolt heads, nuts, and screw heads in use in France

1. Width across flats or diameters of bolt heads, nuts, and screw heads.
2. Height of bolt and screw heads and thickness of nuts.
3. Length below head and length of threaded portion of bolts and screws.
4. Angles of counter sunk heads.

(Page 100)

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

100-100000-100000

IX. The Loewenherg screw thread system and screw heads

I. INTRODUCTION

This Circular is a collection of data appertaining to screw thread systems and standard dimensions for bolt and screw heads and nuts in use in various European countries. It covers, particularly, those standards which originated in Great Britain, France, Switzerland, and Germany, although they are used by other European nations as well.

So far as practicable the nomenclature in vogue in the United States and sanctioned by the National Screw Thread Commission has been used, in order that the information given may be understood and applied with as little difficulty as possible. An effort has been made to give a complete presentation of all essential data.

Since American standards for the dimensions of bolt and screw heads are still in the process of formulation, this collection of data may prove of use in arriving at such standards. These data should also prove useful to those who manufacture machinery for export.

II. BRITISH STANDARD WHITWORTH AND BRITISH STANDARD FINE SCREW THREADS

1. British standard Whitworth and British Standard Fine Screw threads.

The Whitworth series of screw threads was proposed in 1841 by Joseph Whitworth of Great Britain in a paper read before the Institution of Civil Engineers. The Whitworth thread angle, diameters, and pitches were chosen because they represented the average engineering practice at that time. Of thread angle, Mr. Whitworth said: "The mean of the angles in one inch screws was found to be about 55 deg. which was also nearly the mean in screws of different diameters, hence, it is adopted throughout the scale."

The British Engineering Standards Association adopted the British Standard Whitworth Screw Threads (B.S.W.) in 1905 and issued a report giving the essential dimensions of the series. The thread angle in an axial plane is 55 deg.; the threads are rounded equally at crest and root to a radius of 0.137329 times the pitch, and the resulting depth of thread becomes 0.640327

1. INTRODUCTION

This Committee is a sub-committee of the Committee on the Work of the Committee. It was established in 1951 to study the work of the Committee and to report to the Committee on its findings. The Committee has since that time been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports.

The Committee has since that time been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports.

The Committee has since that time been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports.

II. THE WORK OF THE COMMITTEE

1. The Committee's work in 1951 and 1952

The Committee's work in 1951 and 1952 was devoted to the study of the work of the Committee. The Committee has since that time been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports.

The Committee has since that time been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports. The Committee has also been engaged in a study of the work of the Committee and has produced a number of reports.

times the pitch. Thus, one-sixth of the depth of the basic triangle is removed from the crest of the thread, and one-sixth of the depth is filled in at the root. This form of thread is designated the "Whitworth" thread form, and is shown in Fig. 1.

The Whitworth form of thread is also used in the British Standard Fine Screw Threads (B.S.F.), British Standard Pipe Threads (B.S.P.), and British Standard Conduit Threads.

The British Standard Fine Screw Threads were introduced in 1908 by the British Engineering Standards Association, and are said to be well suited to the purposes for which they were designated. The pitches are obtained by the formula,

$$p = 0.1 D^{2/3}$$

for sizes up to and including one inch, and

$$p = 0.1 D^{5/8}$$

for sizes above one inch. In these formulas,

p = pitch

and D = major diameter

3. Dimensions, Allowances, and Tolerances.

The basic dimensions of British Standard Whitworth and British Standard Fine Screw Threads are given in Tables 1 and 4. In Tables 2, 3, 5, 6, 7, and 8 are given the dimensions and tolerances on bolts and nuts for both series.

Since the pitch. Thus, one-half of the depth of the hole is removed from the area of the thread, and one-half of the depth is filled in at the root. This form of thread is designated the "Whitworth thread form," and is shown in Fig. 1.

The Whitworth form of thread is also used in the British Standard Pipe Threads (B.S.P.), British Standard Pipe Threads (B.S.P.), and British Standard Whitworth Threads (B.S.W.).

The British Standard Whitworth Threads were introduced in 1841 by the British Engineering Standards Association, and are said to be well suited to the purposes for which they were designated. The pitches are obtained by the formula:

$$p = 0.1 D$$

for sizes up to and including one inch, and

$$p = 0.1 D^{0.8}$$

for sizes above one inch. In these formulas,

$$p = \text{pitch}$$

$$D = \text{major diameter}$$

and

1. Dimensions, Allowances, and Tolerances.

The basic dimensions of British Standard Whitworth and British Standard Pipe Threads are given in Tables 1 and 2. In Tables 3, 4, 5, 6, 7, and 8 are given the dimensions and tolerances on holes and nuts for both series.

The maximum screw is made to the basic size. For example, the maximum major diameter of a 1/4 inch B.S.W. screw is 0.2500 inch, and the minimum major diameter is equal to the maximum major diameter minus the tolerance. The tolerance is given in Table 2 as 0.0018 inch, hence, the maximum major diameter is 0.2482 inch.

All allowances to provide for clearance are in the nut, the minimum diameter of the nut being above basic size. As shown in Table 3, the minimum diameter of the nut being above basic size. As shown in Table 3, the minimum major diameter of a 1/4 inch nut is 0.0005 inch above basic size, or 0.2505 inch. The maximum major diameter is 0.2533, being greater than the minimum major diameter by an amount equal to the tolerance, namely, 0.0018 inch.

3. British Standard Automobile Threads

In a report submitted by the Sub-Committee on Automobile Threads, which was adopted by the Sectional Committee on Screw Threads and Limit Gages, and approved by the British Engineering Standards Association in 1911, the sizes of the British Standard Fine Screw Threads from 1/4 in. to 1 in., inclusive, as given under bolt dimensions in Table 4, were taken as standard for threads used in automobile construction.

4. Interchangeability of United States National Coarse and British Standard Whitworth Threads by Diameter Modification.

Table 9 shows that the diameters and pitches of the U.S. National Coarse Thread Series and the British Standard Whitworth Threads, in most cases, correspond. Consequently the question of interchangeability between them has caused considerable discussion, both in this country and in England. A method of securing interchangeability is based on a slight modification of the diameters of either the National or the Whitworth threads, or both, without changing the angle or thread form of either. Table 10 shows the modification of diameters of either of the systems necessary to produce assembly. Since the Whitworth thread angle is 5 deg. less than that of the National thread, contact occurs near the crest of the Whitworth thread and near the root of the National thread. Table 10 includes only those threads whose pitches are common to both systems.

Fig. 2 shows the two possible combinations of the Whitworth and National threads. The conditions of stress developed in the thread would be the same in either system as would ordinarily

The maximum value of the diameter of the British Standard Wire Gauge is 0.0001 inch, and the minimum value of the diameter of the British Standard Wire Gauge is 0.0001 inch. The maximum value of the diameter of the British Standard Wire Gauge is 0.0001 inch, and the minimum value of the diameter of the British Standard Wire Gauge is 0.0001 inch.

All dimensions are given in inches, and the dimensions are given in inches. The dimensions are given in inches, and the dimensions are given in inches. The dimensions are given in inches, and the dimensions are given in inches. The dimensions are given in inches, and the dimensions are given in inches.

3. British Standard Wire Gauge

In a report submitted by the Sub-Committee on British Wire Gauge, which was adopted by the British Standard Wire Gauge Committee, and approved by the British Standard Wire Gauge Committee, the dimensions of the British Standard Wire Gauge are given. The dimensions of the British Standard Wire Gauge are given in inches, and the dimensions of the British Standard Wire Gauge are given in inches.

4. International System of Units (SI)

Table 1 shows the dimensions and values of the SI units. The dimensions of the SI units are given in inches, and the values of the SI units are given in inches. The dimensions of the SI units are given in inches, and the values of the SI units are given in inches. The dimensions of the SI units are given in inches, and the values of the SI units are given in inches.

Fig. 1 shows the possible combinations of the SI units and British Standard Wire Gauge. The dimensions of the SI units are given in inches, and the values of the SI units are given in inches. The dimensions of the SI units are given in inches, and the values of the SI units are given in inches.

occur with a slight difference in angle between bolt and nut.

Institute of Civil Engineers, 1841, Vol. 1, page 157.

British Engineering Standards Association Reports Nos.

20 - 1913. Screw Threads

38 - 1913. Standard Systems for Limit Gages for Screw Threads.

54 - 1911. British Standard Threads, Nuts, and Bolt Heads
for use in Automobile Construction.

84 - 1918. British Standard Fine Screw Threads and their
Tolerances.

III. BRITISH ASSOCIATION SCREW THREADS

In 1878 the Horological Section of the Geneva Society of Arts recommended a system of screw threads designed by Prof. H. Thury. This system was based on the measurement of well proportioned watch and small instrument screws in actual use in European countries. This thread has an angle of 47.5 degrees; is rounded at the crest to a radius equal to one-sixth of the pitch; and is rounded at the root to a radius of one-fifth of the pitch. The sizes were designated by consecutive numbers (n) the pitch (p) corresponding to any size number being given by the formula $p = 0.9^n$, and the outside diameter (D) corresponding to any pitch being given by the formula $D = 6 p^{6/5}$.

IN 1975 THE NATIONAL BUREAU OF INVESTIGATION (FBI) WAS RECOMMENDED TO CONDUCT A STUDY OF THE EFFECTS OF THE 1975 ACT ON THE ECONOMY. THIS STUDY WAS CONDUCTED BY THE NATIONAL BUREAU OF INVESTIGATION (FBI) AND THE RESULTS WERE REPORTED IN A REPORT DATED 1976. THE REPORT WAS TITLED "THE EFFECTS OF THE 1975 ACT ON THE ECONOMY". THE REPORT WAS DIVIDED INTO TWO PARTS. THE FIRST PART WAS TITLED "THE EFFECTS OF THE 1975 ACT ON THE ECONOMY" AND THE SECOND PART WAS TITLED "THE EFFECTS OF THE 1975 ACT ON THE ECONOMY". THE REPORT WAS DIVIDED INTO TWO PARTS. THE FIRST PART WAS TITLED "THE EFFECTS OF THE 1975 ACT ON THE ECONOMY" AND THE SECOND PART WAS TITLED "THE EFFECTS OF THE 1975 ACT ON THE ECONOMY".

In 1884 the British Association for the Advancement of Science recommended the use of the Thury system, with modifications, for all screws less than 1/4 inch in diameter. The thread form was modified to give an equal rounding at crest and root of approximately 2 p. See Fig. 2. The British

11

Engineering Standards Association in their Report No. 20 on British Standard Screw Threads give dimensions of British Association screw threads, including recommended clearances between crests and roots of threads, which are given in tables 11 and 12.

References:

Systematique des Vis Horologeries by M. Thury.
Reports of the British Association for the Advancement of Science, 1884 and 1900.
British Engineering Standards Association
Report No. 20-1913. Screw Threads.

IN THE COURT OF COMMONS, 18th May 1891.
The following is a list of the names of the
persons who have been appointed to the
office of Clerk of the House of Commons,
from the year 1801 to the present time.

1801-1802. Mr. John Lubbock.
1802-1803. Mr. John Lubbock.
1803-1804. Mr. John Lubbock.
1804-1805. Mr. John Lubbock.
1805-1806. Mr. John Lubbock.
1806-1807. Mr. John Lubbock.
1807-1808. Mr. John Lubbock.
1808-1809. Mr. John Lubbock.
1809-1810. Mr. John Lubbock.
1810-1811. Mr. John Lubbock.
1811-1812. Mr. John Lubbock.
1812-1813. Mr. John Lubbock.
1813-1814. Mr. John Lubbock.
1814-1815. Mr. John Lubbock.
1815-1816. Mr. John Lubbock.
1816-1817. Mr. John Lubbock.
1817-1818. Mr. John Lubbock.
1818-1819. Mr. John Lubbock.
1819-1820. Mr. John Lubbock.
1820-1821. Mr. John Lubbock.
1821-1822. Mr. John Lubbock.
1822-1823. Mr. John Lubbock.
1823-1824. Mr. John Lubbock.
1824-1825. Mr. John Lubbock.
1825-1826. Mr. John Lubbock.
1826-1827. Mr. John Lubbock.
1827-1828. Mr. John Lubbock.
1828-1829. Mr. John Lubbock.
1829-1830. Mr. John Lubbock.
1830-1831. Mr. John Lubbock.
1831-1832. Mr. John Lubbock.
1832-1833. Mr. John Lubbock.
1833-1834. Mr. John Lubbock.
1834-1835. Mr. John Lubbock.
1835-1836. Mr. John Lubbock.
1836-1837. Mr. John Lubbock.
1837-1838. Mr. John Lubbock.
1838-1839. Mr. John Lubbock.
1839-1840. Mr. John Lubbock.
1840-1841. Mr. John Lubbock.
1841-1842. Mr. John Lubbock.
1842-1843. Mr. John Lubbock.
1843-1844. Mr. John Lubbock.
1844-1845. Mr. John Lubbock.
1845-1846. Mr. John Lubbock.
1846-1847. Mr. John Lubbock.
1847-1848. Mr. John Lubbock.
1848-1849. Mr. John Lubbock.
1849-1850. Mr. John Lubbock.
1850-1851. Mr. John Lubbock.
1851-1852. Mr. John Lubbock.
1852-1853. Mr. John Lubbock.
1853-1854. Mr. John Lubbock.
1854-1855. Mr. John Lubbock.
1855-1856. Mr. John Lubbock.
1856-1857. Mr. John Lubbock.
1857-1858. Mr. John Lubbock.
1858-1859. Mr. John Lubbock.
1859-1860. Mr. John Lubbock.
1860-1861. Mr. John Lubbock.
1861-1862. Mr. John Lubbock.
1862-1863. Mr. John Lubbock.
1863-1864. Mr. John Lubbock.
1864-1865. Mr. John Lubbock.
1865-1866. Mr. John Lubbock.
1866-1867. Mr. John Lubbock.
1867-1868. Mr. John Lubbock.
1868-1869. Mr. John Lubbock.
1869-1870. Mr. John Lubbock.
1870-1871. Mr. John Lubbock.
1871-1872. Mr. John Lubbock.
1872-1873. Mr. John Lubbock.
1873-1874. Mr. John Lubbock.
1874-1875. Mr. John Lubbock.
1875-1876. Mr. John Lubbock.
1876-1877. Mr. John Lubbock.
1877-1878. Mr. John Lubbock.
1878-1879. Mr. John Lubbock.
1879-1880. Mr. John Lubbock.
1880-1881. Mr. John Lubbock.
1881-1882. Mr. John Lubbock.
1882-1883. Mr. John Lubbock.
1883-1884. Mr. John Lubbock.
1884-1885. Mr. John Lubbock.
1885-1886. Mr. John Lubbock.
1886-1887. Mr. John Lubbock.
1887-1888. Mr. John Lubbock.
1888-1889. Mr. John Lubbock.
1889-1890. Mr. John Lubbock.
1890-1891. Mr. John Lubbock.

Continued.

1891-1892. Mr. John Lubbock.
1892-1893. Mr. John Lubbock.
1893-1894. Mr. John Lubbock.
1894-1895. Mr. John Lubbock.
1895-1896. Mr. John Lubbock.
1896-1897. Mr. John Lubbock.
1897-1898. Mr. John Lubbock.
1898-1899. Mr. John Lubbock.
1899-1900. Mr. John Lubbock.
1900-1901. Mr. John Lubbock.
1901-1902. Mr. John Lubbock.
1902-1903. Mr. John Lubbock.
1903-1904. Mr. John Lubbock.
1904-1905. Mr. John Lubbock.
1905-1906. Mr. John Lubbock.
1906-1907. Mr. John Lubbock.
1907-1908. Mr. John Lubbock.
1908-1909. Mr. John Lubbock.
1909-1910. Mr. John Lubbock.
1910-1911. Mr. John Lubbock.
1911-1912. Mr. John Lubbock.
1912-1913. Mr. John Lubbock.
1913-1914. Mr. John Lubbock.
1914-1915. Mr. John Lubbock.
1915-1916. Mr. John Lubbock.
1916-1917. Mr. John Lubbock.
1917-1918. Mr. John Lubbock.
1918-1919. Mr. John Lubbock.
1919-1920. Mr. John Lubbock.
1920-1921. Mr. John Lubbock.
1921-1922. Mr. John Lubbock.
1922-1923. Mr. John Lubbock.
1923-1924. Mr. John Lubbock.
1924-1925. Mr. John Lubbock.
1925-1926. Mr. John Lubbock.
1926-1927. Mr. John Lubbock.
1927-1928. Mr. John Lubbock.
1928-1929. Mr. John Lubbock.
1929-1930. Mr. John Lubbock.
1930-1931. Mr. John Lubbock.
1931-1932. Mr. John Lubbock.
1932-1933. Mr. John Lubbock.
1933-1934. Mr. John Lubbock.
1934-1935. Mr. John Lubbock.
1935-1936. Mr. John Lubbock.
1936-1937. Mr. John Lubbock.
1937-1938. Mr. John Lubbock.
1938-1939. Mr. John Lubbock.
1939-1940. Mr. John Lubbock.
1940-1941. Mr. John Lubbock.
1941-1942. Mr. John Lubbock.
1942-1943. Mr. John Lubbock.
1943-1944. Mr. John Lubbock.
1944-1945. Mr. John Lubbock.
1945-1946. Mr. John Lubbock.
1946-1947. Mr. John Lubbock.
1947-1948. Mr. John Lubbock.
1948-1949. Mr. John Lubbock.
1949-1950. Mr. John Lubbock.
1950-1951. Mr. John Lubbock.
1951-1952. Mr. John Lubbock.
1952-1953. Mr. John Lubbock.
1953-1954. Mr. John Lubbock.
1954-1955. Mr. John Lubbock.
1955-1956. Mr. John Lubbock.
1956-1957. Mr. John Lubbock.
1957-1958. Mr. John Lubbock.
1958-1959. Mr. John Lubbock.
1959-1960. Mr. John Lubbock.
1960-1961. Mr. John Lubbock.
1961-1962. Mr. John Lubbock.
1962-1963. Mr. John Lubbock.
1963-1964. Mr. John Lubbock.
1964-1965. Mr. John Lubbock.
1965-1966. Mr. John Lubbock.
1966-1967. Mr. John Lubbock.
1967-1968. Mr. John Lubbock.
1968-1969. Mr. John Lubbock.
1969-1970. Mr. John Lubbock.
1970-1971. Mr. John Lubbock.
1971-1972. Mr. John Lubbock.
1972-1973. Mr. John Lubbock.
1973-1974. Mr. John Lubbock.
1974-1975. Mr. John Lubbock.
1975-1976. Mr. John Lubbock.
1976-1977. Mr. John Lubbock.
1977-1978. Mr. John Lubbock.
1978-1979. Mr. John Lubbock.
1979-1980. Mr. John Lubbock.
1980-1981. Mr. John Lubbock.
1981-1982. Mr. John Lubbock.
1982-1983. Mr. John Lubbock.
1983-1984. Mr. John Lubbock.
1984-1985. Mr. John Lubbock.
1985-1986. Mr. John Lubbock.
1986-1987. Mr. John Lubbock.
1987-1988. Mr. John Lubbock.
1988-1989. Mr. John Lubbock.
1989-1990. Mr. John Lubbock.
1990-1991. Mr. John Lubbock.

IV. BRITISH STANDARD PIPE THREADS

1. The British Standard Pipe Thread for Iron and Steel Tubes (B.S.P.) (Ditto) was adopted in 1905 by the Sectional Committee on Screw Threads and Limit Gages of the British Engineering Standards Association. It was approved by the Association in March 1905.

The Whitworth form of thread was adopted. Two classes of pipe threads were recognized by the Association, and are now in use, namely,-

Class I - the taper thread

Class II- the parallel (straight) thread.

Class I. The thread at the pipe end is tapered 1/16 inch per inch of length, the threads being perpendicular to the surface of the cone and pitch being measured parallel to the axis of the thread. The thread in the coupling may be either straight or tapered; ordinarily, a straight coupling and tapered pipe end are used. Taper couplings are used to secure exceptionally good fits.

Dimensions of Class I tapered threads are given in Table 13. All threads for iron and steel pipe and tubing purporting to be of British Standard Dimensions shall have the dimensions given in this table.

Class II. Straight pipe threads have the same diameters as the diameters of tapered threads at the gaging notch. (See Column 3, Table 13).

2. British Standard Thread for Steel Conduit. Two classes of steel conduit are recognized as standard:-

Class A - plain,

Class B - threaded.

Class "A" is a light gage conduit. The coupling joining the lengths of tubing is a sleeve and neither the ends of the conduit, nor the coupling joining the lengths are threaded.

Class "B" is a heavy gage conduit. Both ends of the conduit are threaded with the Whitworth form of thread as defined for British Standard Pipe Threads.

The length of thread on the ends of conduits, which shall be the same for binds, tees, junction, boxes and other threaded accessories, is given in Table 14, and is deduced by the formula,

$$L = 1/2 D + 3/8 \text{ inches,}$$

in which
and

L = length of thread,
D = outside diameter.

IV. BRITISH STANDARD PIPE THREADS

1. The British Standard Pipe Thread for Iron and Steel Pipes (B.S.P.) (Metric) was adopted in 1903 by the Institution of Mechanical Engineers and the Institution of Civil Engineers. It was approved by the Association in March 1908.

The Whitworth form of thread was adopted. Two classes of pipe threads were recognized by the Association, and are now in use, namely:-

- Class I - the taper thread
- Class II - the parallel (straight) thread.

Class I. The thread on the pipe end is tapered 1/16 inch per inch of length, the threads being perpendicular to the surface of the end and with being assumed parallel to the axis of the thread. The thread in the coupling may be either straight or tapered; ordinarily, a straight coupling and tapered pipe end are used. Larger couplings are used to secure exceptionally good fits.

Dimensions of Class I tapered threads are given in Table I. All threads for iron and steel pipe and ending pipe are given in Table I. of British Standard Dimensions shall have the dimensions given in this table.

Class II. Straight pipe threads have the same dimensions as the diameters of tapered threads at the gaging notch. (See Column 2, Table I.)

2. British Standard Thread for Steel Couplings. Two classes of steel couplings are recognized as standard:-

- Class A - plain
- Class B - threaded.

Class "A" is a light pipe coupling. The coupling joining the ends of pipe is a sleeve and neither the ends of the coupling, nor the coupling joining the lengths are threaded.

Class "B" is a heavy pipe coupling. Both ends of the coupling are threaded with the Whitworth form of thread as detailed for British Standard Pipe Threads.

The length of thread on the ends of couplings, which shall be the same for Class A, Class B, and Class C, and is shown by the formula, is given in Table I, and is shown by the formula,

$$L = \frac{1}{8} D + \frac{1}{4} \text{ inches}$$

$$L = \text{length of thread}$$

$$D = \text{outside diameter}$$

in inches

British Standard Dimensions of both Class "A" and Class "B" steel conduit are given in Table 14.

3. British Standard Dimensions for Copper Tubes and Their Screw Threads. The report of the Sub-Committee on Metal Tubes and Connections on Standard Specifications for copper tubes and their screw threads was adopted by the Sectional Committee on Screw Threads and Limit Gages, and was approved by the British Engineering Standards Association, in March 1913. For the heavier gage tubes the British Standard Pipe Threads, as given in Tables 13 and 16, were adopted, and for the lighter gage tubes the dimensions given in Table 15 were adopted, the Whitworth form of thread being used.

4. Gaging British Standard Pipe Threads. In order to insure correct gaging, it is necessary to define the position of the gage diameter on the pipe end and in the coupling. Fig. 4 is a drawing of one plug and ring gages which give satisfactory results. Instead of dimensions being given on the drawing, reference is made to column numbers of Table 13. By referring to the table, dimensions may be found for gaging any size of thread.

The distances between the surfaces A and B of the ring gages, for any given size, is the difference between values given in columns 10 and 11. The gage, having a plain conical surface, is slipped over the end of the pipe, and, when pressed on by hand, the pipe end must protrude beyond surface B. On the plug gage surfaces C and D correspond to surfaces A and B on the ring. The plug must enter beyond C, but surface D must remain outside.

References:

- British Engineering Standards Association Reports
Nos. 31-1909. Pipe Threads for Iron or Steel
Pipes and Tubes.
- 31-1910. Steel Conduits for Electrical Wiring
- 61-1913. Copper Tubes and Their Screw Threads.

THESE ARE THE RESULTS OF THE RESEARCHES OF THE
RESEARCHERS OF THE INSTITUTE OF THE HISTORY OF THE
CITY OF MOSCOW.

1. The first of the results of the researches of the
researchers of the Institute of the History of the
City of Moscow is the discovery of the fact that
the first mention of the city of Moscow is found
in the chronicles of the year 1147. This fact is
of great importance for the history of the city
of Moscow, as it shows that the city was already
a well-known and important center of the Russian
state at that time.

2. The second of the results of the researches of the
researchers of the Institute of the History of the
City of Moscow is the discovery of the fact that
the first mention of the city of Moscow is found
in the chronicles of the year 1147. This fact is
of great importance for the history of the city
of Moscow, as it shows that the city was already
a well-known and important center of the Russian
state at that time.

3. The third of the results of the researches of the
researchers of the Institute of the History of the
City of Moscow is the discovery of the fact that
the first mention of the city of Moscow is found
in the chronicles of the year 1147. This fact is
of great importance for the history of the city
of Moscow, as it shows that the city was already
a well-known and important center of the Russian
state at that time.

THESE ARE THE RESULTS OF THE RESEARCHES OF THE

RESEARCHERS OF THE INSTITUTE OF THE HISTORY OF THE
CITY OF MOSCOW.

V. BRITISH STANDARD BOLT HEADS, NUTS, AND SCREW HEADS.

1. British Standard Bolt Heads and Nuts.

Standard dimensions for hexagonal bright nuts and bright bolt heads; black nuts, black lock nuts, and black bolt heads; spanners; and castle nuts which were adopted by the Sectional Committee on Screw Threads and Limit Gages, and approved by the British Engineering Standards Association in 1906 are given in Tables 17, 18, and 19.

2. British Standard Automobile Bolt Heads and Nuts.

Standard dimensions for nuts and bolt heads used in automobile construction as given in Table 20 were submitted by the Sub-Committee on Automobile Threads, adopted by the Sectional Committee on Screw Threads and Limit Gages, and approved by the British Engineering Standards Association in 1911.

3. British Standard Heads for British Association Screws.

The proportions of heads for small screws, namely,-- counter-sunk, instrument, round, cheese, filister, capstan, connection, and hexagon, for sizes 0 to 15 ("British Association" designation numbers) were established by the Sectional Committee on Machine Parts, their Gaging and Nomenclature, and approved on behalf of the British Engineering Standards Association in 1920. The sizes standardized range from 6 mm to 0.9 mm (0.236 in. to 0.035 in.) The smaller sizes not being in general use, except in special cases, were not standardized. See Tables 21-24, inclusive.

References:

- British Engineering Standards Association Reports Nos.
28-1908. Nuts, Bolt Heads, and Spanners.
54-1911. Screw Threads, Nuts, and Bolt Heads for use in Automobile Construction.
57-1920. Heads for British Association Screws.

1. British Association of Physicians (BAP) - Founded in 1859, the BAP is the largest medical association in the UK. It represents the interests of its members, who are primarily general practitioners, and provides a platform for them to voice their concerns and influence medical policy.

2. General Medical Council (GMC) - The GMC is the regulatory body for doctors in the UK. It is responsible for setting standards for medical education, training, and professional conduct. It also has the power to discipline doctors who breach these standards.

3. British Medical Association (BMA) - The BMA is a trade union for doctors, representing their interests in relation to pay, working conditions, and other employment issues. It also provides legal support to its members and engages in political lobbying on their behalf.

Continued...

4. Royal College of Physicians (RCP) - The RCP is one of the four professional colleges in the UK. It is responsible for setting standards for the education and training of specialists in internal medicine. It also provides a platform for its members to voice their concerns and influence medical policy.

VI. INTERNATIONAL METRIC SCREW THREAD STANDARD.

The International Screw Thread Standard (S. I.) was adopted by a congress representing principal continental countries at Zurich in 1898. The system proposed was based on the French Metric Screw Thread System as adapted by the Societe d'Encouragement de l'Industrie Nationale in 1894. The principal difference between the two systems is in the pitch of three screws 8, 9 and 12 mm; the French system specifying 1, 1, and 1.5 mm pitch respectively while the International gives 1.25, 1.35, and 1.75 mm. The International form of thread has a 60° angle and the crest of thread is flattened $1/8$ th the height of the basic triangle while the root is filled in $1/16$ the height, either flat or rounded, as shown in Fig. 14. This gives a definite clearance between the tops and bottoms of the threads of screw and nut. The actual form at the root is left to the choice of the manufacturer.

The dimensions of the International Screw Thread System are given in Table 25. The sizes from 6 mm to 80 mm, inclusive, were standardized at the Congress of Zurich, and those above 80 mm were added by the Societe de Encouragement pour l'Industrie Nationale of France. No tables of allowances and tolerances for this thread series are available. A chart showing a comparison of the pitches and diameters of the International with the U. S. National Coarse and Fine Thread Series is given in Fig. 15.

References:

- Bulletin Soc. d'Encouragement l'Industrie Nationale,
Mar. 1899 and Sept.-Oct. 1919.
- Protokoll International Commission, 1898 (Druck von
F. Lehbauer)

[illegible]

The dimensions of the International Paper Thread System are given in Table 6. The sizes from 5 to 50 are indicated, and were established at the Congress of London, and those above 50 were added by the Society to International Paper Thread System. The table of sizes and dimensions for this thread series is available. A more detailed comparison of the sizes and dimensions of the International Paper Thread System and the French Series is given in Fig. 15.

1. 1995

Federal Bureau of Investigation
 Washington, D. C. 20535
 Date: 10/10/68
 To: Director, FBI
 From: SAC, New York (100-100000)
 Subject: [Illegible]

VII. SOREW THREAD STANDARDS IN USE IN FRANCE

The International form of thread (Fig. 13) is the standard form for screw threads used in France. The diameters and pitches of the International System are most widely used for those sizes which fall within the range of this series. The Societe d'Encouragement pour l'Industrie Nationale has supplemented the International series by introducing sizes between 13 mm and 40 mm so that the series advances by 1 mm steps throughout this range. The interpolated diameters have, in each case, the same pitch as the next larger diameter in the Congress of Zurich series. See Table 26.

A small machine screw series (Serie de la Petite Mecanique) below the International series, from 2.5 to 5.5 mm inclusive, Tables 26 and 27, were added by the Societe d'Encouragement in 1906, and the small watchmakers' screws (Systeme Horlogere), Table 27, were standardized by the same body in 1909.

The various commercial interests recognize selected sizes, given in Table 26, of the International and Societe d'Encouragement series, with the following exceptions and additions:

1. The Etablissements Schneider et Cie add a size having a diameter of 106 mm and a pitch of 8.5 mm.
2. In the series of the Chambre Syndicale des Constructeurs d'Automobiles, the sizes 0.3 mm and 0.5 mm have the pitches 0.5 mm and 0.75 mm respectively, and are, therefore, not interchangeable with the corresponding sizes of the "Serie de la Petite Mecanique". The same is true of the 5 mm size in the series of the Chambre Syndicale des Industries Aeronautiques.

There are also variations in practice as to the form of thread at crest and root. The Societe d'Encouragement does not specify a clearance at the major and minor diameters of screw and nut, and the Syndicale des Constructeurs d'Automobiles do not round the profile at the root. Neither of these modifications, however, prevent interchangeability with S. I. threads.

No tables of allowances and tolerances are available except those for the Aircraft Threads given in Tables 28 and 29. These tolerances were suggested by the British Engineering Standards Association at the request of the Naval and Military Air Service.

References:

Bulletin Soc. d'Encouragement l'Industrie Nationale,
Sept.-Oct. 1919.

[illegible]

(The above information was obtained from the files of the FBI, New York Office, dated 10/18/67.)

The various studies and reports on the subject of the
effect of the use of the word "I" in the
sentence "I am" are as follows:

1. The Laboratory examined 6 bottles of Old and 4 bottles of New Scotch Whisky and found 100 mg of water in a pint.

[illegible][illegible]

No tables of this nature are available
 except those for the Atlantic Ocean in
 "The Atlantic Ocean" by the British
 Association of the Pacific and Atlantic
 Oceans.

: 2004.9.10

[illegible]

VIII. STANDARD DIMENSIONS OF BOLT HEADS, NUTS, AND SCREW HEADS IN USE IN FRANCE

The commercial practice in France as to dimensions of bolt heads, nuts, and screw heads, varies among the various industrial organizations. The standard practice of each organization is given separately for each element in Tables, 30, 31, 32. This information was taken from two numbers of the Bulletin of the Societe d'Encouragement pour l'Industrie Nationale, September - October 1919 and April 1921. The wrench openings specified by the Congress of Zurich, all dimensions specified by L'Union des Syndicats d'Electricite, the depth of slot of circular heads, and the angle of countersunk heads were copied directly from tables published in the Bulletin. The remainder of the dimensions given in the tables herein were computed from the formulas published in the Bulletin.

1. Width Across Flats or Diameters of Bolt Heads, Nuts, and Screw Heads (Table 30)

Congress of Zurich. The Congress of Zurich did not fix the sizes of heads as such but specified a wrench opening for every diameter of the International Standard Series, determined by the formula $1.4 D + 4$ mm, in which D is the diameter of body in millimeters. These wrench openings thus determine the widths across flats of both hexagon and square heads and nuts.

Societe d'Encouragement pour l'Industrie Nationale. For hexagon heads and nuts of the small machine screw series, a diameter across corners of $3 D$ is recommended, that is, $1.732 D$ is the width across flats. For circular heads a diameter of $3 D$ is recommended.

Etablissemments Schneider et Cie. The widths across flats of hexagon and square heads, and hexagon nuts are the same as the wrench openings specified by the Congress of Zurich, that is, $1.4 D + 4$ mm. The diameters of circular heads are the same as the widths across flats of the corresponding hexagon heads.

Chambre Syndicale des Constructeurs d'Automobiles. The widths across flats of square and hexagon heads are determined by the width of a hexagon inscribed in a circle whose diameter is $3 D$ (that is, $1.732 D$), in which D is the diameter of body of the next smaller size in the series. More than half of the sizes thus determined do not fit the wrench sizes specified by the Congress of Zurich.

REPORT OF THE BOARD OF TRUSTEES

The University of Chicago is a private institution of higher learning, founded in 1837, and is one of the leading universities in the United States. It is a non-sectarian institution, and its purpose is to advance the frontiers of knowledge in all fields of human endeavor. The University is organized into several divisions, including the Faculty, the Administration, and the Student Body. The Faculty is composed of the highest caliber of scholars, and the Administration is dedicated to the efficient management of the University's affairs. The Student Body is a diverse group of individuals from all over the world, who come to the University to pursue their education and to contribute to the advancement of knowledge.

The Board of Trustees is the governing body of the University, and it is responsible for the overall management and financial affairs of the institution. The Board is composed of representatives from the Faculty, the Administration, and the Student Body, and it meets regularly to discuss and decide on matters of importance to the University.

The Board of Trustees is pleased to report that the University has achieved significant accomplishments during the past year. The Faculty has made important contributions to the fields of science, literature, and the arts. The Administration has successfully implemented a number of new initiatives to improve the quality of the University's education and to enhance its financial stability. The Student Body has shown a strong commitment to their studies and to the University's values.

The Board of Trustees is confident that the University will continue to achieve great success in the years ahead. We are grateful to the many individuals and organizations that have supported the University, and we look forward to the continued support of the public. We are also proud to be part of a community that is dedicated to the pursuit of knowledge and to the betterment of society.

The Board of Trustees is pleased to announce that the University has received a number of new grants and donations during the past year. These funds will be used to support a variety of programs and initiatives, including research, education, and the arts. We are grateful to the donors and grant-making organizations for their generous support of the University.

The Board of Trustees is also pleased to report that the University has achieved a number of other important milestones. We have successfully completed a major renovation of our main building, and we have launched a number of new programs and initiatives. We are confident that these efforts will further enhance the University's reputation and its ability to advance the frontiers of knowledge.

The diameters of circular heads are not listed in Table 30, since they are permitted to vary from $1.8 D$ to $3 D$ for cylindrical and countersunk heads. Round heads are somewhat smaller.

The widths across flats of hexagon nuts is $1.732 D$, D being the diameter of the body of the bolt. The nuts are, thus, larger than the corresponding bolt heads.

Union des Syndicats d'Electricite. For sizes from 2.5 to 7 mm the widths across flats for square and hexagon heads and nuts are equal to the diameter of the body four steps larger in the series. For sizes from 8 to 12 mm. the widths across flats are $1.4 d'' + 4 \text{ mm.}$, d'' being the diameter of body of two steps smaller in the series. Thus the same widths across flats, or wrench openings are used as those specified by the Congress of Zurich, but are associated with different sizes of bolts or screws.

For circular heads, whether rounded, cylindrical or countersunk, the diameters are equal to the diameter d' of the bolt four steps larger in the series. The diameters of circular heads agree, therefore, with those of the body diameters of bolts and screws, thus reducing the necessary number of sizes of bar stock.

3. Height of Bolt and Screw Heads and Thickness of Nuts (Tables 31 and 32)

Congress of Zurich. The Congress of Zurich recommended a height of $0.7 D$ for square and hexagon bolt and screw heads, and a thickness equal to D for nuts, D being the major diameter of the thread.

Societe d'Encouragement pour l'Industrie Nationale. The height of heads, whether hexagonal or circular, and also the thickness of nuts, is equal to the diameter of thread, D .

Etablissements Schneider et Cie. The height of hexagonal or cylindrical heads is approximately $0.7 D$. Two different thicknesses of nuts are provided, - thick nuts whose thickness is equal to D , and lock nuts of a thickness equal to $0.7 D$.

Chambre Industrielle des Constructeurs d'Automobiles. The heights of heads approved by this association vary considerably. For hexagonal or square heads, the height is about $2/3 D$. The thicknesses of nuts are equal to D , and of lock-nuts, $2/3 D$.

L'Union des Syndicats d'Electricite. The heights of heads for corresponding sizes are the same for hexagonal, cylindrical, and rounded forms, and are equal to $0.7 D$. The height of the conical portion of a countersunk head is determined by the cone-angle, 84° , and the diameter of the head. It is equal to 1.555 times the difference between the diameters of the head and body.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

When the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

1. Diameter of hole and distance between holes (mm)

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

The diameter of the hole is 1.5 mm. The hole is located in the center of the hole. The hole is located in the center of the hole. The hole is located in the center of the hole.

A cylindrical portion surmounts the cone, its height being equal to one-half the pitch of the thread. The total height of the flat countersunk head is equal to the sum of the heights of these two portions. If the head is convex, the height of the rounded portion is added to this height.

Two thicknesses of nuts are provided, both of which apply to either square or hexagonal nuts. For thick nuts, the thickness is equal to the diameter of body, D, two steps smaller in the series. The thickness of thin nuts is equal to $\frac{2}{3}$ that of the thick nuts.

3. Dimensions of Slots in Screw Heads (Table 33)

Neither the Congress of Zurich nor the Societe d'Encouragement have specified the dimensions of slots in circular screw heads.

Etablissemments Schneider et Cie. The width of slot is specified for screws from 6 mm to 18 mm in diameter. The depth of slot varies for different types of head between the limits indicated in Table 33.

Chambre Syndicale des Constructeurs d'Automobiles. The width of slot is specified for screws from 3 mm to 30 mm in diameter. The depth of slot varies for different types of head between the limits indicated in Table 33.

Union des Syndicats d'Electricite. The width of slot is the same for corresponding sizes of all forms of heads. The depth of slot is the same for cylindrical and rounded heads, and is equal to $\frac{1}{3}$ the height of the head. For countersunk heads the depth of slot is equal to one-half the total height of head.

4. Length Below Head and Length of Threaded Portion of Bolts and Screws. (Tables 34 and 35)

Etablissemments Schneider et Cie. There are twenty-nine lengths of bolts, studs, and screws listed in Column 1 of Table 34, which are obtained by adding to the minimum length of 10 mm the successive increments listed in Column 3, which are also used in determining threaded lengths.

The length of threading is such that if the screw, stud, or bolt were cut down to the next shorter length in the series, the threaded part would still remain long enough to take a nut. The formula applied is

$$F = D + \frac{3}{2} R,$$

in which F = length of threaded part,

D = diameter of thread,

and R = difference in length between the bolt and the next shorter one in the series.

These girls' songs are very old and have been collected by the
 1. It was in 1901 that the first collection was made and it was
 2. and was in 1901 that the first collection was made and it was
 3. and was in 1901 that the first collection was made and it was
 4. and was in 1901 that the first collection was made and it was
 5. and was in 1901 that the first collection was made and it was
 6. and was in 1901 that the first collection was made and it was
 7. and was in 1901 that the first collection was made and it was
 8. and was in 1901 that the first collection was made and it was
 9. and was in 1901 that the first collection was made and it was
 10. and was in 1901 that the first collection was made and it was

[illegible][illegible][illegible]

When the threaded part must also carry a locknut, the threaded length is increased by the thickness of the locknut and becomes,

$$F' = F + 0.7 D = 1.7 D + 3/2 R.$$

Chambre Syndicale des Constructeurs d'Automobiles. The total lengths below heads are graduated as follows:

by 5 mm steps between 10 mm and 100 mm,
" 10 " " " 100 " " 200 "
" 50 " " " 200 " " 300 "

Thus there are 30 different lengths from 10 mm to 300 mm.

Threads to take nut and locknut have a length equal to 2 d, and for nut and washer equal to 1.5 d, d being the diameter of the next smaller (in diameter) bolt in the series. For sizes up to and including 12 mm this length is increased by 2 mm. This is not sufficient, in all cases, to permit a bolt cut down to the next shorter length to take a nut.

Union des Syndicats d'Electricite. The minimum lengths below head for each diameter of screw are given in Table 35. The series of lengths above these minima corresponds to the series obtained by adding successively and cumulatively to the base 4 mm the natural series of numbers 1, 2, 3, 4, 5, etc. giving the lengths given in Column 7, Table 34. These values serve only as a suggestion and are those recognized by Etablissements Schneider et Cie, and Chemus de fer Francais.

5. Angles of Countersunk Heads.

The Congress of Zurich made no recommendation in regard to the cone angle of countersunk heads. The angles specified by other organizations are as follows:

Societe d'Encouragement,	84 degrees,
Schneider et Cie,	84 "
Constructeurs d'Automobiles,	90 "
Syndicats d'Electricite,	84 "

The first of these is the fact that the
 second of these is the fact that the

1950年10月1日

[illegible][illegible]

... ..

There is no doubt that the above information is correct and that the above information is correct and that the above information is correct.

The first of these is the fact that the
 value of the function $f(x)$ is
 always positive for all values of x .
 This is because the function is
 defined as the sum of two
 positive functions, $f_1(x)$ and $f_2(x)$,
 both of which are positive for all
 values of x . The second fact is
 that the function $f(x)$ is
 continuous for all values of x .
 This is because the functions $f_1(x)$
 and $f_2(x)$ are both continuous
 for all values of x , and the
 sum of two continuous functions
 is also continuous. The third
 fact is that the function $f(x)$
 is differentiable for all values of x .
 This is because the functions $f_1(x)$
 and $f_2(x)$ are both differentiable
 for all values of x , and the
 sum of two differentiable functions
 is also differentiable.

should demonstrate to us that

IX. THE LOEWENHERZ SCREW THREAD SYSTEM AND STANDARD INSTRUMENT AND MACHINE SCREWS

The Lowenherz Screw Thread System and Screw Heads. The Verein Deutscher Ingenieure in 1888 adopted a system of metric screw threads for sizes from 6 mm to 40 mm diameter inclusive. The thread form selected, shown in Fig. 15, has an angle of $53^{\circ} 8'$ and is flattened at top and bottom $1/8$ th the height of the basic triangle. The angle $53^{\circ} 8'$ gives a triangle whose height is equal to its base, therefore, the depth of thread is $3/4$ of the pitch.

In December 1893 a commission representing German instrument makers, technical societies, and government departments, adopted a system of threads ranging in diameter from 1 mm to 10 mm and especially intended for use in small machines and instruments. The same form of thread is employed as in the earlier system and the overlapping sizes 6 mm to 10 mm are identical. The system was called the Loewenherz System after Dr. Leopold Loewenherz, at one time Director of the Physikalisch-Technische Reichsanstalt. The dimensions of the Lowenherz Screw Thread System are given in Table 36.

At the same time standard proportions for instrument and machine screws for sizes from 1.0 to 10.0 mm were adopted by the commission, which are given in Table 37.

References:

Zeitschrift Verein Deutscher Ingenieure, 1888,
Zeitschrift fur Instrumentkunde, February 1893,
pages 41-58; June 1893, pages 246-249; and
August 1894, pages 285-291.

The following facts have been obtained from the records of the University of Chicago Press, and are given in this report as they appear in the original records. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received.

The following facts have been obtained from the records of the University of Chicago Press, and are given in this report as they appear in the original records. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received.

The following facts have been obtained from the records of the University of Chicago Press, and are given in this report as they appear in the original records. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received.

Continued

Reference is made to the records of the University of Chicago Press, and are given in this report as they appear in the original records. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received. The facts are given in the order in which they were received, and are not necessarily in the order in which they were received.



