

NATIONAL BUREAU OF STANDARDS REPORT

6212

CAPACITY TESTS
OF
FOUR 3/4-TON GASOLINE-POWERED REFRIGERATING UNITS
THERMO KING, MODEL Q9

by

Clinton W. Phillips and Paul R. Achenbach

Report to
Mechanical Engineering Division
Headquarters, Quartermaster Research and Engineering Command
Natick, Massachusetts



U. S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

THE NATIONAL BUREAU OF STANDARDS

Functions and Activities

The functions of the National Bureau of Standards are set forth in the Act of Congress, March 3, 1901, as amended by Congress in Public Law 619, 1950. These include the development and maintenance of the national standards of measurement and the provision of means and methods for making measurements consistent with these standards; the determination of physical constants and properties of materials; the development of methods and instruments for testing materials, devices, and structures; advisory services to Government Agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; and the development of standard practices, codes, and specifications. The work includes basic and applied research, development, engineering, instrumentation, testing, evaluation, calibration services, and various consultation and information services. A major portion of the Bureau's work is performed for other Government Agencies, particularly the Department of Defense and the Atomic Energy Commission. The scope of activities is suggested by the listing of divisions and sections on the inside of the back cover.

Reports and Publications

The results of the Bureau's work take the form of either actual equipment and devices or published papers and reports. Reports are issued to the sponsoring agency of a particular project or program. Published papers appear either in the Bureau's own series of publications or in the journals of professional and scientific societies. The Bureau itself publishes three monthly periodicals, available from the Government Printing Office: The Journal of Research, which presents complete papers reporting technical investigations; the Technical News Bulletin, which presents summary and preliminary reports on work in progress; and Basic Radio Propagation Predictions, which provides data for determining the best frequencies to use for radio communications throughout the world. There are also five series of nonperiodical publications: The Applied Mathematics Series, Circulars, Handbooks, Building Materials and Structures Reports, and Miscellaneous Publications.

Information on the Bureau's publications can be found in NBS Circular 460, Publications of the National Bureau of Standards (\$1.25) and its Supplement (\$0.75), available from the Superintendent of Documents, Government Printing Office, Washington 25, D. C.

Inquiries regarding the Bureau's reports should be addressed to the Office of Technical Information, National Bureau of Standards, Washington 25, D. C.

NATIONAL BUREAU OF STANDARDS REPORT

NBS PROJECT

1003-20-4832

NBS REPORT

6212

November 7, 1958

CAPACITY TESTS OF
OF
FOUR 3/4-TON GASOLINE-POWERED REFRIGERATING UNITS
THERMO KING, MODEL Q9

by

Clinton W. Phillips and Paul R. Achenbach
Air Conditioning, Heating, and Refrigeration Section
Building Technology Division

to

Mechanical Engineering Division
Headquarters, Quartermaster Research and Engineering Command
Natick, Massachusetts

IMPORTANT NOTICE

NATIONAL BUREAU OF STANDARDS
Intended for use within the
to additional evaluation and
listing of this Report, either
the Office of the Director, NBS
however, by the Government
to reproduce additional copies

Approved for public release by the
Director of the National Institute of
Standards and Technology (NIST)
on October 9, 2015.

progress accounting documents
formally published it is subjected
g, reproduction, or open-literature
permission is obtained in writing from
Such permission is not needed,
ly prepared if that agency wishes



U. S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

Capacity Tests
of
Four 3/4-Ton Gasoline-Powered Refrigerating Units
Thermo King, Model Q9

1. Introduction

Capacity tests of four Thermo King, Model Q9 3/4-ton, gasoline-engine-driven refrigerating units were made at the request of the Mechanical Engineering Division of the Quartermaster Research and Engineering Command, United States Army, to determine their refrigerating capacity when used in conjunction with 21-foot military-type refrigerating semi-trailers. Figure 1 shows one of the four Model Q9 units.

Three military-type refrigerated semi-trailers, which had previously been tested for heat leakage by the reverse heat-flow method, were used as calorimeters for these tests. Figure 2 is a view of one of these trailers. The heat transmission coefficients, or "U" factors, determined for the three vehicles in the previous trailer tests, were used for computing the heat leakage of these same vehicles when each was used as a calorimeter during the capacity tests of the refrigerating units. These heat transmission factors ranged from 56.1 to 68.3 Btu/hr (F).

This report is a summary of nine refrigerating capacity tests, the results of which have previously been transmitted, either verbally or by letter, to representatives of the Quartermaster Research and Engineering Command. Tests numbered 4 and 8 were made at 110 F ambient temperature and the lowest obtainable trailer temperature. The other seven tests were made at 110 F ambient temperature and 0 F trailer temperature.

2. Test Procedure

Each of the gasoline-engine-driven refrigerating units was installed in a semi-trailer which was in a test chamber in which the desired ambient temperature could be maintained throughout the test. The engine exhaust was connected to an exhaust stack to conduct the fumes from the test chamber. All temperature measurements were made by means of thermocouples and potentiometers, and all temperatures used in computing the test results were corrected by the amount of the observed deviation of a typical thermocouple immersed in an ice bath.

In the tests at 110 F ambient temperature and 0 F interior temperature, a thermostatically-controlled heater, with shielded, resistance-type elements and a built-in blower, was placed inside the trailer to maintain the desired interior temperature. Electrical power supplying the heater, the blower, and circulating fans was measured by means of separate calibrated watt hour meters.

Each test was continued for a sufficient length of time to insure that steady rates of heat exchange between the interior and ambient air had been reached and for a six hour period thereafter. The tabulated test results were obtained from these six hour periods at steady state conditions.

The heat introduced into the interior of the trailer, as computed from the measured amount of electric power supplied to the resistance heater, the blower, and the fans, plus the computed heat leakage of the vehicle, was taken as the net refrigerating capacity of the Q9 refrigerating unit being tested.

3. Test Results

The conditions under which the refrigerating capacity of each of the four Thermo King, Model Q9, 3/4-ton refrigerating units was determined, and the results of these nine tests are shown in Table I.

The units bearing Serial Nos. 367 and 369 were tested as received, without adjustment. The unit bearing Serial No. 364 was received installed in Trailer B from the Field Evaluation Agency at Fort Lee. It had been tested there and the units were reported to be incapable of bringing the interior of the trailer down to a temperature of 0.0 F. In order to install the necessary thermocouple harness on the unit, to prepare it for the capacity tests, it was removed from the vehicle, and while it was being prepared, Tests 3 and 4 were made, with Model Q9 Serial No. 367 installed in Trailer B.

The important effect of suction pressure on net cooling capacity is indicated by comparing the results of Tests 1 and 2 on the unit with Serial No. 369 and of Tests 3 and 4 on the unit with Serial No. 367. In the first case, a change of 2 inches of vacuum in the suction pressure caused a vari-

ation of about 5% in net cooling capacity with virtually no difference in evaporator inlet temperature. In the second case, a decrease in evaporator inlet temperature of 9.3°F caused a decrease in suction pressure of about 2.7 psig and a decrease in net cooling capacity of 26 percent. In each comparison there was less than one percent change in compressor speed.

At the beginning of Test No. 5, with Model Q9 Serial No. 364 installed in Trailer B, it was found that this unit would *not* reduce the interior temperature of the vehicle to 0.0°F. It was found necessary to make several adjustments on the thermal expansion valve to establish a suitable super-heat condition and to adjust the engine speed of the unit to the design speed of 2800 rpm. Tests 5, 6, and 7 show the results of the capacity tests after these adjustments had been made.

Good consistency in results was obtained in Tests 5, 6, and 7 at the same operating conditions on this unit. There was only a half percent difference in net cooling capacity among the three tests.

Test 8 was made with the Model Q9 Serial No. 111 as received, and installed in Trailer C. Test No. 9 was made after several adjustments had been made to the thermal expansion valve to establish correct super-heat. Note the lower engine speed during Tests 8 and 9. A comparison of the results of Tests 8 and 9 made on the unit with Serial No. 111 shows that a reduction of 3.2°F in the evaporator inlet air temperature caused a decrease in suction pressure of 1.5 psig and a reduction in capacity of 9.5 percent.

Comparisons of the net cooling capacities of the four Q9 Thermo King refrigerating units of the same model provides some information on the tolerance to be expected in a group of such units. A comparison of Test 3 with Tests 5, 6, and 7 at the same evaporator inlet air temperature shows a variation in capacity of 6 to 7 percent for these two units. However, the net cooling capacity of the unit with Serial No. 369 as indicated by Tests 1 and 2 was 7 to 11 percent below that for the unit with Serial No. 364 and 13 to 17 percent below that for the unit with Serial No. 367.

The net cooling capacity of the unit with Serial No. 111, as shown in Test No. 9, at a compressor speed of 1750 rpm was about equal to that of the unit with Serial No. 369 at a compressor speed 300 rpm higher.

4. Discussion and Conclusions

The test results show that the Q9 unit, properly adjusted for super-heat and engine speed was capable of reducing the interior temperature of a stationary 21-foot military trailer, as typified by the three specimens used as a calorimeter, to a temperature below 0°F in an ambient temperature of 110 F. The margin of capacity above that required to produce a cargo space temperature of 0 F, ranged from 1500 to 3400 Btu/hr, representing from 20% to 50% excess capacity in the several trailers. It should be noted that the cooling loads of the three trailers ranged from 6200 Btu/hr to 7500 Btu/hr.

In two cases, an oil leak was observed at the front crankshaft oil seal of the gasoline engine after about 100 hours of operation. This leakage was apparently due to malfunctioning of a pressure-equalizing device intended to relieve crankcase pressure.

The heat transmission coefficients of the trailers, used as calorimeters for these tests, were measured using the reverse heat loss method. In this method, the interior temperature is raised above the ambient temperature, and the heat input is divided by the difference in temperature to determine the heat transmission coefficient.

More recent investigation has shown that the reverse heat flow method does not usually indicate as great a heat transmission coefficient as is observed when the refrigerated enclosure is tested with the interior temperature lower than the ambient dew point temperature. In most cases, the heat transmission coefficient will be greater when the interior of the trailer is refrigerated because of the latent heat transfer caused by condensation of water vapor entering with any leakage air which may penetrate the exterior skin.

Because of this, the computed trailer heat gains and also the refrigerating capacities reported in Table I for the four units may be slightly smaller than the actual values. It is probable that this error does not exceed five percent.

It should be noted that in all cases, the units tested, properly adjusted, and in an ambient temperature of 110 F, were of greater capacity than needed to reduce the trailer

temperature to 0 F when the trailers were stationary. Tests of commercial trailers on the road also indicate that the cooling load of such vehicles when in motion was greater than when tested in a stationary condition in the laboratory because additional air and moisture entered the trailer body under the impact of the air. This increment of additional heat gain amounted to 20 to 30% of the heat gain measured in the laboratory.

Q9 Serial No.		111	111
Test No.		8	9
Time		10-0500	1800-2400
Date		12-23/56	7/3/56
Trailer		C	C
Head Pressure	Psig	175	179
Suction Pressure	Psig or <u>In.HgVac.</u>	3	2.8
Ambient Temp.	°F	110.3	110.5
Cargo Space Temp.	°F	2.7	0.7
Evaporator Inlet Air Temp.	°F	2.7	0.5
Engine Speed	RPM	2388	2363
Compressor Speed	RPM	1765	1747
Fan Speed	RPM	1362	1347
Trailer Heat Gain	Btu/hr	700	7500
Electric Heat Input	Btu/hr	450	1500
Net Cooling Capacity	Btu/hr	150	9000

Table I
CAPACITY TESTS OF THERMO KING Q9 3/4-TON REFRIGERATING UNITS

Q9 Serial No.		369	369	367	367	364	364	364	111	111
Test No.		1	2	3	4	5	6	7	8	9
Time		1900-0100	0700-1300	1500-2100	1400-2000	2230-0430	1800-2400	0200-0800	2300-0500	1800-2400
Date		1/6-7/56	2/24/56	3/23/56	3/24/56	4/5-6/56	4/6/56	4/7/56	6/22-23/56	7/3/56
Trailer		A	A	B	B	B	B	B	C	C
Head Pressure	Psig	176	185	180	168	185	193	190	175	179
Suction Pressure	Psig or <u>In.HgVac</u>	<u>2" Vac</u>	0.0	2.5	<u>0.4 "Vac</u>	2.0	3.1	2.8	1.3	2.8
Ambient Temp.	°F	110.3	109.9	110.9	110.4	110.4	110.4	110.0	110.3	110.5
Cargo Space Temp.	°F	0.0	-0.2	0.4	-9.5	0.2	0.4	-0.2	-2.7	0.7
Evaporator Inlet Air Temp.	°F	1.4	1.9	0.6	-9.9	0.3	0.4+	-1.0	-2.7	0.5
Engine Speed	RPM	2805	2796	2726	*2737	2825	2794	2807	2388	2363
Compressor Speed	RPM	2054	2049	2014	*2025	2038	2056	2063	1765	1747
Fan Speed	RPM	1543	1542	1544	*1549	1609	1571	1583	1362	1347
Trailer Heat Gain	Btu/hr	6200	6200	7250	7550	7200	7200	7250	7700	7500
Electric Heat Input	Btu/hr	2650	3100	3400	0	2750	2750	2750	450	1500
Net Cooling Capacity	Btu/hr	8850	9300	10650	7550	9950	9950	10000	8150	9000

*Average
1500-2400 hrs.
3/24/56




FIG. 1




FIG. 2

U. S. DEPARTMENT OF COMMERCE

Sinclair Weeks, *Secretary*

NATIONAL BUREAU OF STANDARDS

A. V. Astin, *Director*



THE NATIONAL BUREAU OF STANDARDS

The scope of activities of the National Bureau of Standards at its headquarters in Washington, D. C., and its major laboratories in Boulder, Colo., is suggested in the following listing of the divisions and sections engaged in technical work. In general, each section carries out specialized research, development, and engineering in the field indicated by its title. A brief description of the activities, and of the resultant publications, appears on the inside front cover.

WASHINGTON, D. C.

Electricity and Electronics. Resistance and Reactance. Electron Devices. Electrical Instruments. Magnetic Measurements. Dielectrics. Engineering Electronics. Electronic Instrumentation. Electrochemistry.

Optics and Metrology. Photometry and Colorimetry. Optical Instruments. Photographic Technology. Length. Engineering Metrology.

Heat. Temperature Physics. Thermodynamics. Cryogenic Physics. Rheology. Engine Fuels. Free Radicals Research.

Atomic and Radiation Physics. Spectroscopy. Radiometry. Mass Spectrometry. Solid State Physics. Electron Physics. Atomic Physics. Neutron Physics. Nuclear Physics. Radioactivity. X-rays. Betatron. Nucleonic Instrumentation. Radiological Equipment.

Chemistry. Organic Coatings. Surface Chemistry. Organic Chemistry. Analytical Chemistry. Inorganic Chemistry. Electrodeposition. Molecular Structure and Properties of Gases. Physical Chemistry. Thermochemistry. Spectrochemistry. Pure Substances.

Mechanics. Sound. Mechanical Instruments. Fluid Mechanics. Engineering Mechanics. Mass and Scale. Capacity, Density, and Fluid Meters. Combustion Controls.

Organic and Fibrous Materials. Rubber. Textiles. Paper. Leather. Testing and Specifications. Polymer Structure. Plastics. Dental Research.

Metallurgy. Thermal Metallurgy. Chemical Metallurgy. Mechanical Metallurgy. Corrosion. Metal Physics.

Mineral Products. Engineering Ceramics. Glass. Refractories. Enameled Metals. Concreting Materials. Constitution and Microstructure.

Building Technology. Structural Engineering. Fire Protection. Air Conditioning, Heating, and Refrigeration. Floor, Roof, and Wall Coverings. Codes and Safety Standards. Heat Transfer.

Applied Mathematics. Numerical Analysis. Computation. Statistical Engineering. Mathematical Physics.

Data Processing Systems. SEAC Engineering Group. Components and Techniques. Digital Circuitry. Digital Systems. Analog Systems. Application Engineering.

• Office of Basic Instrumentation.

• Office of Weights and Measures.

BOULDER, COLORADO

Cryogenic Engineering. Cryogenic Equipment. Cryogenic Processes. Properties of Materials. Gas Liquefaction.

Radio Propagation Physics. Upper Atmosphere Research. Ionospheric Research. Regular Propagation Services. Sun-Earth Relationships. VHF Research.

Radio Propagation Engineering. Data Reduction Instrumentation. Modulation Systems. Navigation Systems. Radio Noise. Tropospheric Measurements. Tropospheric Analysis. Radio Systems Application Engineering. Radio Meteorology.

Radio Standards. High Frequency Electrical Standards. Radio Broadcast Service. High Frequency Impedance Standards. Calibration Center. Microwave Physics. Microwave Circuit Standards.

