



Federal Implementation Guideline for Electronic Data Interchange

ASC X12 003040 Transaction Set 997 Functional Acknowledgment

Implementation Convention



U.S. DEPARTMENT OF COMMERCE
Technology Administration
National Institute of
Standards and Technology

Federal Implementation Guideline for Electronic Data Interchange

ASC X12 003040 Transaction Set 997 Functional Acknowledgment

Implementation Convention

Electronic Commerce Acquisition Program Management Office
Standard Management Committee - Secretariat
National Institute of Standards and Technology
Gaithersburg, MD 20899-0001

Editor: Dr. Jean-Philippe Favreau

March 1997



U.S. DEPARTMENT OF COMMERCE
William M. Daley, Secretary

Technology Administration
Mary L. Good, Under Secretary for Technology

National Institute of Standards and Technology
Arati Prabhakar, Director

Reports on Information Technology

The National Institute of Standards and Technology (NIST)'s Information Technology Laboratory (ITL) develops standards and guidelines, provides technical assistance, and conducts research for computers and resources. As part of the overall federal effort to establish a single face to industry for conducting electronic commerce, ITL has been designated as the organization responsible for coordinating the development of Federal Implementation Conventions (ICs) for Electronic Data Interchange (EDI). ICs are defined by functional-area experts who create and select options from standard EDI Transaction Sets to yield the implementations to be used for practical EDI. These ICs are made available to federal agencies and industry by electronic means and this Special Publication Series.

National Institute of Standards and Technology Special Publication 881-13
Natl. Inst. Stand. Technol. Spec. Publ. 881-13, 16 pages (March 1997)
CODEN: NSPUE2

U.S. GOVERNMENT PRINTING OFFICE
WASHINGTON: 1997

For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402

997 Functional Acknowledgment

Functional Group ID=**FA**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Functional Acknowledgment Transaction Set (997) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to define the control structures for a set of acknowledgments to indicate the results of the syntactical analysis of the electronically encoded documents. The encoded documents are the transaction sets, which are grouped in functional groups, used in defining transactions for business data interchange. This standard does not cover the semantic meaning of the information encoded in the transaction sets.

Notes:

1. Use this transaction set to acknowledge the receipt, and acceptance or rejection of a functional group and the transaction set(s) contained within it based upon EDI translation software syntax edits.
2. No acknowledgment of a Functional Acknowledgment transaction set, in the case of receipt and acceptance notification, shall be provided.
3. Trading Partners should limit the scope of the data provided in the case of transaction set receipt and rejection notification to the transaction set level, i.e., the 1/AK3/040 loop should not be used. However, if separate arrangements with trading partners of flexibility within the translation software do not permit this level of response, the procedures identified herein, as applicable to the 1/AK3/040 loop should be followed.

Pos. No.	Seg. ID	Name	Req. Des.	Max. Use	Loop Repeat	Notes and Comments
010	ST	Transaction Set Header	M	1		n1
020	AK1	Functional Group Response Header	M	1		n2
LOOP ID - AK2 999999						
030	AK2	Transaction Set Response Header	O	1		n3
LOOP ID - AK3 999999						
040	AK3	Data Segment Note	O	1		c1
050	AK4	Data Element Note	O	99		
060	AK5	Transaction Set Response Trailer	M	1		
070	AK9	Functional Group Response Trailer	M	1		
080	SE	Transaction Set Trailer	M	1		

Transaction Set Notes

1. These acknowledgments shall not be acknowledged, thereby preventing an endless cycle of acknowledgments of acknowledgments.
The Functional Group Header Segment (GS) is used to start the envelope for the Functional Acknowledgment Transaction Sets. In preparing the functional group of acknowledgments, the application sender's code and the application receiver's code, taken from the functional group being acknowledged, are exchanged; therefore, one acknowledgment functional group responds to only those functional groups from one application receiver's code to one application sender's code.
There is only one Functional Acknowledgment Transaction Set per acknowledged functional group.

2. AK1 is used to respond to the functional group header and to start the acknowledgement for a functional group. There shall be one AK1 segment for the functional group that is being acknowledged.
3. AK2 is used to start the acknowledgement of a transaction set within the received functional group. The AK2 segments shall appear in the same order as the transaction sets in the functional group that has been received and is being acknowledged.

Transaction Set Comments

1. The data segments of this standard are used to report the results of the syntactical analysis of the functional groups of transaction sets; they report the extent to which the syntax complies with the standards for transaction sets and functional groups. They do not report on the semantic meaning of the transaction sets (for example, on the ability of the receiver to comply with the request of the sender).

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Notes:
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the invoice transaction set).

Comments:

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
>> ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set. 997 X12.20 Functional Acknowledgment	M ID 3/3
>> ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set <i>Use to transmit a unique number assigned by the originator of the transaction set. This number may be system generated.</i>	M AN 4/9

Segment: **AK1** Functional Group Response Header
Position: 020
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To start acknowledgment of a functional group.
Notes: 1. Use to identify the unique identification number of the functional group in which the transaction set(s) being acknowledged was received.
 2. Only one functional group may be referenced in a single 997 acknowledgment transaction set.

Syntax Notes:
Semantic Notes: 1 AK101 is the functional ID found in the GS segment (GS01) in the functional group being acknowledged.
 2 AK102 is the data interchange control number found in the GS segment in the functional group being acknowledged.

Comments:

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		<u>M</u> <u>ID</u> <u>2/2</u>
>> AK101	479	Functional Identifier Code Code identifying a group of application related Transaction Sets.	
		CA Purchase Order Change Acknowledgement/Request - Seller Initiated (865)	
		FA Functional Acknowledgement (997) <i>Use only when rejecting a Functional Acknowledgment, 997 transaction set, containing syntactical errors.</i>	
		IN Invoice Information (810, 819)	
		MS Material Safety Data Sheet (848)	
		PC Purchase Order Change Request - Buyer Initiated (860)	
		PO Purchase Order (850)	
		PR Purchase Order Acknowledgement (855)	
		RA Payment Order/Remittance Advice (820)	
		RQ Request for Quotation (840) and Contract Award (836)	
		RR Response to Request For Quotation (843)	
		RS Order Status Information (869, 870)	
		SC Price/Sales Catalog (832)	
		SH Ship Notice/Manifest (856)	
		SP Specifications/Technical Information (841)	
		TD Trading Partner Profile (838)	
>> AK102	28	Group Control Number Assigned number originated and maintained by the sender. <i>Use to identify the number cited in GS06 of the functional group being acknowledged.</i>	M N0 1/9

Segment: **AK2** Transaction Set Response Header
Position: 030
Loop: AK2
Level:
Usage: Optional
Max Use: 1
Purpose: To start acknowledgment of a single transaction set.
Notes: Use to identify the unique identification number of the transaction set being acknowledged.

Syntax Notes:
Semantic Notes: 1 AK201 is the transaction set ID found in the ST segment (ST01) in the transaction set being acknowledged.
 2 AK202 is the transaction set control number found in the ST segment in the transaction set being acknowledged.

Comments:

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		<u>M</u> <u>ID</u> <u>3/3</u>
>> AK201	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set.	
		810 X12.2 Invoice	
		820 X12.4 Payment Order/Remittance Advice	
		832 X12.13 Price/Sales Catalog	
		836 X12.54 Contract Award	
		838 X12.17 Trading Partner Profile	
		840 X12.7 Request for Quotation	
		841 X12.51 Specifications/Technical Information	
		843 X12.8 Response to Request for Quotation	
		848 X12.36 Material Safety Data Sheet	
		850 X12.1 Purchase Order	
		855 X12.9 Purchase Order Acknowledgment	
		856 X12.10 Ship Notice/Manifest	
		860 X12.15 Purchase Order Change Request - Buyer Initiated	
		865 X12.16 Purchase Order Change Acknowledgment/Request - Seller Initiated	
		869 X12.11 Order Status Inquiry	
		870 X12.23 Order Status Report	
		997 X12.20 Functional Acknowledgment <i>Use only when rejecting a Functional Acknowledgment, 997, transaction set, containing syntactical errors.</i>	
>> AK202	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set <i>Use to identify the number cited in the ST02 of the transaction set being</i>	M AN 4/9

acknowledged.

Segment: **AK3** Data Segment Note
Position: 040
Loop: AK3
Level:
Usage: Optional
Max Use: 1
Purpose: To report errors in a data segment and to identify the location of the data segment.
Notes: 1. Use the 1/AK3/040 loop only when Trading Partner Agreements or translation software do not permit the level of receipt and rejection reporting to be limited to the group or transaction set level.
 2. This 1/AK3/040 loop is used only to identify one or more segments containing syntactical errors resulting in rejection of the transaction set or functional group. This loop is not used when transaction set and functional group receipt and acceptance is being acknowledged.
 3. Use to identify one or more segments containing syntax errors.

Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		
>>	AK301	721 Segment ID Code Code defining the segment ID of the data segment in error. See Appendix A - Number 77. <i>Use to identify the segment containing syntactical errors, as it appears in the ASC X12 Data Segment Dictionary, e.g., REF.</i>	M ID 2/3
>>	AK302	719 Segment Position in Transaction Set The numerical count position of this data segment from the start of the transaction set: the transaction set header is count position 1. <i>Use to identify the segment sequential position within the data stream of the transaction set as transmitted. This is not the segment portrayed in the transaction set structure.</i>	M N0 1/6
X	AK303	447 Loop Identifier Code The loop ID number given on the transaction set diagram is the value for this data element in segments LS and LE	O AN 1/4
>>	AK304	720 Segment Syntax Error Code Code indicating error found based on the syntax editing of a segment <i>1. Use only when a segment is being rejected to identify the basis for transaction set rejection.</i> <i>2. Do not use when the error is in a data element within the segment.</i> <i>3. Use any code.</i> Refer to 003040 Data Element Dictionary for acceptable code values.	O ID 1/3
X	AK305	720 Segment Syntax Error Code Code indicating error found based on the syntax editing of a segment	O ID 1/3
X	AK306	720 Segment Syntax Error Code Code indicating error found based on the syntax editing of a segment	O ID 1/3

X	AK307	720	Segment Syntax Error Code Code indicating error found based on the syntax editing of a segment	O ID	1/3
X	AK308	720	Segment Syntax Error Code Code indicating error found based on the syntax editing of a segment	O ID	1/3

Segment: **AK4** Data Element Note
Position: 050
Loop: AK3
Level:
Usage: Optional
Max Use: 99
Purpose: To report errors in a data element and to identify the location of the data element.
Notes: 1. Use to identify an erroneous data element. The segment which contains the erroneous data element must be identified in the preceding AK3 segment.
 2. Use multiple occurrences of this segment to identify one or more data element errors within the segment specified in the preceding AK3 segment.

Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

Ref.	Data Element	Name	Attributes
>> AK401	722	Element Position in Segment This is used to indicate the relative position of the data element in error in this data segment. The count starts with 1 for the data element immediately following the segment ID. This value is 0 for an error in the segment ID. <i>Use to indicate the relative position of the data element containing the syntactical error within the segment. for example, in the N1 segment: 1 indicates an error in element N101, 2 indicates and error in element N102, etc. (Note: An error in the segment ID is identified in the AK3 segment and need not be identified at this level.</i>	M N0 1/2
AK402	725	Data Element Reference Number Reference number used to locate the Data Element Dictionary. <i>Use to identify the data element number as it appears in the ASC X12 data Element Dictionary. For example, the data element number for the AK402 data element is 725.</i>	O N0 1/4
>> AK403	723	Data Element Syntax Error Code Code indicating the error found after syntax edits of a data element. <i>Use any code.</i> Refer to 003040 Data Element Dictionary for acceptable code values.	M ID 1/3
X AK404	724	Copy of Bad Data Element This is a copy of the data element in error.	O AN 1/99

Segment: **AK5** Transaction Set Response Trailer
Position: 060
Loop: AK2
Level:
Usage: Mandatory
Max Use: 1
Purpose: To acknowledge acceptance or rejection and to report errors in a transaction set.
Notes: 1. Use to indicate whether the transaction set indicated in the corresponding AK2 segment was accepted or rejected.
 2. If the transaction set is rejected, use to identify up to five (5) syntax errors at the transaction set level.

Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
>> AK501	717	Transaction Set Acknowledgment Code Code indicating accept or reject condition based on the syntax editing of the transaction set. A Accepted E Accepted But Errors Were Noted R Rejected X Rejected, Content After Decryption Could Not Be Analyzed	M ID 1/1
AK502	718	Transaction Set Syntax Error Code Code indicating error found based on the syntax editing of a transaction set. 1. Use only when a transaction set is being rejected to identify the basis for rejection. 2. Use any code. Codes may also be used in AK503-06 but no individual code may be used more than once. 3. When the 1/AK3/040 loop is not used and syntactical errors occurred below the transaction set level, use code 5. Refer to 003040 Data Element Dictionary for acceptable code values.	O ID 1/3
AK503	718	Transaction Set Syntax Error Code Code indicating error found based on the syntax editing of a transaction set. Refer to 003040 Data Element Dictionary for acceptable code values.	O ID 1/3
AK504	718	Transaction Set Syntax Error Code Code indicating error found based on the syntax editing of a transaction set. Refer to 003040 Data Element Dictionary for acceptable code values.	O ID 1/3
AK505	718	Transaction Set Syntax Error Code Code indicating error found based on the syntax editing of a transaction set. Refer to 003040 Data Element Dictionary for acceptable code values.	O ID 1/3
AK506	718	Transaction Set Syntax Error Code	O ID 1/3

Code indicating error found based on the syntax editing of a transaction set.
Refer to 003040 Data Element Dictionary for acceptable code values.

Segment: **AK9** Functional Group Response Trailer
Position: 070
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To acknowledge acceptance or rejection of a functional group and report the number of included transaction sets from the original trailer, the accepted sets, and the received sets in this functional group.
Notes: 1. Use only to indicate whether the functional group was accepted or rejected based on syntax errors in the functional group header or trailer.
 2. If the functional group is rejected, use to identify up to five (5) syntax errors at the functional group level.

Syntax Notes:
Semantic Notes:

Comments: 1 If AK901 is 'A' or 'E', then the transmitted functional group is accepted. If AK901 is 'R', then the transmitted group is rejected.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
>> AK901	715	Functional Group Acknowledge Code Code indicating accept or reject condition based on the syntax editing of the functional group. A Accepted E Accepted, But Errors Were Noted. P Partially Accepted, At Least One Transaction Set Was Rejected R Rejected	M ID 1/1
>> AK902	97	Number of Transaction Sets Included Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element.	M N0 1/6
>> AK903	123	Number of Received Transaction Sets Number of Transaction Sets received.	M N0 1/6
>> AK904	2	Number of Accepted Transaction Sets Number of accepted Transaction Sets in a Functional Group.	M N0 1/6
AK905	716	Functional Group Syntax Error Code Code indicating error found based on the syntax editing of the functional group header and/or trailer. <i>1. Use only when a functional group is being rejected to identify the basis for rejection.</i> <i>2. Use any code. Codes may also be used in AK906-09 but no individual code may be used more than once.</i> Refer to 003040 Data Element Dictionary for acceptable code values.	O ID 1/3
AK906	716	Functional Group Syntax Error Code Code indicating error found based on the syntax editing of the functional group header and/or trailer.	O ID 1/3

- AK907 716 **Functional Group Syntax Error Code** O ID 1/3
Code indicating error found based on the syntax editing of the functional group header and/or trailer.
Refer to 003040 Data Element Dictionary for acceptable code values.
- AK908 716 **Functional Group Syntax Error Code** O ID 1/3
Code indicating error found based on the syntax editing of the functional group header and/or trailer.
Refer to 003040 Data Element Dictionary for acceptable code values.
- AK909 716 **Functional Group Syntax Error Code** O ID 1/3
Code indicating error found based on the syntax editing of the functional group header and/or trailer.
Refer to 003040 Data Element Dictionary for acceptable code values.

Segment: **SE** Transaction Set Trailer
Position: 080
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments).
Notes:
Syntax Notes:
Semantic Notes:
Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
<u>Des.</u>	<u>Element</u>		
>> SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments.	M N0 1/10
>> SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set <i>Use the same number cited in ST02.</i>	M AN 4/9

NIST Technical Publications

Periodical

Journal of Research of the National Institute of Standards and Technology—Reports NIST research and development in those disciplines of the physical and engineering sciences in which the Institute is active. These include physics, chemistry, engineering, mathematics, and computer sciences. Papers cover a broad range of subjects, with major emphasis on measurement methodology and the basic technology underlying standardization. Also included from time to time are survey articles on topics closely related to the Institute's technical and scientific programs. Issued six times a year.

Nonperiodicals

Monographs—Major contributions to the technical literature on various subjects related to the Institute's scientific and technical activities.

Handbooks—Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications—Include proceedings of conferences sponsored by NIST, NIST annual reports, and other special publications appropriate to this grouping such as wall charts, pocket cards, and bibliographies.

National Standard Reference Data Series—Provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated. Developed under a worldwide program coordinated by NIST under the authority of the National Standard Data Act (Public Law 90-396). NOTE: The Journal of Physical and Chemical Reference Data (JPCRD) is published bimonthly for NIST by the American Chemical Society (ACS) and the American Institute of Physics (AIP). Subscriptions, reprints, and supplements are available from ACS, 1155 Sixteenth St., NW, Washington, DC 20056.

Building Science Series—Disseminates technical information developed at the Institute on building materials, components, systems, and whole structures. The series presents research results, test methods, and performance criteria related to the structural and environmental functions and the durability and safety characteristics of building elements and systems.

Technical Notes—Studies or reports which are complete in themselves but restrictive in their treatment of a subject. Analogous to monographs but not so comprehensive in scope or definitive in treatment of the subject area. Often serve as a vehicle for final reports of work performed at NIST under the sponsorship of other government agencies.

Voluntary Product Standards—Developed under procedures published by the Department of Commerce in Part 10, Title 15, of the Code of Federal Regulations. The standards establish nationally recognized requirements for products, and provide all concerned interests with a basis for common understanding of the characteristics of the products. NIST administers this program in support of the efforts of private-sector standardizing organizations.

Order the following NIST publications—FIPS and NISTIRs—from the National Technical Information Service, Springfield, VA 22161.

Federal Information Processing Standards Publications (FIPS PUB)—Publications in this series collectively constitute the Federal Information Processing Standards Register. The Register serves as the official source of information in the Federal Government regarding standards issued by NIST pursuant to the Federal Property and Administrative Services Act of 1949 as amended, Public Law 89-306 (79 Stat. 1127), and as implemented by Executive Order 11717 (38 FR 12315, dated May 11, 1973) and Part 6 of Title 15 CFR (Code of Federal Regulations).

NIST Interagency Reports (NISTIR)—A special series of interim or final reports on work performed by NIST for outside sponsors (both government and nongovernment). In general, initial distribution is handled by the sponsor; public distribution is by the National Technical Information Service, Springfield, VA 22161, in paper copy or microfiche form.

U.S. Department of Commerce
National Institute of Standards
and Technology
Gaithersburg, MD 20899-0001

Official Business
Penalty for Private Use \$300