

ARMY RESEARCH LABORATORY



**XM982 155-mm Artillery Projectile Container Support
System: Finite-Element Model Development and Analysis**

by Michael Minnicino

ARL-TR-3619

September 2005

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5069

ARL-TR-3619

September 2005

XM982 155-mm Artillery Projectile Container Support System: Finite-Element Model Development and Analysis

**Michael Minnicino
Weapons and Materials Research Directorate, ARL**

REPORT DOCUMENTATION PAGE			<i>Form Approved</i> OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) September 2005		2. REPORT TYPE Final	3. DATES COVERED (From - To) March 2004–February 2005		
4. TITLE AND SUBTITLE XM982 155-mm Artillery Projectile Container Support System: Finite-Element Model Development and Analysis			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Michael Minnicino			5d. PROJECT NUMBER 2152040H80		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory AMSRD-ARL-WM-MB Aberdeen Proving Ground, MD 21005-5069			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-3619		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The XM982 Excalibur container support system is intended to protect the Excalibur munition during transportation by mitigating shock and vibration loadings in addition to performing other functions such as supplementing insensitive munition capabilities. The development of a finite-element (FE) model is a valuable tool for investigating design modifications to the container-foam support system without the need for expensive experimental tests. The FE model facilitates the determination of any design issues and provides insight for future design iterations. The FE model also enables the estimation of the loading conditions the Excalibur munition experiences during drop and vibration events. The focus of this report is the container-munition system response due to container-base-down (CBD) drop events as specified by International Test Operations Procedure. Of the CBD drop events, the 2.1-m CBD, commonly called the 7-ft CBD drop, test is considered the most severe and is investigated in this effort. The developed FE model results compares well to experimental data only after significantly altering the foam stress-strain curves to account for the strain-rate effects.					
15. SUBJECT TERMS container, foam, modeling					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 36	19a. NAME OF RESPONSIBLE PERSON Michael Minnicino
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (Include area code) 410-306-1919

Contents

List of Figures	iv
List of Tables	v
1. Introduction	1
2. Three-Dimensional (3-D) Model Development	1
3. Foam Material Model and Properties	7
4. Drop Simulation	8
4.1 Initial Condition Setup	8
4.2 Large Deformation Considerations	9
4.3 Results	11
5. Conclusions and Recommendations	14
6. References	15
Distribution List	16

List of Figures

Figure 1. Excalibur container support system solid model.....	1
Figure 2. Cross section of the full FE model.	2
Figure 3. Corresponding quarter-symmetric FE model.	2
Figure 4. Container FE grid and anatomy.....	3
Figure 5. Cover (a) solid model geometry and (b) corresponding FE grid.....	3
Figure 6. Slug-foam system cross section and anatomy.	4
Figure 7. Detailed anatomy of ogive foam system.	5
Figure 8. Detailed anatomy of warhead foam.....	5
Figure 9. Slug nose (a) perspective view and (b) side view.	6
Figure 10. The 9-lb foam stress-strain curves at various temperatures and rates (vertical orientation).....	8
Figure 11. Initial velocity problem setup.....	9
Figure 12. Element erosion process that creates spurious peaks in acceleration data: (a) before erosion, (b) time-step before erosion, and (c) new contact surface at time-step after erosion.....	10
Figure 13. Unfiltered axial-direction projectile acceleration measurements for cold 7-ft CBD drop.	11
Figure 14. The 1.5-kHz low-passed axial-direction projectile acceleration measurements and simulated response for 7-ft CBD drop.	12
Figure 15. Experimentally measured stress-strain curves comparison with modified stress-strain curves to get presented results for 9-lb vertical direction foam.	12
Figure 16. Experimentally measured stress-strain curves comparison with modified stress-strain curves to get presented results for 9-lb extruded direction foam.	13
Figure 17. Experimentally measured stress-strain curves comparison with modified stress-strain curves to get presented results for 20-lb foam.	13
Figure 18. Comparison of (a) experimental ogive foam after 7-ft CBD test to (b) simulated ogive foam at maximum displacement. (c) Experimental and simulated results overlaid for qualitative comparison.	14

List of Tables

Table 1. Container material properties (plain mild steel).	4
Table 2. HDPE and foam material properties.....	6
Table 3. Slug material properties (aluminum).	7
Table 4. Erosion parameters.	10

INTENTIONALLY LEFT BLANK.

1. Introduction

The XM982 Excalibur container support system shown in figure 1 is intended to protect the Excalibur munition during transportation by mitigating shock and vibration loadings in addition to performing other functions such as supplementing insensitive munition capabilities. The development of a finite-element (FE) model is a valuable tool for investigating design modifications to the container-foam support system without the need for expensive experimental tests. The FE model facilitates the determination of any design issues and provides insight for future design iterations. The FE model also enables the estimation of the loading conditions the Excalibur munition experiences during drop and vibration events. The focus of this report is the container-munition system response due to container-base-down (CBD) drop events as specified by the International Test Operations Procedure (1) The commercial FE software LS-DYNA is used for the drop simulations (2).




Figure 1. Excalibur container support system solid model.

2. Three-Dimensional (3-D) Model Development

The analysis of the container system during the 7-ft CBD drop orientation is the primary objective of this effort, since prior experiments indicate this orientation has the highest

probability for the munition to impact the container and become damaged. The FE model uses quarter symmetry, thus allowing a more computationally efficient analysis of the CBD drop orientation. The full and quarter-symmetric FE models are shown in figures 2 and 3, respectively. The new 44.5-in container FE mesh is adapted from the previous 49.79-in container FE mesh. The foam system of the FE model is created independently using drawings received from the U.S. Army Armament Research, Development, and Engineering Center (ARDEC) located at Picatinny Arsenal, NJ. The munition FE mesh is identical to the munition mesh of the 49.79-in container configuration FE model.




Figure 2. Cross section of the full FE model.




Figure 3. Corresponding quarter-symmetric FE model.

The defeatured container FE model, figure 4, does not include the container windows, window brackets, fasteners, nor cover locking assembly. The complex stamped geometry of the container cover is modeled as a simple circular plate with a uniform 0.060-in thickness (figure 5). Since the simulation effort focuses on the 7-ft CBD drop and the container cover is distant relative to the area of interaction, it is assumed that the container cover has little effect on the event. The window and window brackets were not included in the FE model due to their geometric complexity in addition to unknown window material properties. From the previous 49.79-in container FE analyses, it was observed that omission of the windows is an adequate




Figure 4. Container FE grid and anatomy.




Figure 5. Cover (a) solid model geometry and (b) corresponding FE grid.

assumption for CBD drops as the results matched well with the experimental data (3). The container mesh is created on the corresponding mid-surfaces of the solid-model. The container is modeled with shell elements and has a uniform thickness of 0.060 in. This uniform thickness does not capture the thickness increase of the container body at the rim and ring attachments but is a reasonable approximation since the increase in thickness has an insignificant effect on the load experienced by the munition during the impact. The container is modeled with shell elements with an elastic-plastic kinematic hardening material model, LS-Dyna material model *MAT_ELASTIC_PLASTIC. The shells have the appropriate thickness values except at the ring and rim “attachment flanges” where the rim and rings are affixed to the container body. The container material properties are listed in table 1.

Table 1. Container material properties (plain mild steel).

Property	Value
ρ	7.25 E-04 lb-s ² /in ⁴
E	3.00 E+07 psi
ν	0.3
σ_y	4.00 E+04 psi
E_{tan}	2.01 E+05 psi

The foam-projectile slug assembly is modeled using hexahedral (brick) elements. A cross section is shown in figure 6. The foam is modeled using LS-Dyna's *CRUSHABLE_FOAM material model. This material model behaves like a nonlinear elastic-plastic material constitutive model in that it does not unload to zero strain, but rather to an effective plastic strain. This is because the crushable foam material model unloads at a rate equal to the largest modulus in the stress-strain curve. Due to this experimentally unmeasured behavior, the solution is questionable after the projectile reverses direction (i.e., crosses zero velocity) and the foam begins to unload.




Figure 6. Slug-foam system cross section and anatomy.

The ogive foam assembly shown in figure 7 consists of (from left to right) 9-lb foam, 20-lb foam, HDPE, and 9-lb foam oriented in its extruded direction relative to the container centerline axis. The foams are assumed to be homogeneous orthotropic materials; however, only the extruded direction is distinguished from the remaining two orientations due to its relatively larger increased stiffness (4). Additionally, there is a HDPE annulus located on the munition ogive for the purpose of transferring the load to the 9-lb foam at a location away from the sensitive and highly-stressed section due to the CBD drops on the munition nose. The Warhead foam assembly consists of alternating annuluses of 6-lb foam and HDPE as shown in figure 8.

The foam is orthotropic; however, the *MAT_CRUSHABLE_FOAM material model is the constitutive law for an isotropic material. Therefore, the dominate properties of the foam relative to the load direction are used to represent the isotropic response of the foam. For example, the extruded 9-lb foam found between the HDPE plate and the container bottom is modeled as if it is isotropic with properties of the extruded direction. The parameters used for the HDPE and foam material models are listed in table 2.




Figure 7. Detailed anatomy of ogive foam system.




Figure 8. Detailed anatomy of warhead foam.

The slug used in the drop tests is aluminum and is machined to have the profile of the Excalibur munition. Additionally, the slug is ballasted to have the same mass properties as the Excalibur munition. The FE mesh of the slug nose is shown in figure 9. The projectile “slug” is modeled as a rigid body with the properties of aluminum using LS-Dyna’s *MAT_RIGID material model. This was done to easily specify the body’s mass properties, e.g., its center of gravity, translational mass, and principal moments of inertia. As an additional benefit, the rigid body assumption also improves computational efficiency. If the slug is modeled as a deformable aluminum body, the time-step may be limited by the small hexahedral elements in the nose of the slug as shown in figure 9, which results in a longer run time. Lastly, this rigid body assumption

Table 2. HDPE and foam material properties.

Property	Value
(a) HDPE	
ρ	8.97 E-05 lb-s ² /in ⁴
E	3.00 E+05 psi
ν	0.33
(b) Foam 6 lb	
ρ	9.00 E-06 lb-s ² /in ⁴
E	1.00 E+05 psi
ν	0.01
Stress-strain curve: modified 6 lb (original 9-lb stress-strain curve)	
(c) Foam 9 lb	
ρ	1.35 E-05 lb-s ² /in ⁴
E	8.00 E+03 psi
ν	0.01
Stress-strain curve: modified 9 lb	
(d) Foam 9 lb extruded	
ρ	1.35 E-05 lb-s ² /in ⁴
E	5.50 E+04 psi
ν	0.01
Stress-strain curve: modified 9 lb extruded	
(e) Foam 20 lb	
ρ	1.35 E-05 lb-s ² /in ⁴
E	5.50 E+04 psi
ν	0.01
Stress-strain curve: modified 20 lb	

is reasonable since relative to the foam, the aluminum slug is approximately rigid. This implies that the internal strain energy stored by deformation of the slug is negligible in comparison to the strain energy stored in the rest of the system. The material parameters for this rigid material model are listed in table 3.




Figure 9. Slug nose (a) perspective view and (b) side view.

Table 3. Slug material properties (aluminum).

Property	Value
ρ	2.59 E-04 lb-s ² /in ⁴
E	1.00 E+07 psi
ν	0.3
X _c	22 in
Y _c	0 in
Z _c	0 in
T _m	2.72 E-01 lb-s ² /in ⁴
I _{xx}	1.37 lb-s ² /in ⁴
I _{xy}	~0 lb-s ² /in ⁴
I _{xz}	~0 lb-s ² /in ⁴
I _{yy}	21.5 lb-s ² /in ⁴
I _{yz}	~0 lb-s ² /in ⁴
I _{zz}	21.5 lb-s ² /in ⁴

3. Foam Material Model and Properties

Initial foam material properties were obtained from Dow Chemical’s customer support group (4). Dow Chemical supplied the load-displacement and stress-strain curves for the Ethafoam HS 900 tested at room temperature, 70 °F (23 °C), at a crosshead rate of 39.37 in/s (1.0 m/s). Additionally, Dow provided a table consisting of five data points along these curves.

The foam material was modeled in LS-Dyna using the *MAT_CRUSHABLE_FOAM constitutive model (2). The necessary material properties for this constitutive model for a given temperature are

- density,
- Poisson’s ratio,
- stress-strain curve,
- modulus of elasticity (initial), and
- tensile strength.

The Dow information provides density, tensile strength, and a limited number of stress-strain curve data points, all of which are at room temperature. In order to adequately characterize the foam, in-house material testing was conducted to determine the foam’s compressive stress-strain curves at 170 °F (77 °C), –60 °F (–51 °C), and 70 °F (21 °C) (5). Poisson’s ratio could not be determined due to the porosity of the foam, so a value of 0.01 is assumed in the following analyses. This Poisson’s ratio value was obtained from reference (6), which has data for similar foams. Also, a small parametric study was conducted in which the Poisson’s ratio was varied from 0.01 to 0.10 and was found to have little influence on the foam response (7).

The average 9-lb and 9-lb extruded foam stress-strain curves for all temperatures are shown in figure 10. The stress-strain curves agree with intuition since the cold curves have both a larger initial modulus of elasticity and yield strength than compared to curves obtained at warmer temperatures. Notice for the room temperature curves that the 9-lb foam stress-strain curves agree well with the plotted Dow data points. Two strain rates were used to load the foam specimens: a slow strain rate of 2.1 m/m-s and a higher strain rate of 18-30 m/m-s.




Figure 10. The 9-lb foam stress-strain curves at various temperatures and rates (vertical orientation).

4. Drop Simulation

4.1 Initial Condition Setup

The FE model is setup for a 7-ft CBD drop simulation using the cold foam material properties. The drop simulation is formulated as an initial velocity problem since the response before impact is irrelevant and its calculation is unproductive. To calculate the relevant impact response, the model is defined so the container system is slightly offset (0.005 in) from a user-defined rigid surface at a user-defined orientation with a uniform initial velocity as illustrated in figure 11. Gravity is not included in the analysis. However, the initial impact velocity is determined by considering gravity and the drop height. Thus, the effect of gravity on the rebound of the container is not considered. For the impact event, this is acceptable. The model is conservative

since it does not include friction. Friction is not included because the appropriate foam-aluminum coefficient of friction value is unknown. This model represents a worst-case scenario since the inclusion of friction between the slug and foam will increase the dissipation of energy and reduce the overall displacement of the slug. The initial impact velocity is determined by considering conservation of energy

$$mgh = \frac{1}{2}mv^2 \text{ or } v = \sqrt{2gh}, \quad (1)$$

where v is initial impact velocity, m is the system mass, g is gravity, and h is the drop height. For example, a 3-ft drop results in an initial impact velocity of 167 in/s.




Figure 11. Initial velocity problem setup.

4.2 Large Deformation Considerations

Difficulties are encountered when simulating a CBD drop test due to excessive distortion of the ogive foam elements located near the slug nose. These difficulties are the result of the foam being relatively soft (see Foam Material Model and Properties section). At low-to-moderate strain rates, the 9-lb foam does not begin to significantly resist compressive load until a compressive strain of ~ 0.85 . At these large strains, the FE mesh can become severely distorted, which causes numerical issues in the solution. Thus, in order to capture the foam deformation, a very fine mesh is needed to alleviate or prevent element distortion. The avoidance of severe element distortion is important for three main reasons. First, severe element distortion causes the Jacobian to approach zero, and results in a runtime error, causing the solver to halt. Secondly, excessive element distortion causes contact definitions between entities to become ineffective (loss of contact), thereby enabling the slug to move freely into the ogive foam region where the elements are highly distorted. The third reason is that severe element distortion causes the elements critical time-step to become very small, resulting in longer run times.

A simple and often utilized method to prevent element distortion is to remove, or erode, elements prior to the elements reaching a highly distorted state. The FE erosion sequence is shown in figure 12. Although this method can conserve energy at the cost of computational efficiency, it was implemented in this analysis such that the eroded element and its associated mass and

energy are omitted. Therefore, once an element meets or exceeds a user-defined failure criteria, the element has no further effect on the subsequent system behavior. For light and relatively slow moving materials, such as the foam, omitting the mass and energy loss is a reasonable approximation. The 9-lb extruded direction foam material was not permitted to erode. It is observed that element erosion allows the simulation to reach completion, and the results appear reasonable during the compression phase of the impact event. The erosion parameters are listed in table 4.




Figure 12. Element erosion process that creates spurious peaks in acceleration data: (a) before erosion, (b) time-step before erosion, and (c) new contact surface at time-step after erosion.

Table 4. Erosion parameters.

Property	Value
Foam 9 lb	
σ_{vm}	2000 psi
ϵ_l	—
τ	—
Foam 9 lb extruded	
σ_{vm}	—
ϵ_l	—
τ	—
Foam 20 lb	
σ_{vm}	45 ksi
ϵ_l	0.5 in/in
τ	1.95 in/in

Also, interior contact was implemented to further improve the element behavior under large deformation. Interior contact is a new type of contact model in LS-Dyna version 970 specifically developed for enclosed foams (2). Interior contact attempts to prevent highly localized element distortion by creating additional contact surfaces within each element. For soft material slave elements, such as the foam, traditional contact loading will significantly deform the slave

element closest to the master contact element and leave interior slave contact elements virtually undeformed. However, using interior contact surfaces effectively distributes the contact load to the adjacent slave contact elements. This contact is seen to help prevent element distortion and is used in the analyses. See reference (2) for more information.

4.3 Results

Drop tests were conducted at ARDEC and the results are presented in Bahia et al. (8). The cold 7-ft CBD drop experimental acceleration-time histories of the slug at the Fuze Safe and Arm (FSA) and Inertial Measurement Unit (IMU) are shown in figure 13, measured with Endevco accelerometers models 7259 and 7270, respectively. The source of high-frequency content in the acceleration-time histories is unknown. Simple rigid body momentum calculations reveal that the peak acceleration is ~66-131 G, depending on the assumed waveform shape (square, half-sine, or triangular waveforms). The acceleration-time histories are subsequently digitally low-pass filtered using a 4th-order Butterworth filter with a cutoff frequency of 1.5 kHz. The filtered acceleration-time histories are shown in figure 14. The FSA and IMU have peak accelerations of ~110 G and 140 G, respectively, and are in the range of the expected peak values based on simple momentum calculations.




Figure 13. Unfiltered axial-direction projectile acceleration measurements for cold 7-ft CBD drop.

For the quarter-symmetry model results, the rigid slug maximum displacement is 1.350 in. The projectile crossed zero velocity at ~8.2 ms. The maximum deceleration of the projectile is about 138 G. The simulated rigid body acceleration-time history for the slug is shown with the experimental plots in figure 14. The modified foam stress-strain curves (6-lb foam stress-strain curve is not modified), relative to the experimentally determined stress-strain curves, that are used to get the acceleration-time history are shown in figures 15–17. The primary reason the stress-strain curves are significantly different from their original curves is due to the foam's




Figure 14. The 1.5-kHz low-passed axial-direction projectile acceleration measurements and simulated response for 7-ft CBD drop.




Figure 15. Experimentally measured stress-strain curves comparison with modified stress-strain curves to get presented results for 9-lb vertical direction foam.

strain-rate dependence and the lack of stress-strain curves at the strain rate of the drop event—LS-Dyna predicts a strain-rate, given the modified stress-strain curves, of approximately an order of magnitude higher than the tested 20–30 m/m-s for most of the foam system and a strain rate of several hundred for the foam near the slug nose. Lack of real stress-strain curves at these high strain-rates prevents accurate simulation of the drop event. Lastly, a cross section of the ogive foam is after a 7-ft drop test is shown in figure 18(a). The quarter-symmetric cross section of the

ogive foam of the simulation is shown in figure 18b at maximum displacement. The net ogive foam system deformation is seen to be similar to the simulated maximum displacement as shown in 18c.




Figure 16. Experimentally measured stress-strain curves comparison with modified stress-strain curves to get presented results for 9-lb extruded direction foam.




Figure 17. Experimentally measured stress-strain curves comparison with modified stress-strain curves to get presented results for 20-lb foam.




Figure 18. Comparison of (a) experimental ogive foam after 7-ft CBD test to (b) simulated ogive foam at maximum displacement. (c) Experimental and simulated results overlaid for qualitative comparison.

5. Conclusions and Recommendations

The 3-D quarter-symmetric FE model is developed in addition to the full 3-D FE model in LS-Dyna for the drop simulations. The quarter-symmetric FE model was developed for quicker solution times. The quarter-symmetric model can be used only for symmetric loading conditions: nose-down and base-down orientations. The symmetric loading condition assumes that the container perfectly impacts the rigid surface. The full FE model is required for horizontal, diagonal, and edgewise (nonsymmetric) oriented simulations.

The 7-ft CBD drop simulation compares well to experimental data only after significantly altering the foam stress-strain curves to account for the strain-rate effects. To better predict the system response, the foam behavior at these high strain-rates is required. It is recommended that the full-field behavior of the system be determined during the drop event as the acceleration-time histories do not provide a unique solution. This may be achieved by using photogrammetry and removing a pie or wedge-shaped volume from the container-foam to allow for visual inspection of the slug-foam behavior during the drop event.

6. References

1. International Text Operations Procedure (ITOP) 4-2-602. AD No. B220218. Rough Handling Tests, 11 October 1996.
2. Livermore Software Technology Corporation. *LS-DYNA Keyword User's Manual, version 970*; Livermore, CA, April 2003.
3. Minnicino, M. Status of Container Stress Model, First Configuration. Oral presentation. Picatinny, NJ, February 2004.
4. Dow Chemical Research Center. *Ethafoam*; Dow Data Sheet; Product Performance Lab: Midland, MI, 4 December 2003.
5. Leadore, M.; Lieb, R. *Foam Characterization Data*; private empirical data distribution, December 2003.
6. Hassan, J.; Schuser, P.; and Frederick, G. Polyurethane Material Models for Simulating Leg-Form Impact in Explicit Transient Dynamics. *6th International LS-DYNA Users Conference Simulation 2000*, Dearborn, MI, April 2000.
7. Minnicino, M. Container Stress Model, Second Configuration. Oral presentation. Picatinny, NJ, January 2005.
8. Bahia, A.; Guevara, M.; Vega, J. *Container Test*; experimental data brief; U.S. Army Armament Research, Development, and Engineering Center: Picatinny Arsenal, NJ, December 2004.

NO. OF
COPIES ORGANIZATION

1 DEFENSE TECHNICAL
(PDF INFORMATION CTR
ONLY) DTIC OCA
8725 JOHN J KINGMAN RD
STE 0944
FORT BELVOIR VA 22060-6218

1 US ARMY RSRCH DEV &
ENGRG CMD
SYSTEMS OF SYSTEMS
INTEGRATION
AMSRD SS T
6000 6TH ST STE 100
FORT BELVOIR VA 22060-5608

1 INST FOR ADVNCD TCHNLGY
THE UNIV OF TEXAS
AT AUSTIN
3925 W BRAKER LN
AUSTIN TX 78759-5316

1 DIRECTOR
US ARMY RESEARCH LAB
IMNE ALC IMS
2800 POWDER MILL RD
ADELPHI MD 20783-1197

3 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CI OK TL
2800 POWDER MILL RD
ADELPHI MD 20783-1197

3 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CS IS T
2800 POWDER MILL RD
ADELPHI MD 20783-1197

ABERDEEN PROVING GROUND

1 DIR USARL
AMSRD ARL CI OK TP (BLDG 4600)

NO. OF
COPIES ORGANIZATION

1 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL SE DE
R ATKINSON
2800 POWDER MILL RD
ADELPHI MD 20783-1197

5 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL WM MB
A ABRAHAMIAN
M BERMAN
M CHOWDHURY
T LI
E SZYMANSKI
2800 POWDER MILL RD
ADELPHI MD 20783-1197

1 COMMANDER
US ARMY MATERIEL CMD
AMXMI INT
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

2 PM MAS
SFAE AMO MAS MC
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR CC
COL JENKER
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR FSE
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR TD
PICATINNY ARSENAL NJ
07806-5000

NO. OF
COPIES ORGANIZATION

13 COMMANDER
US ARMY ARDEC
AMSTA AR CCH A
F ALTAMURA
M NICOLICH
M PALATHINGUL
D VO
R HOWELL
A VELLA
M YOUNG
L MANOLE
S MUSALLI
R CARR
M LUCIANO
E LOGSDEN
T LOUZEIRO
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR CCH P
J LUTZ
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR FSF T
C LIVECCHIA
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA ASF
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR QAC T C
J PAGE
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR M
D DEMELLA
PICATINNY ARSENAL NJ
07806-5000

NO. OF
COPIES ORGANIZATION

3 COMMANDER
US ARMY ARDEC
AMSTA AR FSA
A WARNASH
B MACHAK
M CHIEFA
PICATINNY ARSENAL NJ
07806-5000

2 COMMANDER
US ARMY ARDEC
AMSTA AR FSP G
M SCHIKSNIS
D CARLUCCI
PICATINNY ARSENAL NJ
07806-5000

2 COMMANDER
US ARMY ARDEC
AMSTA AR CCH C
H CHANIN
S CHICO
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR QAC T
D RIGOGLIOSO
PICATINNY ARSENAL NJ
07806-5000

1 US ARMY ARDEC
INTELLIGENCE SPECIALIST
AMSTA AR WEL F
M GUERRIERE
PICATINNY ARSENAL NJ
07806-5000

9 COMMANDER
US ARMY ARDEC
AMSTA AR CCH B
P DONADIA
F DONLON
P VALENTI
C KNUTSON
G EUSTICE
K HENRY
J MCNABOC
R SAYER
F CHANG
PICATINNY ARSENAL NJ
07806-5000

NO. OF
COPIES ORGANIZATION

1 PM ARMS
SFAE GCSS ARMS
BLDG 171
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY ARDEC
AMSTA AR WEA
J BRESCIA
PICATINNY ARSENAL NJ
07806-5000

1 PM MAS
SFAE AMO MAS
PICATINNY ARSENAL NJ
07806-5000

1 PM MAS
SFAE AMO MAS
CHIEF ENGINEER
PICATINNY ARSENAL NJ
07806-5000

1 PM MAS
SFAE AMO MAS PS
PICATINNY ARSENAL NJ
07806-5000

2 PM MAS
SFAE AMO MAS LC
PICATINNY ARSENAL NJ
07806-5000

1 COMMANDER
US ARMY TACOM
PM COMBAT SYSTEMS
SFAE GCS CS
6501 ELEVEN MILE RD
WARREN MI 48397-5000

1 COMMANDER
US ARMY TACOM
AMSTA SF
WARREN MI 48397-5000

1 DIRECTOR
AIR FORCE RESEARCH LAB
MLLMD
D MIRACLE
2230 TENTH ST
WRIGHT PATTERSON AFB OH
45433-7817

NO. OF COPIES ORGANIZATION

- 1 OFC OF NAVAL RESEARCH
J CHRISTODOULOU
ONR CODE 332
800 N QUINCY ST
ARLINGTON VA 22217-5600
- 1 COMMANDER
US ARMY TACOM
PM SURVIVABLE SYSTEMS
SFAE GCSS W GSI H
M RYZYI
6501 ELEVEN MILE RD
WARREN MI 48397-5000
- 1 COMMANDER
US ARMY TACOM
CHIEF ABRAMS TESTING
SFAE GCSS W AB QT
T KRASKIEWICZ
6501 ELEVEN MILE RD
WARREN MI 48397-5000
- 1 COMMANDER
WATERVLIET ARSENAL
SMCWV QAE Q
B VANINA
BLDG 44
WATERVLIET NY 12189-4050
- 2 HQ IOC TANK
AMMUNITION TEAM
AMSIO SMT
R CRAWFORD
W HARRIS
ROCK ISLAND IL 61299-6000
- 2 COMMANDER
US ARMY AMCOM
AVIATION APPLIED TECH DIR
J SCHUCK
FORT EUSTIS VA 23604-5577
- 1 NSWC
DAHLGREN DIV CODE G06
DAHLGREN VA 22448
- 2 US ARMY CORPS OF ENGR
CERD C
T LIU
CEW ET
T TAN
20 MASSACHUSETTS AVE NW
WASHINGTON DC 20314

NO. OF COPIES ORGANIZATION

- 1 US ARMY COLD REGIONS
RSCH & ENGRNG LAB
P DUTTA
72 LYME RD
HANOVER NH 03755
- 13 COMMANDER
US ARMY TACOM
AMSTA TR R
R MCCLELLAND
D THOMAS
J BENNETT
D HANSEN
AMSTA JSK
S GOODMAN
J FLORENCE
D TEMPLETON
A SCHUMACHER
AMSTA TR D
D OSTBERG
L HINOJOSA
B RAJU
AMSTA CS SF
H HUTCHINSON
F SCHWARZ
WARREN MI 48397-5000
- 14 BENET LABS
AMSTA AR CCB
R FISCELLA
M SOJA
E KATHE
M SCAVULO
G SPENCER
P WHEELER
S KRUPSKI
J VASILAKIS
G FRIAR
R HASENBEIN
AMSTA CCB R
S SOPOK
E HYLAND
D CRAYON
R DILLON
WATERVLIET NY 12189-4050
- 1 USA SBCCOM PM SOLDIER SPT
AMSSB PM RSS A
J CONNORS
KANSAS ST
NATICK MA 01760-5057

NO. OF
COPIES ORGANIZATION

1 NSWC
TECH LIBRARY CODE B60
17320 DAHLGREN RD
DAHLGREN VA 22448

2 USA SBCCOM
MATERIAL SCIENCE TEAM
AMSSB RSS
J HERBERT
M SENNETT
KANSAS ST
NATICK MA 01760-5057

2 OFC OF NAVAL RESEARCH
D SIEGEL CODE 315
J KELLY
800 N QUINCY ST
ARLINGTON VA 22217-5560

1 NSWC
CRANE DIVISION
M JOHNSON CODE 20H4
LOUISVILLE KY 40214-5245

2 NSWC
U SORATHIA
C WILLIAMS CODE 6551
9500 MACARTHUR BLVD
WEST BETHESDA MD 20817

2 COMMANDER
NSWC
CARDEROCK DIVISION
R PETERSON CODE 2020
M CRITCHFIELD CODE 1730
BETHESDA MD 20084

8 DIRECTOR
US ARMY NGIC
D LEITER MS 404
M HOLTUS MS 301
M WOLFE MS 307
S MINGLEDORF MS 504
J GASTON MS 301
W GSTATTENBAUER MS 304
R WARNER MS 305
J CRIDER MS 306
2055 BOULDERS RD
CHARLOTTESVILLE VA
22911-8318

NO. OF
COPIES ORGANIZATION

1 NAVAL SEA SYSTEMS CMD
D LIESE
1333 ISAAC HULL AVE SE 1100
WASHINGTON DC 20376-1100

7 US ARMY SBCCOM
SOLDIER SYSTEMS CENTER
BALLISTICS TEAM
J WARD
W ZUKAS
P CUNNIFF
J SONG
MARINE CORPS TEAM
J MACKIEWICZ
AMSSB RCP SS
W NYKVIST
S BEAUDOIN
KANSAS ST
NATICK MA 01760-5019

7 US ARMY RESEARCH OFC
A CROWSON
H EVERITT
J PRATER
G ANDERSON
D STEPP
D KISEROW
J CHANG
PO BOX 12211
RESEARCH TRIANGLE PARK NC
27709-2211

1 AFRL MLBC
2941 P ST RM 136
WRIGHT PATTERSON AFB OH
45433-7750

1 DIRECTOR
LOS ALAMOS NATL LAB
F L ADDESSIO T 3 MS 5000
PO BOX 1633
LOS ALAMOS NM 87545

8 NSWC
J FRANCIS CODE G30
D WILSON CODE G32
R D COOPER CODE G32
J FRAYSSE CODE G33
E ROWE CODE G33
T DURAN CODE G33
L DE SIMONE CODE G33
R HUBBARD CODE G33
DAHLGREN VA 22448

NO. OF
COPIES ORGANIZATION

1 NSWC
CARDEROCK DIVISION
R CRANE CODE 6553
9500 MACARTHUR BLVD
WEST BETHESDA MD 20817-5700

1 AFRL MLMP
R THOMSON
2977 HOBSON WAY
BLDG 653 RM 215
WRIGHT PATTERSON AFB OH
45433-7739

2 AFRL MLMP
F ABRAMS
J BROWN
2977 HOBSON WAY
BLDG 653 RM 215
WRIGHT PATTERSON AFB OH
45433-7739

5 DIRECTOR
LLNL
R CHRISTENSEN
S DETERESA
F MAGNESS
M FINGER MS 313
M MURPHY L 282
PO BOX 808
LIVERMORE CA 94550

1 AFRL MLS OL
L COULTER
5851 F AVE
BLDG 849 RM AD1A
HILL AFB UT 84056-5713

1 OSD
JOINT CCD TEST FORCE
OSD JCCD
R WILLIAMS
3909 HALLS FERRY RD
VICKSBURG MS 29180-6199

3 DARPA
M VANFOSSEN
S WAX
L CHRISTODOULOU
3701 N FAIRFAX DR
ARLINGTON VA 22203-1714

NO. OF
COPIES ORGANIZATION

1 OAK RIDGE NATL LAB
R M DAVIS
PO BOX 2008
OAK RIDGE TN 37831-6195

1 OAK RIDGE NATL LAB
C EBERLE MS 8048
PO BOX 2008
OAK RIDGE TN 37831

3 DIRECTOR
SANDIA NATL LABS
APPLIED MECHS DEPT
MS 9042
J HANDROCK
Y R KAN
J LAUFFER
PO BOX 969
LIVERMORE CA 94551-0969

1 OAK RIDGE NATL LAB
C D WARREN MS 8039
PO BOX 2008
OAK RIDGE TN 37831

4 NIST
M VANLANDINGHAM MS 8621
J CHIN MS 8621
J MARTIN MS 8621
D DUTHINH MS 8611
100 BUREAU DR
GAITHERSBURG MD 20899

1 HYDROGEOLOGIC INC
SERDP ESTCP SPT OFC
S WALSH
1155 HERNDON PKWY STE 900
HERNDON VA 20170

3 NASA LANGLEY RESEARCH CTR
AMSRD ARL VT
W ELBER MS 266
F BARTLETT JR MS 266
G FARLEY MS 266
HAMPTON VA 23681-0001

1 FHWA
E MUNLEY
6300 GEORGETOWN PIKE
MCLEAN VA 22101

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	USDOT FEDERAL RAILROAD M FATEH RDV 31 WASHINGTON DC 20590
3	CYTEC FIBERITE R DUNNE D KOHLI R MAYHEW 1300 REVOLUTION ST HAVRE DE GRACE MD 21078
1	DIRECTOR NGIC IANG TMT 2055 BOULDERS RD CHARLOTTESVILLE VA 22911-8318
2	3TEX CORP A BOGDANOVICH J SINGLETARY 109 MACKENAN DR CARY NC 27511
1	DIRECTOR DEFENSE INTLLGNC AGNCY TA 5 K CRELLING WASHINGTON DC 20310
1	COMPOSITE MATERIALS INC D SHORTT 19105 63 AVE NE PO BOX 25 ARLINGTON WA 98223
1	JPS GLASS L CARTER PO BOX 260 SLATER RD SLATER SC 29683
1	COMPOSITE MATERIALS INC R HOLLAND 11 JEWEL CT ORINDA CA 94563

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	SIMULA R HUYETT 10016 S 51ST ST PHOENIX AZ 85044
2	PROTECTION MATERIALS INC M MILLER F CRILLEY 14000 NW 58 CT MIAMI LAKES FL 33014
2	FOSTER MILLER M ROYLANCE W ZUKAS 195 BEAR HILL RD WALTHAM MA 02354-1196
1	ROM DEVELOPMENT CORP R O MEARA 136 SWINEBURNE ROW BRICK MARKET PLACE NEWPORT RI 02840
2	TEXTRON SYSTEMS M TREASURE T FOLTZ 1449 MIDDLESEX ST LOWELL MA 01851
1	O GARA HESS & EISENHARDT M GILLESPIE 9113 LESAINTE DR FAIRFIELD OH 45014
1	MILLIKEN RESEARCH CORP M MACLEOD PO BOX 1926 SPARTANBURG SC 29303
1	CONNEAUGHT INDUSTRIES INC J SANTOS PO BOX 1425 COVENTRY RI 02816
1	ARMTEC DEFENSE PRODUCTS S DYER 85 901 AVE 53 PO BOX 848 COACHELLA CA 92236

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
3	PACIFIC NORTHWEST LAB M SMITH G VAN ARSDALE R SHIPPELL PO BOX 999 RICHLAND WA 99352
1	ALLIANT TECHSYSTEMS INC 4700 NATHAN LN N PLYMOUTH MN 55442-2512
1	APPLIED COMPOSITES W GRISCH 333 NORTH SIXTH ST ST CHARLES IL 60174
1	CUSTOM ANALYTICAL ENG SYS INC A ALEXANDER 13000 TENSOR LANE NE FLINTSTONE MD 21530
1	AAI CORP DR N B MCNELLIS PO BOX 126 HUNT VALLEY MD 21030-0126
1	OFC DEPUTY UNDER SEC DEFNS J THOMPSON 1745 JEFFERSON DAVIS HWY CRYSTAL SQ 4 STE 501 ARLINGTON VA 22202
3	ALLIANT TECHSYSTEMS INC J CONDON E LYNAM J GERHARD WV01 16 STATE RT 956 PO BOX 210 ROCKET CENTER WV 26726-0210
1	PROJECTILE TECHNOLOGY INC 515 GILES ST HAVRE DE GRACE MD 21078
1	PRATT & WHITNEY C WATSON 400 MAIN ST MS 114 37 EAST HARTFORD CT 06108

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
5	NORTHROP GRUMMAN B IRWIN K EVANS D EWART A SHREKENHAMER J MCGLYNN BLDG 160 DEPT 3700 1100 W HOLLYVALE ST AZUSA CA 91701
1	BRIGS COMPANY J BACKOFEN 2668 PETERBOROUGH ST HERNDON VA 22071-2443
1	ZERNOW TECHNICAL SERVICES L ZERNOW 425 W BONITA AVE STE 208 SAN DIMAS CA 91773
2	GENERAL DYNAMICS OTS FLINCHBAUGH DIV K LINDE T LYNCH PO BOX 127 RED LION PA 17356
1	GKN WESTLAND AEROSPACE D OLDS 450 MURDOCK AVE MERIDEN CT 06450-8324
5	SIKORSKY AIRCRAFT G JACARUSO T CARSTENSAN B KAY S GARBO MS S330A J ADELMANN 6900 MAIN ST PO BOX 9729 STRATFORD CT 06497-9729
1	AEROSPACE CORP G HAWKINS M4 945 2350 E EL SEGUNDO BLVD EL SEGUNDO CA 90245
2	CYTEC FIBERITE M LIN W WEB 1440 N KRAEMER BLVD ANAHEIM CA 92806

NO. OF
COPIES ORGANIZATION

2 UDLP
G THOMAS
M MACLEAN
PO BOX 58123
SANTA CLARA CA 95052

2 UDLP
R BRYNSVOLD
P JANKE MS 170
4800 E RIVER RD
MINNEAPOLIS MN 55421-1498

1 LOCKHEED MARTIN
SKUNK WORKS
D FORTNEY
1011 LOCKHEED WAY
PALMDALE CA 93599-2502

1 NORTHRUP GRUMMAN CORP
ELECTRONIC SENSORS
& SYSTEMS DIV
E SCHOCH MS V 16
1745A W NURSERY RD
LINTHICUM MD 21090

1 GDLS DIVISION
D BARTLE
PO BOX 1901
WARREN MI 48090

2 GDLS
D REES
M PASIK
PO BOX 2074
WARREN MI 48090-2074

1 GDLS
MUSKEGON OPER
M SOIMAR
76 GETTY ST
MUSKEGON MI 49442

1 GENERAL DYNAMICS
AMPHIBIOUS SYS
SURVIVABILITY LEAD
G WALKER
991 ANNAPOLIS WAY
WOODBIDGE VA 22191

NO. OF
COPIES ORGANIZATION

6 INST FOR ADVANCED
TECH
H FAIR
I MCNAB
P SULLIVAN
S BLESS
W REINECKE
C PERSAD
3925 W BRAKER LN STE 400
AUSTIN TX 78759-5316

1 ARROW TECH ASSOC
1233 SHELBURNE RD STE D8
SOUTH BURLINGTON VT
05403-7700

1 R EICHELBERGER
CONSULTANT
409 W CATHERINE ST
BEL AIR MD 21014-3613

1 SAIC
G CHRYSSOMALLIS
8500 NORMANDALE LAKE BLVD
SUITE 1610
BLOOMINGTON MN 55437-3828

1 UCLA MANE DEPT ENGR IV
H T HAHN
LOS ANGELES CA 90024-1597

1 UMASS LOWELL
PLASTICS DEPT
N SCHOTT
1 UNIVERSITY AVE
LOWELL MA 01854

1 IIT RESEARCH CTR
D ROSE
201 MILL ST
ROME NY 13440-6916

1 GA TECH RESEARCH INST
GA INST OF TCHNLGY
P FRIEDERICH
ATLANTA GA 30392

1 MICHIGAN ST UNIV
MSM DEPT
R AVERILL
3515 EB
EAST LANSING MI 48824-1226

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	PENN STATE UNIV R S ENGEL 245 HAMMOND BLDG UNIVERSITY PARK PA 16801
1	PENN STATE UNIV C BAKIS 212 EARTH ENGR SCIENCES BLDG UNIVERSITY PARK PA 16802
1	PURDUE UNIV SCHOOL OF AERO & ASTRO C T SUN W LAFAYETTE IN 47907-1282
1	UNIV OF MAINE ADV STR & COMP LAB R LOPEZ ANIDO 5793 AEWB BLDG ORONO ME 04469-5793
1	JOHNS HOPKINS UNIV APPLIED PHYSICS LAB P WIENHOLD 11100 JOHNS HOPKINS RD LAUREL MD 20723-6099
1	UNIV OF DAYTON J M WHITNEY COLLEGE PARK AVE DAYTON OH 45469-0240
5	UNIV OF DELAWARE CTR FOR COMPOSITE MTRLS J GILLESPIE M SANTARE S YARLAGADDA S ADVANI D HEIDER 201 SPENCER LAB NEWARK DE 19716
1	DEPT OF MTRLS SCIENCE & ENGRG UNIV OF ILLINOIS AT URBANA CHAMPAIGN J ECONOMY 1304 W GREEN ST 115B URBANA IL 61801

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	MISSISSIPPI STATE UNIV DEPT OF AEROSPACE ENGRG A J VIZZINI MISSISSIPPI STATE MS 39762
1	DREXEL UNIV A S D WANG 3141 CHESTNUT ST PHILADELPHIA PA 19104
3	UNIV OF TEXAS AT AUSTIN CTR FOR ELECTROMECHANICS J PRICE A WALLS J KITZMILLER 10100 BURNET RD AUSTIN TX 78758-4497
1	SOUTHWEST RESEARCH INST ENGR & MATL SCIENCES DIV J RIEGEL 6220 CULEBRA RD PO DRAWER 28510 SAN ANTONIO TX 78228-0510
3	DIRECTOR US ARMY RESEARCH LAB AMSRD ARL WM MB A FRYDMAN 2800 POWDER MILL RD ADELPHI MD 20783-1197
<u>ABERDEEN PROVING GROUND</u>	
1	US ARMY ATC CSTE DTC AT AC I W C FRAZER 400 COLLERAN RD APG MD 21005-5059
88	DIR USARL AMSRD ARL CI AMSRD ARL O AP EG M ADAMSON AMSRD ARL SL BA AMSRD ARL SL BB D BELY AMSRD ARL WM J SMITH AMSRD ARL WM B CHIEF T KOGLER AMSRD ARL WM BA D LYON

NO. OF
COPIES ORGANIZATION

AMSRD ARL WM BC
J NEWILL
P PLOSTINS
AMSRD ARL WM BD
P CONROY
B FORCH
M LEADORE
C LEVERITT
R LIEB
R PESCE-RODRIGUEZ
B RICE
A ZIELINSKI
AMSRD ARL WM BF
S WILKERSON
AMSRD ARL WM M
J MCCAULEY
S MCKNIGHT
AMSRD ARL WM MA
CHIEF
L GHIORSE
E WETZEL
AMSRD ARL WM MB
J BENDER
T BOGETTI
J BROWN
L BURTON
R CARTER
K CHO
W DE ROSSET
G DEWING
R DOWDING
W DRYSDALE
R EMERSON
D GRAY
D HOPKINS
R KASTE
L KECSKES
M MINNICINO
B POWERS
D SNOHA
J SOUTH
M STAKER
J SWAB
J TZENG
AMSRD ARL WM MC
CHIEF
R BOSSOLI
E CHIN
S CORNELISON
D GRANVILLE
B HART
J LASALVIA
J MONTGOMERY
F PIERCE

NO. OF
COPIES ORGANIZATION

E RIGAS
W SPURGEON
AMSRD ARL WM MD
B CHEESEMAN
P DEHMER
R DOOLEY
G GAZONAS
S GHIORSE
M KLUSEWITZ
W ROY
J SANDS
D SPAGNUOLO
S WALSH
S WOLF
AMSRD ARL WM RP
J BORNSTEIN
C SHOEMAKER
AMSRD ARL WM T
B BURNS
AMSRD ARL WM TA
W BRUCHEY
M BURKINS
W GILLICH
B GOOCH
T HAVEL
C HOPPEL
E HORWATH
J RUNYEON
M ZOLTOSKI
AMSRD ARL WM TB
P BAKER
AMSRD ARL WM TC
R COATES
AMSRD ARL WM TD
D DANDEKAR
M RAFTENBERG
S SCHOENFELD
T WEERASOORIYA
AMSRD ARL WM TE
CHIEF
J POWELL

NO. OF
COPIES ORGANIZATION

1 LTD
R MARTIN
MERL
TAMWORTH RD
HERTFORD SG13 7DG
UK

1 CIVIL AVIATION
ADMINSTRATION
T GOTTESMAN
PO BOX 8
BEN GURION INTRNL AIRPORT
LOD 70150
ISRAEL

1 AEROSPATIALE
S ANDRE
A BTE CC RTE MD132
316 ROUTE DE BAYONNE
TOULOUSE 31060
FRANCE

1 DRA FORT HALSTEAD
P N JONES
SEVEN OAKS KENT TN 147BP
UK

1 SWISS FEDERAL ARMAMENTS
WKS
W LANZ
ALLMENDSTRASSE 86
3602 THUN
SWITZERLAND

1 DYNAMEC RESEARCH LAB
AKE PERSSON
BOX 201
SE 151 23 SODERTALJE
SWEDEN

1 ISRAEL INST OF TECHLGY
S BODNER
FACULTY OF MECHANICAL
ENGR
HAIFA 3200
ISRAEL

1 DSTO
WEAPONS SYSTEMS DIVISION
N BURMAN RLLWS
SALISBURY
SOUTH AUSTRALIA 5108
AUSTRALIA

NO. OF
COPIES ORGANIZATION

1 DEF RES ESTABLISHMENT
VALCARTIER
A DUPUIS
2459 BLVD PIE XI NORTH
VALCARTIER QUEBEC
CANADA
PO BOX 8800 COURCELETTE
GOA IRO QUEBEC
CANADA

1 ECOLE POLYTECH
J MANSON
DMX LTC
CH 1015 LAUSANNE
SWITZERLAND

1 TNO DEFENSE SECURITY & SAFETY
R R IJSSELSTEIN
PO BOX 96864
2509 JG THE HAGUE
THE NETHERLANDS

2 FOA NATL DEFENSE RESEARCH
ESTAB
DIR DEPT OF WEAPONS &
PROTECTION
B JANZON
R HOLMLIN
S 172 90 STOCKHOLM
SWEDEN

2 DEFENSE TECH & PROC
AGENCY GROUND
I CREWTER
GENERAL HERZOG HAUS
3602 THUN
SWITZERLAND

1 MINISTRY OF DEFENCE
RAFAEL
ARMAMENT DEVELOPMENT
AUTH
M MAYSELESS
PO BOX 2250
HAIFA 31021
ISRAEL

1 B HIRSCH
TACHKEMONY ST 6
NETAMUA 42611
ISRAEL

NO. OF
COPIES ORGANIZATION

1 DEUTSCHE AEROSPACE AG
DYNAMICS SYSTEMS
M HELD
PO BOX 1340
D 86523 SCHROBENHAUSEN
GERMANY