112TH CONGRESS 2D SESSION

H. R. 5495

To suspend temporarily the duty on certain switchgear assemblies and panel boards specifically designed for wind turbine generators.

IN THE HOUSE OF REPRESENTATIVES

May 7, 2012

Ms. Schakowsky introduced the following bill; which was referred to the Committee on Ways and Means

A BILL

To suspend temporarily the duty on certain switchgear assemblies and panel boards specifically designed for wind turbine generators.

- 1 Be it enacted by the Senate and House of Representa-
- 2 tives of the United States of America in Congress assembled,
- 3 SECTION 1. CERTAIN SWITCHGEAR ASSEMBLIES AND
- 4 PANEL BOARDS SPECIFICALLY DESIGNED
- 5 FOR WIND TURBINE GENERATORS.
- 6 (a) IN GENERAL.—Subchapter II of chapter 99 of
- 7 the Harmonized Tariff Schedule of the United States is
- 8 amended by inserting in numerical sequence the following
- 9 new heading:

" " " " " " " " " " " " "		I	1	1	İ	ı	i i	
designed for wind turbine generators in excess of 2 MW; designed to transfer electric power to and from a utility power grid at 2100 kW at 600 V with a nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90)	"	9902.01.00	Switchgear assemblies and					
generators in excess of 2 MW; designed to transfer electric power to and from a utility power grid at 2100 kW at 600 V with a nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90)			panel boards specifically					
MW; designed to transfer electric power to and from a utility power grid at 2100 kW at 600 V with a nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; eapable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90)			designed for wind turbine					
electric power to and from a utility power grid at 2100 kW at 600 V with a nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90)			generators in excess of 2					
a utility power grid at 2100 kW at 600 V with a nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90)			MW; designed to transfer					
2100 kW at 600 V with a nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90)			electric power to and from					
nominal full load of 2190 amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90)			a utility power grid at					
amperes; each measuring 1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90) Free No change No change On or before			2100 kW at 600 V with a					
1950 mm or more but not over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90)			nominal full load of 2190					
over 2050 mm in length, 550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90) Free No change No change On or before			amperes; each measuring					
550 mm or more but not over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90) Free No change No change On or before			1950 mm or more but not					
over 650 mm in width and 1950 mm or more but not over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90) Free No change No change On or before			over 2050 mm in length,					
1950 mm or more but not over 2050 mm in height; capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90) Free No change No change On or before			550 mm or more but not					
over 2050 mm in height; capable of monitoring min- imum wind speed, yaw po- sition and blade pitch angle (provided for in sub- heading 8537.10.90) Free No change No change On or before			over 650 mm in width and					
capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90) Free No change No change On or before			1950 mm or more but not					
capable of monitoring minimum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90) Free No change No change On or before			over 2050 mm in height;					
imum wind speed, yaw position and blade pitch angle (provided for in subheading 8537.10.90) Free No change No change On or before			capable of monitoring min-					
sition and blade pitch angle (provided for in sub- heading 8537.10.90) Free No change No change On or before								
angle (provided for in subheading 8537.10.90) Free No change No change On or before								
heading 8537.10.90) Free No change No change On or before			•					
				Free	No change	No change	On or before	
							12/31/2015	,,

- 1 (b) Effective Date.—The amendment made by
- 2 subsection (a) applies to goods entered, or withdrawn from
- 3 warehouse for consumption, on or after the 15th day after
- 4 the date of the enactment of this Act.

 \bigcirc