

## § 407.83

[Metric units, kg/kg of final product; English units, lb/1,000 lb of final product]

| Commodity (specialties)                 | TSS effluent limitations |                                                                   |                                  |
|-----------------------------------------|--------------------------|-------------------------------------------------------------------|----------------------------------|
|                                         | Maximum for any 1 day    | Average of daily values for 30 consecutive days shall not exceed— | Annual average shall not exceed— |
| Added ingredients .....                 | 0.00                     | 0.00                                                              | 0.00                             |
| Baby food .....                         | 2.23                     | 1.55                                                              | 0.95                             |
| Chips:                                  |                          |                                                                   |                                  |
| Corn .....                              | 2.90                     | 2.17                                                              | 1.53                             |
| Potato .....                            | 6.25                     | 4.49                                                              | 2.97                             |
| Tortilla .....                          | 4.34                     | 3.11                                                              | 2.04                             |
| Ethnic foods .....                      | 4.23                     | 2.91                                                              | 1.73                             |
| Jams/jellies .....                      | 0.76                     | 0.54                                                              | 0.36                             |
| Mayonnaise and dressings .....          | 0.67                     | 0.49                                                              | 0.33                             |
| Soups .....                             | 7.38                     | 5.09                                                              | 3.10                             |
| Tomato-starch-cheese canned specialties | 3.31                     | 2.23                                                              | 1.30                             |

(c) The following limitations establish the quality of pH controlled by this section, which may be discharged by a “medium” or “large” existing point source subject to the provisions of this subpart after application of the best practicable control technology currently available.

| Effluent characteristic | Effluent limitations                                     |
|-------------------------|----------------------------------------------------------|
| Oil and grease .....    | Shall not exceed 20 mg/l.                                |
| pH .....                | At all times within the range 6.0 to 9.5 except 10 mg/l. |
| pH .....                | At all times within the range 6.0 to 9.5.                |

[41 FR 16284, Apr. 16, 1976, as amended at 60 FR 33939, June 29, 1995]

## § 407.83 [Reserved]

## § 407.84 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by any existing point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| Oil and grease .....            | Do.                   |

## 40 CFR Ch. I (7–1–25 Edition)

[41 FR 16281, Apr. 16, 1976, as amended at 60 FR 33939, June 29, 1995]

## § 407.85 [Reserved]

## § 407.86 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| Oil and grease .....            | Do.                   |

[41 FR 16281, Apr. 16, 1976, as amended at 60 FR 33939, June 29, 1995]

## § 407.87 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 407.82 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## PART 408—CANNED AND PRESERVED SEAFOOD PROCESSING POINT SOURCE CATEGORY

### Subpart A—Farm-Raised Catfish Processing Subcategory

Sec.  
408.10 Applicability; description of the farm-raised catfish processing subcategory.

## Environmental Protection Agency

Pt. 408

- 408.11 Specialized definitions.
- 408.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.13 [Reserved]
- 408.14 Pretreatment standards for existing sources.
- 408.15 Standards of performance for new sources.
- 408.16 Pretreatment standards for new sources.
- 408.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart B—Conventional Blue Crab Processing Subcategory

- 408.20 Applicability; description of the conventional blue crab processing subcategory.
- 408.21 Specialized definitions.
- 408.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.23 [Reserved]
- 408.24 Pretreatment standards for existing sources.
- 408.25 Standards of performance for new sources.
- 408.26 Pretreatment standards for new sources.
- 408.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart C—Mechanized Blue Crab Processing Subcategory

- 408.30 Applicability; description of the mechanized blue crab processing subcategory.
- 408.31 Specialized definitions.
- 408.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.33 [Reserved]
- 408.34 Pretreatment standards for existing sources.
- 408.35 Standards of performance for new sources.
- 408.36 Pretreatment standards for new sources.
- 408.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best

conventional pollutant control technology (BCT).

### Subpart D—Non-Remote Alaskan Crab Meat Processing Subcategory

- 408.40 Applicability; description of the non-remote Alaskan crab meat processing subcategory.
- 408.41 Specialized definitions.
- 408.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.43 [Reserved]
- 408.44 Pretreatment standards for existing sources.
- 408.45 Standards of performance for new sources.
- 408.46 Pretreatment standards for new sources.
- 408.47 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart E—Remote Alaskan Crab Meat Processing Subcategory

- 408.50 Applicability; description of the remote Alaskan crab meat processing subcategory.
- 408.51 Specialized definitions.
- 408.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.53 [Reserved]
- 408.54 Pretreatment standards for existing sources.
- 408.55 Standards of performance for new sources.
- 408.56 Pretreatment standards for new sources.
- 408.57 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart F—Non-Remote Alaskan Whole Crab and Crab Section Processing Subcategory

- 408.60 Applicability; description of the non-remote Alaskan whole crab and crab section processing subcategory.
- 408.61 Specialized definitions.
- 408.62 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.63 [Reserved]

**Pt. 408**

**40 CFR Ch. I (7–1–25 Edition)**

- 408.64 Pretreatment standards for existing sources.
- 408.65 Standards of performance for new sources.
- 408.66 Pretreatment standards for new sources.
- 408.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart G—Remote Alaskan Whole Crab and Crab Section Processing Subcategory**

- 408.70 Applicability; description of the remote Alaskan whole crab and crab section processing subcategory.
- 408.71 Specialized definitions.
- 408.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.73 [Reserved]
- 408.74 Pretreatment standards for existing sources.
- 408.75 Standards of performance for new sources.
- 408.76 Pretreatment standards for new sources.
- 408.77 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart H—Dungeness and Tanner Crab Processing in the Contiguous States Subcategory**

- 408.80 Applicability; description of the dungeness and tanner crab processing in the contiguous States subcategory.
- 408.81 Specialized definitions.
- 408.82 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.83 [Reserved]
- 408.84 Pretreatment standards for existing sources.
- 408.85 Standards of performance for new sources.
- 408.86 Pretreatment standards for new sources.
- 408.87 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart I—Non-Remote Alaskan Shrimp Processing Subcategory**

- 408.90 Applicability; description of the non-remote Alaskan shrimp processing subcategory.
- 408.91 Specialized definitions.
- 408.92 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.93 [Reserved]
- 408.94 Pretreatment standards for existing sources.
- 408.95 Standards of performance for new sources.
- 408.96 Pretreatment standards for new sources.
- 408.97 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart J—Remote Alaskan Shrimp Processing Subcategory**

- 408.100 Applicability; description of the remote Alaskan shrimp processing subcategory.
- 408.101 Specialized definitions.
- 408.102 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.103 [Reserved]
- 408.104 Pretreatment standards for existing sources.
- 408.105 Standards of performance for new sources.
- 408.106 Pretreatment standards for new sources.
- 408.107 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart K—Northern Shrimp Processing in the Contiguous States Subcategory**

- 408.110 Applicability; description of the Northern shrimp processing in the contiguous States subcategory.
- 408.111 Specialized definitions.
- 408.112 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.113 [Reserved]
- 408.114 Pretreatment standards for existing sources.
- 408.115 Standards of performance for new sources.

## Environmental Protection Agency

Pt. 408

408.116 Pretreatment standards for new sources.

408.117 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart I—Southern Non-Breaded Shrimp Processing in the Contiguous States Subcategory

408.120 Applicability; description of the Southern non-breaded shrimp processing in the contiguous States subcategory.

408.121 Specialized definitions.

408.122 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.123 [Reserved]

408.124 Pretreatment standards for existing sources.

408.125 Standards of performance for new sources.

408.126 Pretreatment standards for new sources.

408.127 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart M—Breaded Shrimp Processing in the Contiguous States Subcategory

408.130 Applicability; description of the breaded shrimp processing in the contiguous States subcategory.

408.131 Specialized definitions.

408.132 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.133 [Reserved]

408.134 Pretreatment standards for existing sources.

408.135 Standards of performance for new sources.

408.136 Pretreatment standards for new sources.

408.137 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart N—Tuna Processing Subcategory

408.140 Applicability; description of the tuna processing subcategory.

408.141 Specialized definitions.

408.142 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best

practicable control technology currently available.

408.143 [Reserved]

408.144 Pretreatment standards for existing sources.

408.145 Standards of performance for new sources.

408.146 Pretreatment standards for new sources.

408.147 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart O—Fish Meal Processing Subcategory

408.150 Applicability; description of the fish meal processing subcategory.

408.151 Specialized definitions.

408.152 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.153 [Reserved]

408.154 Pretreatment standards for existing sources.

408.155 Standards of performance for new sources.

408.156 Pretreatment standards for new sources.

408.157 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart P—Alaskan Hand-Butchered Salmon Processing Subcategory

408.160 Applicability; description of the Alaskan hand-butchered salmon processing subcategory.

408.161 Specialized definitions.

408.162 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.163 [Reserved]

408.164 Pretreatment standards for existing sources.

408.165 Standards of performance for new sources.

408.166 Pretreatment standards for new sources.

408.167 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

**Subpart Q—Alaskan Mechanized Salmon Processing Subcategory**

- 408.170 Applicability; description of the Alaskan mechanized salmon processing subcategory.
- 408.171 Specialized definitions.
- 408.172 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.173 [Reserved]
- 408.174 Pretreatment standards for existing sources.
- 408.175 Standards of performance for new sources.
- 408.176 Pretreatment standards for new sources.
- 408.177 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart R—West Coast Hand-Butchered Salmon Processing Subcategory**

- 408.180 Applicability; description of the West Coast hand-butchered salmon processing subcategory.
- 408.181 Specialized definitions.
- 408.182 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.183 [Reserved]
- 408.184 Pretreatment standards for existing sources.
- 408.185 Standards of performance for new sources.
- 408.186 Pretreatment standards for new sources.
- 408.187 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart S—West Coast Mechanized Salmon Processing Subcategory**

- 408.190 Applicability; description of the West Coast mechanized salmon processing subcategory.
- 408.191 Specialized definitions.
- 408.192 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.193 [Reserved]
- 408.194 Pretreatment standards for existing sources.
- 408.195 Standards of performance for new sources.

- 408.196 Pretreatment standards for new sources.
- 408.197 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart T—Alaskan Bottom Fish Processing Subcategory**

- 408.200 Applicability; description of the Alaskan bottom fish processing subcategory.
- 408.201 Specialized definitions.
- 408.202 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.203 [Reserved]
- 408.204 Pretreatment standards for existing sources.
- 408.205 Standards of performance for new sources.
- 408.206 Pretreatment standards for new sources.
- 408.207 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

**Subpart U—Non-Alaskan Conventional Bottom Fish Processing Subcategory**

- 408.210 Applicability; description of the non-Alaskan conventional bottom fish processing subcategory.
- 408.211 Specialized definitions.
- 408.212 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 408.213 [Reserved]
- 408.214 Pretreatment standards for existing sources.
- 408.215 Standards of performance for new sources.
- 408.216 Pretreatment standards for new sources.
- 408.217 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart V—Non-Alaskan Mechanized Bottom Fish Processing Subcategory**

- 408.220 Applicability; description of the non-Alaskan mechanized bottom fish processing subcategory.
- 408.221 Specialized definitions.
- 408.222 Effluent limitations guidelines representing the degree of effluent reduction

## Environmental Protection Agency

Pt. 408

attainable by the application of the best practicable control technology currently available.

408.223 [Reserved]

408.224 Pretreatment standards for existing sources.

408.225 Standards of performance for new sources.

408.226 Pretreatment standards for new sources.

408.227 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart W—Hand-Shucked Clam Processing Subcategory

408.230 Applicability; description of the hand-shucked clam processing subcategory.

408.231 Specialized definitions.

408.232 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.233 [Reserved]

408.234 Pretreatment standards for existing sources.

408.235 Standards of performance for new sources.

408.236 Pretreatment standards for new sources.

408.237 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart X—Mechanized Clam Processing Subcategory

408.240 Applicability; description of the mechanized clam processing subcategory.

408.241 Specialized definitions.

408.242 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.243 [Reserved]

408.244 Pretreatment standards for existing sources.

408.245 Standards of performance for new sources.

408.246 Pretreatment standards for new sources.

408.247 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

### Subpart Y—Pacific Coast Hand-Shucked Oyster Processing Subcategory

408.250 Applicability; description of the Pacific Coast hand-shucked oyster processing subcategory.

408.251 Specialized definitions.

408.252 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.253 [Reserved]

408.254 Pretreatment standards for existing sources.

408.255 Standards of performance for new sources.

408.256 Pretreatment standards for new sources.

408.257 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

### Subpart Z—Atlantic and Gulf Coast Hand-Shucked Oyster Processing Subcategory

408.260 Applicability; description of the Atlantic and Gulf Coast hand-shucked oyster processing subcategory.

408.261 Specialized definitions.

408.262 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.263 [Reserved]

408.264 Pretreatment standards for existing sources.

408.265 Standards of performance for new sources.

408.266 Pretreatment standards for new sources.

408.267 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

### Subpart AA—Steamed and Canned Oyster Processing Subcategory

408.270 Applicability; description of the steamed and canned oyster processing subcategory.

408.271 Specialized definitions.

408.272 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

408.273 [Reserved]

408.274 Pretreatment standards for existing sources.

408.275 Standards of performance for new sources.

**Pt. 408**

**40 CFR Ch. I (7–1–25 Edition)**

- 408.276 Pretreatment standards for new sources.  
408.277 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart AB—Sardine Processing Subcategory**

- 408.280 Applicability; description of the sardine processing subcategory.  
408.281 Specialized definitions.  
408.282 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.  
408.283 [Reserved]  
408.284 Pretreatment standards for existing sources.  
408.285 Standards of performance for new sources.  
408.286 Pretreatment standards for new sources.  
408.287 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart AC—Alaskan Scallop Processing Subcategory**

- 408.290 Applicability; description of the Alaskan scallop processing subcategory.  
408.291 Specialized definitions.  
408.292 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.  
408.293 [Reserved]  
408.294 Pretreatment standards for existing sources.  
408.295 Standards of performance for new sources.  
408.296 Pretreatment standards for new sources.  
408.297 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

**Subpart AD—Non-Alaskan Scallop Processing Subcategory**

- 408.300 Applicability; description of the non-Alaskan scallop processing subcategory.  
408.301 Specialized definitions.  
408.302 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

- 408.303 [Reserved]  
408.304 Pretreatment standards for existing sources.  
408.305 Standards of performance for new sources.  
408.306 Pretreatment standards for new sources.  
408.307 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

**Subpart AE—Alaskan Herring Fillet Processing Subcategory**

- 408.310 Applicability; description of the Alaskan herring fillet processing subcategory.  
408.311 Specialized definitions.  
408.312 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.  
408.313 [Reserved]  
408.314 Pretreatment standards for existing sources.  
408.315 Standards of performance for new sources.  
408.316 Pretreatment standards for new sources.  
408.317 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart AF—Non-Alaskan Herring Fillet Processing Subcategory**

- 408.320 Applicability; description of the non-Alaskan herring fillet processing subcategory.  
408.321 Specialized definitions.  
408.322 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.  
408.323 [Reserved]  
408.324 Pretreatment standards for existing sources.  
408.325 Standards of performance for new sources.  
408.326 Pretreatment standards for new sources.  
408.327 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

## Environmental Protection Agency

## § 408.14

### Subpart AG—Abalone Processing Subcategory

- 408.330 Applicability; description of the abalone processing subcategory.  
 408.331 Specialized definitions.  
 408.332 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.  
 408.333 [Reserved]  
 408.334 Pretreatment standards for existing sources.  
 408.335 Standards of performance for new sources.  
 408.336 Pretreatment standards for new sources.  
 408.337 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

AUTHORITY: Secs. 301, 304 (b) and (c), 306 (b) and (c), 307(c), of the Federal Water Pollution Control Act, as amended; 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), 1317(c); 86 Stat. 816 *et seq.*, Pub. L. 92-500; 91 Stat. 1567, Pub. L. 95-217.

SOURCE: 39 FR 23140, June 26, 1974, unless otherwise noted.

### Subpart A—Farm-Raised Catfish Processing Subcategory

#### § 408.10 Applicability; description of the farm-raised catfish processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of farm-raised catfish by existing facilities which process more than 1362 kg (3000 lbs) of raw material per day on any day during a calendar year and all new sources.

[40 FR 55780, Dec. 1, 1975]

#### § 408.11 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

#### § 408.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 28                                     | 9.2                                                               |
| Oil and grease .....    | 10                                     | 3.4                                                               |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 28                                     | 9.2                                                               |
| Oil and grease .....    | 10                                     | 3.4                                                               |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33940, June 29, 1995]

#### § 408.13 [Reserved]

#### § 408.14 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |



## § 408.15

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| TSS .....                       | Do.                   |

[40 FR 6437, Feb. 11, 1975, as amended at 60 FR 33940, June 29, 1995]

### § 408.15 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood)       |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 4.6                   | 2.3                                                               |
| TSS .....                              | 11                    | 5.7                                                               |
| Oil and grease .....                   | 0.90                  | 0.45                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 4.6                   | 2.3                                                               |
| TSS .....                              | 11                    | 5.7                                                               |
| Oil and grease .....                   | 0.90                  | 0.45                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.16 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33940, June 29, 1995]

### § 408.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants

## 40 CFR Ch. I (7–1–25 Edition)

(which are defined in § 401.16) in § 408.12 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart B—Conventional Blue Crab Processing Subcategory

#### § 408.20 Applicability; description of the conventional blue crab processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of blue crab in which manual picking or separation of crab meat from the shell is utilized. The effluent limitations contained in this subpart B are applicable to existing facilities processing more than 1362 kg (3000 lbs) of raw material per day on any day during a calendar year and all new sources.

[40 FR 55780, Dec. 1, 1975]

#### § 408.21 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

#### § 408.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

## Environmental Protection Agency

## § 408.30

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood)       |                       |                                                                   |
| TSS .....                              | 2.2                   | 0.74                                                              |
| Oil and grease .....                   | 0.60                  | 0.20                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 2.2                   | 0.74                                                              |
| Oil and grease .....                   | 0.60                  | 0.20                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33940, June 29, 1995]

### § 408.23 [Reserved]

### § 408.24 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33940, June 29, 1995]

### § 408.25 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood)       |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 0.30                  | 0.15                                                              |
| TSS .....                              | 0.90                  | 0.45                                                              |
| Oil and grease .....                   | 0.13                  | 0.065                                                             |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 0.30                  | 0.15                                                              |
| TSS .....                              | 0.90                  | 0.45                                                              |
| Oil and grease .....                   | 0.13                  | 0.065                                                             |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.26 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33940, June 29, 1995]

### § 408.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.22 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart C—Mechanized Blue Crab Processing Subcategory

### § 408.30 Applicability; description of the mechanized blue crab processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of blue crab in which

## § 408.31

mechanical picking or separation of crab meat from the shell is utilized.

[40 FR 55780, Dec. 1, 1975]

## § 408.31 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

## § 408.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent limitations                   |                                  |                                                                   |
|----------------------------------------|----------------------------------|-------------------------------------------------------------------|
| Effluent characteristic                | Metric units (kg/kkg of seafood) |                                                                   |
|                                        | Maximum for any 1 day            | Average of daily values for 30 consecutive days shall not exceed— |
| TSS .....                              | 36                               | 12.0                                                              |
| Oil and grease .....                   | 13                               | 4.2                                                               |
| pH .....                               | ( <sup>1</sup> )                 | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                                  |                                                                   |
| TSS .....                              | 36                               | 12.0                                                              |
| Oil and grease .....                   | 13                               | 4.2                                                               |
| pH .....                               | ( <sup>1</sup> )                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33941, June 29, 1995]

## 40 CFR Ch. I (7–1–25 Edition)

## § 408.33 [Reserved]

## § 408.34 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33941, June 29, 1995]

## § 408.35 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood)       |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 5.0                   | 2.5                                                               |
| TSS .....                              | 13                    | 6.3                                                               |
| Oil and grease .....                   | 2.6                   | 1.3                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 5.0                   | 2.5                                                               |
| TSS .....                              | 13                    | 6.3                                                               |
| Oil and grease .....                   | 2.6                   | 1.3                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

## § 408.36 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned

## Environmental Protection Agency

## § 408.44

treatment works must comply with 40 CFR part 403.

[60 FR 33941, June 29, 1995]

### § 408.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.32 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart D—Non-Remote Alaskan Crab Meat Processing Subcategory

### § 408.40 Applicability; description of the non-remote Alaskan crab meat processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing, in non-remote Alaska, of dungeness, tanner, and king crab meat. The effluent limitations contained in this subpart D are applicable to facilities located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg.

[40 FR 55780, Dec. 1, 1975]

### § 408.41 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, An-

alytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 19                                     | 6.2                                                               |
| Oil and grease .....    | 1.8                                    | 0.61                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
|                         | 19                                     | 6.2                                                               |
|                         | 1.8                                    | 0.61                                                              |
|                         | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33941, June 29, 1995]

### § 408.43 [Reserved]

### § 408.44 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

## § 408.45

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33941, June 29, 1995]

### § 408.45 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood)       |                                                                   |
| TSS .....               | 16                                     | 5.3                                                               |
| Oil and grease .....    | 1.6                                    | 0.52                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
| TSS .....               | 16                                     | 5.3                                                               |
| Oil and grease .....    | 1.6                                    | 0.52                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.46 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33941, June 29, 1995]

### § 408.47 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants

## 40 CFR Ch. I (7–1–25 Edition)

(which are defined in § 401.16) in § 408.42 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart E—Remote Alaskan Crab Meat Processing Subcategory

#### § 408.50 Applicability; description of the remote Alaskan crab meat processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing, in remote Alaska, of dungeness, tanner, and king crab meat. The effluent limitations contained in subpart E are applicable to facilities not covered under subpart D.

[40 FR 55780, Dec. 1, 1975]

#### § 408.51 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

#### § 408.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[60 FR 33941, June 29, 1995]

## Environmental Protection Agency

## § 408.62

### § 408.53 [Reserved]

### § 408.54 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33941, June 29, 1995]

### § 408.55 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55780, Dec. 1, 1975]

### § 408.56 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33941, June 29, 1995]

### § 408.57 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollut-

ant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in §401.16) in §408.52 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart F—Non-Remote Alaskan Whole Crab and Crab Section Processing Subcategory

### § 408.60 Applicability; description of the non-remote Alaskan whole crab and crab section processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing, in non-remote Alaska, of dungeness, tanner and king whole crab and crab sections. The effluent limitations contained in this subpart F are applicable to facilities located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg.

[40 FR 55780, Dec. 1, 1975]

### § 408.61 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.62 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall

### § 408.63

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood)       |                                                                   |
| TSS .....               | 12                                     | 12                                                                |
| Oil and grease .....    | 1.3                                    | 0.42                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
| TSS .....               | 12                                     | 3.9                                                               |
| Oil and grease .....    | 1.3                                    | 0.42                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33941, June 29, 1995]

### § 408.63 [Reserved]

### § 408.64 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33941, June 29, 1995]

### § 408.65 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

### 40 CFR Ch. I (7–1–25 Edition)

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood—)      |                                                                   |
| TSS .....               | 9.9                                    | 3.3                                                               |
| Oil and grease .....    | 1.1                                    | 0.36                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
| TSS .....               | 9.9                                    | 3.3                                                               |
| Oil and grease .....    | 1.1                                    | 0.36                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.66 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33941, June 29, 1995]

### § 408.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.62 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart G—Remote Alaskan Whole Crab and Crab Section Processing Subcategory

### § 408.70 Applicability; description of the remote Alaskan whole crab and crab section processing subcategory.

The provisions of this subpart are applicable to discharges resulting from

## Environmental Protection Agency

## § 408.77

the processing, in remote Alaska, of dungeness, tanner, and king whole crab and crab sections. The effluent limitations contained in this subpart G are applicable to facilities not covered under subpart F of this part.

[40 FR 55780, Dec. 1, 1975]

### § 408.71 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[60 FR 33941, June 29, 1995]

### § 408.73 [Reserved]

### § 408.74 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a

publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

### § 408.75 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55780, Dec. 1, 1975]

### § 408.76 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33942, June 29, 1995]

### § 408.77 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.72 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]



§ 408.80

**Subpart H—Dungeness and Tanner Crab Processing in the Contiguous States Subcategory**

**§ 408.80 Applicability; description of the dungeness and tanner crab processing in the contiguous States subcategory.**

The provisions of this subpart are applicable to discharges resulting from the processing of dungeness and tanner crab in the contiguous States.

[40 FR 55780, Dec. 1, 1975]

**§ 408.81 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amendable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

**§ 408.82 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic         | Effluent limitations  |                                                                   |
|---------------------------------|-----------------------|-------------------------------------------------------------------|
|                                 | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood) |                       |                                                                   |
| TSS .....                       | 8.1                   | 2.7                                                               |
| Oil and grease .....            | 1.8                   | 0.61                                                              |

**40 CFR Ch. I (7–1–25 Edition)**

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 8.1                   | 2.7                                                               |
| Oil and grease .....                   | 1.8                   | 0.61                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33942, June 29, 1995]

**§ 408.83 [Reserved]**

**§ 408.84 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

**§ 408.85 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic         | Effluent limitations  |                                                                   |
|---------------------------------|-----------------------|-------------------------------------------------------------------|
|                                 | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....          | 10                    | 4.1                                                               |
| TSS .....                       | 1.7                   | 0.69                                                              |

## Environmental Protection Agency

## § 408.92

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Oil and grease .....                   | 0.25                  | 0.10                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 10                    | 4.1                                                               |
| TSS .....                              | 1.7                   | 0.69                                                              |
| Oil and grease .....                   | 0.25                  | 0.10                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.86 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33942, June 29, 1995]

### § 408.87 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.82 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart I—Non-Remote Alaskan Shrimp Processing Subcategory

#### § 408.90 Applicability; description of the non-remote Alaskan shrimp processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of shrimp in non-remote Alaska. The effluent limitations contained in this subpart I are applicable to facilities located in population or processing centers including but not

limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg.

[40 FR 55780, Dec. 1, 1975]

### § 408.91 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.92 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 320                   | 210                                                               |
| Oil and grease .....                   | 51                    | 17                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 320                   | 210                                                               |
| Oil and grease .....                   | 51                    | 17                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33942, June 29, 1995]

## § 408.93

### § 408.93 [Reserved]

### § 408.94 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

### § 408.95 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 270                   | 180                                                               |
| Oil and grease .....                   | 45                    | 15                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 270                   | 180                                                               |
| Oil and grease .....                   | 45                    | 15                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.96 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned

## 40 CFR Ch. I (7–1–25 Edition)

treatment works must comply with 40 CFR part 403.

[60 FR 33942, June 29, 1995]

### § 408.97 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.92 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart J—Remote Alaskan Shrimp Processing Subcategory

### § 408.100 Applicability; description of the remote Alaskan shrimp processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of shrimp in remote Alaska. The effluent limitations contained in this subpart J are applicable to facilities not covered under subpart I of this part.

[40 FR 55781, Dec. 1, 1975]

### § 408.101 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and

## Environmental Protection Agency

## § 408.111

saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.102 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[60 FR 33942, June 29, 1995]

### § 408.103 [Reserved]

### § 408.104 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

### § 408.105 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: No pollutants may be discharged which ex-

ceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55781, Dec. 1, 1975]

### § 408.106 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33942, June 29, 1995]

### § 408.107 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.102 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart K—Northern Shrimp Processing in the Contiguous States Subcategory

### § 408.110 Applicability; description of the Northern shrimp processing in the contiguous States subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of shrimp in the Northern contiguous States, including Washington, Oregon, California, Maine, New Hampshire, and Massachusetts. The effluent limitations contained in this subpart K are applicable to existing facilities processing more than 908 kg (2000 lbs) of raw material per day on any day during a calendar year and all new sources.

[40 FR 55781, Dec. 1, 1975]

### § 408.111 Specialized definitions.

For the purpose of this subpart:

## § 408.112

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.112 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent limitations                   |                                 |                                                                   |
|----------------------------------------|---------------------------------|-------------------------------------------------------------------|
| Effluent characteristic                | Metric units (kg/kg of seafood) |                                                                   |
|                                        | Maximum for any 1 day           | Average of daily values for 30 consecutive days shall not exceed— |
| TSS .....                              | 160                             | 54                                                                |
| Oil and grease .....                   | 126                             | 42                                                                |
| pH .....                               | ( <sup>1</sup> )                | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                                 |                                                                   |
| TSS .....                              | 160                             | 54                                                                |
| Oil and grease .....                   | 126                             | 42                                                                |
| pH .....                               | ( <sup>1</sup> )                | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33942, June 29, 1995]

### § 408.113 [Reserved]

### § 408.114 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned

## 40 CFR Ch. I (7–1–25 Edition)

treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

### § 408.115 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| BOD5 .....                             | 155                   | 62                                                                |
| TSS .....                              | 38                    | 15                                                                |
| Oil and grease .....                   | 14                    | 5.7                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD5 .....                             | 155                   | 62                                                                |
| TSS .....                              | 38                    | 15                                                                |
| Oil and grease .....                   | 14                    | 5.7                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.116 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33943, June 29, 1995]

## Environmental Protection Agency

## § 408.124

### § 408.117 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.112 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart L—Southern Non-Breaded Shrimp Processing in the Contiguous States Subcategory

### § 408.120 Applicability; description of the Southern non-breaded shrimp processing in the contiguous States subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of non-breaded shrimp in the Southern contiguous States, including North and South Carolina, Georgia, Florida, Alabama, Mississippi, Louisiana, and Texas. The effluent limitations contained in this subpart L are applicable to existing facilities processing more than 908 kg (2000 lbs) of raw material per day on any day during a calendar year and all new sources.

[40 FR 55781, Dec. 1, 1975]

### § 408.121 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.122 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 110                   | 38                                                                |
| Oil and grease .....                   | 36                    | 12                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 110                   | 38                                                                |
| Oil and grease .....                   | 36                    | 12                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33943, June 29, 1995]

### § 408.123 [Reserved]

### § 408.124 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |

## § 408.125

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33943, June 29, 1995]

### § 408.125 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| BOD5 .....                             | 63                    | 25                                                                |
| TSS .....                              | 25                    | 10                                                                |
| Oil and grease .....                   | 4.0                   | 1.6                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD5 .....                             | 63                    | 25                                                                |
| TSS .....                              | 25                    | 10                                                                |
| Oil and grease .....                   | 4.0                   | 1.6                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.126 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33943, June 29, 1995]

### § 408.127 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants

## 40 CFR Ch. I (7–1–25 Edition)

(which are defined in § 401.16) in § 408.122 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart M—Breaded Shrimp Processing in the Contiguous States Subcategory

### § 408.130 Applicability; description of the breaded shrimp processing in the contiguous States subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of breaded shrimp in the contiguous States by existing facilities processing more than 908 kg (2000 lbs) of raw material per day on any day during a calendar year and all new sources.

[40 FR 55781, Dec. 1, 1975]

### § 408.131 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.132 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

## Environmental Protection Agency

## § 408.137

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood)       |                       |                                                                   |
| TSS .....                              | 280                   | 93                                                                |
| Oil and grease .....                   | 36                    | 12                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 280                   | 93                                                                |
| Oil and grease .....                   | 36                    | 12                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 60 FR 33943, June 29, 1995]

### § 408.133 [Reserved]

### § 408.134 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| Oil and grease .....            | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33943, June 29, 1995]

### § 408.135 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood)       |                       |                                                                   |
| BOD5 .....                             | 100                   | 40                                                                |
| TSS .....                              | 55                    | 22                                                                |
| Oil and grease .....                   | 3.8                   | 1.5                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD5 .....                             | 100                   | 40                                                                |
| TSS .....                              | 55                    | 22                                                                |
| Oil and grease .....                   | 3.8                   | 1.5                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.136 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33943, June 29, 1995]

### § 408.137 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.132 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]



§ 408.140

**Subpart N—Tuna Processing Subcategory**

**§ 408.140 Applicability; description of the tuna processing subcategory.**

The provisions of this subpart are applicable to discharges resulting from the processing of tuna.

[40 FR 55781, Dec. 1, 1975]

**§ 408.141 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

**§ 408.142 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 8.3                                    | 3.3                                                               |
| Oil and grease .....    | 2.1                                    | 0.84                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
| Effluent characteristic | Effluent limitations                   |                                                                   |
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
| TSS .....               | 8.3                                    | 3.3                                                               |

**40 CFR Ch. I (7–1–25 Edition)**

| Effluent characteristic | Effluent limitations  |                                                                   |
|-------------------------|-----------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Oil and grease .....    | 2.1                   | 0.84                                                              |
| pH .....                | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 23140, June 26, 1974, as amended at 44 FR 45945, Aug. 9, 1979; 60 FR 33943, June 29, 1995]

**§ 408.143 [Reserved]**

**§ 408.144 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| BOD <sub>5</sub> .....          | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33943, June 29, 1995]

**§ 408.145 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations            |                                                                   |
|-------------------------|---------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day           | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood) |                                                                   |
| BOD <sub>5</sub> .....  | 20                              | 8.1                                                               |
| TSS .....               | 7.5                             | 3.0                                                               |
| Oil and grease .....    | 1.9                             | 0.76                                                              |
| pH .....                | ( <sup>1</sup> )                | ( <sup>1</sup> )                                                  |

## Environmental Protection Agency

## § 408.152

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD5 .....                             | 20                    | 8.1                                                               |
| TSS .....                              | 7.5                   | 3.0                                                               |
| Oil and grease .....                   | 1.9                   | 0.76                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.146 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33943, June 29, 1995]

### § 408.147 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.142 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart O—Fish Meal Processing Subcategory

SOURCE: 40 FR 55781, Dec. 1, 1975, unless otherwise noted.

### § 408.150 Applicability; description of the fish meal processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of menhaden on the Gulf and Atlantic Coasts and the processing of anchovy on the West Coast into fish meal, oil and solubles.

### § 408.151 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.152 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any menhaden or anchovy fish meal reduction facility which utilizes a solubles plant to process stick water or bail water shall meet the following limitations.

| Effluent characteristic                          | Effluent limitations  |                                                                   |
|--------------------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of seafood) |                       |                                                                   |
| BOD5 .....                                       | 7.0                   | 3.9                                                               |
| TSS .....                                        | 3.7                   | 1.5                                                               |
| Oil and grease .....                             | 1.4                   | 0.76                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (pounds per 1,000 lb of seafood)   |                       |                                                                   |
| BOD5 .....                                       | 7.0                   | 3.9                                                               |
| TSS .....                                        | 3.7                   | 1.5                                                               |
| Oil and grease .....                             | 1.4                   | 0.76                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any menhaden or anchovy fish meal reduction facility not covered under § 408.152(a) shall meet the following limitations:

## § 408.153

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 3.5                   | 2.8                                                               |
| TSS .....                              | 2.6                   | 1.7                                                               |
| Oil and grease .....                   | 3.2                   | 1.4                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....                 | 3.5                   | 2.8                                                               |
| TSS .....                              | 2.6                   | 1.7                                                               |
| Oil and grease .....                   | 3.2                   | 1.4                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55781, Dec. 1, 1975, as amended at 41 FR 31821, July 30, 1976; 60 FR 33943, June 29, 1995]

## § 408.153 [Reserved]

### § 408.154 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD <sub>5</sub> .....          | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55781, Dec. 1, 1975, as amended at 60 FR 33943, June 29, 1995]

### § 408.155 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

## 40 CFR Ch. I (7–1–25 Edition)

| Effluent characteristic                          | Effluent limitations  |                                                                   |
|--------------------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of seafood) |                       |                                                                   |
| BOD <sub>5</sub> .....                           | 6.7                   | 3.8                                                               |
| TSS .....                                        | 3.7                   | 1.5                                                               |
| Oil and grease .....                             | 1.4                   | 0.76                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (pounds per 1,000 lb of seafood)   |                       |                                                                   |
| BOD <sub>5</sub> .....                           | 6.7                   | 3.8                                                               |
| TSS .....                                        | 3.7                   | 1.5                                                               |
| Oil and grease .....                             | 1.4                   | 0.76                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55781, Dec. 1, 1975, as amended at 41 FR 31821, July 30, 1976]

### § 408.156 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD <sub>5</sub> .....          | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55781, Dec. 1, 1975, as amended at 60 FR 33944, June 29, 1995]

### § 408.157 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those

## Environmental Protection Agency

## § 408.165

specified for conventional pollutants (which are defined in § 401.16) in § 408.152 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart P—Alaskan Hand-Butchered Salmon Processing Subcategory

SOURCE: 40 FR 55782, Dec. 1, 1975, unless otherwise noted.

#### § 408.160 Applicability; description of the Alaskan hand-butchered salmon processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the hand-butchered of salmon in Alaska.

#### § 408.161 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

#### § 408.162 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any hand-butchered salmon processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 2.6                                              | 1.6                                                               |
| Oil and grease .....    | 0.31                                             | 0.19                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of seafood)   |                                                                   |
| TSS .....               | 2.6                                              | 1.6                                                               |
| Oil and grease .....    | 0.31                                             | 0.19                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any hand-butchered salmon processing facility not covered under § 408.162(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55782, Dec. 1, 1975, as amended at 41 FR 31821, July 30, 1976; 60 FR 33944, June 29, 1995]

#### § 408.163 [Reserved]

#### § 408.164 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55781, Dec. 1, 1975, as amended at 60 FR 33944, June 29, 1995]

#### § 408.165 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section,

## § 408.166

which may be discharged by a new source subject to the provisions of this subpart:

(1) Any hand-butchered salmon processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 2.3                                              | 1.4                                                               |
| Oil and grease .....    | 0.28                                             | 0.17                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of seafood)   |                                                                   |
| TSS .....               | 2.3                                              | 1.4                                                               |
| Oil and grease .....    | 0.28                                             | 0.17                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(2) Any hand-butchered salmon processing facility not covered under § 408.165(a)(1) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

(b) [Reserved]

[40 FR 55782, Dec. 1, 1975, as amended at 41 FR 31821, July 30, 1976]

## § 408.166 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

## 40 CFR Ch. I (7–1–25 Edition)

[40 FR 55781, Dec. 1, 1975, as amended at 60 FR 33944, June 29, 1995]

## § 408.167 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

(a) [Reserved]

(b) Except as provided in §§ 125.30 through 125.32, any hand-butchered salmon processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.162(b)(2) of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24998, July 9, 1986]

## Subpart Q—Alaskan Mechanized Salmon Processing Subcategory

SOURCE: 40 FR 55783, Dec. 1, 1975, unless otherwise noted.

## § 408.170 Applicability; description of the Alaskan mechanized salmon processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the mechanized butchering of salmon in Alaska.

## § 408.171 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

## Environmental Protection Agency

## § 408.175

### § 408.172 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any mechanized salmon processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 44                                               | 26                                                                |
| Oil and grease .....    | 29                                               | 11                                                                |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of seafood)   |                                                                   |
| TSS .....               | 44                                               | 26                                                                |
| Oil and grease .....    | 29                                               | 11                                                                |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any mechanized salmon processing facility not covered under § 408.172(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55783, Dec. 1, 1975, as amended at 41 FR 31821, July 30, 1976; 60 FR 33944, June 29, 1995]

### § 408.173 [Reserved]

### § 408.174 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the

quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55783, Dec. 1, 1975, as amended at 60 FR 33944, June 29, 1995]

### § 408.175 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(1) Any mechanized salmon processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 42                                               | 25                                                                |
| Oil and grease .....    | 28                                               | 10                                                                |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of seafood)   |                                                                   |
| TSS .....               | 42                                               | 25                                                                |
| Oil and grease .....    | 28                                               | 10                                                                |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(2) Any mechanized salmon processing facility not covered under § 408.175(a)(1) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

(b) [Reserved]

[40 FR 55783, Dec. 1, 1975, as amended at 41 FR 31822, July 30, 1976]

**§ 408.176**

**40 CFR Ch. I (7–1–25 Edition)**

**§ 408.176 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55783, Dec. 1, 1975, as amended at 60 FR 33944, June 29, 1995]

**§ 408.177 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.172 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

**Subpart R—West Coast Hand-Butchered Salmon Processing Subcategory**

SOURCE: 40 FR 55784, Dec. 1, 1975, unless otherwise noted.

**§ 408.180 Applicability; description of the West Coast hand-butchered salmon processing subcategory.**

The provisions of this subpart are applicable to discharges resulting from the hand-butchered salmon on the West Coast.

**§ 408.181 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

**§ 408.182 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                          | Effluent limitations  |                                                                   |
|--------------------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of seafood) |                       |                                                                   |
| TSS .....                                        | 2.6                   | 1.6                                                               |
| Oil and grease .....                             | 0.31                  | 0.19                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (pounds per 1,000 lb of seafood)   |                       |                                                                   |
| TSS .....                                        | 2.6                   | 1.6                                                               |
| Oil and grease .....                             | 0.31                  | 0.19                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55784, Dec. 1, 1975, as amended at 41 FR 31822, July 30, 1976; 60 FR 33944, June 29, 1995]

**§ 408.183 [Reserved]**

**§ 408.184 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the

## Environmental Protection Agency

## § 408.191

quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55784, Dec. 1, 1975, as amended at 60 FR 33944, June 29, 1995]

### § 408.185 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                          | Effluent limitations  |                                                                   |
|--------------------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of seafood) |                       |                                                                   |
| BOD5 .....                                       | 2.7                   | 1.7                                                               |
| TSS .....                                        | 0.70                  | 0.42                                                              |
| Oil and grease .....                             | 0.045                 | 0.026                                                             |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (pounds per 1,000 lb of seafood)   |                       |                                                                   |
| BOD5 .....                                       | 2.7                   | 1.7                                                               |
| TSS .....                                        | 0.70                  | 0.42                                                              |
| Oil and grease .....                             | 0.045                 | 0.026                                                             |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55784, Dec. 1, 1975, as amended at 41 FR 31822, July 30, 1976]

### § 408.186 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a

new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55783, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.187 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.182 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart S—West Coast Mechanized Salmon Processing Subcategory

SOURCE: 40 FR 55786, Dec. 1, 1975, unless otherwise noted.

### § 408.190 Applicability; description of the West Coast mechanized salmon processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the mechanized butchering of salmon on the West Coast.

### § 408.191 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and



## § 408.192

saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.192 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 44                                               | 26                                                                |
| Oil and grease .....    | 29                                               | 11                                                                |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
| Effluent characteristic | English units (pounds per 1,000 lb of seafood)   |                                                                   |
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 44                                               | 26                                                                |
| Oil and grease .....    | 29                                               | 11                                                                |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55786, Dec. 1, 1975, as amended at 41 FR 31822, July 30, 1976; 60 FR 33945, June 29, 1995]

### § 408.193 [Reserved]

### § 408.194 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |

## 40 CFR Ch. I (7–1–25 Edition)

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55786, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.195 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| BOD5 .....              | 62                                               | 38                                                                |
| TSS .....               | 13                                               | 7.6                                                               |
| Oil and grease .....    | 4.2                                              | 1.5                                                               |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
| Effluent characteristic | English units (pounds per 1,000 lb of seafood)   |                                                                   |
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| BOD5 .....              | 62                                               | 38                                                                |
| TSS .....               | 13                                               | 7.6                                                               |
| Oil and grease .....    | 4.2                                              | 1.5                                                               |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55786, Dec. 1, 1975, as amended at 41 FR 31822, July 30, 1976]

### § 408.196 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

## Environmental Protection Agency

## § 408.204

[40 FR 55786, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.197 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.192 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart T—Alaskan Bottom Fish Processing Subcategory

SOURCE: 40 FR 55787, Dec. 1, 1975, unless otherwise noted.

### § 408.200 Applicability; description of the Alaskan bottom fish processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of bottom fish such as halibut in Alaska.

### § 408.201 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.202 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point

source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any Alaskan bottom fish processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 3.1                   | 1.9                                                               |
| Oil and grease .....                   | 4.3                   | 0.56                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 3.1                   | 1.9                                                               |
| Oil and grease .....                   | 4.3                   | 0.56                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any Alaskan bottom-fish processing facility not covered under § 408.202(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55787, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.203 [Reserved]

### § 408.204 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |

## § 408.205

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55787, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.205 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(1) Any Alaskan bottom fish processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood)       |                                                                   |
| TSS .....               | 1.9                                    | 1.1                                                               |
| Oil and grease .....    | 2.6                                    | 0.34                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood)       |                                                                   |
| TSS .....               | 1.9                                    | 1.1                                                               |
| Oil and grease .....    | 2.6                                    | 0.34                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(2) Any Alaskan bottom-fish processing facility not covered under § 408.205(a)(1) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

(b) [Reserved]

### § 408.206 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or

## 40 CFR Ch. I (7–1–25 Edition)

pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55787, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.207 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

(a) [Reserved]

(b) Except as provided in §§ 125.30 through 125.32, any Alaskan bottom fish processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.202(b)(2) of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24998, July 9, 1986]

## Subpart U—Non-Alaskan Conventional Bottom Fish Processing Subcategory

SOURCE: 40 FR 55788, Dec. 1, 1975, unless otherwise noted.

### § 408.210 Applicability; description of the non-Alaskan conventional bottom fish processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of bottom fish outside of Alaska in which the unit operations are carried out predominately through manual methods. However, the use of scaling machines and/or skinning machines are considered to be normal practice within this subcategory. The

## Environmental Protection Agency

## § 408.215

provisions of this subpart apply to the processing of currently, commercially processed species of bottom fish such as flounder, ocean perch, haddock, cod, sea catfish, sole, halibut, and rockfish. These provisions apply to existing facilities processing more than 1816 kg (4000 lbs) of raw material per day on any day during a calendar year and all new sources.

### § 408.211 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.212 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| TSS .....               | 3.6                                              | 2.0                                                               |
| Oil and grease .....    | 1.0                                              | 0.55                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of seafood)   |                                                                   |
| TSS .....               | 3.6                                              | 2.0                                                               |
| Oil and grease .....    | 1.0                                              | 0.55                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55788, Dec. 1, 1975, as amended at 41 FR 31822, July 30, 1976; 60 FR 33945, June 29, 1995]

### § 408.213 [Reserved]

### § 408.214 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55788, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.215 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of seafood) |                                                                   |
| BOD5 .....              | 1.2                                              | 0.71                                                              |
| TSS .....               | 1.5                                              | 0.73                                                              |
| Oil and grease .....    | 0.077                                            | 0.042                                                             |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of seafood)   |                                                                   |
| BOD5 .....              | 1.2                                              | 0.71                                                              |
| TSS .....               | 1.5                                              | 0.73                                                              |
| Oil and grease .....    | 0.077                                            | 0.042                                                             |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55788, Dec. 1, 1975, as amended at 41 FR 31823, July 30, 1976]

## § 408.216

### § 408.216 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55788, Dec. 1, 1975, as amended at 60 FR 33945, June 29, 1995]

### § 408.217 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.212 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart V—Non-Alaskan Mechanized Bottom Fish Processing Subcategory

SOURCE: 40 FR 55789, Dec. 1, 1975, unless otherwise noted.

### § 408.220 Applicability; description of the non-Alaskan mechanized bottom fish processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of bottom fish outside of Alaska in which the unit operations

## 40 CFR Ch. I (7–1–25 Edition)

(particularly the butchering and/or filleting operations) are carried out predominately through mechanized methods. The provisions of this subpart apply to the processing of bottom fish such as whiting and croaker.

### § 408.221 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.222 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                          | Effluent limitations  |                                                                   |
|--------------------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of seafood) |                       |                                                                   |
| TSS .....                                        | 22                    | 12                                                                |
| Oil and grease .....                             | 9.9                   | 3.9                                                               |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (pounds per 1,000 lb of seafood)   |                       |                                                                   |
| TSS .....                                        | 22                    | 12                                                                |
| Oil and grease .....                             | 9.9                   | 3.9                                                               |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55789, Dec. 1, 1975, as amended at 41 FR 31823, July 30, 1976; 60 FR 33946, June 29, 1995]

## Environmental Protection Agency

## § 408.230

### § 408.223 [Reserved]

### § 408.224 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55789, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.225 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                          | Effluent limitations  |                                                                   |
|--------------------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kilograms per 1,000 kg of seafood) |                       |                                                                   |
| BOD5 .....                                       | 13                    | 7.5                                                               |
| TSS .....                                        | 5.3                   | 2.9                                                               |
| Oil and grease .....                             | 1.2                   | 0.47                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (pounds per 1,000 lb of seafood)   |                       |                                                                   |
| BOD5 .....                                       | 13                    | 7.5                                                               |
| TSS .....                                        | 5.3                   | 2.9                                                               |
| Oil and grease .....                             | 1.2                   | 0.47                                                              |
| pH .....                                         | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55789, Dec. 1, 1975, as amended at 41 FR 31823, July 30, 1976]

### § 408.226 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55789, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.227 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.222 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

## Subpart W—Hand-Shucked Clam Processing Subcategory

SOURCE: 40 FR 55790, Dec. 1, 1975, unless otherwise noted.

### § 408.230 Applicability; description of the hand-shucked clam processing subcategory.

The provisions of this subpart are applicable to discharges resulting from existing hand-shucked clam processing facilities which process more than 1816 kg (4000 lbs) of raw material per day on

## § 408.231

any day during a calendar year and all new sources.

### § 408.231 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.232 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent limitations                   |                       |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
| Effluent characteristic                | Effluent limitations  |                                                                   |
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 59                    | 18                                                                |
| Oil and grease .....                   | 0.60                  | 0.23                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 59                    | 18                                                                |
| Oil and grease .....                   | 0.60                  | 0.23                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55790, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.233 [Reserved]

### § 408.234 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following

## 40 CFR Ch. I (7–1–25 Edition)

pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55790, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.235 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 55                    | 17                                                                |
| Oil and grease .....                   | 0.56                  | 0.21                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 55                    | 17                                                                |
| Oil and grease .....                   | 0.56                  | 0.21                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.236 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

## Environmental Protection Agency

## § 408.244

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55790, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.237 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.232 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart X—Mechanized Clam Processing Subcategory

SOURCE: 40 FR 55791, Dec. 1, 1975, unless otherwise noted.

### § 408.240 Applicability; description of the mechanized clam processing subcategory.

The provisions of this subpart are applicable to discharges resulting from mechanized clam processing.

### § 408.241 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.242 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 90                    | 15                                                                |
| Oil and grease .....                   | 4.2                   | 0.97                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 90                    | 15                                                                |
| Oil and grease .....                   | 4.2                   | 0.97                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55791, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.243 [Reserved]

### § 408.244 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55791, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]



## § 408.245

### § 408.245 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| BOD <sub>5</sub> .....  | 15                                     | 5.7                                                               |
| TSS .....               | 26                                     | 4.4                                                               |
| Oil and grease .....    | 0.40                                   | 0.092                                                             |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
| BOD <sub>5</sub> .....  | 15                                     | 5.7                                                               |
| TSS .....               | 26                                     | 4.4                                                               |
| Oil and grease .....    | 0.40                                   | 0.092                                                             |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.246 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD <sub>5</sub> .....          | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55791, Dec. 1, 1975, as amended at 60 FR 33946, June 29, 1995]

### § 408.247 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall

## 40 CFR Ch. I (7–1–25 Edition)

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.242 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart Y—Pacific Coast Hand-Shucked Oyster Processing Subcategory

SOURCE: 40 FR 55792, Dec. 1, 1975, unless otherwise noted.

### § 408.250 Applicability; description of the Pacific Coast hand-shucked oyster processing subcategory.

The provisions of this subpart are applicable to discharges resulting from existing Pacific Coast handshucked oyster processing facilities which process more than 454 kg (1000 lbs) of product per day on any day during a calendar year and all new sources.

### § 408.251 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *product* shall mean the weight of the oyster meat after shucking.

### § 408.252 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

## Environmental Protection Agency

## § 408.257

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of product) |                                                                   |
| TSS .....               | 47                                               | 38                                                                |
| Oil and grease .....    | 2.4                                              | 1.8                                                               |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of product)   |                                                                   |
| TSS .....               | 47                                               | 38                                                                |
| Oil and grease .....    | 2.4                                              | 1.8                                                               |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55792, Dec. 1, 1975, as amended at 41 FR 31823, July 30, 1976; 60 FR 33946, June 29, 1995]

### § 408.253 [Reserved]

### § 408.254 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55792, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.255 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of product) |                                                                   |
| TSS .....               | 45                                               | 36                                                                |
| Oil and grease .....    | 2.2                                              | 1.7                                                               |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of product)   |                                                                   |
| TSS .....               | 45                                               | 36                                                                |
| Oil and grease .....    | 2.2                                              | 1.7                                                               |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55792, Dec. 1, 1975, as amended at 41 FR 31823, July 30, 1976]

### § 408.256 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55792, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.257 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Except as provided in §§ 125.30 through 125.32, the following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology:

§ 408.260

| Effluent characteristic | Effluent limitations                             |                                                                       |
|-------------------------|--------------------------------------------------|-----------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for thirty consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of product) |                                                                       |
| TSS .....               | 45                                               | 36                                                                    |
| Oil and grease .....    | 2.2                                              | 1.7                                                                   |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                      |
|                         | English units (pounds per 1,000 lb of product)   |                                                                       |
| TSS .....               | 45                                               | 36                                                                    |
| Oil and grease .....    | 2.2                                              | 1.7                                                                   |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                      |

<sup>1</sup> Within the range 6.0 to 9.0.

[51 FR 24998, July 9, 1986]

**Subpart Z—Atlantic and Gulf Coast Hand-Shucked Oyster Processing Subcategory**

SOURCE: 40 FR 55793, Dec. 1, 1975, unless otherwise noted.

**§ 408.260 Applicability; description of the Atlantic and Gulf Coast hand-shucked oyster processing subcategory.**

The provisions of this subpart are applicable to discharge resulting from existing hand-shucked oyster processing facilities on the Atlantic and Gulf Coasts which process more than 454 kg (1000 lbs) of product per day on any day during a calendar year and all new sources.

**§ 408.261 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *product* shall mean the weight of the oyster meat after shucking.

40 CFR Ch. I (7–1–25 Edition)

**§ 408.262 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of product) |                                                                   |
| TSS .....               | 24                                               | 16                                                                |
| Oil and grease .....    | 1.2                                              | 0.81                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of product)   |                                                                   |
| TSS .....               | 24                                               | 16                                                                |
| Oil and grease .....    | 1.2                                              | 0.81                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55793, Dec. 1, 1975, as amended at 41 FR 31823, July 30, 1976; 60 FR 33947, June 29, 1995]

**§ 408.263 [Reserved]**

**§ 408.264 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

## Environmental Protection Agency

## § 408.271

[40 FR 55793, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.265 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                             |                                                                   |
|-------------------------|--------------------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of product) |                                                                   |
| TSS .....               | 23                                               | 16                                                                |
| Oil and grease .....    | 1.1                                              | 0.77                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |
|                         | English units (pounds per 1,000 lb of product)   |                                                                   |
| TSS .....               | 23                                               | 16                                                                |
| Oil and grease .....    | 1.1                                              | 0.77                                                              |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55793, Dec. 1, 1975, as amended at 41 FR 31824, July 30, 1976]

### § 408.266 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD <sub>5</sub> .....          | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55793, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.267 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Except as provided in §§ 125.30 through 125.32, the following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology:

| Effluent characteristic | Effluent limitations                             |                                                                       |
|-------------------------|--------------------------------------------------|-----------------------------------------------------------------------|
|                         | Maximum for any 1 day                            | Average of daily values for thirty consecutive days shall not exceed— |
|                         | Metric units (kilograms per 1,000 kg of product) |                                                                       |
| TSS .....               | 23                                               | 16                                                                    |
| Oil and grease .....    | 1.1                                              | 0.77                                                                  |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                      |
|                         | English units (pounds per 1,000 lb of product)   |                                                                       |
| TSS .....               | 23                                               | 16                                                                    |
| Oil and grease .....    | 1.1                                              | 0.77                                                                  |
| pH .....                | ( <sup>1</sup> )                                 | ( <sup>1</sup> )                                                      |

<sup>1</sup> Within the range 6.0 to 9.0.

[51 FR 24998, July 9, 1986]

## Subpart AA—Steamed and Canned Oyster Processing Subcategory

SOURCE: 40 FR 55794, Dec. 1, 1975, unless otherwise noted.

### § 408.270 Applicability; description of the steamed and canned oyster processing subcategory.

The provisions of this subpart are applicable to discharges resulting from oysters which are mechanically shucked.

### § 408.271 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

## § 408.272

(b) The term *product* shall mean the weight of the oyster meat after shucking.

### § 408.272 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of product)        |                                                                   |
| TSS .....               | 270                                    | 190                                                               |
| Oil and grease .....    | 2.3                                    | 1.7                                                               |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of product) |                                                                   |
| TSS .....               | 270                                    | 190                                                               |
| Oil and grease .....    | 2.3                                    | 1.7                                                               |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55794, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.273 [Reserved]

### § 408.274 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

## 40 CFR Ch. I (7–1–25 Edition)

[40 FR 55794, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.275 Standards of performance for new sources.

Except for those steamed and canned oyster processing facilities which utilize air flotation treatment systems to meet the shrimp processing standards of performance for new sources under § 408.115, § 408.125, or § 408.135 and for which standards of performance should be derived on a case-by-case basis, the following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of product)        |                                                                   |
| BOD5 .....              | 67                                     | 17                                                                |
| TSS .....               | 56                                     | 39                                                                |
| Oil and grease .....    | 0.84                                   | 0.42                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of product) |                                                                   |
| BOD5 .....              | 67                                     | 17                                                                |
| TSS .....               | 56                                     | 39                                                                |
| Oil and grease .....    | 0.64                                   | 0.42                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55794, Dec. 1, 1975, as amended at 42 FR 6813, Feb. 4, 1977]

### § 408.276 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |

## Environmental Protection Agency

## § 408.282

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| Oil and grease .....            | Do.                   |

[40 FR 55794, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.277 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.272 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart AB—Sardine Processing Subcategory

SOURCE: 40 FR 55795, Dec. 1, 1975, unless otherwise noted.

### § 408.280 Applicability; description of the sardine processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the canning of sardines or sea herring for sardines. These provisions, however, do not cover the relatively new steaking operation in which cutting machines are used for preparing fish steaks.

### § 408.281 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analyses set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.282 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any sardine processing facility which utilizes dry transportation systems from the fish storage area to the fish processing area shall meet the following limitations:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 36                    | 10                                                                |
| Oil and grease .....                   | 3.5                   | 1.4                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 36                    | 10                                                                |
| Oil and grease .....                   | 3.5                   | 1.4                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any sardine processing facility not covered under § 408.282(a) shall meet the following limitations:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 48                    | 16                                                                |
| Oil and grease .....                   | 6.3                   | 2.8                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 48                    | 16                                                                |
| Oil and grease .....                   | 6.3                   | 2.8                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

## § 408.283

[40 FR 55795, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.283 [Reserved]

### § 408.284 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55795, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

### § 408.285 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 36                                     | 10                                                                |
| Oil and grease .....    | 1.4                                    | 0.57                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
| TSS .....               | 36                                     | 10                                                                |
| Oil and grease .....    | 1.4                                    | 0.57                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.286 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned

## 40 CFR Ch. I (7–1–25 Edition)

treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55795, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.287 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.282 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart AC—Alaskan Scallop Processing Subcategory

SOURCE: 40 FR 55796, Dec. 1, 1975, unless otherwise noted.

### § 408.290 Applicability; description of the Alaskan scallop processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of scallops in Alaska.

### § 408.291 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part

## Environmental Protection Agency

## § 408.295

401 of this chapter shall apply to this subpart.

(b) The term *product* shall mean the weight of the scallop meat after processing.

### § 408.292 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any Alaskan scallop processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of product)        |                                                                   |
| TSS .....               | 6.6                                    | 1.4                                                               |
| Oil and grease .....    | 7.7                                    | 0.24                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
| Effluent characteristic | English units (lb/1,000 lb of product) |                                                                   |
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of product)        |                                                                   |
| TSS .....               | 6.0                                    | 1.4                                                               |
| Oil and grease .....    | 7.7                                    | 0.24                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any Alaskan scallop processing facility not covered under § 408.292(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm. (0.5 inch) in any dimension.

[40 FR 55796, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.293 [Reserved]

### § 408.294 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned

treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55796, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.295 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(1) Any Alaskan scallop processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of product)        |                                                                   |
| TSS .....               | 5.7                                    | 1.4                                                               |
| Oil and grease .....    | 7.3                                    | 0.23                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
| Effluent characteristic | English units (lb/1,000 lb of product) |                                                                   |
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of product)        |                                                                   |
| TSS .....               | 5.7                                    | 1.4                                                               |
| Oil and grease .....    | 7.3                                    | 0.23                                                              |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(2) Any Alaskan scallop processing facility not covered under § 408.295(a) (1) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

(b) [Reserved]



## § 408.296

### § 408.296 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD <sub>5</sub> .....          | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55796, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.297 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

(a) [Reserved]

(b) Except as provided in §§ 125.30 through 125.32, any Alaskan scallop processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak, and Petersburg shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.292(b)(2) of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24998, July 9, 1986]

### Subpart AD—Non-Alaskan Scallop Processing Subcategory

SOURCE: 40 FR 55797, Dec. 1, 1975, unless otherwise noted.

## 40 CFR Ch. I (7–1–25 Edition)

### § 408.300 Applicability; description of the non-Alaskan scallop processing subcategory.

With the exception of land-based processing of calico scallops, the provisions of this subpart are applicable to discharges resulting from the processing of scallops outside of Alaska.

### § 408.301 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *product* shall mean the weight of the scallop meat after processing.

### § 408.302 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of product)        |                       |                                                                   |
| TSS .....                              | 6.0                   | 1.4                                                               |
| Oil and grease .....                   | 7.7                   | 0.24                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of product) |                       |                                                                   |
| TSS .....                              | 6.0                   | 1.4                                                               |
| Oil and grease .....                   | 7.7                   | 0.24                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55797, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

## Environmental Protection Agency

## § 408.307

### § 408.303 [Reserved]

### § 408.304 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55797, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.305 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of product)        |                       |                                                                   |
| TSS .....                              | 5.7                   | 1.4                                                               |
| Oil and grease .....                   | 7.3                   | 0.23                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of product) |                       |                                                                   |
| TSS .....                              | 5.7                   | 1.4                                                               |
| Oil and grease .....                   | 7.3                   | 0.23                                                              |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 408.306 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the

quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55797, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.307 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Except as provided in §§ 125.30 through 125.32, the following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology:

| Effluent characteristic                        | Effluent limitations  |                                                                       |
|------------------------------------------------|-----------------------|-----------------------------------------------------------------------|
|                                                | Maximum for any 1 day | Average of daily values for thirty consecutive days shall not exceed— |
| Metric units (kg/kg of product)                |                       |                                                                       |
| TSS .....                                      | 5.7                   | 1.4                                                                   |
| Oil and grease .....                           | 7.3                   | 0.23                                                                  |
| pH .....                                       | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                      |
| English units (pounds per 1,000 lb of product) |                       |                                                                       |
| TSS .....                                      | 5.7                   | 1.4                                                                   |
| Oil and grease .....                           | 7.3                   | 0.23                                                                  |
| pH .....                                       | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                      |

<sup>1</sup> Within the range 6.0 to 9.0.

[51 FR 24998, July 9, 1986]

### Subpart AE—Alaskan Herring Fillet Processing Subcategory

SOURCE: 40 FR 55798, Dec. 1, 1975, unless otherwise noted.

## § 408.310

### § 408.310 Applicability; description of the Alaskan herring fillet processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of herring fillets in Alaska.

### § 408.311 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.312 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any herring fillet processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 32                                     | 24                                                                |
| Oil and grease .....    | 27                                     | 10                                                                |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
| Effluent characteristic | English units (lb/1,000 lb of seafood) |                                                                   |
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood)        |                                                                   |
| TSS .....               | 32                                     | 24                                                                |
| Oil and grease .....    | 27                                     | 10                                                                |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

## 40 CFR Ch. I (7–1–25 Edition)

(b) Any Alaskan herring fillet processing facility not covered under § 408.312(a) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.313 [Reserved]

### § 408.314 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

### § 408.315 Standards of performance for new sources.

(a) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

(1) Any herring fillet processing facility located in population or processing centers including but not limited to Anchorage, Cordova, Juneau, Ketchikan, Kodiak and Petersburg shall meet the following limitations:

| Effluent characteristic | Effluent limitations            |                                                                   |
|-------------------------|---------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day           | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kg of seafood) |                                                                   |
| TSS .....               | 23                              | 18                                                                |

## Environmental Protection Agency

## § 408.322

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Oil and grease .....                   | 20                    | 7.3                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 23                    | 18                                                                |
| Oil and grease .....                   | 20                    | 7.3                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

(2) Any Alaskan herring fillet processing facility not covered under § 408.315(a)(1) shall meet the following limitations: No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

(b) [Reserved]

### § 408.316 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55798, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

### § 408.317 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those

specified for conventional pollutants (which are defined in § 401.16) in § 408.312 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart AF—Non-Alaskan Herring Fillet Processing Subcategory

SOURCE: 40 FR 55799, Dec. 1, 1975, unless otherwise noted.

### § 408.320 Applicability; description of the non-Alaskan herring fillet processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of herring fillets outside of Alaska.

### § 408.321 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

### § 408.322 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic         | Effluent limitations  |                                                                   |
|---------------------------------|-----------------------|-------------------------------------------------------------------|
|                                 | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood) |                       |                                                                   |
| TSS .....                       | 32                    | 24                                                                |
| Oil and grease .....            | 27                    | 10                                                                |

**§ 408.323**

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 32                    | 24                                                                |
| Oil and grease .....                   | 27                    | 10                                                                |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.323 [Reserved]**

**§ 408.324 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.325 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic          | Effluent limitations  |                                                                   |
|----------------------------------|-----------------------|-------------------------------------------------------------------|
|                                  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of seafood) |                       |                                                                   |
| BOD5 .....                       | 16                    | 15                                                                |

**40 CFR Ch. I (7–1–25 Edition)**

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| TSS .....                              | 7.0                   | 5.2                                                               |
| Oil and grease .....                   | 2.9                   | 1.1                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| BOD5 .....                             | 16                    | 15                                                                |
| TSS .....                              | 7.0                   | 5.2                                                               |
| Oil and grease .....                   | 2.9                   | 1.1                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

**§ 408.326 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55799, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.327 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.322 of this subpart for the best practicable

## Environmental Protection Agency

## § 408.335

control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

### Subpart AG—Abalone Processing Subcategory

SOURCE: 40 FR 55800, Dec. 1, 1975, unless otherwise noted.

#### § 408.330 Applicability; description of the abalone processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of abalone in the contiguous states.

#### § 408.331 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *seafood* shall mean the raw material, including freshwater and saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

#### § 408.332 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                | Effluent limitations  |                                                                   |
|----------------------------------------|-----------------------|-------------------------------------------------------------------|
|                                        | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of seafood)        |                       |                                                                   |
| TSS .....                              | 27                    | 15                                                                |
| Oil and grease .....                   | 2.2                   | 1.4                                                               |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |
| English units (lb/1,000 lb of seafood) |                       |                                                                   |
| TSS .....                              | 27                    | 15                                                                |

| Effluent characteristic | Effluent limitations  |                                                                   |
|-------------------------|-----------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Oil and grease .....    | 2.2                   | 1.4                                                               |
| pH .....                | ( <sup>1</sup> )      | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55800, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

#### § 408.333 [Reserved]

#### § 408.334 Pretreatment standards for existing sources.

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55800, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

#### § 408.335 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD5 .....                      | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

**§ 408.336**

| Effluent characteristic | Effluent limitations                   |                                                                   |
|-------------------------|----------------------------------------|-------------------------------------------------------------------|
|                         | Maximum for any 1 day                  | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood)       |                                                                   |
| TSS .....               | 26                                     | 14                                                                |
| Oil and grease .....    | 2.1                                    | 1.3                                                               |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |
|                         | English units (lb/1,000 lb of seafood) |                                                                   |
|                         |                                        |                                                                   |
|                         |                                        |                                                                   |
| TSS .....               | 26                                     | 14                                                                |
| Oil and grease .....    | 2.1                                    | 1.3                                                               |
| pH .....                | ( <sup>1</sup> )                       | ( <sup>1</sup> )                                                  |

<sup>1</sup> Within the range 6.0 to 9.0.

**§ 408.336 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| BOD <sub>5</sub> .....          | No limitation.        |
| TSS .....                       | Do.                   |
| pH .....                        | Do.                   |
| Oil and grease .....            | Do.                   |

[40 FR 55800, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

**§ 408.337 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.**

Except as provided in §§ 125.30 through 125.32, the following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology:

**40 CFR Ch. I (7–1–25 Edition)**

| Effluent characteristic | Effluent limitations                           |                                                                       |
|-------------------------|------------------------------------------------|-----------------------------------------------------------------------|
|                         | Maximum for any 1 day                          | Average of daily values for thirty consecutive days shall not exceed— |
|                         | Metric units (kg/kkg of seafood)               |                                                                       |
| TSS .....               | 26                                             | 14                                                                    |
| Oil and grease .....    | 21                                             | 1.3                                                                   |
| pH .....                | ( <sup>1</sup> )                               | ( <sup>1</sup> )                                                      |
|                         | English units (pounds per 1,000 lb of seafood) |                                                                       |
|                         |                                                |                                                                       |
|                         |                                                |                                                                       |
| TSS .....               | 26                                             | 14                                                                    |
| Oil and grease .....    | 2.1                                            | 1.3                                                                   |
| pH .....                | ( <sup>1</sup> )                               | ( <sup>1</sup> )                                                      |

<sup>1</sup> Within the range 6.0 to 9.0.

[51 FR 24999, July 9, 1986]

**PART 409—SUGAR PROCESSING POINT SOURCE CATEGORY**

**Subpart A—Beef Sugar Processing Subcategory**

Sec.

409.10 Applicability; description of the beet sugar processing subcategory.

409.11 Specialized definitions.

409.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

409.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

409.14 Pretreatment standards for existing sources.

409.15 Standards of performance for new sources.

409.16 Pretreatment standards for new sources.

409.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

**Subpart B—Crystalline Cane Sugar Refining Subcategory**

409.20 Applicability; description of the crystalline cane sugar refining subcategory.

409.21 Specialized definitions.

409.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best