

Environmental Protection Agency

§ 98.256

in Laboratory Samples of Coal (incorporated by reference, *see* §98.7).

(j) Determine the quantity of petroleum process streams using company records. These quantities include the quantity of coke produced per cycle, asphalt blown, quantity of crude oil plus the quantity of intermediate products received from off site, and the quantity of unstabilized crude oil received at the facility.

(k) Determine temperature or pressure of delayed coking unit vessel using process instrumentation operated, maintained, and calibrated according to the manufacturer's instructions.

(l) The owner or operator shall document the procedures used to ensure the accuracy of the estimates of fuel usage, gas composition, and heating value including but not limited to calibration of weighing equipment, fuel flow meters, and other measurement devices. The estimated accuracy of measurements made with these devices shall also be recorded, and the technical basis for these estimates shall be provided.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79163, Dec. 17, 2010; 81 FR 89263, Dec. 9, 2016]

EFFECTIVE DATE NOTE: Amendments to §98.254 were published at 89 FR 31930, Apr. 25, 2024, effective Jan. 1, 2025.

§ 98.255 Procedures for estimating missing data.

A complete record of all measured parameters used in the GHG emissions calculations is required (e.g., concentrations, flow rates, fuel heating values, carbon content values). Therefore, whenever a quality-assured value of a required parameter is unavailable (e.g., if a CEMS malfunctions during unit operation or if a required fuel sample is not taken), a substitute data value for the missing parameter shall be used in the calculations.

(a) For stationary combustion sources, use the missing data procedures in subpart C of this part.

(b) For each missing value of the heat content, carbon content, or molecular weight of the fuel, substitute the arithmetic average of the quality-assured values of that parameter immediately preceding and immediately

following the missing data incident. If the "after" value is not obtained by the end of the reporting year, you may use the "before" value for the missing data substitution. If, for a particular parameter, no quality-assured data are available prior to the missing data incident, the substitute data value shall be the first quality-assured value obtained after the missing data period.

(c) For missing CO₂, CO, O₂, CH₄, or N₂O concentrations, gas flow rate, and percent moisture, the substitute data values shall be the best available estimate(s) of the parameter(s), based on all available process data (e.g., processing rates, operating hours, etc.). The owner or operator shall document and keep records of the procedures used for all such estimates.

(d) For hydrogen plants, use the missing data procedures in subpart P of this part.

EFFECTIVE DATE NOTE: Amendments to §98.255 were published at 89 FR 31931, Apr. 25, 2024, effective Jan. 1, 2025.

§ 98.256 Data reporting requirements.

In addition to the reporting requirements of §98.3(c), you must report the information specified in paragraphs (a) through (q) of this section.

(a) For combustion sources, follow the data reporting requirements under subpart C of this part (General Stationary Fuel Combustion Sources).

(b) For hydrogen plants, follow the data reporting requirements under subpart P of this part (Hydrogen Production).

(c)–(d) [Reserved]

(e) For flares, owners and operators shall report:

(1) The flare ID number (if applicable).

(2) A description of the type of flare (steam assisted, air-assisted).

(3) A description of the flare service (general facility flare, unit flare, emergency only or back-up flare) and an indication of whether or not the flare is serviced by a flare gas recovery system.

(4) The calculated CO₂, CH₄, and N₂O annual emissions for each flare, expressed in metric tons of each pollutant emitted.

(5) A description of the method used to calculate the CO₂ emissions for each