

(2) The total input power to the device measured at the battery or the power line terminals shall not exceed 100 milliwatts under any condition of modulation.

(3) The antenna shall be a single element, one meter or less in length, permanently mounted on the enclosure containing the device.

(4) Emissions outside of this band shall be attenuated at least 20 dB below the level of the unmodulated carrier.

(5) The regulations contained in § 15.23 of this part apply to intentional radiators constructed under the provisions of this paragraph.

(d) Cordless telephones are not permitted to operate under the provisions of this section.

§ 15.236 Operation of wireless microphones in the bands 54–72 MHz, 76–88 MHz, 174–216 MHz, 470–608 MHz and 614–698 MHz.

(a) *Definitions.* The following definitions apply in this section.

(1) *Wireless Microphone.* An intentional radiator that converts sound into electrical audio signals that are transmitted using radio signals to a receiver which converts the radio signals back into audio signals that are sent through a sound recording or amplifying system. Wireless microphones may be used for cue and control communications and synchronization of TV camera signals as defined in § 74.801 of this chapter. Wireless microphones do not include auditory assistance devices as defined in § 15.3(a) of this part.

(2) *600 MHz duplex gap.* An 11 megahertz guard band at 652–663 MHz that separates part 27 600 MHz service uplink and downlink frequencies.

(3) *600 MHz guard band.* Designated frequency band at 614–617 MHz that prevents interference between licensed services in the 600 MHz service band and channel 37.

(4) *600 MHz service band.* Frequencies in the 617–652 MHz and 663–698 MHz bands that are reallocated and re-assigned for 600 MHz band services under part 27.

NOTE TO PARAGRAPHS (a)(2), (3) AND (4): The specific frequencies will be determined in light of further proceedings pursuant to GN Docket No. 12–268 and the rules will be up-

dated accordingly pursuant to a future public notice.

(5) *Spectrum Act.* Title VI of the Middle Class Tax Relief and Job Creation Act of 2012 (Pub. L. 112–96).

(b) Operation under this section is limited to wireless microphones as defined in this section.

(c) Operation is permitted in the following frequency bands.

(1) Channels allocated and assigned for the broadcast television service.

(2) Frequencies in the 600 MHz service band on which a 600 MHz service licensee has not commenced operations, as defined in § 27.4 of this chapter. Operation on these frequencies must cease no later than the end of the post-auction transition period, as defined in § 27.4 of this chapter. Operation must cease immediately if harmful interference occurs to a 600 MHz service licensee.

(3) The 657–663 MHz segment of the 600 MHz duplex gap.

(4) [Reserved]

(5) The 614–616 MHz segment of the 600 MHz guard band.

(6) Prior to operation in the frequencies identified in paragraphs (c)(2) through (5) of this section, wireless microphone users shall rely on the white space databases in part 15, Subpart H to determine that their intended operating frequencies are available for unlicensed wireless microphone operation at the location where they will be used. Wireless microphone users must register with and check a white space database to determine available channels prior to beginning operation at a given location. A user must re-check the database for available channels if it moves to another location.

(d) The maximum radiated power shall not exceed the following values:

(1) In the bands allocated and assigned for broadcast television and in the 600 MHz service band: 50 mW EIRP

(2) In the 600 MHz guard band and the 600 MHz duplex gap: 20 mW EIRP.

(e) Operation is limited to locations separated from licensed services by the following distances.

(1) Four kilometers outside the following protected service contours of co-channel TV stations.

§ 15.237

47 CFR Ch. I (10–1–24 Edition)

Type of station	Protected contour		
	Channel	Contour (dBu)	Propagation curve
Analog: Class A TV, LPTV, translator and booster	Low VHF (2–6)	47	F(50,50)
	High VHF (7–13)	56	F(50,50)
	UHF (14–51)	64	F(50,50)
Digital: Full service TV, Class A TV, LPTV, translator and booster.	Low VHF (2–6)	28	F(50,90)
	High VHF (7–13)	36	F(50,90)
	UHF (14–51)	41	F(50,90)

(2) The following distances outside of the area where a 600 MHz service licensee has commenced operations, as defined in §27.4 of this chapter.

Type of station	Separation distance in kilometers	
	Co-channel	Adjacent channel
Base	7	0.2
Mobile	35	31

(f) The operating frequency within a permissible band of operation as defined in paragraph (c) must comply with the following requirements.

(1) The frequency selection shall be offset from the upper or lower band limits by 25 kHz or an integral multiple thereof.

(2) One or more adjacent 25 kHz segments within the assignable frequencies may be combined to form a channel whose maximum bandwidth shall not exceed 200 kHz. The operating bandwidth shall not exceed 200 kHz.

(3) The frequency tolerance of the carrier signal shall be maintained within ±0.005% of the operating frequency over a temperature variation of –20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. Battery operated equipment shall be tested using a new battery.

(g) Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in §8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08), *Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range; Part 1: Technical characteristics and methods of measurement*. Emissions outside of this band shall comply with

the limits specified in section 8.4 of ETSI EN 300 422-1 V1.4.2 (2011-08).

[80 FR 73069, Nov. 23, 2015, as amended at 81 FR 4974, Jan. 29, 2016; 82 FR 41559, Sept. 1, 2017]

§ 15.237 Operation in the bands 72.0–73.0 MHz, 74.6–74.8 MHz and 75.2–76.0 MHz.

(a) The intentional radiator shall be restricted to use as an auditory assistance device.

(b) Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the above specified frequency ranges.

(c) The field strength within the permitted 200 kHz band shall not exceed 80 millivolts/meter at 3 meters. The field strength of any emissions radiated on any frequency outside of the specified 200 kHz band shall not exceed the general radiated emissions limits specified in §15.209. The emission limits in this paragraph are based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

[54 FR 17714, Apr. 25, 1989, as amended at 57 FR 13048, Apr. 15, 1992; 78 FR 34927, June 11, 2013]

§ 15.239 Operation in the band 88–108 MHz.

(a) Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88–108 MHz.

(b) The field strength of any emissions within the permitted 200 kHz band shall not exceed 250 microvolts/meter at 3 meters. The emission limit