490.750 493.750

or the applicant, as required, have agreed in writing to accept any interference resulting from operation of the proposed transmitter.

(b) Encompassment exhibit. An exhibit showing that the area within the interfering contour of the proposed transmitter would be totally encompassed by interfering contours of operating cochannel base transmitters controlled by the applicant is required for applications to operate a transmitter with ERP exceeding the basic power and height-power limits of §22.565. This encompassment exhibit may substitute for the interference exhibit required in paragraph (a) of this section.

[59 FR 59507, Nov. 17, 1994, as amended at 62 FR 11636, Mar. 12, 1997]

POINT-TO-POINT OPERATION

§ 22.591 Channels for point-to-point operation.

The following channels are allocated for assignment to fixed transmitters that support other transmitters that provide public mobile service. Unless otherwise indicated, all channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

Meganeruz.							
	VHF	Channels					
72.02	72.36	72.80	75.66				
72.04	72.38	72.82	75.68				
72.06	72.40	72.84	75.70				
72.08	72.42	72.86	75.72				
72.10	72.46	72.88	75.74				
72.12	72.50	72.90	75.76				
72.14	72.54	72.92	75.78				
72.16	72.58	72.94	75.80				
72.18	72.62	72.96	75.82				
72.20	72.64	72.98	75.84				
72.22	72.66	75.42	75.86				
72.24	72.68	75.46	75.88				
72.26	72.70	75.50	75.90				
72.28	72.72	75.54	75.92				
72.30	72.74	75.58	75.94				
72.32	72.76	75.62	75.96				
72.34	72.78	75.64	75.98				
72.10	72.46	72.88	75.74				
72.12	72.50	72.90	75.76				
72.14	72.54	72.92	75.78				
72.16	72.58	72.94	75.80				
72.18	72.62	72.96	75.82				
72.20	72.64	72.98	75.84				
72.22	72.66	75.42	75.86				
72.24	72.68	75.46	75.88				
72.26	72.70	75.50	75.90				
72.28	72.72	75.54	75.92				
72.30	72.74	75.58	75.94				
72.32	72.76	75.62	75.96				

72.34		72.78	75.64	75.98
	UHF	Channels	S—State of	Hawaii
488.250		491.250	489.750 .	492.750
488.750		491.750	490.250 .	493.250

- (a) The 72–76 MHz channels may be used in point-to-multipoint configurations. The 72–76 MHz channels are also allocated for assignment in the Private Radio Services (see part 90 of this chapter).
 - (b) [Reserved]

489.250 492.250

(c) Channels in the frequency ranges 488.250–490.750 and 491.250–493.750 MHz may be assigned only to inter-island fixed stations located in the State of Hawaii.

[59 FR 59507, Nov. 17, 1994; 60 FR 9889, Feb. 22, 1995, as amended at 70 FR 19309, Apr. 13, 2005; 78 FR 25174, Apr. 29, 2013]

§ 22.593 Effective radiated power limits.

The effective radiated power of fixed stations operating on the channels listed in §22.591 must not exceed 150 Watts. The equivalent isotropically radiated power of existing fixed microwave stations (2110–2130 and 2160–2180 MHz) licensed under this part (pursuant to former rules) must not exceed the applicable limits set forth in §101.113 of this chapter.

 $[70~{\rm FR}~19309,~{\rm Apr.}~13,~2005]$

§ 22.601 Existing microwave stations licensed under this part.

Existing microwave stations (2110–2130 and 2160–2180 MHz) licensed under this part (pursuant to former rules) are subject to the transition rules in $\S 22.602$. No new microwave systems will be authorized under this part.

(a) Coordination required. Before filing applications for authority to modify existing stations on these channels or major amendments to such applications, carriers must coordinate the planned channel usage, using the procedure outlined in §22.150, with affected parties in this radio service and the Point-to-Point Microwave Service and the Multipoint Distribution Service. Affected parties are licensees and other applicants with previously filed pending applications whose stations could affect or be affected by the proposed