

Federal Communications Commission

§ 22.805

stations. Temporary fixed stations are to be used as rural subscriber, inter-office, or central office stations when those stations are unavailable or when service from those stations is disrupted by storms or emergencies.

(a) *Six month limitation.* If it is necessary for a temporary fixed station to remain at the same location for more than six months, the licensee of that station must apply for authorization to operate the station at the specific location at least 30 days before the end of the six month period.

(b) *International communications.* Communications between the United States and Canada or Mexico must not be carried using a temporary fixed station without prior authorization from the FCC. Licensees desiring to carry such communications should apply sufficiently in advance to allow for the time necessary to coordinate with Canada or Mexico.

BASIC EXCHANGE TELEPHONE RADIO SYSTEMS

§ 22.757 Channels for basic exchange telephone radio systems.

The channels listed in § 22.725 are also allocated for paired assignment to transmitters in basic exchange telephone radio systems.

[70 FR 19309, Apr. 13, 2005]

§ 22.759 Power limit for BETRS.

The effective radiated power of central office and rural subscriber station transmitters used in basic exchange telephone radio systems must not exceed the limits in this section.

(a) *Maximum ERP.* The effective radiated power (ERP) of central office and rural subscriber station transmitters in BETRS must not exceed the applicable limits in this paragraph under any circumstances.

Frequency range (MHz)	Maximum ERP (watts)
152–153	1400
157–159	150
454–455	3500
459–460	150

(b) *Height-power limit.* The ERP of central office stations in BETRS must not exceed the amount calculated as follows:

$$ERP_w = 557,418 \div h_m^2$$

where ERP_w is the effective radiated power in Watts

h_m is the average (eight cardinal radial) antenna height above average terrain in meters

Subpart G—Air-Ground Radiotelephone Service

§ 22.801 Scope.

The rules in this subpart govern the licensing and operation of air-ground stations and systems. The licensing and operation of these stations and systems is also subject to rules elsewhere in this part and in part 1 of this chapter that generally apply to the Public Mobile Services. In case of conflict, however, the rules in this subpart govern.

[70 FR 19309, Apr. 13, 2005]

GENERAL AVIATION AIR-GROUND STATIONS

§ 22.805 Channels for general aviation air-ground service.

The following channels are allocated for the provision of radiotelephone service to airborne mobile subscribers in general aviation aircraft. These channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

SIGNALLING CHANNEL PAIR

Ground	Airborne mobile
454.675	459.675

COMMUNICATION CHANNEL PAIRS

Ground	Airborne mobile
454.700	459.700
454.725	459.725
454.750	459.750
454.775	459.775
454.800	459.800
454.825	459.825
454.850	459.850
454.875	459.875
454.900	459.900
454.925	459.925
454.950	459.950
454.975	459.975

(a) Channel 454.675 MHz is assigned to each and every ground station, to be used only for automatically alerting

§ 22.807

airborne mobile stations of incoming calls.

(b) All airborne mobile channels are assigned for use by each and every airborne mobile station.

§ 22.807 General aviation air-ground application requirements.

In addition to the information required by subparts B and D of this part, FCC Form 601 applications for authorization to operate a general aviation air-ground station must contain the applicable supplementary information described in this section.

(a) *Administrative information.* The following information is required by FCC Form 601.

(1) The number of transmitter sites for which authorization is requested.

(2) The call sign(s) of other facilities in the same area that are ultimately controlled by the real party in interest to the application.

(b) *Technical information required.* For each transmitter in the Rural Radiotelephone Service, the following information is required by FCC Form 601:

(1) Location description, city, county, state, geographic coordinates (NAD83) correct to ± 1 second, site elevation above mean sea level, proximity to adjacent market boundaries and international borders;

(2) Antenna height to tip above ground level, antenna gain in the maximum lobe, the electric field polarization of the wave emitted by the antenna when installed as proposed;

(3) The center frequency of each channel requested, the maximum effective radiated power, any non-standard emission types to be used, including bandwidth and modulation type and the transmitter classification (e.g. ground or signaling).

[59 FR 59507, Nov. 17, 1994, as amended at 59 FR 59954, Nov. 21, 1994; 63 FR 68948, Dec. 14, 1998; 64 FR 53240, Oct. 1, 1999. Redesignated and amended at 70 FR 19309, Apr. 13, 2005]

§ 22.809 Transmitting power limits.

The transmitting power of ground and airborne mobile transmitters operating on the channels listed in § 22.805 must not exceed the limits in this section.

(a) *Ground station transmitters.* The effective radiated power of ground sta-

47 CFR Ch. I (10–1–23 Edition)

tions must not exceed 100 Watts and must not be less than 50 Watts, except as provided in § 22.811.

(b) *Airborne mobile transmitters.* The transmitter power output of airborne mobile transmitters must not exceed 25 Watts and must not be less than 4 Watts.

§ 22.813 Technical channel pair assignment criteria.

The rules in this section establish technical assignment criteria for the channel pairs listed in § 22.805. These criteria are intended to provide substantial service volumes over areas that have significant local and regional general aviation activity, while maintaining the continuous nationwide in-route coverage of the original geographical layout.

(a) *Distance separation for co-channel ground stations.* The FCC may grant an application requesting assignment of a communication channel pair to a proposed ground transmitter only if the proposed antenna location is at least 800 kilometers (497 miles) from the antenna location of the nearest co-channel ground transmitter in the United States, its territories and possessions; and 1000 kilometers (621 miles) from the antenna location of the nearest co-channel ground transmitter in Canada.

(b) *Dispersion.* The FCC may grant an application requesting assignment of a communication channel pair to a proposed ground transmitter only if there are no more than five different communication channel pairs already assigned to ground transmitters with antenna locations within a 320 kilometer (199 mile) radius of the proposed antenna location.

§ 22.815 Construction period for general aviation ground stations.

The construction period (see § 1.946 of this chapter) for general aviation ground stations is 12 months.

[70 FR 19310, Apr. 13, 2005]

§ 22.817 Additional channel policies.

The rules in this section govern the processing of applications for authority to operate a ground station transmitter on any ground station communication channel listed in § 22.805 when the applicant has applied or been