

the applicable power flux-density limits set forth in §25.140(a)(3)(iii) and/or (b)(3) shall bear the burden of coordinating with any future co-frequency licensees and permittees of a space station transmitting in the 17.3–17.8 GHz band as required in §25.114(d)(15)(ii).

(c) If no good faith agreement can be reached, the operator of the FSS space station transmitting in the 17.3–17.8 GHz band that does not comply with §25.140(a)(3)(iii) or the operator of the 17/24 GHz BSS space station that does not comply with §25.140(b)(3), shall reduce its power flux-density levels to be compliant with those specified in §25.140(a)(3)(iii) and/or (b)(3) as appropriate.

(d) Any U.S. licensee or permittee of a space station transmitting in the 17.3–17.8 GHz band that is required to provide information in its application pursuant to §25.140(a)(2) or (b)(4) must accept any increased interference that may result from adjacent space stations transmitting in the 17.3–17.8 GHz band that are operating in compliance with the rules for such space stations specified in §§25.140(a) and (b), 25.202(a)(9) and (e) through (g), 25.210(i) through (j), 25.224, 25.262, 25.264(h), and 25.273(a)(3).

(e) Notwithstanding the provisions of this section, licensees and permittees will be allowed to apply for a license or authorization for a replacement satellite that will be operated at the same power level and interference protection as the satellite to be replaced.

[87 FR 72407, Nov. 25, 2022]

**§25.263 Information sharing requirements for SDARS terrestrial repeater operators.**

This section requires SDARS licensees in the 2320–2345 MHz band to share information regarding the location and operation of terrestrial repeaters with WCS licensees in the 2305–2320 MHz and 2345–2360 MHz bands. Section 27.72 of this chapter requires WCS licensees to share information regarding the location and operation of base stations in the 2305–2320 MHz and 2345–2360 MHz bands with SDARS licensees in the 2320–2345 MHz band.

(a) SDARS licensees must select terrestrial repeater sites and frequencies, to the extent practicable, to minimize

the possibility of harmful interference to WCS base station operations in the 2305–2320 MHz and 2345–2360 MHz bands.

(b) *Notice requirements.* SDARS licensees that intend to operate a new terrestrial repeater must, before commencing such operation, provide 10 business days prior notice to all potentially affected Wireless Communications Service (WCS) licensees. SDARS licensees that intend to modify an existing repeater must, before commencing such modified operation, provide 5 business days prior notice to all potentially affected WCS licensees.

(1) For purposes of this section, a “potentially affected WCS licensee” is a WCS licensee that:

(i) Is authorized to operate a base station in the 2305–2315 MHz or 2350–2360 MHz bands in the same Major Economic Area (MEA) as that in which the terrestrial repeater is to be located;

(ii) Is authorized to operate a base station in the 2315–2320 MHz or 2345–2350 MHz bands in the same Regional Economic Area Grouping (REAG) as that in which the terrestrial repeater is to be located;

(iii) In addition to the WCS licensees identified in paragraphs (b)(1)(i) and (ii) of this section, in cases in which the SDARS licensee plans to deploy or modify a terrestrial repeater within 5 kilometers of the boundary of an MEA or REAG in which the terrestrial repeater is to be located, a potentially affected WCS licensee is one that is authorized to operate a WCS base station in that neighboring MEA or REAG within 5 kilometers of the location of the terrestrial repeater.

(2) For the purposes of this section, a business day is defined by §1.4(e)(2) of this chapter.

(3) For modifications other than changes in location, a licensee may provide notice within 24 hours after the modified operation if the modification does not result in a predicted increase of the power flux density (PFD) at ground level by more than 1 dB since the last advance notice was given. If a demonstration is made by the WCS licensee that such modifications may cause harmful interference to WCS receivers, SDARS licensees will be required to provide notice 5 business days

in advance of additional repeater modifications.

(4) SDARS repeaters operating below 2 watts equivalent isotropically radiated power (EIRP) are exempt from the notice requirements set forth in this paragraph.

(5) SDARS licensees are encouraged to develop separate coordination agreements with WCS licensees to facilitate efficient deployment of and coexistence between each service. To the extent the provisions of any such coordination agreement conflict with the requirements set forth herein, the procedures established under a coordination agreement will control. SDARS licensees must maintain a copy of any coordination agreement with a WCS license in their station files and disclose it to prospective assignees, transferees, or spectrum lessees and, upon request, to the Commission.

(6) SDARS and WCS licensees may enter into agreements regarding alternative notification procedures.

(c) *Contents of notice.* (1) Notification must be written (*e.g.*, certified letter, fax, or e-mail) and include the licensee's name, and the name, address, and telephone number of its coordination representative, unless the SDARS licensee and all potentially affected WCS licensees reach a mutual agreement to provide notification by some other means. WCS licensees and SDARS licensees may establish such a mutually agreeable alternative notification mechanism without prior Commission approval, provided that they comply with all other requirements of this section.

(2) Regardless of the notification method, notification must specify relevant technical details, including, at a minimum:

(i) The coordinates of the proposed repeater to an accuracy of no less than  $\pm 1$  second latitude and longitude;

(ii) The proposed operating power(s), frequency band(s), and emission(s);

(iii) The antenna center height above ground and ground elevation above mean sea level, both to an accuracy of no less than  $\pm 1$  meter;

(iv) The antenna gain pattern(s) in the azimuth and elevation planes that include the peak of the main beam; and

(v) The antenna downtilt angle(s).

(3) An SDARS licensee operating terrestrial repeaters must maintain an accurate and up-to-date inventory of its terrestrial repeaters operating above 2 watts average EIRP, including the information set forth in § 25.263(c)(2), which shall be available upon request by the Commission.

(d) *Calculation of Notice Period.* Notice periods are calculated from the date of receipt by the licensee being notified. If notification is by mail, the date of receipt is evidenced by the return receipt on certified mail. If notification is by fax, the date of receipt is evidenced by the notifying party's fax transmission confirmation log. If notification is by e-mail, the date of receipt is evidenced by a return e-mail receipt. If the SDARS licensee and all potentially affected WCS licensees reach a mutual agreement to provide notification by some other means, that agreement must specify the method for determining the beginning of the notice period.

(e) *Duty to cooperate.* SDARS licensees must cooperate in good faith in the selection and use of new repeater sites to reduce interference and make the most effective use of the authorized facilities. SDARS licensees should provide WCS licensees as much lead time as practicable to provide ample time to conduct analyses and opportunity for prudent repeater site selection prior to SDARS licensees entering into real estate and tower leasing or purchasing agreements. Licensees of stations suffering or causing harmful interference must cooperate in good faith and resolve such problems by mutually satisfactory arrangements. If the licensees are unable to do so, the Space Bureau, in consultation with the Office of Engineering and Technology and the Wireless Telecommunications Bureau, will consider the actions taken by the parties to mitigate the risk of and remedy any alleged interference. In determining the appropriate action, the Bureau will take into account the nature and extent of the interference and act promptly to remedy the interference. The Bureau may impose restrictions on SDARS licensees, including specifying the transmitter power, antenna height, or other technical or operational measures to remedy the interference, and

will take into account previous measures by the licensees to mitigate the risk of interference.

[75 FR 45069, Aug. 2, 2010, as amended at 78 FR 9619, Feb. 11, 2013; 88 FR 21441, Apr. 10, 2023]

**§ 25.264 Requirements to facilitate reverse-band operation in the 17.3–17.8 GHz band.**

(a) Each applicant or licensee for a space station transmitting in the 17.3–17.8 GHz band must submit a series of tables or graphs containing predicted off-axis gain data for each antenna that will transmit in any portion of the 17.3–17.8 GHz band, in accordance with the following specifications. Using a Cartesian coordinate system wherein the X axis is tangent to the geostationary orbital arc with the positive direction pointing east, *i.e.*, in the direction of travel of the satellite; the Y axis is parallel to a line passing through the geographic north and south poles of the Earth, with the positive direction pointing south; and the Z axis passes through the satellite and the center of the Earth, with the positive direction pointing toward the Earth, the applicant or licensee must provide the predicted transmitting antenna off-axis antenna gain information:

(1) In the X–Z plane, *i.e.*, the plane of the geostationary orbit, over a range of  $\pm 30$  degrees from the positive and negative X axes in increments of 5 degrees or less.

(2) In planes rotated from the X–Z plane about the Z axis, over a range of  $\pm 60$  degrees relative to the equatorial plane, in increments of 10 degrees or less.

(3) In both polarizations.

(4) At a minimum of one measurement frequency at the center of the portion of the 17.3–17.8 GHz frequency band over which the space station is designed to transmit. Applicants or licensees must provide additional measurement data at 5 MHz above the lower edge of the band and/or at 5 MHz below the upper edge of the band, upon request by the Commission staff.

(5) Over a greater angular measurement range, if necessary, to account for any planned spacecraft orientation bias or change in operating orientation

relative to the reference coordinate system. The applicant or licensee must state the reasons for including such additional information.

(6) The predictive gain information must be submitted to the Commission for each license application that is filed for a space station transmitting in any portion of the 17.3–17.8 GHz band no later than two years after license grant for the space station.

(b) A space station applicant or licensee transmitting in any portion of the 17.3–17.8 GHz band must submit power flux density (pfd) calculations based on the predicted gain data submitted in accordance with paragraph (a) of this section, as follows:

(1) The pfd calculations must be provided at the location of all prior-filed U.S. DBS space stations where the applicant's pfd level exceeds the coordination trigger of  $-117$  dBW/m<sup>2</sup>/100 kHz in the 17.3–17.8 GHz band. In this rule, the term prior-filed U.S. DBS space station refers to any co-frequency Direct Broadcast Satellite service space station for which an application was filed with the Commission, or an authorization was granted by the Commission, prior to the filing of the information and certifications required by paragraphs (a) and (b) of this section. The term prior-filed U.S. DBS space station does not include any applications (or authorizations) that have been denied, dismissed, or are otherwise no longer valid. Prior-filed U.S. DBS space stations may include foreign-licensed DBS space stations seeking authority to serve the United States market, but do not include foreign-licensed DBS space stations that have not filed applications with the Commission for market access in the United States.

(2) The calculations must take into account the aggregate pfd levels at the DBS receiver at each measurement frequency arising from all antenna beams on the space station transmitting in the 17.3–17.8 GHz band. They must also take into account the maximum permitted longitudinal station-keeping tolerance, orbital inclination and orbital eccentricity of both the space station transmitting in the 17.3–17.8 GHz band and DBS space stations, and must: