

## Federal Communications Commission

## § 90.303

will operate pursuant to a recommendation by a frequency coordinator certified for the pool in which the requested frequency is assigned.

[62 FR 18932, Apr. 17, 1997]

### § 90.279 Power limitations applicable to the 421–430 MHz band.

(a) Base station authorizations in the 421–430 MHz band will be subject to Effective Radiated Power (ERP) and Effective Antenna Height (EAH) limitations as shown in the table below. ERP is defined as the product of the power supplied to the antenna and its gain relative to a half-wave dipole in a given direction. EAH is calculated by subtracting the Assumed Average Terrain Elevation (AATE) as listed in table 7 of § 90.619 from the antenna height above mean sea level.

LIMITS OF EFFECTIVE RADIATED POWER (ERP) CORRESPONDING TO EFFECTIVE ANTENNA HEIGHTS (EAH) OF BASE STATIONS IN THE 421–430 MHz BAND

Effective antenna height (EAH) in meters (feet)	Maximum effective radiated power (ERP) (watts)
0–152 (0–500) .....	250
Above 152–305 (above 500–1000) .....	150
Above 305–457 (above 1000–1500) .....	75
Above 457–610 (above 1500–2000) .....	40
Above 610–762 (above 2000–2500) .....	20
Above 762–914 (above 2500–3000) .....	15
Above 914–1219 (above 3000–4000) .....	10
Above 1219 (above 4000) .....	5

(b) The maximum transmitter power output that will be authorized for control stations is 20 watts.

[52 FR 6157, Mar. 2, 1987, as amended at 58 FR 44957, Aug. 25, 1993]

### § 90.281 Restrictions on operational fixed stations in the 421–430 MHz band.

(a) Except for control stations, operational fixed facilities will not be au-

thorized in the 421–430 MHz band. This does not preclude secondary fixed tone signaling and alarm operations authorized in § 90.235.

(b) Control stations associated with one or more mobile relay stations will be authorized only on the assigned frequency of the associated mobile station. Use of a mobile service frequency by a control station of a mobile relay system is subject to the condition that harmful interference shall not be caused to stations of licensees authorized to use the frequency for mobile service communications.

[52 FR 6158, Mar. 2, 1987, as amended at 54 FR 38681, Sept. 20, 1989]

### § 90.283 [Reserved]

## Subpart L—Authorization in the Band 470–512 MHz (UHF-TV Sharing)

### § 90.301 Scope.

This subpart governs the authorization and use of frequencies by land mobile stations in the band 470–512 MHz on a geographically shared basis with Television Broadcast stations. Under this special sharing plan, different frequencies are allocated depending on the geographic urban area involved as fully detailed in the following rule sections.

[43 FR 54791, Nov. 22, 1978, as amended at 62 FR 18932, Apr. 17, 1997]

### § 90.303 Availability of frequencies.

(a) Frequencies in the band 470–512 MHz are available for assignment as described below. Note: coordinates are referenced to the North American Datum 1983 (NAD83).

(b) The following table lists frequency bands that are available for assignment in specific urban areas. The available frequencies are listed in § 90.311 of this part.

Urbanized area	Geographic center		Bands (MHz)	TV channels
	North latitude	West longitude		
Boston, MA .....	42°21'24.4" .....	71°03'23.2" .....	470–476, 482–488	14, 16
Chicago, IL <sup>1</sup> .....	41°52'28.1" .....	87°38'22.2" .....	470–476, 476–482	14, 15
Cleveland, OH <sup>2</sup> .....	41°29'51.2" .....	81°49'49.5" .....	470–476, 476–482	14, 15
Dallas/Fort Worth, TX .....	32°47'09.5" .....	96°47'38.0" .....	482–488	16
Detroit, MI <sup>3</sup> .....	42°19'48.1" .....	83°02'56.7" .....	476–482, 482–488	15, 16
Houston, TX .....	29°45'26.8" .....	95°21'37.8" .....	488–494	17