

dry ice has dissipated. If ice is used, the outside packaging or overpack must be leakproof. If dry ice is used, the requirements in §173.217 must be met. The inner and outer packagings must maintain their integrity at the temperature of the refrigerant used as well as the temperatures and the pressures which could result if refrigeration were lost.

[Amdt. 173–241, 59 FR 67511, Dec. 29, 1994]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §173.224, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and at www.govinfo.gov.

§ 173.225 Packaging requirements and other provisions for organic peroxides.

(a) *General.* When the §172.101 table specifies that an organic peroxide must be packaged under this section, the organic peroxide must be packaged and offered for transportation in accordance with the provisions of this section. Each packaging must conform to the general requirements of subpart B of part 173 and to the applicable requirements of part 178 of this subchapter. Non-bulk packagings must meet Packing Group II performance levels. To avoid unnecessary confinement, metallic non-bulk packagings meeting Packing Group I are not authorized. No used material, other than production residues or regrind from the same production process, may be used in plastic packagings. Organic peroxides that require temperature control are subject to the provisions of §173.21(f). When an IBC or bulk packaging is authorized and meets the requirements of paragraph (f) or (h) of this section, respectively, lower control temperatures than those specified for non-bulk packaging may be required. An organic peroxide not identified in paragraph (c), (e), or (g) of this section by technical name, or not assigned to a generic type in accordance with the provisions in paragraph (b)(3) of this section, must conform to the provisions of paragraph (c) of §173.128.

(b) *New organic peroxides, formulations and samples.* (1) Except as provided for samples in paragraph (b)(2) of this section, no person may offer for transportation an organic peroxide that is not

identified by technical name in the Organic Peroxides Table, Organic Peroxide IBC Table, or the Organic Peroxide Portable Tank Table of this section, or a formulation of one or more organic peroxides that are identified by technical name in one of those tables, unless the organic peroxide is assigned a generic type and shipping description and is approved by the Associate Administrator under the provisions of §173.128(d) of this subchapter.

(2) *Samples.* Samples of new organic peroxides or new formulations of organic peroxides identified in the Organic Peroxides Table in paragraph (c) of this section, for which complete test data are not available, and that are to be transported for further testing or product evaluation, may be assigned an appropriate shipping description for organic peroxide Type C, packaged and offered for transportation, under the following conditions:

(i) Data available to the person offering the material for transportation must indicate that the sample would pose a level of hazard no greater than that of an organic peroxide Type B and that the control temperature, if any, is sufficiently low to prevent any dangerous decomposition and sufficiently high to prevent any dangerous phase separation;

(ii) The sample must be packaged in accordance with packing method OP2, for a liquid or solid, respectively;

(iii) Packages of the organic peroxide may be offered for transportation and transported in a quantity not to exceed 10 kg (22 pounds) per transport vehicle; and

(iv) One of the following shipping descriptions must be assigned:

(A) Organic peroxide Type C, liquid, 5.2, UN 3103;

(B) Organic peroxide Type C, solid, 5.2, UN 3104;

(C) Organic peroxide Type C, liquid, temperature controlled, 5.2, UN 3113; or

(D) Organic peroxide Type C, solid, temperature controlled, 5.2, UN 3114.

(3) *Mixtures.* Mixtures of organic peroxides individually identified in the Organic Peroxides Table in paragraph (c) of this section may be classified as the same type of organic peroxide as that of the most dangerous component and be transported under the conditions for

transportation given for this type. If the stable components form a thermally less stable mixture, the SADT of the mixture must be determined and the new control and emergency temperature derived under the provisions of § 173.21(f).

(c) *Organic peroxides table.* The following Organic Peroxides Table specifies by technical name those organic peroxides that are authorized for transportation and not subject to the approval provisions of § 173.128 of this part. An organic peroxide identified by technical name in the following table is authorized for transportation only if it conforms to all applicable provisions of the table. The column headings of the Organic Peroxides Table are as follows:

(1) *Technical name.* The first column specifies the technical name.

(2) *ID number.* The second column specifies the identification (ID) number which is used to identify the proper shipping name in the § 172.101 table. The word "EXEMPT" appearing in the column denotes that the material is not regulated as an organic peroxide.

(3) *Concentration of organic peroxide.* The third column specifies concentration (mass percent) limitations, if any, in mixtures or solutions for the organic peroxide. Limitations are given as minimums, maximums, or a range, as appropriate. A range includes the lower and upper limits (*i.e.*, "53-100" means from, and including, 53% to, and including 100%). See introductory paragraph of § 172.203(k) of this subchapter for additional description requirements for an organic peroxide that may qualify for more than one generic listing, depending on its concentration.

(4) *Concentration of diluents.* The fourth column specifies the type and concentration (mass percent) of diluent or inert solid, when required. Other types and concentrations of diluents may be used if approved by the Associate Administrator.

(i) The required mass percent of "Diluent type A" is specified in column 4a. A diluent type A is an organic liq-

uid that does not detrimentally affect the thermal stability or increase the hazard of the organic peroxide and with a boiling point not less than 150 °C at atmospheric pressure. Type A diluents may be used for desensitizing all organic peroxides.

(ii) The required mass percent of "Diluent type B" is specified in column 4b. A diluent type B is an organic liquid which is compatible with the organic peroxide and which has a boiling point, at atmospheric pressure, of less than 150 °C (302 °F) but at least 60 °C (140 °F), and a flash point greater than 5 °C (41 °F). Type B diluents may be used for desensitizing all organic peroxides, when specified in the organic peroxide tables, provided that the boiling point is at least 60 °C (140 °F) above the SADT of the peroxide in a 50 kg (110 lbs) package. A type A diluent may be used to replace a type B diluent in equal concentration.

(iii) The required mass percent of "Inert solid" is specified in column 4c. An inert solid is a solid that does not detrimentally affect the thermal stability or hazard of the organic peroxide.

(5) *Concentration of water.* Column 5 specifies, in mass percent, the minimum amount of water, if any, which must be in formulation.

(6) *Packing method.* Column 6 specifies the highest packing method (largest packaging capacity) authorized for the organic peroxide. Lower numbered packing methods (smaller packaging capacities) are also authorized. For example, if OP3 is specified, then OP2 and OP1 are also authorized. The Table of Packing Methods in paragraph (d) of this section defines the non-bulk packing methods.

(7) *Temperatures.* Column 7a specifies the control temperature. Column 7b specifies the emergency temperature. Temperatures are specified only when temperature controls are required. (See § 173.21(f)).

(8) *Notes.* Column 8 specifies other applicable provisions, as set forth in notes following the table.

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
Acetyl acetone peroxide	UN3105 ..	≤42	≥48	≥8	OP7	2
Acetyl acetone peroxide [as a paste].	UN3106 ..	≤32	OP7	21
Acetyl cyclohexanesulfonyl peroxide.	UN3112 ..	≤82	≥12 ...	OP4	−10	0.	
Acetyl cyclohexanesulfonyl peroxide.	UN3115 ..	≤32	≥68	OP7	−10	0.	
tert-Amyl hydroperoxide	UN3107 ..	≤88	≥6	≥6	OP8		
tert-Amyl peroxyacetate	UN3105 ..	≤62	≥38	OP7		
tert-Amyl peroxybenzoate.	UN3103 ..	≤100	OP5		
tert-Amyl peroxy-2- ethylhexanoate.	UN3115 ..	≤100	OP7	+20 ..	+25.	
tert-Amyl peroxy-2- ethylhexyl carbonate.	UN3105 ..	≤100	OP7		
tert-Amyl peroxy iso- propyl carbonate.	UN3103 ..	≤77	≥23	OP5		
tert-Amyl peroxyneodecanoate.	UN3115 ..	≤77	≥23	OP7	0	+10.	
tert-Amyl peroxyneodecanoate.	UN3119 ..	≤47	≥53	OP8	0	+10.	
tert-Amyl peroxy-pivalate	UN3113 ..	≤77	≥23	OP5	+10 ..	+15.	
tert-Amyl peroxy-pivalate	UN3119 ..	≤32	≥68	OP8	+10 ..	+15.	
tert-Amyl peroxy-3,5,5- trimethylhexanoate.	UN3105 ..	≤100	OP7		
tert-Butyl cumyl peroxide	UN3109 ..	>42 – 100	OP8	9
tert-Butyl cumyl peroxide	UN3108 ..	≤52	≥48	OP8	9
n-Butyl-4,4-di-(tert- butylperoxy)valerate.	UN3103 ..	>52 – 100	OP5		
n-Butyl-4,4-di-(tert- butylperoxy)valerate.	UN3108 ..	≤52	≥48	OP8		
tert-Butyl hydroperoxide	UN3103 ..	>79 – 90	≥10 ...	OP5	13
tert-Butyl hydroperoxide	UN3105 ..	≤80	≥20	OP7	4, 13
tert-Butyl hydroperoxide	UN3107 ..	≤79	>14 ...	OP8	13, 16
tert-Butyl hydroperoxide	UN3109 ..	≤72	≥28 ...	OP8	13
tert-Butyl hydroperoxide [and] Di-tert- butylperoxide.	UN3103 ..	<82 + >9	≥7	OP5	13
tert-Butyl monoperoxymaleate.	UN3102 ..	>52 – 100	OP5		
tert-Butyl monoperoxymaleate.	UN3103 ..	≤52	≥48	OP6		
tert-Butyl monoperoxymaleate.	UN3108 ..	≤52	≥48	OP8		
tert-Butyl monoperoxymaleate [as a paste].	UN3108 ..	≤52	OP8		
tert-Butyl peroxyacetate	UN3101 ..	>52 – 77	≥23	OP5		
tert-Butyl peroxyacetate	UN3103 ..	>32 – 52	≥48	OP6		
tert-Butyl peroxyacetate	UN3109 ..	≤32	≥68	OP8		
tert-Butyl peroxybenzoate.	UN3103 ..	>77 – 100	OP5		
tert-Butyl peroxybenzoate.	UN3105 ..	>52 – 77	≥23	OP7	1
tert-Butyl peroxybenzoate.	UN3106 ..	≤52	≥48	OP7		
tert-Butyl peroxybenzoate.	UN3109 ..	≤32	≥68	OP8		
tert-Butyl peroxybutyl fu- marate.	UN3105 ..	≤52	≥48	OP7		
tert-Butyl peroxycrotonate.	UN3105 ..	≤77	≥23	OP7		
tert-Butyl peroxydiethylacetate.	UN3113 ..	≤100	OP5	+20 ..	+25.	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
tert-Butyl peroxy-2-ethylhexanoate.	UN3113 ..	>52 – 100	OP6	+20 ..	+25.	
tert-Butyl peroxy-2-ethylhexanoate.	UN3117 ..	>32 – 52	≥48	OP8	+30 ..	+35.	
tert-Butyl peroxy-2-ethylhexanoate.	UN3118 ..	≤52	≥48	OP8	+20 ..	+25.	
tert-Butyl peroxy-2-ethylhexanoate.	UN3119 ..	≤32	≥68	OP8	+40 ..	+45.	
tert-Butyl peroxy-2-ethylhexanoate [and] 2,2-di-(tert-Butylperoxy)butane.	UN3106 ..	≤12 + ≤14	≥14	≥60	OP7	
tert-Butyl peroxy-2-ethylhexanoate [and] 2,2-di-(tert-Butylperoxy)butane.	UN3115 ..	≤31 + ≤36	≥33	OP7	+35 ..	+40.	
tert-Butyl peroxy-2-ethylhexylcarbonate.	UN3105 ..	≤100	OP7	
tert-Butyl peroxyisobutyrate.	UN3111 ..	>52 – 77	≥23	OP5	+15 ..	+20.	
tert-Butyl peroxyisobutyrate.	UN3115 ..	≤52	≥48	OP7	+15 ..	+20.	
tert-Butylperoxy isopropylcarbonate.	UN3103 ..	≤77	≥23	OP5	
1-(2-tert-Butylperoxy isopropyl)-3-isopropenylbenzene.	UN3105 ..	≤77	≥23	OP7	
1-(2-tert-Butylperoxy isopropyl)-3-isopropenylbenzene.	UN3108 ..	≤42	≥58	OP8	
tert-Butyl peroxy-2-methylbenzoate.	UN3103 ..	≤100	OP5	
tert-Butyl peroxyneodecanoate.	UN3115 ..	>77 – 100	OP7	– 5 ...	+5.	
tert-Butyl peroxyneodecanoate.	UN3115 ..	≤77	≥23	OP7	0	+10.	
tert-Butyl peroxyneodecanoate [as a stable dispersion in water].	UN3119 ..	≤52	OP8	0	+10.	
tert-Butyl peroxyneodecanoate [as a stable dispersion in water (frozen)].	UN3118 ..	≤42	OP8	0	+10.	
tert-Butyl peroxyneodecanoate.	UN3119 ..	≤32	≥68	OP8	0	+10.	
tert-Butyl peroxyneohexanoate.	UN3115 ..	≤77	≥23	OP7	0	+10.	
tert-Butyl peroxyneohexanoate [as a stable dispersion in water].	UN3117 ..	≤42	OP8	0	+10.	
tert-Butyl peroxyneopentanoate.	UN3113 ..	>67 – 77	≥23	OP5	0	+10.	
tert-Butyl peroxyneopentanoate.	UN3115 ..	>27 – 67	≥33	OP7	0	+10.	
tert-Butyl peroxyneopentanoate.	UN3119 ..	≤27	≥73	OP8	+30 ..	+35.	
tert-Butylperoxy stearylcarbonate.	UN3106 ..	≤100	OP7	
tert-Butyl peroxy-3,5,5-trimethylhexanoate.	UN3105 ..	>37 – 100	OP7	
tert-Butyl peroxy-3,5,5-trimethylhexanoate.	UN3106 ..	≤42	≥58	OP7	
tert-Butyl peroxy-3,5,5-trimethylhexanoate.	UN3109 ..	≤37	≥63	OP8	
3-Chloroperoxybenzoic acid.	UN3102 ..	>57 – 86	≥14	OP1	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
3-Chloroperoxybenzoic acid.	UN3106 ..	≤57	≥3	≥40 ...	OP7		
3-Chloroperoxybenzoic acid.	UN3106 ..	≤77	≥6	≥17 ...	OP7		
Cumyl hydroperoxide	UN3107 ..	>90 – 98	≤10	OP8	13
Cumyl hydroperoxide	UN3109 ..	≤90	≥10	OP8	13, 15
Cumyl peroxyneodecanoate.	UN3115 ..	≤87	≥13	OP7	– 10	0.	
Cumyl peroxyneodecanoate.	UN3115 ..	≤77	≥23	OP7	– 10	0.	
Cumyl peroxyneodecanoate [as a stable dispersion in water].	UN3119 ..	≤52	OP8	– 10	0.	
Cumyl peroxyneohexanoate.	UN3115 ..	≤77	≥23	OP7	– 10	0.	
Cumyl peroxyneopentanoate.	UN3115 ..	≤77	≥23	OP7	– 5	+5.	13
Cyclohexanone peroxide(s).	UN3104 ..	≤91	≥9	OP6	
Cyclohexanone peroxide(s).	UN3105 ..	≤72	≥28	OP7	5
Cyclohexanone peroxide(s) [as a paste].	UN3106 ..	≤72	OP7	5, 21
Cyclohexanone peroxide(s).	Exempt ...	≤32	>68	Exempt	29
Diacetone alcohol peroxides.	UN3115 ..	≤57	≥26	≥8	OP7	+40 ..	+45 ...	5
Diacetyl peroxide	UN3115 ..	≤27	≥73	OP7	+20 ..	+25 ...	8, 13
Di-tert-amyl peroxide	UN3107 ..	≤100	OP8		
([3R- (3R, 5aS, 6S, 8aS, 9R, 10R, 12S, 12aR**)]-Decahydro-10-methoxy-3, 6, 9-trimethyl-3, 12-epoxy-12H-pyrano [4, 3- j]-1, 2-benzodioxepin).	UN3106 ..	≤100	OP7		
2,2-Di-(tert-amylperoxy)-butane.	UN3105 ..	≤57	≥43	OP7		
1,1-Di-(tert-amylperoxy)cyclohexane.	UN3103 ..	≤82	≥18	OP6		
Dibenzoyl peroxide	UN3102 ..	>52 – 100	≤48	OP2	3
Dibenzoyl peroxide	UN3102 ..	>77 – 94	≥6	OP4	3
Dibenzoyl peroxide	UN3104 ..	≤77	≥23 ...	OP6		
Dibenzoyl peroxide	UN3106 ..	≤62	≥28 ...	≥10 ...	OP7		
Dibenzoyl peroxide [as a paste].	UN3106 ..	>52 – 62	OP7	21
Dibenzoyl peroxide	UN3106 ..	>35 – 52	≥48	OP7		
Dibenzoyl peroxide	UN3107 ..	>36 – 42	≥18	≤40 ...	OP8		
Dibenzoyl peroxide [as a paste].	UN3108 ..	≤56.5	≥15 ...	OP8		
Dibenzoyl peroxide [as a paste].	UN3108 ..	≤52	OP8	21
Dibenzoyl peroxide [as a stable dispersion in water].	UN3109 ..	≤42	OP8		
Dibenzoyl peroxide	Exempt ...	≤35	≥65	Exempt	29
Di-(4-tert-butylcyclohexyl)peroxydicarbonate.	UN3114 ..	≤100	OP6	+30 ..	+35.	
Di-(4-tert-butylcyclohexyl)peroxydicarbonate [as a stable dispersion in water].	UN3119 ..	≤42	OP8	+30 ..	+35.	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
Di-(4-tert-butylcyclohexyl)peroxydicarbonate [as a paste].	UN3116 ..	≤42	OP7	+35 ..	+40.	24
Di-tert-butyl peroxide	UN3107 ..	>52 – 100	OP8	
Di-tert-butyl peroxide	UN3109 ..	≤52	≥48	OP8	
Di-tert-butyl peroxyazelaate.	UN3105 ..	≤52	≥48	OP7	
2,2-Di-(tert-butylperoxy)butane.	UN3103 ..	≤52	≥48	OP6	
1,6-Di-(tert-butylperoxycarbonyloxy)hexane.	UN3103 ..	≤72	≥28	OP5	30
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3101 ..	>80 – 100	OP5	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3103 ..	>52 – 80	≥20	OP5	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3103 ..	≤72	≥28	OP5	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3105 ..	>42 – 52	≥48	OP7	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3106 ..	≤42	≥13	≥45	OP7	22
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3107 ..	≤27	≥25	OP8	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3109 ..	≤42	≥58	OP8	
1,1-Di-(tert-Butylperoxy)cyclohexane.	UN3109 ..	≤37	≥63	OP8	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3109 ..	≤25	≥25	≥50	OP8	
1,1-Di-(tert-butylperoxy)cyclohexane.	UN3109 ..	≤13	≥13	≥74	OP8	6
1,1-Di-(tert-butylperoxy)cyclohexane + tert-Butyl peroxy-2-ethylhexanoate.	UN3105 ..	≤43 + ≤16	≥41	OP7	
Di-n-butyl peroxydicarbonate.	UN3115 ..	>27 – 52	≥48	OP7	– 15	– 5.	
Di-n-butyl peroxydicarbonate.	UN3117 ..	≤27	≥73	OP8	– 10	0.	
Di-n-butyl peroxydicarbonate [as a stable dispersion in water (frozen)].	UN3118 ..	≤42	OP8	– 15	– 5.	
Di-sec-butyl peroxydicarbonate.	UN3113 ..	>52 – 100	OP4	– 20	– 10 ..	1, 9
Di-sec-butyl peroxydicarbonate.	UN3115 ..	≤52	≥48	OP7	– 15	– 5.	
Di-(tert-butylperoxyisopropyl)benzene(s).	UN3106 ..	>42 – 100	≤57	OP7	
Di-(tert-butylperoxyisopropyl)benzene(s).	Exempt ...	≤42	≥58	Exempt	
Di-(tert-butylperoxy)phthalate.	UN3105 ..	>42 – 52	≥48	OP7	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A	B	I			Con- trol (7a)	Emer- gency (7b)	
(1)	(2)	(3)	(4a)	(4b)	(4c)	(5)	(6)	(7a)	(7b)	(8)
Di-(tert-butylperoxy)phthalate [as a paste].	UN3106 ..	≤52	OP7	21
Di-(tert-butylperoxy)phthalate.	UN3107 ..	≤42	≥58	OP8	
2,2-Di-(tert-butylperoxy)propane.	UN3105 ..	≤52	≥48	OP7	
2,2-Di-(tert-butylperoxy)propane.	UN3106 ..	≤42	≥13	≥45	OP7	
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3101 ..	>90 – 100	OP5	
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3103 ..	>57 – 90	≥10	OP5	
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3103 ..	≤77	≥23	OP5	
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3103 ..	≤90	≥10	OP5	30
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3110 ..	≤57	≥43	OP8	
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3107 ..	≤57	≥43	OP8	
1,1-Di-(tert-butylperoxy)-3,3,5-trimethylcyclohexane.	UN3107 ..	≤32	≥26	≥42	OP8	
Dicetyl peroxydicarbonate.	UN3120 ..	≤100	OP8	+30 ..	+35.	
Dicetyl peroxydicarbonate [as a stable dispersion in water].	UN3119 ..	≤42	OP8	+30 ..	+35.	
Di-4-chlorobenzoyl peroxide.	UN3102 ..	≤77	≥23 ...	OP5	
Di-4-chlorobenzoyl peroxide.	Exempt ...	≤32	≥68	Exempt	29
Di-2,4-dichlorobenzoyl peroxide [as a paste].	UN3118 ..	≤52	OP8	+20 ..	+25.	
Di-4-chlorobenzoyl peroxide [as a paste].	UN3106 ..	≤52	OP7	21
Dicumyl peroxide	UN3110 ..	>52 – 100	≤48	OP8	9
Dicumyl peroxide	Exempt ...	≤52	≥48	Exempt	29
Dicyclohexyl peroxydicarbonate.	UN3112 ..	>91 – 100	OP3	+10 ..	+15.	
Dicyclohexyl peroxydicarbonate.	UN3114 ..	≤91	≥9	OP5	+10 ..	+15.	
Dicyclohexyl peroxydicarbonate [as a stable dispersion in water].	UN3119 ..	≤42	OP8	+15 ..	+20.	
Didecanoyl peroxide	UN3114 ..	≤100	OP6	+30 ..	+35.	
2,2-Di-(4,4-di(tert-butylperoxy)cyclohexyl)propane.	UN3106 ..	≤42	≥58	OP7	
2,2-Di-(4,4-di(tert-butylperoxy)cyclohexyl)propane.	UN3107 ..	≤22	≥78	OP8	
Di-2,4-dichlorobenzoyl peroxide.	UN3102 ..	≤77	≥23 ...	OP5	
Di-2,4-dichlorobenzoyl peroxide [as a paste with silicone oil].	UN3106 ..	≤52	OP7	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
Di-(2-ethoxyethyl) peroxydicarbonate.	UN3115 ..	≤52	≥48	OP7	− 10	0.	17
Di-(2-ethylhexyl) peroxydicarbonate.	UN3113 ..	>77 – 100	OP5	− 20	− 10.	
Di-(2-ethylhexyl) peroxydicarbonate.	UN3115 ..	≤77	≥23	OP7	− 15	− 5.	
Di-(2-ethylhexyl) peroxydicarbonate [as a stable dispersion in water].	UN3119 ..	≤62	OP8	− 15	− 5.	
Di-(2-ethylhexyl) peroxydicarbonate [as a stable dispersion in water].	UN3119 ..	≤52	OP8	− 15	− 5.	
Di-(2-ethylhexyl) peroxydicarbonate [as a stable dispersion in water (frozen)].	UN3120 ..	≤52	OP8	− 15	− 5.	
2,2- Dihydroperoxypropane.	UN3102 ..	≤27	≥73	OP5	
Di-(1- hydroxycyclohexy- l)peroxide.	UN3106 ..	≤100	OP7	
Diisobutyl peroxide	UN3111 ..	>32 – 52	≥48	OP5	− 20	− 10.	
Diisobutyl peroxide [as a stable dispersion in water].	UN3119 ..	≤42	OP8	− 20	− 10.	
Diisobutyl peroxide	UN3115 ..	≤32	≥68	OP7	− 20	− 10.	
Diisopropylbenzene dihydroperoxide.	UN3106 ..	≤82	≥5	≥5	OP7	
Diisopropyl peroxydicarbonate.	UN3112 ..	>52 – 100	OP2	− 15	− 5.	
Diisopropyl peroxydicarbonate.	UN3115 ..	≤52	≥48	OP7	− 20	− 10.	
Diisopropyl peroxydicarbonate.	UN3115 ..	≤32	≥68	OP7	− 15	− 5.	
Dilauroyl peroxide	UN3106 ..	≤100	OP7	
Dilauroyl peroxide [as a stable dispersion in water].	UN3109 ..	≤42	OP8	
Di-(3-methoxybutyl) peroxydicarbonate.	UN3115 ..	≤52	≥48	OP7	− 5	+5.	
Di-(2- methylbenzoy- l)peroxide.	UN3112 ..	≤87	≥13 ...	OP5	+30 ..	+35.	
Di-(4- methylbenzoy- l)peroxide [as a paste with silicone oil].	UN3106 ..	≤52	OP7	
Di-(3-methylbenzoyl) per- oxide + Benzoyl (3- methylbenzoyl) per- oxide + Dibenzoyl per- oxide.	UN3115 ..	≤20 + ≤18 + ≤4.	≥58	OP7	+35 ..	+40.	
2,5-Dimethyl-2,5-di- (benzoylperox- y)hexane.	UN3102 ..	>82 – 100	OP5	
2,5-Dimethyl-2,5-di- (benzoylperox- y)hexane.	UN3106 ..	≤82	≥18	OP7	
2,5-Dimethyl-2,5-di- (benzoylperox- y)hexane.	UN3104 ..	≤82	≥18 ...	OP5	
2,5-Dimethyl-2,5-di-(tert- butylperoxy)hexane.	UN3103 ..	>90 – 100	OP5	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane.	UN3105 ..	>52—90	≥10	OP7		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane.	UN3108 ..	≤77	≥23	OP8		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane.	UN3109 ..	≤52	≥48	OP8		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexane [as a paste].	UN3108 ..	≤47	OP8		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexyne-3.	UN3101 ..	>86—100	OP5		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexyne-3.	UN3103 ..	>52—86	≥14	OP5		
2,5-Dimethyl-2,5-di-(tert-butylperoxy)hexyne-3.	UN3106 ..	≤52	≥48	OP7		
2,5-Dimethyl-2,5-di-(2-ethylhexanoylperoxy)hexane.	UN3113 ..	≤100	OP5	+20 ..	+25.	
2,5-Dimethyl-2,5-dihydroperoxyhexane.	UN3104 ..	≤82	≥18 ...	OP6		
2,5-Dimethyl-2,5-di-(3,5,5-trimethylhexanoylperoxy)hexane.	UN3105 ..	≤77	≥23	OP7		
1,1-Dimethyl-3-hydroxybutylperoxyne-oheptanoate.	UN3117 ..	≤52	≥48	OP8	0	+10.	
Dimyristyl peroxydicarbonate.	UN3116 ..	≤100	OP7	+20 ..	+25.	
Dimyristyl peroxydicarbonate [as a stable dispersion in water].	UN3119 ..	≤42	OP8	+20 ..	+25.	
Di-(2-neodecanoylperoxyisopropyl)benzene.	UN3115 ..	≤52	≥48	OP7	−10	0.	
Di-(2-neodecanoylperoxyisopropyl)benzene, as stable dispersion in water.	UN3119 ..	≤42	OP8	−15	−5.	
Di-n-nonanoyl peroxide ..	UN3116 ..	≤100	OP7	0	+10.	
Di-n-octanoyl peroxide ...	UN3114 ..	≤100	OP5	+10 ..	+15.	
Di-(2-phenoxyethyl)peroxydicarbonate.	UN3102 ..	>85—100	OP5		
Di-(2-phenoxyethyl)peroxydicarbonate.	UN3106 ..	≤85	≥15 ...	OP7		
Dipropionyl peroxide	UN3117 ..	≤27	≥73	OP8	+15 ..	+20.	
Di-n-propyl peroxydicarbonate.	UN3113 ..	≤100	OP3	−25	−15.	
Di-n-propyl peroxydicarbonate.	UN3113 ..	≤77	≥23	OP5	−20	−10.	
Disuccinic acid peroxide	UN3102 ..	>72—100	OP4	18
Disuccinic acid peroxide	UN3116 ..	≤72	≥28 ...	OP7	+10 ..	+15.	
Di-(3,5,5-trimethylhexanoyl) peroxide.	UN3115 ..	>52—82	≥18	OP7	0	+10.	
Di-(3,5,5-trimethylhexanoyl)peroxide [as a stable dispersion in water].	UN3119 ..	≤52	OP8	+10 ..	+15.	
Di-(3,5,5-trimethylhexanoyl) peroxide.	UN3119 ..	>38—52	≥48	OP8	+10 ..	+15.	

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
Di-(3,5,5-trimethylhexanoyl)peroxide.	UN3119 ..	≤38	≥62	OP8	+20 ..	+25.	
Ethyl 3,3-di-(tert-amyloxy)butyrate.	UN3105 ..	≤67	≥33	OP7	
Ethyl 3,3-di-(tert-butylperoxy)butyrate.	UN3103 ..	>77 – 100	OP5	
Ethyl 3,3-di-(tert-butylperoxy)butyrate.	UN3105 ..	≤77	≥23	OP7	
Ethyl 3,3-di-(tert-butylperoxy)butyrate.	UN3106 ..	≤52	≥48	OP7	
1-(2-ethylhexanoylperoxy)-1,3-Dimethylbutyl peroxydipivalate.	UN3115 ..	≤52	≥45	≥10	OP7	– 20	– 10.	
tert-Hexyl peroxyneodecanoate.	UN3115 ..	≤71	≥29	OP7	0	+10.	
tert-Hexyl peroxydipivalate	UN3115 ..	≤72	≥28	OP7	+10 ..	+15.	
3-Hydroxy-1,1-dimethylbutyl peroxyneodecanoate.	UN3115 ..	≤77	≥23	OP7	– 5 ..	+5.	
3-Hydroxy-1,1-dimethylbutyl peroxyneodecanoate [as a stable dispersion in water].	UN3119 ..	≤52	OP8	– 5 ..	+5.	
3-Hydroxy-1,1-dimethylbutyl peroxyneodecanoate.	UN3117 ..	≤52	≥48	OP8	– 5 ..	+5.	
Isopropyl sec-butyl peroxydicarbonate + Di-sec-butyl peroxydicarbonate + Di-isopropyl peroxydicarbonate.	UN3111 ..	≤52 + ≤28 + ≤22.	OP5	– 20	– 10.	
Isopropyl sec-butyl peroxydicarbonate + Di-sec-butyl peroxydicarbonate + Di-isopropyl peroxydicarbonate.	UN3115 ..	≤32 + ≤15 – 18 + ≤12 – 15.	≥38	OP7	– 20	– 10.	
Isopropylcumyl hydroperoxide.	UN3109 ..	≤72	≥28	OP8	13
p-Menthyl hydroperoxide	UN3105 ..	>72 – 100	OP7	13
p-Menthyl hydroperoxide	UN3109 ..	≤72	≥28	OP8	
Methylcyclohexanone peroxide(s).	UN3115 ..	≤67	≥33	OP7	+35 ..	+40.	
Methyl ethyl ketone peroxide(s).	UN3101 ..	≤52	≥48	OP5	5, 13
Methyl ethyl ketone peroxide(s).	UN3105 ..	≤45	≥55	OP7	5
Methyl ethyl ketone peroxide(s).	UN3107 ..	≤40	≥60	OP8	7
Methyl isobutyl ketone peroxide(s).	UN3105 ..	≤62	≥19	OP7	5, 23
Methyl isopropyl ketone peroxide(s).	UN3109 ..	(See re-mark 31).	≥70	OP8	31
Organic peroxide, liquid, sample.	UN3103	OP2	12
Organic peroxide, liquid, sample, temperature controlled.	UN3113	OP2	12
Organic peroxide, solid, sample.	UN3104	OP2	12

TABLE 1 TO PARAGRAPH (c)—ORGANIC PEROXIDE TABLE—Continued

Technical name (1)	ID No. (2)	Con- centration (mass %) (3)	Diluent (mass %)			Water (mass %) (5)	Packing method (6)	Temperature (°C)		Notes (8)
			A (4a)	B (4b)	I (4c)			Con- trol (7a)	Emer- gency (7b)	
Organic peroxide, solid, sample, temperature controlled.	UN3114	OP2	12
3,3,5,7,7-Pentamethyl- 1,2,4-Trioxepane.	UN3107 ..	≤100	OP8	
Peroxyacetic acid, type D, stabilized.	UN3105 ..	≤43	OP7	13, 20
Peroxyacetic acid, type E, stabilized.	UN3107 ..	≤43	OP8	13, 20
Peroxyacetic acid, type F, stabilized.	UN3109 ..	≤43	OP8	13, 20, 28
Peroxyacetic acid or per- acetic acid [with not more than 7% hydro- gen peroxide].	UN3107 ..	≤36	≥15 ...	OP8	13, 20, 28
Peroxyacetic acid or per- acetic acid [with not more than 20% hydro- gen peroxide].	Exempt ...	≤6	≥60 ...	Exempt	28
Peroxyacetic acid or per- acetic acid [with not more than 26% hydro- gen peroxide].	UN3109 ..	≤17	OP8	13, 20, 28
Peroxylic acid	UN3118 ..	≤100	OP8	+35 ..	+40.	
1-Phenylethyl hydroperoxide.	UN3109 ..	≤38	≥62	OP8	
Pinanyl hydroperoxide ...	UN3105 ..	>56 – 100	OP7	13
Pinanyl hydroperoxide ...	UN3109 ..	≤56	≥44	OP8	
Polyether poly-tert- butylperoxycarbonate.	UN3107 ..	≤52	≥48	OP8	
Tetrahydronaphthyl hydroperoxide.	UN3106 ..	≤100	OP7	
1,1,3,3-Tetramethylbutyl hydroperoxide.	UN3105 ..	≤100	OP7	
1,1,3,3-Tetramethylbutyl peroxy-2- ethylhexanoate.	UN3115 ..	≤100	OP7	+15 ..	+20.	
1,1,3,3-Tetramethylbutyl peroxyneodecanoate.	UN3115 ..	≤72	≥28	OP7	– 5 ...	+5.	
1,1,3,3-Tetramethylbutyl peroxyneodecanoate [as a stable dispersion in water].	UN3119 ..	≤52	OP8	– 5 ...	+5.	
1,1,3,3-tetramethylbutyl peroxypivalate.	UN3115 ..	≤77	≥23	OP7	0	+10.	
3,6,9-Triethyl-3,6,9- trimethyl-1,4,7- triperxonane.	UN3110 ..	≤17	≥18	≥65	OP8	
3,6,9-Triethyl-3,6,9- trimethyl-1,4,7- triperxonane.	UN3105 ..	≤42	≥58	OP7	26

Notes:

- For domestic shipments, OP8 is authorized.
- Available oxygen must be <4.7%.
- For concentrations <80% OP5 is allowed. For concentrations of at least 80% but <85%, OP4 is allowed. For concentrations of at least 85%, maximum package size is OP2.
- The diluent may be replaced by di-tert-butyl peroxide.
- Available oxygen must be ≤9% with or without water.
- For domestic shipments, OP5 is authorized.
- Available oxygen must be ≤8.2% with or without water.
- Only non-metallic packagings are authorized.
- For domestic shipments this material may be transported under the provisions of paragraph (h)(3)(xii) of this section.
- [Reserved]
- [Reserved]
- Samples may only be offered for transportation under the provisions of paragraph (b)(2) of this section.
- "Corrosive" subsidiary risk label is required.
- [Reserved]
- No "Corrosive" subsidiary risk label is required for concentrations below 80%.

16. With <6% di-tert-butyl peroxide.
 17. With ≤8% 1-isopropylhydroperoxy-4-isopropylhydroxybenzene.
 18. Addition of water to this organic peroxide will decrease its thermal stability.
 19. [Reserved]
 20. Mixtures with hydrogen peroxide, water and acid(s).
 21. With diluent type A, with or without water.
 22. With ≥36% diluent type A by mass, and in addition ethylbenzene.
 23. With ≥19% diluent type A by mass, and in addition methyl isobutyl ketone.
 24. Diluent type B with boiling point >100 °C.
 25. No "Corrosive" subsidiary risk label is required for concentrations below 56%.
 26. Available oxygen must be ≤7.6%.
 27. Formulations derived from distillation of peroxyacetic acid originating from peroxyacetic acid in a concentration of not more than 41% with water, total active oxygen less than or equal to 9.5% (peroxyacetic acid plus hydrogen peroxide).
 28. For the purposes of this section, the names "Peroxyacetic acid" and "Peracetic acid" are synonymous.
 29. Not subject to the requirements of this subchapter for Division 5.2.
 30. Diluent type B with boiling point >130 °C (266 °F).
 31. Available oxygen ≤6.7%.

(d) *Packing Method Table.* Packagings for organic peroxides and self-reactive substances are listed in the Maximum Quantity per Packing Method Table. The packing methods are designated OP1 to OP8. The quantities specified for each packing method represent the maximum that is authorized.

(1) The following types of packagings are authorized:

- (i) Drums: 1A1, 1A2, 1B1, 1B2, 1D, 1G, 1H1, 1H2;
 (ii) Jerricans: 3A1, 3A2, 3B1, 3B2, 3H1, 3H2;
 (iii) Boxes: 4C1, 4C2, 4D, 4F, 4G, 4H1, 4H2, 4A, 4B; or

(iv) Composite packagings with a plastic inner receptacle: 6HA1, 6HA2, 6HB1, 6HB2, 6HC, 6HD1, 6HD2, 6HG1, 6HG2, 6HH1, 6HH2.

(2) Metal packaging (including inner packagings of combination packagings and outer packagings of combination or composite packagings) are used only for packing methods OP7 and OP8.

(3) In combination packagings, glass receptacles are used only as inner packagings with a maximum content of 0.5 kg for solids or 0.5 L for liquids.

(4) The maximum quantity per packaging or package for Packing Methods OP1–OP8 must be as follows:

TABLE TO PARAGRAPH (d): MAXIMUM QUANTITY PER PACKAGING/PACKAGE

[For packing methods OP1 to OP8]

Maximum quantity	Packing method							
	OP1	OP2 ¹	OP3	OP4 ¹	OP5	OP6	OP7	OP8
Solids and combination packagings (liquid and solid) (kg)	0.5	0.5/10	5	5/25	25	50	50	² 400
Liquids (L)	0.5	5	30	60	60	³ 225

¹ If two values are given, the first applies to the maximum net mass per inner packaging and the second to the maximum net mass of the complete package.

² 60 kg for jerricans/200 kg for boxes and, for solids, 400 kg in combination packagings with outer packagings comprising boxes (4C1, 4C2, 4D, 4F, 4G, 4H1, and 4H2) and with inner packagings of plastics or fiber with a maximum net mass of 25 kg.

³ 60 L for jerricans.

(e) *Organic Peroxide IBC Table.* The following Organic Peroxide IBC Table specifies, by technical name, those organic peroxides that are authorized for transportation in certain IBCs and not subject to the approval provisions of § 173.128 of this part. The formulations

listed below may also be transported packed in accordance with packing method OP8 of this section, with the same control and emergency temperatures, if applicable. Additional requirements for authorized IBCs are found in paragraph (f) of this section.

TABLE 3 TO PARAGRAPH (e)—ORGANIC PEROXIDE IBC TABLE

UN No.	Organic peroxide	Type of IBC	Maximum quantity (liters)	Control temperature	Emergency temperature
3109	ORGANIC PEROXIDE, TYPE F, LIQUID: tert-Butyl cumyl peroxide	31HA1	1000		

TABLE 3 TO PARAGRAPH (e)—ORGANIC PEROXIDE IBC TABLE—Continued

UN No.	Organic peroxide	Type of IBC	Maximum quantity (liters)	Control temperature	Emergency temperature
3110	tert-Butyl hydroperoxide, not more than 72% with water.	31A	1250		
	tert-Butyl peroxyacetate, not more than 32% in diluent type A.	31HA1	1000		
		31A	1250		
	tert-Butyl peroxybenzoate, not more than 32% in diluent type A.	31HA1	1000		
		31A	1250		
	tert-Butyl peroxy-3,5,5-trimethylhexanoate, not more than 37% in diluent type A.	31A	1250		
	Cumyl hydroperoxide, not more than 90% in diluent type A.	31HA1	1000		
		31HA1	1250		
	Dibenzoyl peroxide, not more than 42% as a stable dispersion.	31H1	1000		
	2,5-Dimethyl-2,5-di(tert-butylperoxy)hexane, not more than 52% in diluent type A.	31HA1	1000		
	Di-tert-butyl peroxide, not more than 52% in diluent type B.	31A	1250		
		31HA1	1000		
	1,1-Di-(tert-Butylperoxy) cyclohexane, not more than 37% in diluent type A.	31A	1250		
	1,1-Di-(tert-butylperoxy) cyclohexane, not more than 42% in diluent type A.	31H1	1000		
	Dicumyl peroxide, less than or equal to 100%.	31A	1250		
		31HA1	1000		
	Dilauroyl peroxide, not more than 42%, stable dispersion, in water.	31HA1	1000		
		31HA1	1000		
	Isopropyl cumyl hydroperoxide, not more than 72% in diluent type A.	31HA1	1250		
	p-Menthyl hydroperoxide, not more than 72% in diluent type A.	31HA1	1250		
	Peroxyacetic acid, stabilized, not more than 17%.	31A	1500		
		31H1	1500		
		31H2	1500		
		31HA1	1500		
	Peroxyacetic acid, not more than 26% hydrogen peroxide.	31A	1500		
		31HA1	1500		
	Peroxyacetic acid, type F, stabilized.	31HA1	1500		
		31A	1500		
	3,6,9-Triethyl-3,6,9-trimethyl-1,4,7-triperoxonane not more than 27% diluent type A.	31HA1	1500		
		31HA1	1000		
3110	ORGANIC PEROXIDE TYPE F, SOLID:				
	Dicumyl peroxide, less than or equal to 100%.	31A	2000		
3119	ORGANIC PEROXIDE, TYPE F, LIQUID, TEMPERATURE CONTROLLED:	31H1			
		31HA1			
	tert-Amyl peroxy-2-ethylhexanoate, not more than 62% in a diluent type A.	31HA1	1000	+15 °C	+20 °C

TABLE 3 TO PARAGRAPH (e)—ORGANIC PEROXIDE IBC TABLE—Continued

UN No.	Organic peroxide	Type of IBC	Maximum quantity (liters)	Control temperature	Emergency temperature
	tert-Amyl peroxy-pivalate, not more than 32% in diluent type A.	31A	1250	+10 °C	+15 °C
	tert-Amyl peroxy-pivalate, not more than 42% as a stable dispersion in water.	31HA1	1,000	0 °C	+10 °C
	tert-Butyl peroxy-2-ethylhexanoate, not more than 32% in diluent type B.	31HA1	1000	+30 °C	+35 °C
	tert-Butyl peroxyneodecanoate, not more than 32% in diluent type A.	31A 31A	1250 1250	+30 °C 0 °C	+35 °C +10 °C
	tert-Butyl peroxyneodecanoate, not more than 52%, stable dispersion, in water.	31A	1250	− 5 °C	+5 °C
	tert-Butyl peroxy-pivalate, not more than 27% in diluent type B.	31HA1	1000	+10 °C	+15 °C
	tert-Butyl peroxy-pivalate, not more than 42% in a diluent type A.	31A 31HA1 31A	1250 1,000 1,250	+10 °C 10 °C 10 °C	+15 °C 15 °C 15 °C
	Cumyl peroxyneodecanoate, not more than 52%, stable dispersion, in water.	31A	1250	− 15 °C	− 5 °C
	Di-(4-tert-butylcyclohexyl) peroxydicarbonate, not more than 42%, stable dispersion, in water.	31HA1	1000	+30 °C	+35 °C
	Dicetyl peroxydicarbonate, not more than 42%, stable dispersion, in water.	31HA1	1000	+30 °C	+35 °C
	Dicyclohexylperoxydicarbonate, not more than 42% as a stable dispersion, in water.	31A	1250	+10 °C	+15 °C
	Di-(2-ethylhexyl) peroxydicarbonate, not more than 62%, stable dispersion, in water.	31A	1250	− 20 °C	− 10 °C
	Diisobutryl peroxide, not more than 28% as a stable dispersion in water.	31HA1 31HA1	1000 1000	− 20 °C − 20 °C	− 10 °C − 10 °C
	Diisobutryl peroxide, not more than 42% as a stable dispersion in water.	31A 31HA1	1250 1000	− 20 °C − 25 °C	− 10 °C − 15 °C
	Dimyristyl peroxydicarbonate, not more than 42%, stable dispersion, in water.	31A 31HA1	1250 1000	− 25 °C +15 °C	− 15 °C +20 °C
	Di-(2-neodecanoylperoxyisopropyl) benzene, not more than 42%, stable dispersion, in water.	31A	1250	− 15 °C	− 5 °C
	Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 52% in diluent type A.	31HA1	1000	+10 °C	+15 °C
	Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 52%, stable dispersion, in water.	31A 31A	1250 1250	+10 °C +10 °C	+15 °C +15 °C
	3-Hydroxy-1,1-dimethylbutyl peroxy-neodecanoate, not more than 52%, stable dispersion, in water.	31A	1250	− 15 °C	− 5 °C

TABLE 3 TO PARAGRAPH (e)—ORGANIC PEROXIDE IBC TABLE—Continued

UN No.	Organic peroxide	Type of IBC	Maximum quantity (liters)	Control temperature	Emergency temperature
	1,1,3,3-Tetramethylbutyl peroxy-2-ethylhexanoate, not more than 67%, in diluent type A.	31HA1	1000	+15 °C	+20 °C
	1,1,3,3-Tetramethylbutyl peroxyneodecanoate, not more than 52%, stable dispersion, in water.	31A	1250	–5 °C	+5 °C
		31HA1	1000	–5 °C	+5 °C

(f) *IBCs.* IBCs are authorized subject to the conditions and limitations of this section if the IBC type is authorized according to paragraph (e) of this section, as applicable, and the IBC conforms to the requirements in subpart O of part 178 of this subchapter at the Packing Group II performance level. Type F organic peroxides or self-reactive substances are not authorized for transportation in IBCs other than those specified, unless approved by the Associate Administrator.

(1) IBCs shall be provided with a device to allow venting during transportation. The inlet to the pressure relief device shall be sited in the vapor space of the IBC under maximum filling conditions during transportation.

(2) To prevent explosive rupture of metal IBCs or composite IBCs with a complete metal casing, the emergency-relief devices shall be designed to vent all the decomposition products and vapors evolved during self-accelerating decomposition or during a period of not

less than one hour of complete fire-engulfment as calculated by the formula in paragraph (h)(3)(v) of this section. The control and emergency temperatures specified in the Organic Peroxide IBC Table are based on a non-insulated IBC.

(g) *Organic Peroxide Portable Tank Table.* The following Organic Peroxide Portable Tank Table provides certain portable tank requirements and identifies, by technical name, those organic peroxides that are authorized for transportation in the bulk packagings listed in paragraph (h) of this section. Organic peroxides listed in this table, provided they meet the specific packaging requirements found in paragraph (h) of this section, are not subject to the approval provisions of §173.128 of this part. In addition, the formulations listed below may also be transported packed in accordance with packing method OP8 of this section, with the same control and emergency temperatures, if applicable.

TABLE TO PARAGRAPH (g): ORGANIC PEROXIDE PORTABLE TANK TABLE

UN No.	Hazardous material	Minimum test pressure (bar)	Minimum shell thickness (mm-reference steel) See. . .	Bottom opening requirements See. . .	Pressure-relief requirements See. . .	Filling limits	Control temperature	Emergency temperature
3109	ORGANIC PEROXIDE, TYPE F, LIQUID. tert-Butyl hydroperoxide, not more than 72% with water. *Provided that steps have been taken to achieve the safety equivalence of 65% tert-Butyl hydroperoxide and 35% water. Cumyl hydro-peroxide, not more than 90% in diluent type A. Di-tert-butyl peroxide, not more than 32% in diluent type A. Dicumyl peroxide, less than or equal to 100% in diluent type B. Isopropyl cumyl hydro-peroxide, not more than 72% in diluent type A. p-Menthyl hydro-peroxide, not more than 72% in diluent type A. Pinanyl hydro-peroxide, not more than 56% in diluent type A.	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
3110	ORGANIC PEROXIDE, TYPE F, SOLID. Dicumyl peroxide less than or equal to 100% with inert solids. *Maximum quantity per portable tank 2,000 kg.	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)		
3119	ORGANIC PEROXIDE, TYPE F, LIQUID, TEMPERATURE CONTROLLED. tert-Amyl peroxyneodecanoate, not more than 47% in diluent type A. tert-Butyl peroxyacetate, not more than 32% in diluent type B. tert-Butyl peroxy-2-ethylhexanoate, not more than 32% in diluent B.	4	§ 178.274 (d)(2)	§ 178.275 (d)(3)	§ 178.275 (g)(1)	Not more than 90% at 59 °F (15 °C)	– 10 °C	– 5 °C.
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+ 30 °C	+ 35 °C
		4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+ 15 °C	+ 20 °C

TABLE TO PARAGRAPH (g): ORGANIC PEROXIDE PORTABLE TANK TABLE—Continued

UN No.	Hazardous material	Minimum test pressure (bar)	Minimum shell thickness (mm-reference steel) See. . .	Bottom opening requirements See. . .	Pressure-relief requirements See. . .	Filling limits	Control temperature	Emergency temperature
	tert-Butylperoxypivalate, not more than 27% in diluent type B.	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+ 5 °C	+ 10 °C
	tert-Butyl peroxy-3,5,5-trimethylhexanoate, not more than 32% in diluent type B.	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+ 35 °C	+ 40 °C
	Di-(3,5,5-trimethyl-hexanoyl) peroxide, not more than 38% in diluent type A or type B.	4	§ 178.274 (d)(2)	§ 178.275 (d)(3)	§ 178.275 (g)(1)	Not more than 90% at 59 °F (15 °C)	0 °C	+ 5 °C.
	Peroxyacetic acid, distilled, stabilized, not more than 41%. ¹ .	4	§ 178.274(d)(2)	§ 178.275(d)(3)	§ 178.275(g)(1)	Not more than 90% at 59 °F (15 °C)	+ 30 °C	+ 35 °C

Note: 1. "Corrosive" subsidiary risk placard is required.

(h) *Bulk packagings other than IBCs.* The following bulk packagings are authorized, subject to the conditions and limitations of this section, if the organic peroxide is listed in the Organic Peroxide Portable Tank Table and bulk packagings are authorized, or if the organic peroxide is specifically authorized for transport in a bulk packaging by this paragraph (h), and the bulk packaging conforms to the requirements of this subchapter:

(1) *Rail cars.* Class DOT 103, 104, 105, 109, 111, 112, 114, 115, or 120 fusion-weld tank car tanks are authorized. DOT 103W, 111A60F1 and 111A60W1 tank car tanks must have bottom outlets effectively sealed from inside. Gauging devices are required on DOT 103W tank car tanks. Riveted tank car tanks are not authorized.

(2) *Cargo tanks.* Specification MC 307, MC 310, MC 311, MC 312, DOT 407, and DOT 412 cargo tank motor vehicles with a tank design pressure of at least 172 kPa (25 psig) are authorized.

(3) *Portable tanks.* The following requirements apply to portable tanks intended for the transport of organic peroxides or self-reactive substances. DOT 51, 57, IM 101 portable tanks, and UN portable tanks that conform to the requirements of paragraph (g) of this section, are authorized. Type F organic peroxide or self-reactive substance formulations other than those indicated in the Organic Peroxide Portable Tank Table may be transported in portable tanks if approved by the Associate Administrator. The following conditions also apply:

(i) The portable tank must be designed for a test pressure of at least 0.4 MPa (4 bar).

(ii) The portable tank must be fitted with temperature-sensing devices.

(iii) The portable tank must be fitted with pressure relief devices and emergency-relief devices. Vacuum-relief devices may also be used. Pressure relief devices must operate at pressures determined according to both the properties of the hazardous material and the construction characteristics of the portable tank. Fusible elements are not allowed in the shell.

(iv) The pressure relief devices must consist of reclosing devices fitted to prevent significant build-up within the

portable tank of the decomposition products and vapors released at a temperature of 50 °C (122 °F). The capacity and start-to-discharge pressure of the relief devices must be in accordance with the applicable requirements of this subchapter specified for the portable tank. The pressure relief devices must not allow liquid to escape in the event the portable tank is overturned in a loaded condition.

(v)(A) The emergency-relief devices may be of the reclosing or frangible types, or a combination of the two, designed to vent all the decomposition products and vapors evolved during a period of not less than one hour of complete fire engulfment as calculated by the following formula:

$$q = 70961 F A^{0.82}$$

Where:

q = heat absorption (W)

A = wetted area (m²)

F = insulation factor (—)

(B) Insulation factor (F) in the formula in paragraph (h)(3)(v)(A) of this section equals 1 for non-insulated vessels and for insulated vessels F is calculated using the following formula:

$$F = \frac{U (923 - T_{PO})}{47032}$$

Where:

U = K/L = heat transfer coefficient of the insulation (W·m⁻²·K⁻¹); where K = heat conductivity of insulation layer (W·m⁻¹·K⁻¹), and L = thickness of insulation layer (m).

T_{PO} = temperature of material at relieving conditions (K).

(vi) The start-to-discharge pressure of emergency-relief devices must be higher than that specified for the pressure relief devices in paragraph (h)(3)(iv) of this section. The emergency-relief devices must be sized and designed in such a way that the maximum pressure in the shell never exceeds the test pressure of the portable tank.

NOTE TO PARAGRAPH (h)(3)(vi): An example of a method to determine the size of emergency-relief devices is given in Appendix 5 of the UN Manual of Tests and Criteria (IBR, see §171.7 of this subchapter). A second example of a test method for venting sizing is given in the American Institute of Chemical

§ 173.226

Engineers Process Safety Progress Journal, June 2002 issue (Vol. 21, No. 2) (Informational materials not requiring incorporation by reference, see § 171.7(b)).

(vii) For insulated portable tanks, the capacity and setting of emergency-relief devices must be determined assuming a loss of insulation from 1% of the surface area.

(viii) Vacuum-relief devices and reclosing devices on portable tanks used for flammable hazardous materials must be provided with flame arresters. Any reduction of the relief capacity caused by the flame arrester must be taken into account and the appropriate relief capacity must be provided.

(ix) Service equipment such as devices and external piping must be designed and constructed so that no hazardous material remains in them after filling the portable tank.

(x) Portable tanks may be either insulated or protected by a sun-shield. If the SADT of the hazardous material in the portable tank is 55 °C (131 °F) or less, the portable tank must be completely insulated. The outer surface must be finished in white or bright metal.

(xi) The degree of filling must not exceed 90% at 15 °C (59 °F).

(xii) DOT 57 metal portable tanks are authorized only for those materials or mixtures of two or more materials that are provided with a reference to Note 9 in Column 8 of the Organic Peroxide Table, found in paragraph (c) of this section. DOT 57 portable tanks must conform to the venting requirements of paragraph (f) of this section. These portable tanks are not subject to any other requirements of paragraph (h) of this section.

(4) For tertiary butyl hydroperoxide (TBHP), each tank car, cargo tank or portable tank must contain 7.6 cm (3.0 inches) low density polyethylene (PE) saddles having a melt index of at least 0.2 grams per 10 minutes (for example see, ASTM D1238, condition E) as part of the lading, with a ratio of PE to TBHP over a range of 0.008 to 0.012 by mass. Alternatively, plastic or metal containers equipped with fusible plugs having a melting point between 69 °C (156 °F) and 71 °C (160 °F) and filled with a sufficient quantity of water to dilute the TBHP to 65% or less by mass may

49 CFR Ch. I (10–1–23 Edition)

be used. The PE saddles must be visually inspected after each trip and, at a minimum, once every 12 months, and replaced when discoloration, fracture, severe deformation, or other indication of change is noted.

[69 FR 76159, Dec. 20, 2004, as amended at 70 FR 34398, June 14, 2005; 72 FR 55693, Oct. 1, 2007; 74 FR 2260, Jan. 14, 2009; 78 FR 1089, Jan. 7, 2013; 78 FR 65482, Oct. 31, 2013; 80 FR 1160, Jan. 8, 2015; 81 FR 35542, June 2, 2016; 82 FR 15884, Mar. 30, 2017; 85 FR 27889, May 11, 2020; 87 FR 44996, July 26, 2022; 87 FR 79777, Dec. 27, 2022]

§ 173.226 Materials poisonous by inhalation, Division 6.1, Packing Group I, Hazard Zone A.

Division 6.1, Packing Group I, Zone A poisonous by inhalation (see § 173.133) must be packed in non-bulk packagings in accordance with the following paragraphs:

(a) In seamless specification or UN cylinders conforming to the requirements of § 173.40.

(b) In 1A1, 1B1, 1H1, 1N1, or 6HA1 drums further packed in a 1A2 or 1H2 drum. Both inner and outer drums must conform to the performance test requirements of subpart M of part 178 of this subchapter at the Packing Group I performance level. The outer drums may be tested either as a package intended to contain inner packagings (combination package) or as a single packaging intended to contain solids or liquids at a mass corresponding to the mass of the assembled packaging system. All outer drums, even those tested to contain inner packaging or as single packagings for solids, must withstand a hydrostatic test pressure of 100 kPa (15 psig). The outer drum must have a minimum thickness of 1.35 mm (0.053 inch) for a 1A2 outer drum or 6.3 mm (0.248 inch) for a 1H2 outer drum. In addition, the inner drum must—

(1) Be capable of satisfactorily withstanding the hydrostatic pressure test in § 178.605 of this subchapter at a test pressure of 300 kPa (45 psig);

(2) Satisfactorily withstand the leakproofness test in § 178.604 of this subchapter using an internal air pressure of at least twice the vapor pressure at 55 °C (131 °F) of the material to be packaged;