

DEPARTMENT OF COMMERCE**International Trade Administration**

[A-588-824]

Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order**AGENCY:** Import Administration, International Trade Administration, Department of Commerce.**ACTION:** Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order.

SUMMARY: On March 19, 2003, the Department of Commerce ("the Department") published a notice of initiation and preliminary results of a changed circumstances review with the intent to revoke, in part, the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. See *Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Initiation and Preliminary Results of Changed Circumstances Review of the Antidumping Order and Intent to Revoke Order in Part*, 68 FR 13256 (March 19, 2003) ("Initiation and Preliminary Results"). In our *Initiation and Preliminary Results*, we gave interested parties an opportunity to comment; however, we did not receive any comments. We are now revoking this order, in part, with respect to the particular carbon steel flat products described below, based on the fact that domestic parties have expressed no interest in the continuation of the order with respect to these particular carbon steel flat products. The Department will instruct the U.S. Customs Service ("Customs") to proceed with liquidation, without regard to antidumping duties, of all unliquidated entries of certain corrosion-resistant carbon steel flat products meeting the specifications indicated below entered, or withdrawn from warehouse, for consumption on or after August 1, 1998, the day after the most recent time period that was subject to final results of an administrative review (08/01/97 - 07/31/98).

EFFECTIVE DATE: April 23, 2003.**FOR FURTHER INFORMATION CONTACT:** Catherine Bertrand or Peter Mueller, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, N.W.,

Washington, D.C. 20230; telephone: (202) 482-3207, and (202) 482-5811, respectively.

SUPPLEMENTARY INFORMATION:**Background**

On January 31, 2003, Nippon Steel ("Nippon") requested that the Department revoke in part the antidumping duty order on certain corrosion-resistant carbon steel flat products from Japan. Specifically, Nippon requested that the Department revoke the order with respect to imports meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40 percent by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): carbon not over 0.06 percent by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over 0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) products with one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron-diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron-diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface

coating layer of hard nickel and a topmost nickel-phosphorus-plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (C) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent-added nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length.

On February 13, 2003, domestic producers of the like product, Bethlehem Steel Corporation; National Steel Corporation; and United States Steel Corporation, informed the Department that they have no interest in the importation or sale of steel from Japan with these specialized characteristics. Subsequently, as noted above, we gave interested parties an opportunity to comment on the *Initiation and Preliminary Results*. We received no comments from interested parties.

New Scope Based on Changed Circumstances Review

The merchandise covered by this changed circumstances review is certain corrosion-resistant carbon steel flat products from Japan. This changed circumstances administrative review covers all manufacturers/exporters of carbon steel flat products meeting the specifications as noted above in the background section. The new scope of this order is as follows: the products covered by the antidumping duty order

include flat-rolled carbon steel products, of rectangular shape, either clad, plated, or coated with corrosion-resistant metals such as zinc, aluminum, or zinc-, aluminum-, nickel- or iron-based alloys, whether or not corrugated or painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating, in coils (whether or not in successively superimposed layers) and of a width of 0.5 inch or greater, or in straight lengths which, if of a thickness less than 4.75 millimeters, are of a width of 0.5 inch or greater and which measures at least 10 times the thickness or if of a thickness of 4.75 millimeters or more are of a width which exceeds 150 millimeters and measures at least twice the thickness, as currently classifiable in the HTSUS under item numbers

7210.30.0030, 7210.30.0060,
7210.41.0000, 7210.49.0030,
7210.49.0090, 7210.61.0000,
7210.69.0000, 7210.70.6030,
7210.70.6060, 7210.70.6090,
7210.90.1000, 7210.90.6000,
7210.90.9000, 7212.20.0000,
7212.30.1030, 7212.30.1090,
7212.30.3000, 7212.30.5000,
7212.40.1000, 7212.40.5000,
7212.50.0000, 7212.60.0000,
7215.90.1000, 7215.90.3000,
7215.90.5000, 7217.20.1500,
7217.30.1530, 7217.30.1560,
7217.90.1000, 7217.90.5030,
7217.90.5060, 7217.90.5090. Included in this order are corrosion-resistant flat-rolled products of non-rectangular cross-section where such cross-section is achieved subsequent to the rolling process (*i.e.*, products which have been "worked after rolling") for example, products which have been beveled or rounded at the edges.

Excluded from this order are flat-rolled steel products either plated or coated with tin, lead, chromium, chromium oxides, both tin and lead ("terne plate"), or both chromium and chromium oxides ("tin-free steel"), whether or not painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating.

Also excluded from this order are clad products in straight lengths of 0.1875 inch or more in composite thickness and of a width which exceeds 150 millimeters and measures at least twice the thickness.

Also excluded from this order are certain clad stainless flat-rolled products, which are three-layered corrosion-resistant carbon steel flat-rolled products less than 4.75 millimeters in composite thickness that consist of a carbon steel flat-rolled

product clad on both sides with stainless steel in a 20%-60%-20% ratio.

Also excluded from this order are certain corrosion-resistant carbon steel flat products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of chromate, and finally a layer consisting of silicate.

Also excluded from this order are carbon steel flat products measuring 1.84 millimeters in thickness and 43.6 millimeters or 16.1 millimeters in width consisting of carbon steel coil (SAE 1008) clad with an aluminum alloy that is balance aluminum, 20% tin, 1% copper, 0.3% silicon, 0.15% nickel, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Also excluded from this order are carbon steel flat products measuring 0.97 millimeters in thickness and 20 millimeters in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% to 11% tin, 9% to 11% lead, less than 1% zinc, less than 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 45% to 55% lead, 38% to 50% PTFE, 3% to 5% molybdenum disulfide and less than 2% other materials.

Also excluded from this order are doctor blades meeting the following specifications: carbon steel coil or strip, plated with nickel phosphorous, having a thickness of 0.1524 millimeters (0.006 inches), a width between 31.75 millimeters (1.25 inches) and 50.80 millimeters (2.00 inches), a core hardness between 580 to 630 HV, a surface hardness between 900 - 990 HV; the carbon steel coil or strip consists of the following elements identified in percentage by weight: 0.90% to 1.05% carbon; 0.15% to 0.35% silicon; 0.30% to 0.50% manganese; less than or equal to 0.03% of phosphorous; less than or equal to 0.006% of sulfur; other

elements representing 0.24%; and the remainder of iron.

Also excluded from this order are products meeting the following specifications: carbon steel flat products measuring 1.64 millimeters in thickness and 19.5 millimeters in width consisting of carbon steel coil (SAE 1008) with a lining clad with an aluminum alloy that is balance aluminum; 10 to 15% tin; 1 to 3% lead; 0.7 to 1.3% copper; 1.8 to 3.5% silicon; 0.1 to 0.7% chromium, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring 1.93 millimeters or 2.75 millimeters (0.076 inches or 0.108 inches) in thickness, 87.3 millimeters or 99 millimeters (3.437 inches or 3.900 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 0.3% antimony, 2.5% silicon, 1% maximum total other (including iron), and remainder aluminum.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, clad with aluminum, measuring 1.75 millimeters (0.069 inches) in thickness, 89 millimeters or 94 millimeters (3.500 inches or 3.700 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 2.5% silicon, 0.3% antimony, 1% maximum total other (including iron), and remainder aluminum.

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring a minimum of and including 1.10mm to a maximum of and including 4.90mm in overall thickness, a minimum of and including 76.00mm to a maximum of and including 250.00mm in overall width, with a low carbon steel back comprised of: carbon under 0.10%, manganese under 0.40%, phosphorous under 0.04%, sulfur under 0.05%, and silicon under 0.05%; clad with aluminum alloy comprised of: under 2.51% copper, under 15.10% tin, and remainder aluminum as listed on the mill specification sheet.

Also excluded from this order are products meeting the following specifications: (1) Diffusion annealed,

non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet ("CRBG") with both sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0-5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004" (0.10mm) to 0.030" (0.762mm) and conforming to the following chemical specifications (%): C \leq 0.08; Mn \leq 0.45; P \leq 0.02; S \leq 0.02; Al \leq 0.15; and Si \leq 0.10; and the following physical specifications: Tensile = 65 KSI maximum; Yield = 32 - 55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85 - 150 Vickers; Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7-12; Delta r value = aim less than +/- 0.2; Lankford value = \geq 1.2.; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) nickel-graphite plated, diffusion annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: top side: nickel-graphite, tin-nickel layer \geq 1.0 micrometers; tin layer only \geq 0.05 micrometers, nickel-graphite layer only $>$ 0.2 micrometers, and bottom side: nickel layer \geq 1.0 micrometers; (b) nickel-graphite, diffusion annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-

graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer \geq 1.0 micrometers; nickel-graphite layer \geq 0.5 micrometers; bottom side: nickel layer \geq 1.0 micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer \geq 1.0 micrometers; bottom side: nickel layer \geq 1.0 micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer \geq 1.0 micrometers; nickel-phosphorous layer \geq 0.1 micrometers; bottom side: nickel layer \geq 1.0 micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip

initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin-nickel combination layer \geq 1.0 micrometers; tin layer only \geq 0.05 micrometers; bottom side: nickel layer \geq 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer \geq 1 micrometer; tin layer alone \geq 0.05 micrometers; bottom side: nickel layer \geq 1.0 micrometer.

Also excluded from this order are products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.00019 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of phosphate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of phosphate, and finally a layer consisting of silicate.

Also excluded from this order are products meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) having a base layer of zinc-based zinc-iron alloy applied by hot-

dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40 percent by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): carbon not over 0.06 percent by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over 0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) Products with one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron-diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron-diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface coating layer of hard nickel and a topmost nickel-phosphorus-plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (C) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent-added nickel which is not heat-treated; with combined coating thickness for all three layers of more

than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron-diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron-diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length.

Final Results of Review; Partial Revocation of Antidumping Duty Order

The affirmative statement of no interest by petitioners concerning carbon steel flat products, as described herein, constitutes changed circumstances sufficient to warrant partial revocation of this order. Also, no party commented on the *Initiation and Preliminary Results*. Therefore, the Department is partially revoking the order on certain corrosion-resistant carbon steel flat products from Japan with regard to products which meet the specifications detailed above, in accordance with sections 751(b) and (d) and 782(h) of the Tariff Act of 1930, as amended ("the Act"), and 19 CFR 351.216(d) of the Department's regulations. The Department will instruct Customs to proceed with liquidation, without regard to antidumping duties, of all unliquidated entries of certain corrosion-resistant carbon steel flat products meeting the specifications indicated above entered, or withdrawn from warehouse, for consumption on or after August 1, 1998, the day after the most recent time period that was subject to final results of an administrative review (08/01/97 - 07/31/98). The Department will further instruct Customs to refund with interest any estimated duties collected with respect to unliquidated entries of certain corrosion-resistant carbon steel flat products meeting the specifications indicated above, entered or withdrawn from warehouse, for consumption on or after August 1, 1998, in accordance with section 778 of the Act.

This notice serves as a reminder to parties subject to administrative protective orders ("APOs") of their responsibility concerning the disposition of proprietary information disclosed under APO in accordance

with 19 CFR 351.306 of the Department's regulations. Timely written notification of the return/destruction of APO materials or conversion to judicial protective order is hereby requested. Failure to comply with the regulations and terms of an APO is a sanctionable violation.

This changed circumstances administrative review, partial revocation of the antidumping duty order and notice are in accordance with sections 751(b) and (d) and 782(h) of the Act and sections 351.216(e) and 351.222(g) of the Department's regulations.

Dated: April 16, 2003.

Joseph A. Spetrini,
Acting Assistant Secretary for Import Administration.

[FR Doc. 03-10060 Filed 4-22-03; 8:45 am]

BILLING CODE 3510-DS-S

DEPARTMENT OF COMMERCE

Notice of Opportunity To Apply for Membership on the U.S. Travel and Tourism Promotion Advisory Board

AGENCY: International Trade Administration.

ACTION: Notice.

SUMMARY: The Department of Commerce is currently seeking applications for membership on the U.S. Travel and Tourism Promotion Advisory Board ("Board"). The purpose of the Board is to recommend to the Secretary of Commerce the appropriate coordinated activities with regards to funding for the Travel and Tourism Advertising and Promotional Campaign ("Campaign"). Pursuant to Pub. L. No. 108-7, Division B, section 210, the Secretary of Commerce shall in consultation with the private sector design, develop and implement an international advertising and promotional campaign, which seeks to encourage foreign individuals to travel to the United States for the purposes of engaging in tourism related activities.

SUPPLEMENTARY INFORMATION: The Board was established pursuant to the Department of Commerce and Related Agencies Appropriations Act, 2003, section 210 (Public Law 108-7), to advise the Secretary of Commerce on appropriate coordinated activities for funding under the Campaign. The Board shall function as an advisory committee in accordance with the Federal Advisory Committee Act, 5 U.S.C. App. 2, and Department of Commerce policies on Advisory Boards.

The Office of the Deputy Assistant Secretary for Service Industries,